1 Identification

- · Product identifier
- · Trade name: 17013- 17503 Classic Coat Aerosol
- · Article number:

17013, 17023, 17033, 17043, 17053, 17063, 17073, 17083, 17093, 17103, 17113, 17123, 17133, 17143, 17153, 17163, 17173, 17183, 17193, 17203, 17213, 17223, 17233, 17243, 17253, 17263, 17273, 17283, 17293, 17303, 17313, 17323, 17333, 17343, 17353, 17503, 17363, 17373, 17383, 17393, 17403, 17413, 17423, 17433

- · Application of the substance / the mixture Coating
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: SEM Products Inc. 1685 Overview Drive Rock Hill, SC 29730

803 207 8225

· Information department:

cust\_care@semproducts.com : SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT

· Emergency telephone number: CHEMTREC 1-800-424-9300

#### 2 Hazard identification

· Classification of the substance or mixture





GHS02 GHS04 Flame, Gas cylinder

Flammable Aerosols - Category 1 H222 Extremely flammable aerosol.



GHS04 Gas cylinder

Gases Under Pressure - Compressed Gas

H280 Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Carcinogenicity – Category 2 H351 Suspected of causing cancer.

Reproductive Toxicity - Category 2 H361 Suspected of damaging fertility or the unborn

child.

Specific Target Organ Toxicity - Repeated Exposure -

Category 2

H373 May cause damage to organs through prolonged or repeated exposure.

Aspiration Hazard - Category 1 H304 May be fatal if swallowed and enters airways.



Skin Irritation - Category 2 H315 Causes skin irritation.

Eye Irritation - Category 2A H319 Causes serious eye irritation.

(Contd. on page 2)

Trade name: 17013-17503 Classic Coat Aerosol

(Contd. of page 1)

Specific Target Organ Toxicity - Single Exposure - H336 May cause drowsiness or dizziness. Category 3

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms









GHS02

GHS04

GHS07

· Signal word Danger

#### · Hazard-determining components of labeling:

toluene

acetone

4-methylpentan-2-one

ethylbenzene

#### · Hazard statements

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

## · Precautionary statements

*P201 Obtain special instructions before use.* 

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

*P211* Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

*P264 Wash thoroughly after handling.* 

P271 Use only outdoors or in a well-ventilated area.

*P280* Wear protective gloves/protective clothing/eye protection/face protection.

*P301+P310 If swallowed: Immediately call a poison center/doctor.* 

*P321* Specific treatment (see on this label).

*P331* Do NOT induce vomiting.

P302+P352 If on skin: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a poison center/doctor if you feel unwell.
P314 Get medical advice/attention if you feel unwell.

P362+P364 Take off contaminated clothing and wash it before reuse.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.

(Contd. on page 3)



Trade name: 17013-17503 Classic Coat Aerosol

(Contd. of page 2)

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

*P410+P403 Protect from sunlight. Store in a well-ventilated place.* 

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 2 Fire = 4 Reactivity = 3

· HMIS-ratings (scale 0 - 4)



Health = \*2
Fire = 4
Reactivity = 3

## 3 Composition/Information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture: consisting of the following components.

Weight percentages

· Dangerous components:		
67-64-1	acetone	15-40% w/w
68476-86-8	Petroleum gases, liquefied, sweetened	10-30% w/w
108-88-3	toluene	10-30% w/w
108-10-1	4-methylpentan-2-one	1-5% w/w
110-19-0	isobutyl acetate	1-5% w/w
	ACRYLIC RESIN	1-5% w/w
<i>78-93-3</i>	butanone	1-5% w/w
108-65-6	2-methoxy-1-methylethyl acetate	1-5% w/w
2807-30-9	2-(propyloxy)ethanol	1-5% w/w
78-83-1	butanol	≥1-<1.5% w/w

## 4 First aid measures

- · Description of first aid measures
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 4)

Trade name: 17013-17503 Classic Coat Aerosol

(Contd. of page 3)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

## 5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · **Protective equipment:** No special measures required.

## 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

- · Handling:
- · Precautions for safe handling No special measures required.
- · Information about protection against explosions and fires:

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurized containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

## 8 Exposure controls/ Personal protection

· Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 5)

Trade name: 17013-17503 Classic Coat Aerosol

(Contd. of page 4)

	ponents with limit values that require monitoring at the workplace:
0/-04	4-1 acetone
EL $S$	Short-term value: 500 ppm
	Long-term value: 250 ppm
EV $S$	Short-term value: 750 ppm
1	Long-term value: 500 ppm
108-	88-3 toluene
EL $I$	Long-term value: 20 ppm
1	R
EV	Long-term value: 20 ppm
108-	10-1 4-methylpentan-2-one
	Short-term value: 75 ppm
	Long-term value: 20 ppm IARC 2B
EV $S$	Short-term value: 75 ppm
1	Long-term value: 205 mg/m³, 50 ppm
110-	19-0 isobutyl acetate
EL $I$	Long-term value: 150 ppm
	Short-term value: 187 ppm
	Long-term value: 150 ppm
<i>78-9</i> .	3-3 butanone
	Short-term value: 100 ppm
	Long-term value: 50 ppm
	Short-term value: 885 mg/m³, 300 ppm
	Long-term value: 590 mg/m³, 200 ppm
	65-6 2-methoxy-1-methylethyl acetate
	Short-term value: 75 ppm
	Long-term value: 50 ppm
	Long-term value: 270 mg/m³, 50 ppm
	-30-9 2-(propyloxy)ethanol
	Long-term value: 110 mg/m³, 25 ppm Skin
<i>78-8</i> .	3-1 butanol

- EV Long-term value: 150 mg/m³, 50 ppm
- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately. Avoid contact with the eyes and skin.

(Contd. on page 6)



Trade name: 17013-17503 Classic Coat Aerosol

(Contd. of page 5)

#### · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

### · Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### · Eye protection:

Safety glasses



Tightly sealed goggles

## 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information

· Appearance:

Form: Aerosol

Color: According to product specification

Odor: CharacteristicOdor threshold: Not determined.

• pH-value: Not determined.

Not determined.

· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 55 °C

· Flash point: -103 °C

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 535 °C

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

• Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

(Contd. on page 7)

Trade name: 17013-17503 Classic Coat Aerosol

		(Contd. of page
Explosion limits:		
Lower:	1.2 Vol %	
Upper:	7 Vol %	
Vapor pressure at 20 °C:	29 hPa	
Density at 20 °C:	$0.74095 \text{ g/cm}^3$	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not applicable.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wa	t <b>ter</b> ): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	92.0 %	
Water:	0.0 %	
VOC content:	60.33 %	
	635.5 g/l / 5.30 lb/gl	
Solids content:	8.1 %	
Other information	No further relevant information available.	

## 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · *Incompatible materials:* No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classifi	cation:
---	---------

#### 108-88-3 toluene Oral LD50 5,000 mg/kg (rat) LD50 Dermal 12,124 mg/kg (rabbit) Inhalative LC50/4 h 5,320 mg/l (mouse)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.

(Contd. on page 8)

SEM

Printing date 03/21/2018 Reviewed on 06/20/2017

Trade name: 17013-17503 Classic Coat Aerosol

(Contd. of page 7)

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)		
108-88-3	toluene	3
108-10-1	4-methylpentan-2-one	2B
13463-67-7	titanium dioxide	2B
1330-20-7	xylene	3
1333-86-4	Carbon black	2B
111-76-2	2-butoxyethanol	3
100-41-4	ethylbenzene	2B
14807-96-6	Talc	3
· NTP (Nation	· NTP (National Toxicology Program)	
None of the ingredients is listed.		

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

 $\Box \Delta$ 

Safety Data Sheet according to HPR, Schedule 1

Printing date 03/21/2018 Reviewed on 06/20/2017

Trade name: 17013-17503 Classic Coat Aerosol

(Contd. of page 8)

4 Transport information	
· UN-Number · DOT, TDG, IMDG, IATA	UN1950
· UN proper shipping name	
$\cdot DOT$	Aerosols, flammable
$\cdot$ $TDG$	1950 Aerosols
· IMDG	AEROSOLS
· IATA	AEROSOLS, flammable
· Transport hazard class(es)	
· DOT	
AMMARIA DIL	
· Class	2.1
· Label	2.1
· TDG (Transport dangerous goods):	
· Class · Label	2 5F Gases 2.1
· IMDG, IATA	
· Class	2.1
· Label	2.1
· Packing group · DOT, TDG, IMDG, IATA	Void
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Gases
· EMS Number:	F- $D$ , $S$ - $U$
· Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of 1 litra
	Category A. For AEROSOLS with a capacity above 1 litr Category B. For WASTE AEROSOLS: Category C, Clear of livin quarters.
	(Contd. on page

(Contd. on page 10)

Safety Data Sheet according to HPR, Schedule 1

Printing date 03/21/2018 Reviewed on 06/20/2017

Trade name: 17013-17503 Classic Coat Aerosol

	(Contd. of page 9)
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· Transport in bulk according to Annex MARPOL73/78 and the IBC Code	<b>II of</b> Not applicable.
· Transport/Additional information:	
$\cdot$ DOT	
· Quantity limitations	On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg
· TDG	
· Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· IMDG	
· Limited quantities (LQ)	IL
$\cdot$ Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· UN ''Model Regulation'':	UN 1950 AEROSOLS, 2.1

# 15 Regulatory information

 $\cdot \textit{Safety, health and environmental regulations/legislation specific for the substance or \textit{mixture}}$ 

· Sara	
· Section 355	(extremely hazardous substances):
None of the	ingredient is listed.
· Section 313	(Specific toxic chemical listings):
108-88-3	toluene
108-10-1	4-methylpentan-2-one
78-93 <i>-</i> 3	butanone
	Acrylic Resin
1330-20-7	xylene
67-56-1	methanol
111-76-2	2-butoxyethanol
100-41-4	ethylbenzene
14807-96-6	Talc
· TSCA (Tox	ic Substances Control Act):
67-64-1	acetone
108-88-3	toluene
108-10-1	4-methylpentan-2-one
110-19-0	isobutyl acetate
9004-36-8	Cellulose Acetate Butyrate
	(Contd on page 11

(Contd. on page 11)

Trade name: 17013-17503 Classic Coat Aerosol

	(Contd. of page
78-93-3 bu	ıtanone
108-65-6 2-1	methoxy-1-methylethyl acetate
807-30-9 2-(	(propyloxy)ethanol
78-83-1 bu	ıtanol
268-70-7 Te	etraethylene Glycol Di 2-ethylhexoate
011-05-6 Ur	rea polymer
463-67-7 tita	tanium dioxide
911-87-5 mc	ontmorilontie clay complex
330-20-7 xyl	lene
274-00-1 YE	ELLOW IRON OXIDE
333-86-4 Ca	arbon black
67-56-1 me	ethanol
332-37-2 <i>Ira</i>	on oxide
111-76-2 2-1	butoxyethanol
123-86-4 n-l	butyl acetate
100-41-4 eth	hylbenzene
791-55-7 An	mines, N-tallow alkyltrimethylenedi-
807-96-6 Ta	alc
57-55-6 Me	lethyl glycol
732-18-5 wa	ater
nadian subsi	ater stance listings: nestic Substances List (DSL)

· Canadian D	· Canadian Domestic Substances List (DSL)	
67-64-1	acetone	
68476-86-8	Petroleum gases, liquefied, sweetened	
108-88-3	toluene	
108-10-1	4-methylpentan-2-one	
110-19-0	isobutyl acetate	
78-93-3	butanone	
108-65-6	2-methoxy-1-methylethyl acetate	
2807-30-9	2-(propyloxy)ethanol	
78-83-1	butanol	
18268-70-7	Tetraethylene Glycol Di 2-ethylhexoate	
9011-05-6	Urea polymer	
13463-67-7	titanium dioxide	
68911-87-5	montmorilontie clay complex	
1330-20-7	xylene	
51274-00-1	YELLOW IRON OXIDE	
1333-86-4	Carbon black	
67-56-1	methanol	
1332-37-2	Iron oxide	
111-76-2	2-butoxyethanol	

(Contd. on page 12)

Trade name: 17013-17503 Classic Coat Aerosol

	(Contd. of page 11)		
123-86-	4 n-butyl acetate		
100-41-	4 ethylbenzene		
61791-55-	7 Amines, N-tallow alkyltrimethylenedi-		
14807-96-	6 Talc		
57-55-	6 Methyl glycol		
7732-18-	5 water		
· Canadian	Canadian Ingredient Disclosure list (limit 0.1%)		
None of th	None of the ingredients is listed.		
· Canadian	Ingredient Disclosure list (limit 1%)		
67-64-1	acetone		
108-88-3	toluene		
108-10-1	4-methylpentan-2-one		
110-19-0	isobutyl acetate		
78-93-3	butanone		
78-83-1	butanol		

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms









GHS02

GHS04

GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

toluene

acetone

4-methylpentan-2-one

ethylbenzene

#### · Hazard statements

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

#### · Precautionary statements

*P201 Obtain special instructions before use.* 

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smokino

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

*P264 Wash thoroughly after handling.* 

(Contd. on page 13)

#### Trade name: 17013-17503 Classic Coat Aerosol

	(Contd. of page 12)
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P321	Specific treatment (see on this label).
P331	Do NOT induce vomiting.
P302+P352	If on skin: Wash with plenty of water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P3	338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a poison center/doctor if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P362+P364	Take off contaminated clothing and wash it before reuse.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P410+P403	Protect from sunlight. Store in a well-ventilated place.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
· Chemical safety	assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Rita Joiner (rjoiner@semproducts.com)
- · Date of preparation / last revision 03/21/2018 / 10
- · Abbreviations and acronyms:

ICAO: International Civil Aviation Organisation

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

\* \* Data compared to the previous version altered.