# 1 Identification

- · Product identifier
- · Trade name: 39023 39583 TPO-Direct Bumper Coaters
- · Article number:

39153, 39253, 39263, 39273, 39163, 39173, 39183, 39193, 39283, 39293, 39413, 39423, 39443, 39583, 39023, 39073, 39083, 39103

- · Application of the substance / the mixture Coating
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SEM Products Inc. 1685 Overview Drive Rock Hill, SC 29730 803 207 8225

· Information department:

cust\_care@semproducts.com: SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730: phone 1-800-831-1122, M - TH 7am - 4pm EDT

· Emergency telephone number: CHEMTREC 1-800-424-9300

# 2 Hazard identification

· Classification of the substance or mixture





GHS02 GHS04 Flame, Gas cylinder

Flammable Aerosols - Category 1

H222 Extremely flammable aerosol.



GHS04 Gas cylinder

Gases Under Pressure - Compressed Gas H280 Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Reproductive Toxicity - Category 2 H361 Suspected of damaging fertility or the unborn

Specific Target Organ Toxicity - Repeated Exposure -

Category 2

Aspiration Hazard - Category 1

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.



Skin Irritation - Category 2

H315 Causes skin irritation.

Specific Target Organ Toxicity - Single Exposure -

H336 May cause drowsiness or dizziness.

Category 3

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 2)

according to HFR, Schedule 1

SEM

Printing date 03/21/2018 Reviewed on 06/21/2017

Trade name: 39023 - 39583 TPO-Direct Bumper Coaters

(Contd. of page 1)

#### · Hazard pictograms









GHS02

S02 GHS04 GH

GHS07 GHS0

#### · Signal word Danger

# · Hazard-determining components of labeling:

toluene

cyclohexane

Stoddard solvent

Solvent naphtha (petroleum), light arom.

#### · Hazard statements

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

#### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

*P201 Obtain special instructions before use.* 

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

*P251 Do not pierce or burn, even after use.* 

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

*P264* Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P302+P352 If on skin: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a poison center/doctor if you feel unwell. P314 Get medical advice/attention if you feel unwell.

P362+P364 Take off contaminated clothing and wash it before reuse.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

(Contd. of page 2)

Printing date 03/21/2018 Reviewed on 06/21/2017

Trade name: 39023 - 39583 TPO-Direct Bumper Coaters

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 1Fire = 4Reactivity = 3

· HMIS-ratings (scale 0 - 4)



Fire = 4

REACTIVITY 3 Reactivity = 3

# 3 Composition/Information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture: consisting of the following components.

Weight percentages

Dangana	· Dangerous components:			
	•			
115-10-6	dimethyl ether	30-60% w/w		
108-88-3	toluene	10-30% w/w		
110-19-0	isobutyl acetate	10-30% w/w		
110-82-7	cyclohexane	1-5% w/w		
108-83-8	2,6-dimethylheptan-4-one	0.5-1.5% w/w		

# 4 First aid measures

- · Description of first aid measures
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

# 5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 4)



Trade name: 39023 - 39583 TPO-Direct Bumper Coaters

(Contd. of page 3)

· Advice for firefighters

· Protective equipment: No special measures required.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# 7 Handling and storage

- · Handling:
- · Precautions for safe handling No special measures required.
- · Information about protection against explosions and fires:

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurized containers.

- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

# 8 Exposure controls/ Personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

115-10-6 dimethyl ether

EL Long-term value: 1000 ppm

108-88-3 toluene

EL Long-term value: 20 ppm

R

EV Long-term value: 20 ppm

(Contd. on page 5)



Trade name: 39023 - 39583 TPO-Direct Bumper Coaters

(Contd. of page 4)

# 110-19-0 isobutyl acetate

EL Long-term value: 150 ppm
EV Short-term value: 187 ppm
Long-term value: 150 ppm

#### 110-82-7 cyclohexane

EL Long-term value: 100 ppm EV Long-term value: 100 ppm

# 108-83-8 2,6-dimethylheptan-4-one

EL Long-term value: 25 ppm

EV Long-term value: 145 mg/m³, 25 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

#### · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

### · Eye protection:

Safety glasses



Tightly sealed goggles

CA.

Trade name: 39023 - 39583 TPO-Direct Bumper Coaters

(Contd. of page 5)

Physical and chemical proper	rties
Information on basic physical and	chemical properties
General Information	T. of the state of
Appearance:	
Form:	Aerosol
Color:	According to product specification
· Odor:	Characteristic
Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	-24 °C
Flash point:	-42 °C
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	235 °C
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	18.6 Vol %
Vapor pressure at 20 °C:	5,200 hPa
Density at 20 °C:	$0.78383 \ g/cm^3$
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not applicable.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	89.8 %
Water:	0.0 %
VOC content:	89.83 %
	704.1 g/l / 5.88 lb/gl
Solids content:	8.6 %
Other information	No further relevant information available.



Trade name: 39023 - 39583 TPO-Direct Bumper Coaters

(Contd. of page 6)

# 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · *Incompatible materials:* No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

# 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 1	· LD/LC50 values that are relevant for classification:						
108-88-3 te	108-88-3 toluene						
Oral		5,000 mg/kg (rat)					
Dermal	LD50	12,124 mg/kg (rabbit)					
Inhalative	LC50/4 h	5,320 mg/l (mouse)					
110-82-7 с	110-82-7 cyclohexane						
Oral	LD50	12,705 mg/kg (rat)					

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (Inter	· IARC (International Agency for Research on Cancer)	
108-88-3	toluene	3
1333-86-4	Carbon black	2B
13463-67-7	titanium dioxide	2B
1330-20-7	xylene	3
	propan-2-ol	3
100-41-4	ethylbenzene	2B
14807-96-6	Talc	3
· NTP (Natio	nal Toxicology Program)	

None of the ingredients is listed.

# 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.

(Contd. on page 8)



Trade name: 39023 - 39583 TPO-Direct Bumper Coaters

(Contd. of page 7)

- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

# 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

7 4 7			•	<sup>f</sup> orma	. •
	ranc	$n \alpha r t$		$\alpha$ r $m$ $\alpha$	пои
		vviv	TO TO I		44U.

- · UN-Number
- · DOT, TDG, IMDG, IATA

UN1950

· UN proper shipping name

DOT Aerosols, flammable
TDG 1950 Aerosols
IMDG AEROSOLS

· IATA AEROSOLS, flammable

- · Transport hazard class(es)
- $\cdot DOT$



· Class
 · Label
 2.1
 2.1

· TDG (Transport dangerous goods):



· Class 2 5F Gases

(Contd. on page 9)

Safety Data Sheet according to HPR, Schedule 1

Printing date 03/21/2018 Reviewed on 06/21/2017

Trade name: 39023 - 39583 TPO-Direct Bumper Coaters

	(Contd. of page
Label	2.1
IMDG, IATA	
Class	2.1
Label	2.1
Packing group DOT, TDG, IMDG, IATA	Void
Environmental hazards:	Not applicable.
Special precautions for user EMS Number: Stowage Code	Warning: Gases F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre Category A. For AEROSOLS with a capacity above 1 litre Category B. For WASTE AEROSOLS: Category C, Clear of livin
Segregation Code	quarters.  SG69 For AEROSOLS with a maximum capacity of 1 litro Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litro Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg
TDG Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
IMDG	
Limited quantities (LQ)	
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

Trade name: 39023 - 39583 TPO-Direct Bumper Coaters

(Contd. of page 9)

1:	5 Re	gu	late	ory ii	nfor	matio	n						
		_	_			_		 	_	 _	_	_	

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara

· Section 355	5 (extremely hazardous substances):
None of the	e ingredient is listed.
· Section 313	3 (Specific toxic chemical listings):

108-88-3	
	cyclohexane
7429-90-5	aluminium
	Acrylic Resin
1330-20-7	
	butanone
	propan-2-ol
	ethylbenzene
	methanol
14807-96-6	Talc Talc

	emylbenzene
	methanol
14807-96-6	Talc
· TSCA (Toxi	ic Substances Control Act):
115-10-6	dimethyl ether
108-88-3	toluene
110-19-0	isobutyl acetate
	cyclohexane
	2,6-dimethylheptan-4-one
	Carbon black
	aluminium
	4,6-dimethylheptan-2-one
13463-67-7	titanium dioxide
	YELLOW IRON OXIDE
1330-20-7	
78-93-3	butanone
	propan-2-ol
	Iron oxide
	2-methoxy-1-methylethyl acetate
	2-(propyloxy)ethanol
	ethylbenzene
	bisphenolA(chloro)oxirane polymer
	methanol
	montmorilontie clay complex
	Amines, N-tallow alkyltrimethylenedi-
14807-96-6	
	butanol
57-55-6	Methyl glycol

(Contd. on page 11)

Trade name: 39023 - 39583 TPO-Direct Bumper Coaters

7722 10 5	(Contd. of page
7732-18-5	
	ubstance listings:
	omestic Substances List (DSL)
	dimethyl ether
108-88-3	
	isobutyl acetate
	cyclohexane
	2,6-dimethylheptan-4-one
	Carbon black
	aluminium
	4,6-dimethylheptan-2-one
	titanium dioxide
	YELLOW IRON OXIDE
	Stoddard solvent
1330-20-7	
	butanone
	propan-2-ol
	Iron oxide
	2-methoxy-1-methylethyl acetate
	2-(propyloxy)ethanol
	ethylbenzene
	bisphenolA(chloro)oxirane polymer
	methanol
	montmorilontie clay complex
	Amines, N-tallow alkyltrimethylenedi-
14807-96-6	
78-83-1	
	Methyl glycol
7732-18-5	water
	ngredient Disclosure list (limit 0.1%)
None of the	ingredients is listed.
	ngredient Disclosure list (limit 1%)
108-88-3 to	
110-19-0 is	obutyl acetate
110-82-7 cy	
108-83-8 2,	6-dimethylheptan-4-one

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 12)

CA -

Printing date 03/21/2018

Trade name: 39023 - 39583 TPO-Direct Bumper Coaters

(Contd. of page 11)

#### · Hazard pictograms









GHS04

GHS07

#### · Signal word Danger

# · Hazard-determining components of labeling:

toluene

cyclohexane

Stoddard solvent

Solvent naphtha (petroleum), light arom.

#### · Hazard statements

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

#### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P321 Specific treatment (see on this label).

Do NOT induce vomiting. P331

P302+P352 If on skin: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a poison center/doctor if you feel unwell. P314 Get medical advice/attention if you feel unwell.

P362+P364 Take off contaminated clothing and wash it before reuse.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.



Trade name: 39023 - 39583 TPO-Direct Bumper Coaters

(Contd. of page 12)

# 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Rita Joiner (rjoiner@semproducts.com)
- · Date of preparation / last revision 03/21/2018 / 4
- · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

· \* Data compared to the previous version altered.

CA