1 Identification

- · Product identifier
- · Trade name: 39221 39225 WB Flexible Primer Surfacer Black
- · Article number: 39221, 39225
- · Application of the substance / the mixture Coating
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SEM Products Inc.

1685 Overview Drive

Rock Hill, SC 29730

803 207 8225

· Information department:

cust_care@semproducts.com: SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730: phone 1-800-831-

1122, M - TH 7am - 4pm EDT

· Emergency telephone number: CHEMTREC 1-800-424-9300

2 Hazard identification

· Classification of the substance or mixture



GHS07

Skin Irritation - Category 2 H315 Causes skin irritation.

Eye Irritation - Category 2A H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure -H335 May cause respiratory irritation.

Category 3

Flammable Liquids - Category 4 H227 Combustible liquid.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard-determining components of labeling:

NEPHELINE SYENITE

Talc

· Hazard statements

H227 Combustible liquid.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

· Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No P210

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

(Contd. on page 2)



Trade name: 39221 39225 WB Flexible Primer Surfacer Black

(Contd. of page 1)

Wash thoroughly after handling. P264

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 If on skin: Wash with plenty of water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. P304+P340

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P312 Call a poison center/doctor if you feel unwell.

P321 *Specific treatment (see on this label).*

P362+P364 Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. P332+P313 *If eye irritation persists: Get medical advice/attention.* P337+P313

P370+P378 *In case of fire: Use for extinction: CO2, powder or water spray.* P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2Fire = 1

3 Composition/Information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture: consisting of the following components.

Weight percentages

· Dangerous	components:	
37244-96-5	NEPHELINE SYENITE	10-30% w/w
14807-96-6	Talc	≥10-≤13% w/w
	1-methoxy-2-propanol	1-5% w/w
1333-86-4	Carbon black	1-5% w/w
872-50-4	N-methyl-2-pyrrolidone	≥0.1-≤1% w/w
108-88-3	toluene	≥0.1-≤1% w/w

4 First aid measures

- · Description of first aid measures
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)



Trade name: 39221 39225 WB Flexible Primer Surfacer Black

(Contd. of page 2)

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

No special measures required.

- · Information about protection against explosions and fires: Keep ignition sources away Do not smoke.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- \cdot *Specific end use*(s) *No further relevant information available.*

8 Exposure controls/ Personal protection

· Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 4)

Trade name: 39221 39225 WB Flexible Primer Surfacer Black

(Contd. of page 3)

70 m t m 0 1 m a m a m a o t a m

Con	ntrol parameters
· Con	nponents with limit values that require monitoring at the workplace:
107	-98-2 1-methoxy-2-propanol
EL	Short-term value: 75 ppm Long-term value: 50 ppm
EV	Short-term value: 550 mg/m³, 150 ppm Long-term value: 365 mg/m³, 100 ppm
133	3-86-4 Carbon black
EL	Long-term value: 3 mg/m³ IARC 2B
EV	Long-term value: 3.5 mg/m³
872	-50-4 N-methyl-2-pyrrolidone
EV	Long-term value: 400 mg/m³
108	-88-3 toluene
EL	Long-term value: 20 ppm R

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:

EV Long-term value: 20 ppm

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Reviewed on 06/20/2017 Printing date 03/21/2018

Trade name: 39221 39225 WB Flexible Primer Surfacer Black

(Contd. of page 4)

· Eye protection:



Tightly sealed goggles

Physical and chemical proper	rties
Information on basic physical and	chemical properties
General Information	
Appearance:	**
Form:	Liquid
Color:	According to product specification
Odor: Odor threshold:	Characteristic Not determined.
pH-value:	Not determined.
•	noi ueterminea.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	100 °C
Flash point:	93 °C
Flammability (solid, gaseous):	Not applicable.
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapor pressure at 20 °C:	23 hPa
Density at 20 °C:	1.22608 g/cm³
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	(er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	7.1 %
Water:	45.9 %
VOC content:	7.12 %

(Contd. on page 6)

Trade name: 39221 39225 WB Flexible Primer Surfacer Black

(Contd. of page 5)

Solids content: 45.8 %

• Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (Inter	rnational Agency for Research on Cancer)	
14807-96-6	Talc	3
1333-86-4	Carbon black	2B
108-88-3	toluene	3
· NTP (Natio	nal Toxicology Program)	
None of the	ingredients is listed.	

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.

(Contd. on page 7)

Trade name: 39221 39225 WB Flexible Primer Surfacer Black

(Contd. of page 6)

· vPvB: Not applicable.

· Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number		
DOT, TDG, ADN, IMDG, IATA	Void	
UN proper shipping name DOT, TDG, ADN, IMDG, IATA	Void	
Transport hazard class(es)		
DOT, TDG, ADN, IMDG, IATA		
Class	Void	
Packing group		
DOT, TDG, IMDG, IATA	Void	
Environmental hazards:		
Marine pollutant:	No	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex	II of	
MARPOL73/78 and the IBC Code	Not applicable.	
UN "Model Regulation":	Void	

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

1480	7-96-	6	Tale

872-50-4 N-methyl-2-pyrrolidone

108-88-3 toluene

1336-21-6 ammonia solution 26%

(Contd. on page 8)

Trade name: 39221 39225 WB Flexible Primer Surfacer Black

	(Contd. of pa
•	Substances Control Act):
14807-96-6	Talc
107-98-2	1-methoxy-2-propanol
1333-86-4	Carbon black
108419-32-5	ACETATE ESTER
29911-28-2	Dipropylene glycol n-butyl ether
872-50-4	N-methyl-2-pyrrolidone
108-88-3	toluene
	Xanthan gum
1336-21-6	ammonia solution 26%
7732-18-5	water
Canadian su	bstance listings:
Canadian Do	omestic Substances List (DSL)
37244-96-5	NEPHELINE SYENITE
14807-96-6	Talc
107-98-2	1-methoxy-2-propanol
1333-86-4	Carbon black
108419-32-5	ACETATE ESTER
29911-28-2	Dipropylene glycol n-butyl ether
872-50-4	N-methyl-2-pyrrolidone
108-88-3	toluene
11138-66-2	Xanthan gum
1336-21-6	ammonia solution 26%
7732-18-5	water
	P (D) 1 P (D) (0.100)
	gredient Disclosure list (limit 0.1%) ngredients is listed.

1333-86-4 Carbon black

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard-determining components of labeling:

NEPHELINE SYENITE

Talc

· Hazard statements

H227 Combustible liquid.

H315 Causes skin irritation.

(Contd. on page 9)

Trade name: 39221 39225 WB Flexible Primer Surfacer Black

(Contd. of page 8)

H319 Causes serious eye irritation. H335 May cause respiratory irritation.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 If on skin: Wash with plenty of water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. P304+P340

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P312 Call a poison center/doctor if you feel unwell.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. P332+P313 If eye irritation persists: Get medical advice/attention. P337+P313

P370+P378 *In case of fire: Use for extinction: CO2, powder or water spray.* P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Rita Joiner (rjoiner@semproducts.com)
- · Date of preparation / last revision 03/21/2018 / 9
- · Abbreviations and acronyms:

ICAO: International Civil Aviation Organisation

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

* Data compared to the previous version altered.