Printing date 03/21/2018

Reviewed on 06/20/2017

1 Identification

- · Product identifier
- · Trade name: 77713 Urethane Bumper Stripper
- · Article number: 77713
- · Application of the substance / the mixture Coating
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SEM Products Inc. 1685 Overview Drive

Rock Hill, SC 29730

803 207 8225

· Information department:

cust_care@semproducts.com: SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730: phone 1-800-831-1122, M - TH 7am - 4pm EDT

· Emergency telephone number: CHEMTREC 1-800-424-9300

2 Hazard identification

· Classification of the substance or mixture





GHS02 GHS04 Flame, Gas cylinder

Flammable Aerosols - Category 1

H222 Extremely flammable aerosol.



GHS04 Gas cylinder

Gases Under Pressure - Compressed Gas H280 Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Germ Cell Mutagenicity - Category 1B H340 May cause genetic defects.

Carcinogenicity - Category 1B

H350 May cause cancer.



GHS07

Acute Toxicity (Oral) - Category 4

H302 Harmful if swallowed.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS07



GHS04

· Signal word Danger

(Contd. on page 2)

Trade name: 77713 Urethane Bumper Stripper

(Contd. of page 1)

· Hazard-determining components of labeling:

dichloromethane

Solvent naphtha (petroleum), light aliph.

· Hazard statements

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H340 May cause genetic defects.

H350 May cause cancer.

· Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P312 If swallowed: Call a poison center/doctor if you feel unwell.

P330 Rinse mouth.

P308+P313 IF exposed or concerned: Get medical advice/attention.

Store locked up. P405

P410+P403 Protect from sunlight. Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 0Fire = 4Reactivity = 3

· HMIS-ratings (scale 0 - 4)



Health = *1Fire = 4

REACTIVITY 3 Reactivity = 3

3 Composition/Information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture: consisting of the following components.

Weight percentages

| · Dangerous components: | |
|--|--------------------|
| 75-09-2 dichloromethane | 60-100% w/w |
| 68476-86-8 Petroleum gases, liquefied, sweetened | 10-30% w/w |
| 67-63-0 propan-2-ol | ≥5-<10% w/w |
| 64742-89-8 Solvent naphtha (petroleum), light aliph. | 1-5% w/w |
| | (Contd. on page 3) |

Trade name: 77713 Urethane Bumper Stripper

(Contd. of page 2) 102-71-6 | 2,2',2''-nitrilotrie than ol | $\ge 0.1-\le 1\%$ w/w|

4 First aid measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

· Information about protection against explosions and fires:

Do not spray on a naked flame or any incandescent material.

(Contd. on page 4)

Trade name: 77713 Urethane Bumper Stripper

(Contd. of page 3)

Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurized containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/Personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

75-09-2 dichloromethane

EL Long-term value: 25 ppm

IARC 2A

EV Long-term value: 175 mg/m³, 50 ppm

67-63-0 propan-2-ol

EL Short-term value: 400 ppm Long-term value: 200 ppm EV Short-term value: 400 ppm

EV Short-term value: 400 ppm Long-term value: 200 ppm

102-71-6 2,2',2"-nitrilotriethanol

EL Long-term value: 5 mg/m³

EV Long-term value: 3.1 mg/m³, 0.5 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)



Trade name: 77713 Urethane Bumper Stripper

(Contd. of page 4)

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Safety glasses

· Relative density

· Evaporation rate

· Solubility in / Miscibility with

· Vapor density

Water:



Tightly sealed goggles

| O DI | 1 1 | 7 | | 7 | 7.0 |
|-------------|-----------|-------|-------|-------|--------|
| 9 Physica | Lana | cn | emica | i nro | nernes |
| - I Ivybucu | v correct | - CIU | | υρισ | perves |

| Information on basic physical and c General Information | hemical properties |
|--|--|
| · Appearance: | |
| Form: | Aerosol |
| Color: | According to product specification |
| · Odor: | Characteristic |
| · Odor threshold: | Not determined. |
| · pH-value: | Not determined. |
| · Change in condition | |
| Melting point/Melting range: | Undetermined. |
| Boiling point/Boiling range: | 40 °C |
| · Flash point: | -103 °C |
| · Flammability (solid, gaseous): | Not applicable. |
| · Ignition temperature: | 425 °C |
| · Decomposition temperature: | Not determined. |
| · Auto igniting: | Product is not selfigniting. |
| · Danger of explosion: | In use, may form flammable/explosive vapour-air mixture. |
| · Explosion limits: | |
| Lower: | 1.9 Vol % |
| Upper: | 22 Vol % |
| · Vapor pressure at 20 °C: | 453 hPa |
| · Density at 20 °C: | 1.0008 g/cm³ |

Not determined.

Not determined. Not applicable.

Not miscible or difficult to mix.

(Contd. on page 6)

SEM

Printing date 03/21/2018 Reviewed on 06/20/2017

Trade name: 77713 Urethane Bumper Stripper

| | | (Contd. of page |
|----------------------------------|--|-----------------|
| · Partition coefficient (n-octan | ol/water): Not determined. | |
| · Viscosity: | | |
| Dynamic: | Not determined. | |
| Kinematic: | Not determined. | |
| · Solvent content: | | |
| Organic solvents: | 100.0 % | |
| VOC content: | 28.00 % | |
| | 611.6 g/l / 5.10 lb/gl | |
| Solids content: | 0.0 % | |
| · Other information | No further relevant information available. | |

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

| · LD/LC50 values that are relevant for classification: | | |
|--|------------|-------------------|
| 75-09-2 die | chlorometl | hane |
| Oral | LD50 | 1,600 mg/kg (rat) |
| Inhalative | LC50/4 h | 88 mg/l (rat) |

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

The product can cause inheritable damage.

· Carcinogenic categories

| · IARC (In | ternational Agency for Research on Cancer) | |
|------------|--|---------|
| 75-09-2 | dichloromethane | 2A |
| 67-63-0 | propan-2-ol | 3 |
| 102-71-6 | 2,2',2"-nitrilotriethanol | 3 |
| | (Contd. on | nage 7) |

(Contd. on page 7)

SEM

Printing date 03/21/2018 Reviewed on 06/20/2017

Trade name: 77713 Urethane Bumper Stripper

(Contd. of page 6)

· NTP (National Toxicology Program)

75-09-2 dichloromethane R

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

| ransvori | | |
|----------|--|--|
| | | |
| | | |

| · UN-Number | |
|-------------|--|
|-------------|--|

· DOT, TDG, IMDG, IATA UN1950

· UN proper shipping name

DOT Aerosols, flammable
TDG 1950 Aerosols
IMDG AEROSOLS

· IATA AEROSOLS, flammable

- · Transport hazard class(es)
- $\cdot DOT$



· Class 2.1

(Contd. on page 8)

Safety Data Sheet according to HPR, Schedule 1

Printing date 03/21/2018 Reviewed on 06/20/2017

Trade name: 77713 Urethane Bumper Stripper

| | (Contd. of page |
|--|---|
| Label TDG (Transport dangerous goods): | 2.1 |
| | |
| · Class · Label | 2 5F Gases 2.1 |
| · IMDG, IATA | |
| *** | |
| · Class · Label | 2.1 2.1 |
| Packing group DOT, TDG, IMDG, IATA | Void |
| Environmental hazards: Marine pollutant: | No |
| Special precautions for user EMS Number: Stowage Code | Warning: Gases F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litr Category A. For AEROSOLS with a capacity above 1 litr Category B. For WASTE AEROSOLS: Category C, Clear of livin |
| · Segregation Code | quarters. SG69 For AEROSOLS with a maximum capacity of 1 litr Segregation as for class 9. Stow "separated from" class 1 except f division 1.4. For AEROSOLS with a capacity above 1 litr Segregation as for the appropriate subdivision of class 2. F WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. |
| Transport in bulk according to Annex I MARPOL73/78 and the IBC Code | I of Not applicable. |
| Transport/Additional information: | |
| · DOT · Quantity limitations | On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg |
| · TDG · Excepted quantities (EQ) | Code: E0 Not permitted as Excepted Quantity |
| · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) | 1L Code: E0 Not permitted as Excepted Quantity |

Trade name: 77713 Urethane Bumper Stripper

(Contd. of page 8)

· UN "Model Regulation": UN 1950 AEROSOLS, 2.1

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

75-09-2 dichloromethane

67-63-0 propan-2-ol

· TSCA (Toxic Substances Control Act):

75-09-2 dichloromethane

67-63-0 propan-2-ol

64742-89-8 Solvent naphtha (petroleum), light aliph.

102-71-6 2,2',2"-nitrilotriethanol

- · Canadian substance listings:
- · Canadian Domestic Substances List (DSL)

All ingredients are listed.

· Canadian Ingredient Disclosure list (limit 0.1%)

75-09-2 dichloromethane

· Canadian Ingredient Disclosure list (limit 1%)

67-63-0 propan-2-ol

102-71-6 2,2',2"-nitrilotriethanol

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms









GHS02

GHS04

GHS07

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

dichloromethane

Solvent naphtha (petroleum), light aliph.

· Hazard statements

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H340 May cause genetic defects.

H350 May cause cancer.

· Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

(Contd. on page 10)

Trade name: 77713 Urethane Bumper Stripper

(Contd. of page 9)

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P312 If swallowed: Call a poison center/doctor if you feel unwell.

P330 Rinse mouth.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- · National regulations:
- · Additional classification according to Decree on Hazardous Materials:

Carcinogenic hazardous material group III (dangerous).

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Rita Joiner (rjoiner@semproducts.com)
- · Date of preparation / last revision 03/21/2018 / 10
- · Abbreviations and acronyms:

ICAO: International Civil Aviation Organisation

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

 $HMIS: \ Hazardous\ Materials\ Identification\ System\ (USA)$

 $VOC:\ Volatile\ Organic\ Compounds\ (USA,\ EU)$

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

* * Data compared to the previous version altered.

CA