



## Safety Data Sheet

Copyright, 2019, 3M Canada Company

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

|                        |            |                         |            |
|------------------------|------------|-------------------------|------------|
| <b>Document group:</b> | 26-8172-4  | <b>Version number:</b>  | 5.00       |
| <b>Issue Date:</b>     | 2019/07/17 | <b>Supersedes Date:</b> | 2019/04/29 |

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Platinum Plus Filler PN 05863

#### Product Identification Numbers

LB-K100-1392-9

#### 1.2. Recommended use and restrictions on use

##### Intended Use

Automotive

##### Specific Use

Body filler, packaged as a cartridge-based two component body repair material for use in the 3M Dynamic Mixing System.

##### Restrictions on use

Not applicable

#### 1.3. Supplier's details

|                   |                                                                        |
|-------------------|------------------------------------------------------------------------|
| <b>Company:</b>   | 3M Canada Company                                                      |
| <b>Division:</b>  | Automotive Aftermarket                                                 |
| <b>Address:</b>   | 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1 |
| <b>Telephone:</b> | (800) 364-3577                                                         |
| <b>Website:</b>   | www.3M.ca                                                              |

#### 1.4. Emergency telephone number

Medical Emergency Telephone: (519) 451-2500, Ext. 2222; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

Flammable Liquid: Category 3.

Serious Eye Damage/Irritation: Category 2A.

Skin Corrosion/Irritation: Category 2.

Reproductive Toxicity: Category 1B.

Carcinogenicity: Category 1A.

Specific Target Organ Toxicity (single exposure): Category 1.  
Specific Target Organ Toxicity (single exposure): Category 3.  
Specific Target Organ Toxicity (repeated exposure): Category 1.

## 2.2. Label elements

### Signal word

Danger

### Symbols

Flame | Exclamation mark | Health Hazard |

### Pictograms



### Hazard statements

Flammable liquid and vapour.

Causes serious eye irritation. Causes skin irritation. May cause drowsiness or dizziness. May damage fertility or the unborn child. May cause cancer.

Causes damage to organs: liver | sensory organs |

Causes damage to organs through prolonged or repeated exposure: respiratory system | sensory organs |  
liver |

### Precautionary statements

#### General:

Keep out of reach of children.

#### Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Use non-sparking tools. Take action to prevent static discharges. Use explosion-proof electrical/ventilating/lighting equipment. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash exposed skin thoroughly after handling.

#### Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF exposed or concerned: Get medical advice/attention. In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

#### Storage:

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

#### Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

## 2.3. Other hazards

None known.

21% of the mixture consists of ingredients of unknown acute oral toxicity.  
 21% of the mixture consists of ingredients of unknown acute dermal toxicity.  
 21% of the mixture consists of ingredients of unknown acute inhalation toxicity.

### SECTION 3: Composition/information on ingredients

This material is a mixture.

| Ingredient                  | C.A.S. No.   | % by Wt                | Common Name                                                                                   |
|-----------------------------|--------------|------------------------|-----------------------------------------------------------------------------------------------|
| Polyester Polymer           | Trade Secret | 10 - 30                | Not Applicable                                                                                |
| Chlorite (Mineral)          | 1318-59-8    | < 3                    | Chlorite-group minerals                                                                       |
| Polyamide                   | Trade Secret | 0.5 - 2                | Not Applicable                                                                                |
| Paraffin Wax                | 8002-74-2    | 0.1 - 1                | Paraffin waxes and Hydrocarbon waxes                                                          |
| Poly(oxypropylene)diamine   | 9046-10-0    | 0.1 - 1 Trade Secret * | Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)-.omega.-(2-aminomethylethoxy)- |
| Styrene Monomer             | 100-42-5     | 10 - 30 Trade Secret * | Benzene, ethenyl-                                                                             |
| Proprietary Polyester Resin | Trade Secret | 10 - 30                | Not Applicable                                                                                |
| Talc                        | 14807-96-6   | 7 - 30 Trade Secret *  | Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )                       |
| Inert Filler                | Trade Secret | 5 - 10                 | Not Applicable                                                                                |
| Magnesium Carbonate         | 546-93-0     | 1 - 5                  | Carbonic acid, magnesium salt (1:1)                                                           |
| Limestone                   | 1317-65-3    | 1 - 5                  | Limestonests primarily of calcium carbonate.                                                  |
| Titanium Dioxide            | 13463-67-7   | 1 - 5 Trade Secret *   | Titanium oxide (TiO <sub>2</sub> )                                                            |
| Zinc Phosphate              | 7779-90-0    | 0.5 - 2.5              | Phosphoric acid, zinc salt (2:3)                                                              |
| Quartz Silica               | 14808-60-7   | 0.01 - 0.24            | Quartz (SiO <sub>2</sub> )                                                                    |

\*The actual concentration of this ingredient has been withheld as a trade secret.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

##### Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

##### Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

##### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

#### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### Hazardous Decomposition or By-Products

| <u>Substance</u> | <u>Condition</u>  |
|------------------|-------------------|
| Hydrocarbons     | During Combustion |
| Carbon monoxide  | During Combustion |
| Carbon dioxide   | During Combustion |

### 5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools.

Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam. An appropriate aqueous film forming foam (AFFF) is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (gloves, respirators, etc.) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

**7.2. Conditions for safe storage including any incompatibilities**

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| <b>Ingredient</b> | <b>C.A.S. No.</b> | <b>Agency</b>           | <b>Limit type</b>                                                                                          | <b>Additional Comments</b> |
|-------------------|-------------------|-------------------------|------------------------------------------------------------------------------------------------------------|----------------------------|
| Styrene Monomer   | 100-42-5          | ACGIH                   | TWA:20 ppm;STEL:40 ppm                                                                                     |                            |
| Titanium Dioxide  | 13463-67-7        | ACGIH                   | TWA:10 mg/m3                                                                                               |                            |
| Talc              | 14807-96-6        | ACGIH                   | TWA(respirable fraction):2 mg/m3                                                                           |                            |
| Quartz Silica     | 14808-60-7        | ACGIH                   | TWA(respirable fraction):0.025 mg/m3                                                                       |                            |
| Paraffin Wax      | 8002-74-2         | ACGIH                   | TWA(as fume):2 mg/m3                                                                                       |                            |
| Inert Filler      | Trade Secret      | Manufacturer determined | TWA(as non-fibrous, inhalable fraction)(8 hours):10 mg/m3;TWA(as non-fibrous, respirable)(8 hours):3 mg/m3 |                            |
| Inert Filler      | Trade Secret      | ACGIH                   | TWA(as fiber):0.2 fiber/cc;TWA(as fiber):1 fiber/cc;TWA(inhalable fraction):5 mg/m3                        |                            |

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

**8.2. Exposure controls****8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

**8.2.2. Personal protective equipment (PPE)****Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

**Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

## Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|                                         |                                                         |
|-----------------------------------------|---------------------------------------------------------|
| Physical state                          | Liquid                                                  |
| Specific Physical Form:                 | Paste                                                   |
| Appearance/Odour                        | Pungent Styrene odour Gold paste                        |
| Odour threshold                         | No Data Available                                       |
| pH                                      | No Data Available                                       |
| Melting point/Freezing point            | No Data Available                                       |
| Boiling point                           | 145 °C                                                  |
| Flash Point                             | 31.1 °C [Test Method:Closed Cup]                        |
| Evaporation rate                        | 0.1 - 0.5 [Ref Std:BUOAC=1]                             |
| Flammability (solid, gas)               | Not Applicable                                          |
| Flammable Limits(LEL)                   | 0.9 % [Details:based on styrene]                        |
| Flammable Limits(UEL)                   | 6.8 % [Details:based on styrene]                        |
| Vapour Pressure                         | 599.9 Pa                                                |
| Vapour Density                          | 3.6 [Ref Std:AIR=1]                                     |
| Density                                 | 0.984 g/ml                                              |
| Relative density                        | 0.984 [Ref Std:WATER=1]                                 |
| Water solubility                        | Negligible                                              |
| Solubility- non-water                   | No Data Available                                       |
| Partition coefficient: n-octanol/ water | No Data Available                                       |
| Autoignition temperature                | No Data Available                                       |
| Decomposition temperature               | No Data Available                                       |
| Viscosity                               | 144,000 mPa-s - 168,000 mPa-s                           |
| Volatile Organic Compounds              | 23.7 % weight [Test Method:calculated per CARB title 2] |
| Volatile Organic Compounds              | 233 g/l [Test Method:calculated SCAQMD rule 443.1]      |
| Percent volatile                        | 24.1 % weight                                           |
| Percent volatile                        | 26.2 % volume                                           |
| VOC Less H2O & Exempt Solvents          | 234 g/l [Test Method:calculated SCAQMD rule 443.1]      |
| Solids Content                          | 38.2 % weight                                           |

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable. Stable under normal conditions. May become unstable at elevated temperatures and/or pressure.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Sparks and/or flames  
Heat

#### 10.5. Incompatible materials

Strong acids  
Strong oxidizing agents  
Alkali and alkaline earth metals  
Strong bases

#### 10.6. Hazardous decomposition products

| <u>Substance</u> | <u>Condition</u> |
|------------------|------------------|
| None known.      |                  |

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

##### Inhalation:

May be harmful if inhaled. Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

##### Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

##### Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

##### Ingestion:

May be harmful if swallowed. Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. May cause additional health effects (see below).

#### Additional Health Effects:

##### Single exposure may cause target organ effects:

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears. Liver Effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice. Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

##### Prolonged or repeated exposure may cause target organ effects:

Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum,

**3M™ Platinum Plus Filler PN 05863**

and changes in lung function tests. Ocular Effects: Signs/symptoms may include blurred or significantly impaired vision. Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears. Liver Effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice.

**Reproductive/Developmental Toxicity:**

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

**Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

| <b>Ingredient</b>       | <b>CAS No.</b> | <b>Class Description</b>       | <b>Regulation</b>                           |
|-------------------------|----------------|--------------------------------|---------------------------------------------|
| SILICA, CRYSTAL AIRRESP | 14808-60-7     | Known human carcinogen         | National Toxicology Program Carcinogens     |
| Inert Filler            | Trade Secret   | Grp. 2B: Possible human carc.  | International Agency for Research on Cancer |
| Inert Filler            | Trade Secret   | Grp. 2B: Possible human carc.  | International Agency for Research on Cancer |
| Inert Filler            | Trade Secret   | Anticipated human carcinogen   | National Toxicology Program Carcinogens     |
| Inert Filler            | Trade Secret   | Anticipated human carcinogen   | National Toxicology Program Carcinogens     |
| Quartz Silica           | 14808-60-7     | Grp. 1: Carcinogenic to humans | International Agency for Research on Cancer |
| Styrene Monomer         | 100-42-5       | Grp. 2A: Probable human carc.  | International Agency for Research on Cancer |
| Styrene Monomer         | 100-42-5       | Anticipated human carcinogen   | National Toxicology Program Carcinogens     |
| Titanium Dioxide        | 13463-67-7     | Grp. 2B: Possible human carc.  | International Agency for Research on Cancer |

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

| <b>Name</b>         | <b>Route</b>                   | <b>Species</b>         | <b>Value</b>                                         |
|---------------------|--------------------------------|------------------------|------------------------------------------------------|
| Overall product     | Dermal                         |                        | No data available; calculated ATE >5,000 mg/kg       |
| Overall product     | Inhalation-Vapor(4 hr)         |                        | No data available; calculated ATE20 - 50 mg/l        |
| Overall product     | Ingestion                      |                        | No data available; calculated ATE2,000 - 5,000 mg/kg |
| Styrene Monomer     | Dermal                         | Rat                    | LD50 > 2,000 mg/kg                                   |
| Styrene Monomer     | Inhalation-Vapor (4 hours)     | Rat                    | LC50 8.3 mg/l                                        |
| Styrene Monomer     | Ingestion                      | Rat                    | LD50 5,000 mg/kg                                     |
| Talc                | Dermal                         |                        | LD50 estimated to be > 5,000 mg/kg                   |
| Talc                | Ingestion                      |                        | LD50 estimated to be > 5,000 mg/kg                   |
| Polyester Polymer   | Dermal                         |                        | LD50 estimated to be > 5,000 mg/kg                   |
| Polyester Polymer   | Ingestion                      |                        | LD50 estimated to be 2,000 - 5,000 mg/kg             |
| Inert Filler        | Dermal                         |                        | LD50 estimated to be > 5,000 mg/kg                   |
| Inert Filler        | Ingestion                      |                        | LD50 estimated to be 2,000 - 5,000 mg/kg             |
| Limestone           | Dermal                         | Rat                    | LD50 > 2,000 mg/kg                                   |
| Limestone           | Inhalation-Dust/Mist (4 hours) | Rat                    | LC50 3 mg/l                                          |
| Limestone           | Ingestion                      | Rat                    | LD50 6,450 mg/kg                                     |
| Magnesium Carbonate | Dermal                         | Professional judgement | LD50 estimated to be 2,000 - 5,000 mg/kg             |
| Magnesium Carbonate | Ingestion                      | Rat                    | LD50 > 2,000 mg/kg                                   |
| Titanium Dioxide    | Dermal                         | Rabbit                 | LD50 > 10,000 mg/kg                                  |
| Titanium Dioxide    | Inhalation-Dust/Mist (4 hours) | Rat                    | LC50 > 6.82 mg/l                                     |
| Titanium Dioxide    | Ingestion                      | Rat                    | LD50 > 10,000 mg/kg                                  |
| Zinc Phosphate      | Dermal                         |                        | LD50 estimated to be > 5,000 mg/kg                   |
| Zinc Phosphate      | Ingestion                      | Rat                    | LD50 > 5,000 mg/kg                                   |
| Chlorite (Mineral)  | Dermal                         |                        | LD50 estimated to be > 5,000 mg/kg                   |



**3M™ Platinum Plus Filler PN 05863**

|                           |           |        |                                    |
|---------------------------|-----------|--------|------------------------------------|
| Chlorite (Mineral)        | Ingestion |        | LD50 estimated to be > 5,000 mg/kg |
| Poly(oxypropylene)diamine | Dermal    | Rabbit | LD50 2,090 mg/kg                   |
| Paraffin Wax              | Dermal    | Rat    | LD50 > 5,000 mg/kg                 |
| Paraffin Wax              | Ingestion | Rat    | LD50 > 5,000 mg/kg                 |
| Poly(oxypropylene)diamine | Ingestion | Rat    | LD50 475 mg/kg                     |
| Quartz Silica             | Dermal    |        | LD50 estimated to be > 5,000 mg/kg |
| Quartz Silica             | Ingestion |        | LD50 estimated to be > 5,000 mg/kg |

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

| Name                      | Species                 | Value                     |
|---------------------------|-------------------------|---------------------------|
| Styrene Monomer           | official classification | Mild irritant             |
| Talc                      | Rabbit                  | No significant irritation |
| Inert Filler              | Professional judgement  | No significant irritation |
| Limestone                 | Rabbit                  | No significant irritation |
| Magnesium Carbonate       | In vitro data           | No significant irritation |
| Titanium Dioxide          | Rabbit                  | No significant irritation |
| Chlorite (Mineral)        | Professional judgement  | No significant irritation |
| Paraffin Wax              | Rabbit                  | No significant irritation |
| Poly(oxypropylene)diamine | Rabbit                  | Corrosive                 |
| Quartz Silica             | Professional judgement  | No significant irritation |

**Serious Eye Damage/Irritation**

| Name                      | Species                 | Value                     |
|---------------------------|-------------------------|---------------------------|
| Styrene Monomer           | official classification | Moderate irritant         |
| Talc                      | Rabbit                  | No significant irritation |
| Inert Filler              | Professional judgement  | No significant irritation |
| Limestone                 | Rabbit                  | No significant irritation |
| Magnesium Carbonate       | Rabbit                  | Mild irritant             |
| Titanium Dioxide          | Rabbit                  | No significant irritation |
| Chlorite (Mineral)        | Professional judgement  | No significant irritation |
| Paraffin Wax              | Rabbit                  | No significant irritation |
| Poly(oxypropylene)diamine | Rabbit                  | Corrosive                 |

**Skin Sensitization**

| Name             | Species          | Value          |
|------------------|------------------|----------------|
| Styrene Monomer  | Guinea pig       | Not classified |
| Titanium Dioxide | Human and animal | Not classified |
| Paraffin Wax     | Guinea           | Not classified |

|  |     |  |
|--|-----|--|
|  | pig |  |
|--|-----|--|

**Respiratory Sensitization**

| Name | Species | Value          |
|------|---------|----------------|
| Talc | Human   | Not classified |

**Germ Cell Mutagenicity**

| Name                      | Route    | Value                                                                        |
|---------------------------|----------|------------------------------------------------------------------------------|
| Styrene Monomer           | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Styrene Monomer           | In vivo  | Some positive data exist, but the data are not sufficient for classification |
| Talc                      | In Vitro | Not mutagenic                                                                |
| Talc                      | In vivo  | Not mutagenic                                                                |
| Inert Filler              | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Titanium Dioxide          | In Vitro | Not mutagenic                                                                |
| Titanium Dioxide          | In vivo  | Not mutagenic                                                                |
| Paraffin Wax              | In Vitro | Not mutagenic                                                                |
| Poly(oxypropylene)diamine | In Vitro | Not mutagenic                                                                |
| Poly(oxypropylene)diamine | In vivo  | Not mutagenic                                                                |
| Quartz Silica             | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Quartz Silica             | In vivo  | Some positive data exist, but the data are not sufficient for classification |

**Carcinogenicity**

| Name             | Route      | Species                 | Value                                                                        |
|------------------|------------|-------------------------|------------------------------------------------------------------------------|
| Styrene Monomer  | Ingestion  | Mouse                   | Carcinogenic                                                                 |
| Styrene Monomer  | Inhalation | Human and animal        | Carcinogenic                                                                 |
| Talc             | Inhalation | Rat                     | Some positive data exist, but the data are not sufficient for classification |
| Inert Filler     | Inhalation | Multiple animal species | Some positive data exist, but the data are not sufficient for classification |
| Titanium Dioxide | Ingestion  | Multiple animal species | Not carcinogenic                                                             |
| Titanium Dioxide | Inhalation | Rat                     | Carcinogenic                                                                 |
| Paraffin Wax     | Ingestion  | Rat                     | Not carcinogenic                                                             |
| Quartz Silica    | Inhalation | Human and animal        | Carcinogenic                                                                 |

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

| Name            | Route      | Value                                  | Species  | Test result         | Exposure Duration |
|-----------------|------------|----------------------------------------|----------|---------------------|-------------------|
| Styrene Monomer | Ingestion  | Not classified for female reproduction | Rat      | NOAEL 21 mg/kg/day  | 3 generation      |
| Styrene Monomer | Inhalation | Not classified for female reproduction | Rat      | NOAEL 2.1 mg/l      | 2 generation      |
| Styrene Monomer | Inhalation | Not classified for male reproduction   | Rat      | NOAEL 2.1 mg/l      | 2 generation      |
| Styrene Monomer | Ingestion  | Not classified for male reproduction   | Rat      | NOAEL 400 mg/kg/day | 60 days           |
| Styrene Monomer | Ingestion  | Not classified for development         | Rat      | NOAEL 400 mg/kg/day | during gestation  |
| Styrene Monomer | Inhalation | Not classified for development         | Multiple | NOAEL 2.1           | during            |

**3M™ Platinum Plus Filler PN 05863**

|           |           |                                |                |                     |                              |
|-----------|-----------|--------------------------------|----------------|---------------------|------------------------------|
|           |           |                                | animal species | mg/l                | gestation                    |
| Talc      | Ingestion | Not classified for development | Rat            | NOAEL 1,600 mg/kg   | during organogenesis         |
| Limestone | Ingestion | Not classified for development | Rat            | NOAEL 625 mg/kg/day | premating & during gestation |

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

| Name                      | Route      | Target Organ(s)                   | Value                                                                        | Species                 | Test result         | Exposure Duration     |
|---------------------------|------------|-----------------------------------|------------------------------------------------------------------------------|-------------------------|---------------------|-----------------------|
| Styrene Monomer           | Inhalation | auditory system                   | Causes damage to organs                                                      | Multiple animal species | LOAEL 4.3 mg/l      | not available         |
| Styrene Monomer           | Inhalation | liver                             | Causes damage to organs                                                      | Mouse                   | LOAEL 2.1 mg/l      | not available         |
| Styrene Monomer           | Inhalation | central nervous system depression | May cause drowsiness or dizziness                                            | Human                   | NOAEL Not available | occupational exposure |
| Styrene Monomer           | Inhalation | respiratory irritation            | Some positive data exist, but the data are not sufficient for classification | Human and animal        | NOAEL Not available |                       |
| Styrene Monomer           | Inhalation | endocrine system                  | Not classified                                                               | Rat                     | NOAEL Not available | not available         |
| Styrene Monomer           | Inhalation | kidney and/or bladder             | Not classified                                                               | Multiple animal species | NOAEL 2.1 mg/l      | not available         |
| Limestone                 | Inhalation | respiratory system                | Not classified                                                               | Rat                     | NOAEL 0.812 mg/l    | 90 minutes            |
| Poly(oxypropylene)diamine | Inhalation | respiratory irritation            | May cause respiratory irritation                                             | similar health hazards  | NOAEL Not available |                       |

**Specific Target Organ Toxicity - repeated exposure**

| Name            | Route      | Target Organ(s)                                                                                    | Value                                                                        | Species                 | Test result         | Exposure Duration     |
|-----------------|------------|----------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------|-------------------------|---------------------|-----------------------|
| Styrene Monomer | Inhalation | eyes                                                                                               | Causes damage to organs through prolonged or repeated exposure               | Human                   | NOAEL Not available | occupational exposure |
| Styrene Monomer | Inhalation | auditory system                                                                                    | May cause damage to organs though prolonged or repeated exposure             | Multiple animal species | NOAEL 1.3 mg/l      | not available         |
| Styrene Monomer | Inhalation | liver                                                                                              | May cause damage to organs though prolonged or repeated exposure             | Mouse                   | LOAEL 0.85 mg/l     | 13 weeks              |
| Styrene Monomer | Inhalation | nervous system                                                                                     | Some positive data exist, but the data are not sufficient for classification | Multiple animal species | LOAEL 1.1 mg/l      | not available         |
| Styrene Monomer | Inhalation | hematopoietic system                                                                               | Not classified                                                               | Rat                     | NOAEL 0.85 mg/l     | 7 days                |
| Styrene Monomer | Inhalation | endocrine system                                                                                   | Not classified                                                               | Rat                     | NOAEL 0.6 mg/l      | 10 days               |
| Styrene Monomer | Inhalation | respiratory system                                                                                 | Not classified                                                               | Multiple animal species | LOAEL 0.09 mg/l     | not available         |
| Styrene Monomer | Inhalation | heart   gastrointestinal tract   bone, teeth, nails, and/or hair   muscles   kidney and/or bladder | Not classified                                                               | Multiple animal species | NOAEL 4.3 mg/l      | 2 years               |
| Styrene Monomer | Ingestion  | nervous system                                                                                     | Some positive data exist, but the data are not sufficient for classification | Rat                     | LOAEL 500 mg/kg/day | 8 weeks               |
| Styrene Monomer | Ingestion  | immune system                                                                                      | Some positive data exist, but the                                            | Multiple                | NOAEL Not           | not available         |

**3M™ Platinum Plus Filler PN 05863**

|                  |            |                                                                                                                                                                                                           |                                                                              |                |                       |                       |
|------------------|------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------|----------------|-----------------------|-----------------------|
|                  |            |                                                                                                                                                                                                           | data are not sufficient for classification                                   | animal species | available             |                       |
| Styrene Monomer  | Ingestion  | liver   kidney and/or bladder                                                                                                                                                                             | Not classified                                                               | Rat            | NOAEL 677 mg/kg/day   | 6 months              |
| Styrene Monomer  | Ingestion  | hematopoietic system                                                                                                                                                                                      | Not classified                                                               | Dog            | NOAEL 600 mg/kg/day   | 470 days              |
| Styrene Monomer  | Ingestion  | heart   respiratory system                                                                                                                                                                                | Not classified                                                               | Rat            | NOAEL 35 mg/kg/day    | 105 weeks             |
| Talc             | Inhalation | pneumoconiosis                                                                                                                                                                                            | Causes damage to organs through prolonged or repeated exposure               | Human          | NOAEL Not available   | occupational exposure |
| Talc             | Inhalation | pulmonary fibrosis   respiratory system                                                                                                                                                                   | Not classified                                                               | Rat            | NOAEL 18 mg/m3        | 113 weeks             |
| Inert Filler     | Inhalation | respiratory system                                                                                                                                                                                        | Not classified                                                               | Human          | NOAEL not available   | occupational exposure |
| Limestone        | Inhalation | respiratory system                                                                                                                                                                                        | Not classified                                                               | Human          | NOAEL Not available   | occupational exposure |
| Titanium Dioxide | Inhalation | respiratory system                                                                                                                                                                                        | Some positive data exist, but the data are not sufficient for classification | Rat            | LOAEL 0.01 mg/l       | 2 years               |
| Titanium Dioxide | Inhalation | pulmonary fibrosis                                                                                                                                                                                        | Not classified                                                               | Human          | NOAEL Not available   | occupational exposure |
| Paraffin Wax     | Ingestion  | heart                                                                                                                                                                                                     | Some positive data exist, but the data are not sufficient for classification | Rat            | NOAEL 15 mg/kg/day    | 90 days               |
| Paraffin Wax     | Ingestion  | hematopoietic system   liver   immune system   skin   endocrine system   bone, teeth, nails, and/or hair   muscles   nervous system   eyes   kidney and/or bladder   respiratory system   vascular system | Not classified                                                               | Rat            | NOAEL 1,500 mg/kg/day | 90 days               |
| Quartz Silica    | Inhalation | silicosis                                                                                                                                                                                                 | Causes damage to organs through prolonged or repeated exposure               | Human          | NOAEL Not available   | occupational exposure |

**Aspiration Hazard**

| Name                      | Value                                                                        |
|---------------------------|------------------------------------------------------------------------------|
| Poly(oxypropylene)diamine | Some positive data exist, but the data are not sufficient for classification |

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information**

No data available.

**SECTION 13: Disposal considerations**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

**SECTION 14: Transport Information**

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Global inventory status**

Contact manufacturer for more information The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

**SECTION 16: Other information**

**National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.**

**Health: 2 Flammability: 3 Instability: 1 Special Hazards: None**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

|                        |            |                         |            |
|------------------------|------------|-------------------------|------------|
| <b>Document group:</b> | 26-8172-4  | <b>Version number:</b>  | 5.00       |
| <b>Issue Date:</b>     | 2019/07/17 | <b>Supersedes Date:</b> | 2019/04/29 |

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

**3M Canada SDSs are available at [www.3M.ca](http://www.3M.ca)**