

# Section 1: Identification of the Substance/Mixture and of the Company Undertaking

Product identifier used on the label:

Product Name: Speed Grip ADHESION PROMOTER "BRUSH TOP"

Other means of identification:

Product Codes: 63642504624

Recommended use of the chemical and restrictions on use:

Product Uses: Primer

Chemical manufacturer address and telephone number:

Manufacturer Name: Saint-Gobain Abrasives, Inc.

Manufacturer Address 1: 1 New Bond Street

Manufacturer City: Worcester

Manufacturer State: MA

Manufacturer Zip Code: 01615

Manufacturer Country: USA

Manufacturer Web: www.Nortonabrasives.com

Business Phone: 508-795-5000

Distributor: Saint-Gobain Canada, Inc.

Distributor Address 1: 28 Albert St, W.

Distributor City: Plattsville

Distributor State: ON

Distributor ZipCode: NOJ 1S0
Distributor Country: Canada

Distributor Web: www.Nortonabrasives.com

Distributor Phone: 519-684-7441

**Emergency phone number:** 

Emergency Phone: 508-795-5000

Creation Date: 2019-01-09

Revision Date: 2019-01-10 13:48:14

Notes from Section 1: CHEMTREC:

For emergencies in the US, call CHEMTREC: 800-424-9300 For emergencies in Canada, call CHEMTREC: 800-424-9300

# Section 2: Hazards Identification

# Classification of the chemical in accordance with CFR 1910.1200(d)(f):









Signal Words: Danger

**Product:** 

GHS Class: GHS CLASSIFICATION:

Flammable liquids Category 2

Acute toxicity Inhalation - Dust and Mist Category 3 Acute toxicity Inhalation - Vapours Category 3

Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2A

Carcinogenicity Category 2 Reproductive toxicity Category 2

Specific target organ systemic toxicity (single exposure) Category 3

Specific target organ systemic toxicity (single exposure) Category 2 circulatory

system, Hematopoietic System

Specific target organ systemic toxicity (repeated exposure) Category 1 Nervous

system, Body

Aspiration hazard Category 1

Hazardous to the aquatic environment - acute hazard Category 2 Hazardous to the aquatic environment - chronic hazard Category 2

Hazard Statements: H225 - Highly flammable liquid and vapour.

H331 - Toxic if inhaled.

H315 - Causes skin irritation.

H319 - Causes serious eye irritation. H351 - Suspected of causing cancer .

 $\ensuremath{\mathsf{H361}}$  - Suspected of damaging fertility or the unborn child .

H336 - May cause drowsiness or dizziness. H335 - May cause respiratory irritation.

H371 - May cause damage to organs.(circulatory system, Hematopoietic System)

H372 - Causes damage to organs through prolonged or repeated exposure.

(Nervous system, Body)

H304 - May be fatal if swallowed and enters airways.

H401 - Toxic to aquatic life.

H411 - Toxic to aquatic life with long lasting effects.

#### **Precautionary Statements:**

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P281 Use personal protective equipment as required.
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P264 Wash thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P273 Avoid release to the environment.
- P370+P378 In case of fire: refer to section 5 of SDS for extinguishing media.
- P311 Call a POISON CENTER or doctor/physician.
- P320x Specific treatment (see supplemental first aid instructions on this label).
- P304+P340 IF INHALED: Remove to fresh air and keep at rest in a position

comfortable for breathing.

P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all

contaminated clothing. Rinse skin with water/shower.

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P331 - Do NOT induce vomiting.

P391 - Collect spillage.

P403+P235 - Store in a well-ventilated place. Keep cool.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with waste/disposal laws and regulations of your country or particular locality.

### Hazards not otherwise classified that have been identified during the classification process:

# Section 3: Composition/Information on Ingredients

### Mixtures:

Ingredient Name	CAS Number	Ingredient Percent	EC Number	Comments
Cyclohexane	110-82-7	Range:65- 70%		
Methyl-n-propyl ketone	107-87-9	Range:25- 30%		
Methyl isobutyl ketone	108-10-1	Range:1- 5%		

#### **Product:**

Comments: Any "PROPRIETARY" component(s) in the above table is considered trade secret,

thus the specific chemical and its exact concentration is beingwithheld.

### Section 4: First Aid Measures

### Description of necessary measures:

Eye Contact: Flush eyes immediately with large amount of water for at least 15 minutes holding

eyelids open while flushing. Get prompt medical attention.

Skin Contact: Flush contaminated skin with large amounts of water while removing contaminated

clothing. Wash affected skin areas with soap and water. Get medical attention if

symptoms occur.

Inhalation: Move person to fresh air. Restore and support continued breathing. If breathing is

difficult, give oxygen. Get immediate medical attention.

Ingestion: If swallowed, do not induce vomiting. Call a physician or poison control center

immediately for further instructions. Never give anything by mouth if victim is

rapidly losing consciousness, unconscious or convulsing.

Most important symptoms/effects, acute and delayed:

Indication of immediate medical attention and special treatment needed

# Section 5: Firefighting Measures

#### Suitable and unsuitable extinguishing media

Extinguishing Media: Carbon Dioxide, Dry Chemical, Foam, Water Fog

#### Specific hazards arising from the chemical

# Special protective equipment and precautions for fire-fighters

Fire Fighting Instructions: PRECAUTIONS FOR FIRE-FIGHTERS: Wear full firefighting protective clothing,

including self-contained breathing apparatus (SCBA). Water spray may be

ineffective. If water is used, fog nozzles are preferable.

Protective Equipment: Wear full firefighting protective clothing, including self-contained breathing

apparatus (SCBA). Water spray may be ineffective. If water is used, fog nozzles are

preferable.

Notes from Section 5: SPECIFIC HAZARDS POSSIBLY ARISING FROM THE CHEMICAL: Extremely flammable

liquid and vapor. Keep containers tightly closed. Isolate from heat, electrical equipment, sparks, open flame, and other sources of ignition. Closed containers may rupture when exposed to extreme heat. Use water spray to keep fire exposed containers cool. During a fire, irritating and/or toxic gases and particulate may be

generated by thermal decomposition or combustion.

## Section 6: Accidental Release Measures

# Personal precautions, protective equipment and emergency procedures

Personnel Precautions: PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY

PROCEDURES: Remove all sources of ignition (flame, hot surfaces, and electrical, static or frictional sparks). Avoid breathing vapors. Use self-contained breathing

equipment. Avoid contact.

# Methods and materials for containment and cleaning up

Methods for Containment: Keep non-essential personnel away from spill area. Notify appropriate authorities

if necessary. Contain and remove with inert absorbent material and non-sparking

tools. Avoid contact. Before attempting cleanup, refer to hazard caution

information in other sections of the SDS form.

Methods for Cleanup: Keep non-essential personnel away from spill area. Notify appropriate authorities

if necessary. Contain and remove with inert absorbent material and non-sparking

tools. Avoid contact. Before attempting cleanup, refer to hazard caution

information in other sections of the SDS form.

#### **Environmental precautions**

Environmental Precautions: Do not contaminate bodies of water, waterways, or ditches, with chemical or used

container.

### Section 7: Handling and Storage

# Precautions for safe handling

Handling:

Keep closure tight and container upright to prevent leakage. Ground and bond containers when transferring material. Avoid skin and eye contact. Wash thoroughly after handling. Avoid breathing of vapor or spray mists. Do not handle until all safety precautions have been read and understood. Empty containers should not be re-used. Use with adequate ventilation. Because empty containers may retain product residue and flammable vapors, keep away from heat, sparks and flame; do not cut, puncture or weld on or near the empty container. Do not smoke where this product is used or stored.

Hygiene Practices:

Wash hands before eating, smoking, or using toilet facility. Do not smoke in any chemical handling or storage area. Food or beverages should not be consumed anywhere this product is handled or stored. Wash thoroughly after handling.

#### Conditions for safe storage, including any incompatibilities

Storage:

Do not store or use near heat, sparks, or open flame.Refer to OSHA 29CFR Part 1910.106 "Flammable and Combustible Liquids" for specific storage requirements.Store only in well-ventilated areas.Do not puncture, drag, or slide container.Keep container closed when not in use. INCOMPATIBILITY: Strong acids, bases, and strong oxidizers.

# Section 8: Exposure Controls/Personal Protection

## **Exposure Guidelines**

#### **Exposure Guidelines - Ingredient Based:**

#### Cyclohexane:

ACGIH - TLV - TWA: 100 ppm

ACGIH - TLV - STEL: N.E

USA - OSHA - PEL - TWA: 1,050 mg/m3 300 ppm

USA - OSHA - PEL - Ceiling: N.E.

Skin: N.A.

### Methyl-n-propyl ketone:

ACGIH - TLV - TWA: 200 ppm

ACGIH - TLV - STEL: 250 ppm

USA - OSHA - PEL - TWA: 700 mg/m3 200 ppm

USA - OSHA - PEL - Ceiling: N.E.

Skin: N.A.

## Methyl isobutyl ketone:

ACGIH - TLV - TWA: 50 ppm

ACGIH - TLV - STEL: 75 ppm

USA - OSHA - PEL - TWA: 410 mg/m3 100 ppm

USA - OSHA - PEL - Ceiling: N.E.

Skin: N.A.

#### Appropriate engineering controls

Engineering Controls: Sufficient ventilation in pattern and volume should be provided in order to maintain

air contaminant levels below recommended exposure limits. Caution: Solvent vapors are heavier than air and collect in lower levels of the work area. Sufficient ventilation (using explosion-proof equipment) should be provided to prevent

flammable vapor/air mixtures from accumulating.

Individual protection measures

Eye Protection: Use safety eyewear including safety glasses with side shields and chemical

goggles where splashing may occur.

Skin Protection: Use neoprene, nitrile, or rubber gloves to prevent skin contact.

Respiratory Protection: Use a NIOSH approved chemical/mechanical filter respirator designed to remove a

combination of particulates and organic vapor if occupational limits are exceeded. For emergency situations, confined space use, or other conditions where exposure limits may be greatly exceeded, use an approved air-supplied respirator. Observe

 ${\sf OSHA\ regulations\ (29CFR\ 1910.134)}\ for\ respirator\ use.$ 

Other Protective: Use disposable or impervious clothing if work clothing contamination is likely.

Remove and wash contaminated clothing before reuse.

Hygiene Practices: Wash hands before eating, smoking, or using toilet facility. Do not smoke in any

chemical handling or storage area. Food or beverages should not be consumed anywhere this product is handled or stored. Wash thoroughly after handling.

Notes from Section 8: N.A. - Not Applicable, N.E. - Not Established, S - Skin Designation

# Section 9: Physical and Chemical Properties

#### Physical and chemical properties

Physical State: Liquid

APPEARANCE: Clear

Odor: Solvent PH: N.A.

Boiling Temperature: 82 - 116 °C
Flash Point: 3 °F, -16 °C

Flash Point Method: SetaflashClosed Cup

Ignition Temperature: N.D.

Lower Flammable Limit: 1.3 %(V)

Upper Flammable Limit: 8 %(V)

Decomposition Temperature: N.D.

Vapor Pressure: N.D.

Vapor Density: Heavier than Air

Freezing Temperature: N.D.

Density: 0.8 g/cm3 - 6.63 lb/gal

Solubility In Water: Insoluble

**Evaporation Rate:** Faster than n-butylacetate.

Percent Volatile: VOLATILE BY WEIGHT: 96.42 %

**VOLATILE BY VOLUME: 97.31 %** 

VOC Content: 6.39 lb/gal, 766 g/l

Viscosity: VISCOSITY, KINEMATIC: N.D.

Odor Threshold: N.D.

Octanol Water Partition Coef: COEFFICIENT OF WATER/OIL N.D.

Dynamic Viscosity: N.D.

Note from Section 9: Typical values, not to be used for specification purposes.

LEGEND: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

# Section 10: Stability and Reactivity

Reactivity:

**Chemical Stability:** 

Chemical Stability: Product is stable under normal storage conditions.

Possibility of hazardous reactions:

Hazardous Polymerization: Hazardous polymerization will not occur under normal conditions.

**Conditions To Avoid:** 

Conditions To Avoid: High temperatures. Sources of ignition.

**Incompatible Materials:** 

Incompatible Materials: Strong acids, bases, and strong oxidizers.

Hazardous Decomposition

Products:

Carbon monoxide, carbon dioxide

# Section 11: Toxicological Information

#### **Toxicological Information:**

**Product:** 

Acute Toxicity: Vapor harmful; may affect the brain or nervous system causing dizziness, headache

or nausea. Possible irritation of the respiratory system can occur causing a variety of symptoms such as dryness of the throat, tightness of the chest, and shortness of breath. May cause central nervous system depression characterized by the

following progressive steps: headache, dizziness, staggering gait, confusion, unconsciousness or coma. This product contains a residual amount of a chemical substance that may cause an allergic skin and/or respiratory reaction. Harmful if swallowed. Ingestion is not an expected route of entry in industrial or commercial

uses.

Chronic Toxicity: Prolonged or repeated contact may result in dermatitis. IARC has designated

Methyl isobutyl ketone to bein Group 2B - possibly carcinogenic to humans.

Route of Exposure: EXPOSURE PATH: Refer to section 2 of this SDS.

Sign and Symptoms: Refer to section 2 of this SDS.

Mutagenicity: No classification proposed

Cyclohexane:

Skin Toxicity: Dermal LD50: Rabbit > 2,000 mg/kg

Ingestion Toxicity: Oral LD50: Rat > 5,000 mg/kg

Inhalation Toxicity: Inhalation LC50: Rat 13.9 mg/l /4 h

Reproductive Toxicity: Category 2 - Suspected of damaging fertility or the unborn child.

Methyl-n-propyl ketone:

Skin Toxicity: Dermal LD50: Rabbit 6,500 mg/kg

Dermal LD50: Rat 6,480 mg/kg

Ingestion Toxicity: Oral LD50: Rat 1,600 mg/kg

Oral LD50: Rat 1,600 mg/kg

Inhalation Toxicity: Inhalation LC50: Rat 2000 ppm/4 h

Methyl isobutyl ketone:

Skin Toxicity: Dermal LD50: Rabbit 3,000 mg/kg

Ingestion Toxicity: Oral LD50: Rat 2,080 mg/kg

Inhalation Toxicity: Inhalation LC50: Rat 8.2 mg/l /4 h

Carcinogenicity: Category 2 - Suspected of causing cancer.

## Section 12: Ecological Information

#### Cyclohexane:

Effect of Material On Aquatic: Fish: Pimephales promelas 3.96 - 5.18 mg/l96 h flow-through

Pimephales promelas 23.03 - 42.07 mg/l96 h Static Lepomis macrochirus 24.99 - 44.69 mg/l96 h Static Poecilia reticulata 48.87 - 68.76 mg/l96 h Static Plants: Desmodesmus subspicatus > 500 mg/l72 h

Methyl-n-propyl ketone:

Effect of Material On Aquatic: Fish: Pimephales promelas 1,190 - 1,290 mg/l96 h flow-through

Methyl isobutyl ketone:

Effect of Material On Aquatic: Fish: Pimephales promelas 496 - 514 mg/l96 h flow-through

Invertebrates: Daphnia magna 170 mg/l48 h

Plants: Pseudokirchneriella subcapitata 400 mg/l96 h

Persistence and degradability:

**Product:** 

Biodegredation: PERSISTENCE AND DEGRADABILITY: Not determined for this product.

Bioaccumulative potential:

**Product:** 

BIOACCUMULATIVE: Not determined for this product.

Mobility in soil:

**Product:** 

Mobility In Environmental

MOBILITY IN SOIL: Not determined for this product.

Media:

Notes from Section 12: OTHER ADVERSE EFFECTS: Not determined for this product.

# Section 13: Disposal Considerations

## Description of waste:

Waste Disposal: Disposal should be done in accordance with Federal (40CFR Part 261), state and

local environmental control regulations. If waste is determined to be hazardous,

use licensed hazardous waste transporter and disposal facility.

### Section 14: Transport Information

Transportation: The listed transportation classification applies to US DOT Road, IATA Cargo, and

IMDG non-bulk shipments. It does not address regulatory variations due to changes in package size, mode of shipment or other regulatory descriptors. For the most accurate shipping information, refer to your transportation/compliance

department.

DOT Shipping Name: Adhesives

DOT UN Number: 1133

DOT Hazard Class: 3
DOT Packing Group: II

DOT Other: Emergency Response Guide Number: 128

SECONDARY HAZARD: None

IMDG Shipping Name: Adhesives

IMDG UN Number: 1133

IMDG Hazard Class: 3
IMDG Packing Group: II

IMDG Other: DOT Hazard Class: 3

EMS: F-E

IATA Shipping Name: Adhesives

IATA UN Number: 1133
IATA Hazard Class: 3
IATA Packing Group: II

IATA Other: DOT Hazard Class: 3

EMS: 3L

# Section 15: Regulatory Information

#### Safety, health and environmental regulations specific for the product:

#### Regulatory - Product Based:

U.S. FEDERAL REGULATIONS: AS

FOLLOWS::

SARA SECTION 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and

Reauthorization Act of 1986 and 40 CFR part 372.: Chemical Name CAS Number Weight % Less Than

Cyclohexane 110-82-7 70.0 %

Methyl isobutyl ketone 108-10-1 5.0 %

TOXIC SUBSTANCES CONTROL

ACT::

INVENTORY STATUS: The chemical substances in this product are on the TSCA

Section 8 Inventory.

**EXPORT NOTIFICATION:** 

This product contains the following chemical substances subject to the reporting

requirements of TSCA 12(B) if exported from the United States: NONE

# Section 16: Additional Information

Creation Date: 2019-01-09

**Revision Date:** 

2019-01-10 13:48:14

Notes from Section 16:

Under HazCom 2012 it is optional to continue using the HMIS rating system. It is important to ensure employees have been trained to recognize the different numeric ratings associated with the HazCom 2012 and HMIS schemes.

\* - Indicates a chronic hazard; see Section 2

HMIS:

Health	2*
Flammability	3
Reactivity	0
PPE	

**Chronic Health Hazard** 

Other Information:

Copyright © 1996-2019 Enviance Inc. All Rights Reserved.