

# **KIT - SAFETY DATA SHEET**

Product identifier used on the label:

Kit Name Speed Grip Epoxy Seam Sealer Controlled Flow

Stock No. 63642506402

Other means of identification:

Address:

Website:

Address:

Product Description: **Epoxy Seam Sealer** 

Synonyms: None

Recommended use of the chemical and restrictions on use:

Epoxy adhesive/sealant Product uses:

Chemical manufacturer address and telephone number:

Manufacturer Name: Saint-Gobain Abrasives, Inc.

> 1 New Bond Street Worcester, MA 01615 www.Nortonabrasives.com

508-795-5000

General Phone Number:

Chemical distributor address and telephone number:

Manufacturer Name: Saint-Gobain Canada, Inc.

> 28 Albert Street, W ON Canada NOJ 1S0

Website: www.Nortonabrasives.com

General Phone Number: 519-684-7441

Emergency phone number:

Kit SDS Revision Date

**Emergency Phone Number:** 508-795-5000

CHEMTREC: For emergencies in the US, call CHEMTREC: 800-424-9300 For emergencies in Canada, call CHEMTREC: 800-424-9300

**Component list** Speed Grip Epoxy Seam Sealer Controlled Flow Part A Speed Grip Epoxy Seam Sealer Controlled Flow Part A Speed Grip Epoxy Seam Sealer Controlled Flow Part B Speed Grip Epoxy Seam Sealer Controlled Flow Part B

07/18/2018



# Section 1: Identification of the Substance/Mixture and of the Company Undertaking

### Product identifier used on the label:

Product Name: Speed Grip Epoxy Seam Sealer Controlled Flow Part A

Other means of identification:

Product Codes: 63642506402

Product Description: Part A Epoxy Seam Sealer

Chemical Family: Epoxy/Époxy

#### Recommended use of the chemical and restrictions on use:

Product Uses: Epoxy adhesive/sealant

#### Chemical manufacturer address and telephone number:

Manufacturer Name: Saint-Gobain Abrasives, Inc.

Manufacturer Address 1: 1 New Bond Street

Manufacturer City: Worcester

Manufacturer State: MA
Manufacturer Zip Code: 01615

Manufacturer Country: USA

Manufacturer Web: www.Nortonabrasives.com

Supplier Name: Saint-Gobain Abrasives, Inc.

Business Phone: 508-795-5000

Distributor: Saint-Gobain Canada, Inc.

Distributor Address 1: 28 Albert St, W.

Distributor Address 2: Plattsville

Distributor State: ON

Distributor ZipCode: NOJ 1S0
Distributor Country: Canada

Distributor Web: www.Nortonabrasives.com

Distributor Phone: 519-684-7441

**Emergency phone number:** 

Emergency Phone: 508-795-5000

Distributor Emergency Phone: 508-795-5000

Creation Date: 05/28/2014

Revision Date: 2018-07-18 15:36:34

Notes from Section 1: CHEMTREC:

For emergencies in the US, call CHEMTREC: 800-424-9300 For emergencies in Canada, call CHEMTREC: 800-424-9300

### Section 2: Hazards Identification

#### Classification of the chemical in accordance with CFR 1910.1200(d)(f):





Signal Words: DANGER

Emergency Overview: Immediate Concerns:

Causes serious eye irritation. Causes skin irritation. May cause sensitization by skin contact. Persons previously sensitized can experience allergic skin reaction

with symptoms of reddening, itching, swelling, and rash.

**Product:** 

GHS Class: Health:

Skin Irritation, Category 2 Eye Irritation, Category 2A Skin Sensitization, Category 1 Reproductive Toxicity, Category 1B

**GHS LABEL:** 

Hazardous components for labelling: Epoxy resin and Benzyl butyl phthalate

Exclamation mark Health hazard

Hazard Statements: H315 - Causes skin irritation.

H319 - Causes serious eye irritation. H317 - May cause an allergic skin reaction. H360 - May damage fertility or the unborn child.

**Precautionary Statements:** 

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P264 - Wash hands thoroughly after handling.

P261 - Avoid breathing vapours.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P280 - Wear protective gloves and eye protection.

P308+P313 - IF exposed or concerned: Get medical advice/attention.
P302+P350 - IF ON SKIN: Gently wash with plenty of soap and water.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 - If eye irritation persists: Get medical advice/attention.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with applicable local, regional

and/or national regulations.

#### Hazards not otherwise classified that have been identified during the classification process:

# Section 3: Composition/Information on Ingredients

#### Mixtures:

Ingredient Name	CAS Number	Ingredient Percent	EC Number	Comments
Epoxy resin	25068-38-6	52 - 56%		
Benzyl butyl phthalate	85-68-7	12 - 15%		
Titanium Dioxide	13463-67-7	1.5 - 2.5%		

#### **Product:**

Notes::

Hazards Not Otherwise Classified: No data available.

Comments:

< 5% of the mixture consists of an ingredient or ingredients of unknown acute toxicity.

See sections 9 and 10 for more detailed information on physicochemical effects.

See section 11 for more detailed information on health effects.

See sections 12 for more detailed information on environmental effects.

The actual container label may not include the above label elements. The labeling shown above applies to products used solely for industrial/professional use.

Consumer products should be labeled in accordance with the Canadian Consumer Chemicals and Containers Regulations and US Consumer Product Safety Commission regulations. Consumer product labeling takes precedence over Canadian WHMIS 2015 and OSHA Hazcom 2012 Hazard Communication labeling.

Comments:

Comments: There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the product and hence require reporting in this section.

### Section 4: First Aid Measures

#### Description of necessary measures:

Eye Contact: Immediately flush with plenty of water. After initial flushing, remove any contact

lenses and continue flushing for at least 15 minutes. Get medical attention, if

irritation persists.

Skin Contact: Wash with soap and water. Get medical attention if irritation develops or persists.

Remove contaminated clothing and wash before reuse.

Inhalation: Not expected to present a significant inhalation hazard under anticipated

conditions of normal use. If you experience eye watering, headaches or dizziness,

increase fresh air or leave the area.

Ingestion: Do not induce vomiting. Rinse mouth with water. Give 1 to 2 glasses of water to

drink. Never give anything by mouth to an unconscious person. Get medical

attention.

### Most important symptoms/effects, acute and delayed:

# Indication of immediate medical attention and special treatment needed

Notes from Section 4:

Signs and Symptoms of Overexposure:

Eye Contact: Contact causes serious eye irritation. Symptoms may include pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a

feeling like that of fine dust in the eyes.

Skin Contact: Causes skin irritation. Prolonged contact with this product can cause reddening, swelling, rash scaling or blistering. In those who have developed skin sensitization, these symptoms can develop as a result of contact with very small

amount of the liquid material.

Ingestion: Substance may be harmful if swallowed. May cause irritation. Symptoms

of ingestion may include abdominal pain, nausea, vomiting and diarrhea.

Inhalation: At room temperature, exposure to vapor is minimal due to low volatility.

Additional Information: No data available.

### Section 5: Firefighting Measures

#### Suitable and unsuitable extinguishing media

Extinguishing Media: Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this

material. Use an extinguishing agent suitable for the surrounding fire.

#### Specific hazards arising from the chemical

Hazardous Combustion During a fire, irritating and highly toxic gases may be generated by thermal

Products: decomposition or combustion.

Sensitivity To Impact: Sensitivity to Mechanical Impact: Product is not sensitive to mechanical impact.

Static Discharge Effects: Sensitivity to Static Discharge: Product is not sensitive to static discharge.

#### Special protective equipment and precautions for fire-fighters

Fire Fighting Instructions: Containers can build up pressure if exposed to heat (fire).

Fire Fighting Equipment: As in any fire, wear self-contained breathing apparatus pressure-demand,

(MSHA/NIOSH approved or equivalent) and full protective gear.

NFPA Health: 2
NFPA Fire: 1
NFPA Reactivity: 0

#### Section 6: Accidental Release Measures

#### Personal precautions, protective equipment and emergency procedures

Personnel Precautions: Special Protective Equipment:

Clean up spills immediately, observing precautions in Protective Equipment section

8.

#### Methods and materials for containment and cleaning up

Small Spill: Ensure adequate ventilation. Cover spill area with suitable absorbent material

(e.g., sand, earth, sawdust, vermiculite, Oil-Dri, Kitty Litter, etc.). Sweep up material being careful not to raise dust. Place in an appropriate disposal container

and seal tightly. Avoid contact with eyes, skin, and clothing.

Land Spill: Avoid runoff into storm sewers and ditches which lead to waterways.

Water Spill: Do not flush to sewer.

#### **Environmental precautions**

#### Section 7: Handling and Storage

#### Precautions for safe handling

Handling: Do not use in the presence of open flame or spark. Wear recommended personal

protective equipment. Avoid contact with eyes, skin, and clothing. After handling,

always wash hands thoroughly with soap and water.

Hygiene Practices: Use good personal hygiene practices. Wash hands before eating, drinking,

smoking, or using toilet facilities. Promptly remove soiled clothing/wash

thoroughly before reuse.

#### Conditions for safe storage, including any incompatibilities

Storage: Store away from heat, sparks, open flames, strong oxidizing agents and direct

sunlight. Protect from physical damage. Keep containers tightly closed, when not in

use. Store in a cool place.

Notes from Section 7: General Procedures:

Ensure thorough ventilation of stores and work areas.

# Section 8: Exposure Controls/Personal Protection

#### **Exposure Guidelines**

Exposure limit: Exposure Guidelines:

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200):

Occupational Exposure Limits: Chemical Name: Epoxy resin

OSHA PEL:

TWA: ppm: [1]; mg/m3: [1]

ACGIH TLV:

TWA: ppm: [2]; mg/m3: [2]

NIOSH REL:

TWA: ppm: [1]; mg/m3: [1]

Chemical Name: Benzyl butyl phthalate

NIOSH REL:

TWA: ppm: [3], 3 mg/m3 [3]

STEL: 5 mg/m3

Chemical Name: Titanium Dioxide

OSHA PEL:

TWA: 15 mg/m3 T

ACGIH TLV: TWA: 10 mg/m3

NIOSH REL:

TWA: ppm: This material does not have established exposure limits.; mg/m3: This

material does not have established exposure limits.

STEL: ppm: This material does not have established exposure limits.; mg/m3: This

material does not have established exposure limits.

#### Footnotes:

1. NL: This material does not have established exposure limits.

2. This material does not have established exposure limits.

3. Austria, Denmark, Sweden

#### Appropriate engineering controls

Engineering Controls: Good general ventilation should be sufficient to control airborne levels.

#### Individual protection measures

Eye Protection: Wear safety glasses with side shields (or goggles). Contact lenses should not be

worn when working with this product. Eye wash fountains should be readily

available to areas of use and handling.

Face Protection: Wear safety glasses with side shields (or goggles). Contact lenses should not be

worn when working with this product. Eye wash fountains should be readily

available to areas of use and handling.

Skin Protection: Wear chemical resistant gloves.

Protective Clothing: Wear protective clothing as necessary to prevent contact.

Respiratory Protection: Generally not required. Wear respiratory protection if ventilation is inadequate.

Hygiene Practices: Use good personal hygiene practices. Wash hands before eating, drinking,

smoking, or using toilet facilities. Promptly remove soiled clothing/wash

thoroughly before reuse.

### Section 9: Physical and Chemical Properties

# Physical and chemical properties

Physical State: Liquid

Appearance: Thixotropic liquid

Color: Light yellow

Odor: Mild

pH: No data available.

Melting Temperature: Not Applicable

Boiling Temperature: No data available.

Flash Point: > 200 deg C
Flash Point Method: Closed Cup

Ignition Temperature: No data available.

Vapor Pressure: No data available.

Vapor Density: No data available.

Freezing Temperature: No data available.

Density: 1.40±0.03 g/l at 20 deg C

Solubility In Water: Practically insoluble

Evaporation Rate: (n-butyl acetate = 1): No data available.

Partition Coefficient: (n-octanol/water): No data available.

Percent Volatile: < 0.5% w/w

**VOC Content:** < 7.0 g/l (< 0.5% w/w)

VOC Compliance Statement:

Part A VOC Content:

Less Exempts: < 7 g/l (< 0.058 lb/gal)
Total Material: < 7 g/l (< 0.058 lb/gal)
Part A Density: 1.40 ± 0.02 g/ml
Part A Total Volatiles: < 0.5% w/w
Part A Exempt Content: 0% w/w; 0% v/v

VOC Regulation: CARB-California, OTC state, Canada proposed Consumer Product

Regulations

Coating Category: Sealant or Caulking Compound, Chemically Curing, non-aerosol

Mixed Kit VOC Content:

< 0.4% w/w

Less Exempts: < 5.0 g/l (< 0.04 lb/gal) Total Material: < 5.0 g/l (< 0.04 lb/gal)

The product VOC content meets the current 3% w/w limit under the CARB Consumer Product Regulations for Sealant or Caulking Compound, Chemically

Curing, non-aerosol. 50 State compliant.

Note: In California this product is exempt under Adhesives and Sealants district rules (meets small container exemption - packaged in  $\leq$ 475 ml (16 fl oz) cartridges)

but is covered by the CARB Consumer Product Regulation.

Viscosity: > 50000 cps at 25 deg C

Odor Threshold: No data available.

Oxidizing Properties: None

Note from Section 9: Flammable Limits: No data available.

# Section 10: Stability and Reactivity

Reactivity:

Reactivity: Reactive Hazard: No

Possibility of Hazardous Reactions: No data available.

**Chemical Stability:** 

Chemical Stability: Stable.

Possibility of hazardous reactions:

Hazardous Polymerization: Not expected to occur.

**Conditions To Avoid:** 

Conditions To Avoid: Keep away from flames and any object that sparks.

**Incompatible Materials:** 

Incompatible Materials: Oxidizing materials.

Hazardous Decomposition

Carbon Monoxide and other toxic vapors.

Products:

### Section 11: Toxicological Information

### **Toxicological Information:**

#### **Product:**

Skin Toxicity: Product Acute Toxicity:

Acute Toxicity - Dermal LD50: The calculated ATE is > 2000 mg/kg.

Notes: Based on available data, the classification criteria for Acute Dermal Toxicity

are not met for this mixture.

Ingestion Toxicity: Product Acute Toxicity:

Acute Toxicity - Oral LD50: The calculated ATE is > 2000 mg/kg.

Notes: Based on available data, the classification criteria for Acute Oral Toxicity

are not met for this mixture.

Inhalation Toxicity: Product Acute Toxicity:

Acute Toxicity - Inhalation LC50: No data available.

Notes: The mixture is not classified due to lack of data. At room temperature, exposure to vapor is minimal due to low volatility. An estimate based on

component information. Not classified.

Carcinogenicity: Notes: Based on available data, the classification criteria for Carcinogenicity are

not met for this mixture. Titanium dioxide is listed as Group 2B (possibly carcinogenic to humans) Titanium dioxide: Applies only to respirable dust. The

product is unlikely to form a respirable dust.

Mutagenicity: Germ Cell Mutagenicity:

Based on available data, the classification criteria for Germ Cell Mutagenicity are not met for this mixture (< 0.1% ingredients classified as Germ Cell Mutagen, category 1A or 1B and < 1.0% ingredients classified as Germ Cell Mutagen,

category 2).

Teratogenicity: Notes: Based on available data, the classification criteria for Carcinogenicity are

not met for this mixture. Titanium dioxide is listed as Group 2B (possibly carcinogenic to humans) Titanium dioxide: applies only to respirable dust. The

product is unlikely to form a respirable dust.

Reproductive Toxicity:

Contains: Benzyl butyl phthalate. May cause adverse reproductive effects. May damage fertility or the unborn child . The mixture is classified as: Reproductive Toxicity, category 1 based on ingredient data using the applicable cut-off/concentration limits (≥ 0.1% ingredients classified as Reproductive Toxicity, category 1).

Irritation:

Eye Irritation/Serious Eye Damage:

Contains: Epoxy resin. Contact causes serious eye irritation. The mixture is classified as: Eye Irritant, category 2, based on summation of ingredient data (> 10% ingredients classified as eye irritant, category 2). Symptoms may include pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

Skin Irritation/Corrosion:

Contains: Epoxy resin. Causes skin irritation. The mixture is classified as: Skin Irritant, category 2, based on summation of ingredient data (> 10% ingredients classified as skin irritant, category 2). Persons previously sensitized can experience allergic skin reaction with symptoms of reddening, itching, swelling, and rash.

Sensitization:

Respiratory/Skin Sensitizer:

Contains: Epoxy resin. May cause sensitization by skin contact. The mixture is classified as: Skin Sensitizer, category 1 based on ingredient data ( $\geq 0.1\%$  ingredients classified as a skin sensitizer, category 1 or subcategory 1A or  $\geq 1.0\%$  ingredients classified as a skin sensitizer, sub-category 1B). Prolonged contact with this product can cause reddening, swelling, rash scaling or blistering. In those who have developed skin sensitization, these symptoms can develop as a result of contact with very small amount of the liquid material.

Based on available data, the classification criteria for respiratory sensitization are not met for this mixture (< 0.1% ingredients classified as a respiratory sensitizer, category 1 or sub-category 1A and < 1.0% ingredients classified as a respiratory sensitizer, sub-category 1B).

Notes from Section 11:

Toxicological Data:

 $\!<$  5% of the mixture consists of an ingredient or ingredients of unknown acute

toxicity.

No additional toxicology information is available for this product itself. (See

Component Toxicity Information).

Titanium Dioxide:

IARC Carcinogen: 2B

Benzyl butyl phthalate:

Skin Toxicity: DERMAL LD50 (rabbit): > 10,000 mg/kg

Ingestion Toxicity: ORAL LD50 (rat): 2330 mg/kg

Inhalation Toxicity: INHALATION LC50 mg/l: No data available.

**Epoxy resin:** 

Skin Toxicity: DERMAL LD50 (rabbit): > 22,800 mg/kg

Ingestion Toxicity: ORAL LD50 mg/kg (rat):

11,400 > 15,000

Inhalation Toxicity: INHALATION LC50 mg/l: No data available.

OSHA Carcinogen: None

IARC Carcinogen: None

NTP Carcinogen: None

### Section 12: Ecological Information

**Ecotoxicity:** 

**Product:** 

**Ecotoxicity**: Ecotoxicological Information: No data available.

Potential Environmental Effects: Environmental Data: No data available.

Effect of Material On Aquatic: Aquatic Toxicity (Acute): No data available.

**Bioaccumulative potential:** 

**Product:** 

BioAccumulation: Accumulation: No data available.

Mobility in soil:

**Product:** 

Notes from Section 12: Distribution: No data available.

Chemical Fate Information: No data available.

### Section 13: Disposal Considerations

Description of waste:

Waste Disposal: Disposal Method:

Comply with applicable local, state or international regulations concerning solid or

hazardous waste disposal and/or container disposal. Do not discharge

substance/product into sewer system.

Product Disposal:

Empty containers retain product residue; observe all precautions for product.

Decontaminate containers prior to disposal.

# Section 14: Transport Information

DOT: DOT (Department of Transportation):

DOT Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

DOT UN Number: NA Number: 3082

DOT Hazard Class: Primary Hazard Class/Division: 9

DOT Packing Group:

DOT Other: Technical Name: Benzyl Butyl Phthalate and Epoxy Resin

Marine Pollutant: Yes

Other Shipping Information:

These Regulations do not apply to the handling, offering for transport or transporting of less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS

SUBSTANCE, LIQUID, N.O.S., on a road vehicle or a railway vehicle.

IMDG: Vessel (IMDG):

IMDG Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

IMDG UN Number: NA Number: 3082

IMDG Hazard Class: Primary Hazard Class/Division: 3

IMDG Packing Group: III

IMDG Other: Technical Name: Benzyl Butyl Phthalate and Epoxy Resin

Marine Pollutant: Yes

Label: None

Note: With an inner packaging < 5.0 L, this product may be shipped as a Limited

Quantity.

IATA: Air:

IATA Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

IATA UN Number: NA Number: 3082

IATA Hazard Class: Primary Hazard Class/Division: 3

IATA Packing Group: III

IATA Other: Technical Name: Benzyl Butyl Phthalate and Epoxy Resin
Canada TDG: Canadian Transportation of Dangerous Goods Regulations:

Canada Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Canada UN Number: NA Number: 3082

Canada Hazard Class: Primary Hazard Class/Division: 3

Canada Other: Technical Name: Benzyl Butyl Phthalate and Epoxy Resin

Packing Group: III

TDG Note: These Regulations do not apply to the handling, offering for transport or transporting of less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS

SUBSTANCE, LIQUID, N.O.S., on a road vehicle or a railway vehicle.

Canada Shipping Label: None ICAO: Air:

ICAO Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

ICAO UN Number: NA Number: 3082

ICAO Packing Group: III

ICAO Hazard Class: Primary Hazard Class/Division: 3

ICAO Other: Technical Name: Benzyl Butyl Phthalate and Epoxy Resin

Notes from Section 14: Vessel (IMO):

Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Technical Name: Benzyl Butyl Phthalate and Epoxy Resin

UN/NA Number: 3082

Primary Hazard Class/Division: 3

Packing Group: III Marine Pollutant: Yes

Label: None

Note: With an inner packaging < 5.0 L, this product may be shipped as a Limited

Quantity.

# Section 15: Regulatory Information

Safety, health and environmental regulations specific for the product:

**Regulatory - Product Based:** 

#### Section 312 Hazard Category:

SARA Section 311/312 Hazard Categories:

Fire Hazard: No

Sudden Release of Pressure: No

Reactive Hazard: No Product Acute Toxicity: Yes Product Chronic Toxicity: Yes

#### Section 313 Toxic Release Form:

**EPCRA Section 313 Toxic Chemicals:** 

This product does not contain any listed toxic chemicals that exceed the threshold reporting levels established by SARA Title III, Section 313.

#### Section 302:

EPCRA Section 302 Extremely Hazardous Substances:

**EPCRA Status:** 

This product contains no listed extremely hazardous substances that are subject to the reporting requirements of SARA Title III, Section 302.

#### TSCA 8(b): Inventory Status:

All components are included or are otherwise exempt from inclusion on this inventory.

#### Section 112(r): Clean Air Act:

CAA 112(r) - List of Substances for Accidental Release Prevention: This product contains no chemicals subject to CAA 112(b) or CAA 112(r).

#### OSHA 29 CFR 1200:

OSHA Hazard Communication Standard (29 CFR 1910.1200): OSHA Status: Hazardous Product (See Section 2 for details).

This product has been classified in accordance with the hazard criteria of the USA OSHA Hazard Communication Standard (29CFR 1910.1200) and the Safety Data Sheet contains all the information required by the OSHA Hazard Communication Standard (HazCom 2012).

#### Canada WHMIS:

WHMIS Hazard Symbol and Classification: See Section 2 for details.

#### WHMIS Regulatory Status:

This product has been classified in accordance with the hazard criteria of the Canadian Hazardous Products Regulations and the Safety Data Sheet contains all the information required by the Hazardous Products Regulations (WHMIS 2015).

# WHMIS Classification:

WHMIS 2015 (Canada) Status: Hazardous Product (See Section 2 for details).

Domestic Substances List (DSL)/Non-Domestic Substances List (NDSL): All components are included or are otherwise exempt from inclusion on this inventory.

#### Comments:

VOC Content -- See section 9.

#### **Regulatory - Ingredient Based:**

#### Benzyl butyl phthalate:

Section 304 CERCLA RQ: CERCLA Hazardous Substances and Reportable Quantities (RQ):

Chemical Name: Benzyl butyl phthalate

Wt. %: 12 - 15 RQ: 100 State: California Proposition 65:

Chemical Name: Benzyl butyl phthalate

Wt. %: 12 - 15

Listed: Developmental Toxicity

Canada WHMIS: CEPA - National Pollutant Release Inventory (NPRI):

Name: Benzyl butyl phthalate

CAS No.: 85-68-7 NPRI Part No.: 1A (VOC)

# Section 16: Additional Information

Creation Date: 05/28/2014

Revision Date: 2018-07-18 15:36:34

Author: Enviance

Notes from Section 16: NFPA 30/30B Storage Classification: Combustible Liquid IIIB.

Comments from Section 16: None

HMIS:

Health	2
Flammability	1
Reactivity	0
PPE	В

Chronic Health Hazard

NFPA:



Other Information:

Copyright © 1996-2018 Enviance Inc. All Rights Reserved.



# Section 1: Identification of the Substance/Mixture and of the Company Undertaking

#### Product identifier used on the label:

Product Name: Speed Grip Epoxy Seam Sealer Controlled Flow Part B

Other means of identification:

Product Codes: 63642506402

Product Description: Part B Epoxy Seam Sealer

Chemical Family: Mercaptan

#### Recommended use of the chemical and restrictions on use:

Product Uses: Epoxy adhesive/sealant

#### Chemical manufacturer address and telephone number:

Manufacturer Name: Saint-Gobain Abrasives, Inc.

Manufacturer Address 1: 1 New Bond Street

Manufacturer City: Worcester

Manufacturer State: MA
Manufacturer Zip Code: 01615

Manufacturer Country: USA

Manufacturer Web: www.Nortonabrasives.com

Supplier Name: Saint-Gobain Abrasives, Inc.

Business Phone: 508-795-5000

Distributor: Saint-Gobain Canada, Inc

Distributor Address 1: 28 Albert St, W.

Distributor City: Plattsville

Distributor State: ON

Distributor ZipCode: NOJ 1S0
Distributor Country: Canada

Distributor Web: www.Nortonabrasives.com

### **Emergency phone number:**

Emergency Phone: 508-795-5000

Distributor Emergency Phone: 508-795-5000

Creation Date: 05/28/2014

Revision Date: 2018-07-18 15:38:02

Notes from Section 1: CHEMTREC:

For emergencies in the US, call CHEMTREC: 800-424-9300 For emergencies in Canada, call CHEMTREC: 800-424-9300

### Section 2: Hazards Identification

### Classification of the chemical in accordance with CFR 1910.1200(d)(f):



Signal Words: Warning

Emergency Overview: Immediate Concerns:

Causes serious eye irritation. Causes skin irritation. May cause respiratory irritation. Strong, offensive odor. Vapors may have a strong offensive odor which

may cause headaches, nausea and vomiting.

**Product:** 

GHS Class: Health:

Skin Irritation, Category 2 Eye Irritation, Category 2

Target Organ Toxicity (Single exposure), Category 3

GHS LABEL:

Hazardous components for labelling:

Mercaptan terminated polymer and 2,4,6-Tris(dimethylaminomethyl) phenol.

**Exclamation mark** 

Hazards Not Otherwise Classified:

May be harmful if swallowed or in contact with skin. (2,4,6-

Tris(dimethylaminomethyl) phenol)

Hazard Statements: H315 - Causes skin irritation.

H319 - Causes serious eye irritation. H335 - May cause respiratory irritation.

Precautionary Statements: P264 - Wash hands thoroughly after handling.

P280 - Wear protective gloves and eye protection.

P261 - Avoid breathing vapours.

P271 - Use only outdoors or in a well-ventilated area.

P302+P350 - IF ON SKIN: Gently wash with plenty of soap and water. P332+P313 - If skin irritation occurs: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 - If eye irritation persists: Get medical advice/attention.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

P312 - Call a POISON CENTER or doctor/physician if you feel unwell.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with applicable local, regional

and/or national regulations.

# Hazards not otherwise classified that have been identified during the classification process:

# Section 3: Composition/Information on Ingredients

### Mixtures:

Ingredient Name	CAS Number	Ingredient Percent	EC Number	Comments		
Mercaptan terminated polymer	101359-87-9	Wt.: 61 - 65%				
2,4,6-Tris (dimethylaminomethyl) phenol	90-72-2	Wt.: 5 - 7%				

#### **Product:**

Notes:: Comments:

 $\!<$  10 % of the mixture consists of an ingredient or ingredients of unknown acute

toxicity.

See sections 9 and 10 for more detailed information on physicochemical effects.

See section 11 for more detailed information on health effects.

See sections 12 for more detailed information on environmental effects.

The actual container label may not include the above label elements. The labeling shown above applies to products used solely for industrial/professional use.

Consumer products should be labeled in accordance with the Canadian Consumer Chemicals and Containers Regulations and US Consumer Product Safety Commission regulations. Consumer product labeling takes precedence over Canadian WHMIS 2015 and OSHA Hazcom 2012 Hazard Communication labeling.

Comments: There are no additional ingredients present which, within the current knowledge of

the supplier, are classified and contribute to the classification of the product and

hence require reporting in this section.

### Section 4: First Aid Measures

# Description of necessary measures:

Eye Contact: Immediately flush with plenty of water. After initial flushing, remove any contact

lenses and continue flushing for at least 15 minutes. Get medical attention, if

irritation persists.

Skin Contact: Wash with soap and water. Get medical attention if irritation develops or persists.

Remove contaminated clothing and wash before reuse.

Inhalation: No specific treatment is necessary since this material is not likely to be hazardous

by inhalation. If you experience eye watering, headaches or dizziness, increase

fresh air or leave the area.

Ingestion: Do not induce vomiting. Rinse mouth with water. Give 1 to 2 glasses of water to

drink. Never give anything by mouth to an unconscious person. Get medical

attention.

#### Most important symptoms/effects, acute and delayed:

### Indication of immediate medical attention and special treatment needed

Notes from Section 4: Signs and Symptoms of Overexposure:

Eye Contact:

Contact causes serious eye irritation. Symptoms may include pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like

that of fine dust in the eyes.

Skin Contact:

Causes skin irritation. Prolonged contact with this product can cause reddening,

swelling, rash scaling or blistering.

Ingestion:

Substance may be harmful if swallowed. May cause irritation. Symptoms of ingestion may include abdominal pain, nausea, vomiting and diarrhea.

Inhalation:

May be irritating to the eyes, nose, throat, and lungs. Prolonged or excessive inhalation may cause respiratory tract irritation. Vapors may have a strong offensive odor which may cause headaches, nausea and vomiting.

Additional Information: No data available.

### Section 5: Firefighting Measures

#### Suitable and unsuitable extinguishing media

Extinguishing Media: Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this

material. Use an extinguishing agent suitable for the surrounding fire.

#### Specific hazards arising from the chemical

Hazardous Combustion During a fire, irritating and highly toxic gases may be generated by thermal

Products: decomposition or combustion.

Sensitivity To Impact: Sensitivity to Mechanical Impact: Product is not sensitive to mechanical impact.

Static Discharge Effects: Sensitivity to Static Discharge: Product is not sensitive to static discharge.

#### Special protective equipment and precautions for fire-fighters

Fire Fighting Instructions: Fire Fighting Procedures: Containers can build up pressure if exposed to heat (fire).

Fire Fighting Equipment: As in any fire, wear self-contained breathing apparatus pressure-demand,

(MSHA/NIOSH approved or equivalent) and full protective gear.

NFPA Health: 2
NFPA Fire: 1
NFPA Reactivity: 0

#### Section 6: Accidental Release Measures

#### Personal precautions, protective equipment and emergency procedures

Personnel Precautions: Special Protective Equipment: Clean up spills immediately, observing precautions

in Protective Equipment section 8.

#### Methods and materials for containment and cleaning up

Small Spill: Ensure adequate ventilation. Cover spill area with suitable absorbent material

(e.g., sand, earth, sawdust, vermiculite, Oil-Dri, Kitty Litter, etc.). Sweep up material being careful not to raise dust. Place in an appropriate disposal container

and seal tightly. Avoid contact with eyes, skin, and clothing.

Land Spill: Avoid runoff into storm sewers and ditches which lead to waterways.

Water Spill: Do not flush to sewer.

### **Environmental precautions**

# Section 7: Handling and Storage

#### Precautions for safe handling

Handling: Use only with adequate ventilation. Avoid breathing vapour. Avoid contact with

eyes, skin, and clothing. Wear recommended personal protective equipment. After

handling, always wash hands thoroughly with soap and water.

Hygiene Practices: Work Hygienic Practices: Use good personal hygiene practices. Wash hands before

eating, drinking, smoking, or using toilet facilities.

Promptly remove soiled clothing/wash thoroughly before reuse.

### Conditions for safe storage, including any incompatibilities

Storage: Store away from heat, sparks, open flames, strong oxidizing agents and direct

sunlight. Protect from physical damage. Keep containers tightly closed, when not in

use. Store in a cool place.

Notes from Section 7: General Procedures: Ensure thorough ventilation of stores and work areas.

### Section 8: Exposure Controls/Personal Protection

#### **Exposure Guidelines**

Exposure limit: OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200):

Chemical Name: Mercaptan terminated polymer

TWA: OSHA PEL:

ppm: NL: This material does not have established exposure limits. mg/m3: NL: This material does not have established exposure limits.

ACGIH TLV:

ppm: This material does not have established exposure limits. mg/m3: This material does not have established exposure limits.

NIOSH REL:

ppm: NL: This material does not have established exposure limits. mg/m3: NL: This material does not have established exposure limits.

Chemical Name: 2,4,6-Tris(dimethylaminomethyl) phenol

TWA: OSHA PEL:

ppm: NL: This material does not have established exposure limits. mg/m3: NL: This material does not have established exposure limits.

ACGIH TLV:

ppm: This material does not have established exposure limits. mg/m3: This material does not have established exposure limits.

NIOSH REL:

ppm: NL: This material does not have established exposure limits. mg/m3: NL: This material does not have established exposure limits.

Footnotes:

NL: This material does not have established exposure limits.
 This material does not have established exposure limits.

#### Appropriate engineering controls

Engineering Controls: Good general ventilation should be sufficient to control airborne levels.

#### Individual protection measures

Eye Protection: Wear safety glasses with side shields (or goggles). Contact lenses should not be

worn when working with this product. Eye wash fountains should be readily

available to areas of use and handling.

Skin Protection: Wear chemical resistant gloves.

Protective Clothing: Wear protective clothing as necessary to prevent contact.

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory equipment.

NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or

canister may be permissible under certain circumstances where airborne

concentrations are expected to exceed exposure limits.

Hygiene Practices: Work Hygienic Practices: Use good personal hygiene practices. Wash hands before

eating, drinking, smoking, or using toilet facilities.

Promptly remove soiled clothing/wash thoroughly before reuse.

# Section 9: Physical and Chemical Properties

#### Physical and chemical properties

Physical State: Liquid

Appearance: Thixotropic liquid

Color: Beige, off-white

Odor: Mercaptan odor, stench

pH: No data available.

Melting Temperature: Not Applicable

Boiling Temperature: No data available.

Flash Point: > 124 deg C
Flash Point Method: Closed Cup

Ignition Temperature:

Vapor Pressure:

No data available.

Vapor Density:

No data available.

Freezing Temperature:

No data available.

Density: 1.37±0.02g/ml at 20 deg C

Solubility In Water: Practically insoluble

Evaporation Rate: (n-butyl acetate = 1): No data available.

Percent Volatile: < 0.2% w/w

**VOC Content:** < 2.5 g/l (< 0.2% w/w)

VOC Compliance Statement:

Part B VOC Content: Less Exempts: < 2.5 g/l (< 0.021 lb/gal)

Total Material: < 2.5 g/l (< 0.021 lb/gal)

Part B Density: 1.37 ± 0.05 g/ml
Part B Total Volatiles: < 0.2 % w/w
Part B Exempt Content: 0 % w/w; 0% v/v

VOC Regulation: CARB-California, OTC state, Canada proposed Consumer Product

Regulations

Coating Category: Sealant or Caulking Compound, Chemically Curing, non-aerosol

Mixed Kit VOC Content: < 0.4 % w/w Less Exempts: < 5.0 g/l (< 0.04 lb/gal) Total Material: < 5.0 g/l (< 0.04 lb/gal)

The product VOC content meets the current 3% w/w limit under the CARB Consumer Product Regulations for Sealant or Caulking Compound, Chemically

Curing, non-aerosol. 50 State compliant.

Note: In California this product is exempt under Adhesives and Sealants district rules (meets small container exemption - packaged in ≤ 475 ml (16 fl oz) cartridges) but is covered by the CARB Consumer Product Regulation.

Viscosity: > 50000 cps at 20 deg C

Odor Threshold: No data available.

Octanol Water Partition Coef: No data available.

Oxidizing Properties: None

Note from Section 9: Flammable Limits: No data available.

### Section 10: Stability and Reactivity

Reactivity:

Reactivity: No

Possibility of Hazardous Reactions: No data available.

**Chemical Stability:** 

Chemical Stability: Stable.

Possibility of hazardous reactions:

Hazardous Polymerization: Not expected to occur.

**Conditions To Avoid:** 

Conditions To Avoid: Keep away from flames and any object that sparks.

**Incompatible Materials:** 

Incompatible Materials: Oxidizing materials.

Hazardous Decomposition By fire and high heat: Carbon monoxide, Carbon dioxide, Oxides of nitrogen and

Products: other undetermined compounds.

### Section 11: Toxicological Information

#### **Toxicological Information:**

**Product:** 

Acute Toxicity: Toxicological Data: < 10% of the mixture consists of an ingredient or ingredients of

unknown acute toxicity.

No additional toxicology information is available for this product itself. (See

Component Toxicity Information).

Skin Toxicity: Acute Toxicity - Dermal LD50: The calculated ATE is > 2000 mg/kg.

Notes:

Based on available data, the classification criteria for Acute Dermal Toxicity are not met for this mixture. Slightly toxic. May be harmful in contact with skin.

Ingestion Toxicity: Acute Toxicity - Oral LD50: The calculated ATE is > 2000 mg/kg.

Notes: Based on available data, the classification criteria for Acute Oral Toxicity

are not met for this mixture. Slightly toxic. May be harmful if swallowed.

Inhalation Toxicity: Acute Toxicity - Inhalation LC50: Not Established

Notes: The mixture is not classified due to inconclusive data. Some data exist, but the data are not sufficient for classification. An estimate based on component information. Vapors may have a strong offensive odor which may cause

headaches, nausea and vomiting.

Route of Exposure: Eye contact. Skin contact. Inhalation.

Carcinogenicity: Notes: Based on available data, the classification criteria for Carcinogenicity are

not met for this mixture (< 0.1% ingredients classified as a Carcinogen, category 1  $\,$ 

or 2).

Mutagenicity: Germ Cell Mutagenicity: Based on available data, the classification criteria for

Germ Cell Mutagenicity are not met for this mixture (< 0.1% ingredients classified as Germ Cell Mutagen, category 1A or 1B and < 1.0% ingredients classified as

Germ Cell Mutagen, category 2).

Reproductive Toxicity: Based on available data, the classification criteria for Reproductive Toxicity are not

met for this mixture (< 0.1% ingredients classified as Reproductive Toxicity,

category 1 or 2).

Irritation: Eye Irritation/Serious Eye Damage:

Contains: Mercaptan terminated polymer and 2,4,6-Tris(dimethylaminomethyl) phenol. Contact causes serious eye irritation. The mixture is classified as: Eye Irritant, category 2, based on summation of ingredient data (> 10% ingredients classified as eye irritant, category 2). Symptoms may include pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like

that of fine dust in the eyes.

Skin Irritation/Corrosion:

Contains: Mercaptan terminated polymer and 2,4,6-Tris(dimethylaminomethyl) phenol. Causes skin irritation. The mixture is classified as: Skin Irritant, category 2, based on summation of ingredient data (> 10% ingredients classified as skin irritant, category 2). Prolonged contact with this product can cause reddening,

swelling, rash scaling or blistering.

Sensitization: Respiratory/Skin Sensitizer: Based on available data, the classification criteria for

respiratory sensitization are not met for this mixture (< 0.1% ingredients classified as a respiratory sensitizer, category 1 or sub-category 1A and < 1.0% ingredients

classified as a respiratory sensitizer, sub-category 1B).

Based on available data, the classification criteria for skin sensitization are not met for this mixture (< 0.1% ingredients classified as a skin sensitizer, category 1 or sub-category 1A and < 1.0% ingredients classified as a skin sensitizer, sub-category 1B).

#### Mercaptan terminated polymer:

Skin Toxicity: DERMAL LD50 mg/kg(rabbit): > 2000 Based on similar compounds.

Ingestion Toxicity: ORAL LD50 mg/kg(rat): > 2000 Based on similar compounds.

Inhalation Toxicity: INHALATION LC50 mg/l: > 10(rat;4h) Based on similar compounds.

### 2,4,6-Tris(dimethylaminomethyl) phenol:

Skin Toxicity: DERMAL LD50 mg/kg(rabbit): 1400(rbt), 1280(rat)

Ingestion Toxicity: ORAL LD50 mg/kg(rat): 1200, 2500, 2169, 1673

Inhalation Toxicity: INHALATION LC50 mg/l: > 0.5(rat;1h)

# Section 12: Ecological Information

#### **Ecotoxicity:**

# Product:

Ecotoxicity: No data available.

Effect of Material On Aquatic: Aquatic Toxicity (Acute): No data available.

#### Persistence and degradability:

**Product:** 

Environmental Fate: Environmental Data: No data available.

Biodegredation: Distribution: No data available.

### **Bioaccumulative potential:**

**Product:** 

BioAccumulation: Bioaccumulation/Accumulation: No data available.

#### Mobility in soil:

**Product:** 

Notes from Section 12:

Chemical Fate Information: No data available.

# Section 13: Disposal Considerations

### Description of waste:

Waste Disposal: Disposal Method: Comply with applicable local, state or international regulations

concerning solid or hazardous waste disposal and/or container disposal. Do not

discharge substance/product into sewer system.

Product Disposal: Empty containers retain product residue; observe all precautions

for product. Decontaminate containers prior to disposal.

# Section 14: Transport Information

DOT Shipping Name: This product is not regulated.

DOT UN Number: Not Applicable

DOT Hazard Class: Division: Not Applicable

DOT Packing Group: Not Applicable

DOT Other: Marine Pollutant: No

Other Shipping Information: No data available.

IMDG Shipping Name: This product is not regulated.

IMDG UN Number: Not Applicable

IMDG Hazard Class: Division: Not Applicable

IMDG Packing Group: Not Applicable

IMDG Other: Marine Pollutant : No

Note: No data available.

Canada Shipping Name: This product is not regulated.

Canada UN Number: Not Applicable

Canada Hazard Class: Division: Not Applicable

Canada Other: Packing Group: Not Applicable

TDG Note: No data available.

Notes from Section 14: Vessel (IMO):

Shipping Name: This product is not regulated.

UN/NA Number: Not Applicable

Primary Hazard Class/Division: Not Applicable

Packing Group: Not Applicable

Marine Pollutant: No Note: No data available.

### Section 15: Regulatory Information

Safety, health and environmental regulations specific for the product:

**Regulatory - Product Based:** 

#### Section 312 Hazard Category:

SARA Section 311/312 Hazard Categories:

Fire Hazard: No

Sudden Release of Pressure: No

Reactive Hazard: No Product Acute Toxicity: Yes Product Chronic Toxicity: No

#### Section 313 Toxic Release Form:

**EPCRA Section 313 Toxic Chemicals:** 

This product does not contain any listed toxic chemicals that exceed the threshold

reporting levels established by SARA Title III, Section 313.

Section 302:

EPCRA Status: This product contains no listed extremely hazardous substances that

are subject to the reporting requirements of SARA Title III, Section 302.

Section 304:

CERCLA Status: This product contains no CERCLA listed hazardous substances.

TSCA 8(b): Inventory Status:

TSCA Status: All components are included or are otherwise exempt from inclusion

on this inventory.

Section 112(r): Clean Air Act:

CAA 112(r) - List of Substances for Accidental Release Prevention:

This product contains no chemicals subject to CAA 112(b) or CAA 112(r).

State:

California Proposition 65:

This product does not contain any chemicals known to the State of California to

cause cancer, birth defects, or any other reproductive harm.

OSHA 29 CFR 1200:

OSHA Hazard Communication Standard (29 CFR 1910.1200):

OSHA Status: Hazardous Product (See Section 2 for details).

This product has been classified in accordance with the hazard criteria of the USA OSHA Hazard Communication Standard (29CFR 1910.1200) and the Safety Data Sheet contains all the information required by the OSHA Hazard Communication

Standard (HazCom 2012).

Canada WHMIS:

WHMIS Hazard Symbol and Classification: See Section 2 for details.

WHMIS Regulatory Status: This product has been classified in accordance with the hazard criteria of the Canadian Hazardous Products Regulations and the Safety Data Sheet contains all the information required by the Hazardous Products

Regulations (WHMIS 2015).

WHMIS Classification: WHMIS 2015 (Canada) Status: Hazardous Product (See

Section 2 for details).

CEPA - National Pollutant Release Inventory (NPRI): This product contains no

chemicals subject to CEPA - NPRI.

Domestic Substances List (DSL)/Non-Domestic Substances List (NDSL):

All components are included or are otherwise exempt from inclusion on this

inventory.

Notes 1:

Comments:

VOC Content -- See section 9.

# Section 16: Additional Information

Creation Date: 05/28/2014

Revision Date: 2018-07-18 15:38:02

Author: Enviance

Notes from Section 16: NFPA 30/30B Storage Classification: Combustible Liquid IIIB

Comments from Section 16: None

HMIS:

Health	2
Flammability	1
Reactivity	0
PPE	В

Chronic Health Hazard

NFPA:



Other Information:

Copyright © 1996-2018 Enviance Inc. All Rights Reserved.