


Kit Name **Metal Bonding Adhesive**
Stock No. 06419
Manufacturer Name: Saint-Gobain Abrasives, Inc.
Address: One New Bond Street
Worcester, MA 01615

SECTION 1 : PRODUCT AND COMPANY IDENTIFICATION

Product Name: **Metal Bonding Adhesive (Part 1)**
Product Code: 06419A
Synonyms: SpeedGrip Metal Door Skin Bonding Adhesive (45 minutes)
Manufacturer Name: Saint-Gobain Abrasives, Inc.
Address: One New Bond Street
Worcester, MA 01615
Website: www.Nortonabrasives.com
General Phone Number: 800-551-4413
Emergency Phone Number: 508-795-5000
CHEMTREC: For emergencies in the US, call CHEMTREC: 800-424-9300
Canutec: In Canada, call CANUTEC: (613) 996-6666 (call collect)



HMIS	
Health Hazard	2
Fire Hazard	3
Reactivity	1
Personal Protection	1

SECTION 2 : COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent	EC Num.
Methacrylate phosphate ester	Proprietary	5 - 10 by weight	
Methacrylate Blend	Proprietary	5 - 10 by weight	
Methacrylic acid	79-41-4	5 - 10 by weight	607-088-00-5
Methyl Methacrylate Monomer	80-62-6	30 - 60 by weight	607-035-00-6

SECTION 3 : HAZARDS IDENTIFICATION

Emergency Overview: WARNING! Flammable. Harmful. Skin Sensitizer.. Irritant.
Route of Exposure: Eyes. Skin. Inhalation. Ingestion.
Potential Health Effects:
Eye: Can cause moderate irritation, burning sensation, tearing, redness, and swelling. Overexposure may cause lacrimation, conjunctivitis, corneal damage and permanent injury.
Skin: Can cause skin irritation; itching, redness, rashes, hives, burning, and swelling. Allergic reactions are possible.
May cause skin sensitization, an allergic reaction, which becomes evident on reexposure to this material.
Inhalation: Respiratory tract irritant. High concentration may cause dizziness, headache, and anesthetic effects. May cause respiratory sensitization with asthma-like symptoms in susceptible individuals.
Ingestion: Causes irritation, a burning sensation of the mouth, throat and gastrointestinal tract and abdominal pain.
Chronic Health Effects: Prolonged skin contact may lead to burning associated with severe reddening, swelling, and possible tissue destruction.
Signs/Symptoms: Overexposure can cause headaches, dizziness, nausea, and vomiting.
Target Organs: Eyes. Skin. Respiratory system. Digestive system. Central nervous system. Liver. Kidney. Olfactory Function.
Aggravation of Pre-Existing Conditions: Individuals with pre-existing skin disorders, asthma, allergies or known sensitization may be more susceptible to the effects of this product.

SECTION 4 : FIRST AID MEASURES

Eye Contact:	Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Get immediate medical attention.
Skin Contact:	Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.
Inhalation:	If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.
Ingestion:	If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.
Other First Aid:	Due to possible aspiration into the lungs, DO NOT induce vomiting if ingested. Provide a glass of water to dilute the material in the stomach. If vomiting occurs naturally, have the person lean forward to reduce the risk of aspiration.

SECTION 5 : FIRE FIGHTING MEASURES

Flammable Properties:	Flammable. Fine mists explosive below flash point.
Flash Point:	60°F (15°C)
Flash Point Method:	Setaflash Closed Cup
Auto Ignition Temperature:	Not determined.
Lower Flammable/Explosive Limit:	1.6%
Upper Flammable/Explosive Limit:	8.8%
Fire Fighting Instructions:	Evacuate area of unprotected personnel. Use cold water spray to cool fire exposed containers to minimize risk of rupture. Do not enter confined fire space without full protective gear. If possible, contain fire run-off water.
Extinguishing Media:	Use foam, water fog, carbon dioxide (CO2) or dry chemical when fighting fires involving this material.
Protective Equipment:	As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear.
Unusual Fire Hazards:	Sealed containers at elevated temperatures may rupture explosively and spread fire due to polymerization.
Universal Fire And Explosion Hazards:	Flammable liquid and vapor. Keep containers tightly closed. Isolate from heat, electrical equipment, sparks, open flame, and other sources of ignition. Closed containers may rupture when exposed to extreme heat. Use water spray to keep fire-exposed containers cool. During a fire, irritating and/or toxic gases and particulate may be generated by thermal decomposition or combustion.
<u>NFPA Ratings:</u>	
NFPA Health:	2
NFPA Flammability:	3
NFPA Reactivity:	1

SECTION 6 : ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Avoid breathing vapors. Notify proper authorities if necessary. Avoid contact. Evacuate area and keep unnecessary and unprotected personnel from entering the spill area.
Environmental Precautions:	Avoid runoff into storm sewers, ditches, and waterways.
Spill Cleanup Measures:	Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Provide ventilation. Collect spill with a non-sparking tool. Place into a suitable container for disposal. Clean up spills immediately observing precautions in the protective equipment section. After removal, flush spill area with soap and water to remove trace residue. Flammable, eliminate ignition sources. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to distant ignition sources and flash back. Ventilate area. Use proper personal protective equipment as listed in Section 8.
Other Precautions:	Pump or shovel to storage/salvage vessels. Add inhibitor to prevent polymerization.

SECTION 7 : HANDLING and STORAGE

Handling:	Use with adequate ventilation. Avoid breathing vapor, aerosol or mist. Material will accumulate static charges which may cause an electrical spark (ignition source). Use proper grounding procedures. Do not reuse containers without proper cleaning or reconditioning.
Storage:	Store in a cool, dry, well ventilated area away from sources of heat, combustible materials, direct sunlight, and incompatible substances. Keep container tightly closed when not in use.
Special Handling Procedures:	Provide appropriate ventilation/respiratory protection against decomposition products (see Section 10) during welding/flame cutting operations and to protect against dust during sanding/grinding of cured product. Hazardous liquid or vapor residue may remain in emptied container. Do not reuse, heat, burn, pressurize, cut, weld, braze, solder, drill, grind, expose to sparks, flame, or ignition sources of empty containers without proper commercial cleaning or reconditioning.
Hygiene Practices:	Wash thoroughly after handling.

SECTION 8 : EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

Engineering Controls:	Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.
Eye/Face Protection:	Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.
Skin Protection Description:	Use neoprene, nitrile or rubber gloves and other protective apparel to prevent skin contact. Consult manufacturer's data for permeability data.
Respiratory Protection:	A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.
Other Protective:	Facilities storing or utilizing this material should be equipped with an eyewash and a deluge shower safety station.

EXPOSURE GUIDELINES

Methacrylic acid :

Guideline ACGIH: 20 ppm
TLV-TWA: 20 ppm

Methyl Methacrylate Monomer :

Guideline ACGIH: 50 ppm
Sensitizer.: Sen
TLV-STEL: 100 ppm
TLV-TWA: 50 ppm

Guideline OSHA: 100 ppm
PEL-TWA: 100 ppm

Notes : Only established PEL and TLV values for the ingredients are listed.

SECTION 9 : PHYSICAL and CHEMICAL PROPERTIES

Physical State Appearance:	Paste.
Color:	Off-white.
Odor:	Sweet.
Boiling Point:	140 - 322°F (60 - 161°C)
Melting Point:	Not determined.
Density:	9.42 lb/gal
Solubility:	Insoluble in water.
Vapor Density:	> 1 (air = 1)
Vapor Pressure:	Not determined.
Percent Volatile:	By Weight: 0.00% By Volume: 0.00%
Evaporation Rate:	Slower than n-butyl acetate.
pH:	Not determined.
Flash Point:	60°F (15°C)
Flash Point Method:	Setaflash Closed Cup
Auto Ignition Temperature:	Not determined.
VOC Content:	0.0 lg/gal, 0.0 g/L

SECTION 10 : STABILITY and REACTIVITY

Chemical Stability:	Unstable.
Hazardous Polymerization:	Polymerization may occur under certain conditions.
Conditions to Avoid:	Extreme heat, sparks, and open flame. Incompatible materials, oxidizers and oxidizing conditions. Oxygen-free atmospheres or inert gas blanketing. Freezing conditions. Material can soften paint and rubber.
Incompatible Materials:	Oxidizing agents (eg peroxides, nitrates), reducing agents, acids, bases, azo-compounds, catalytic metals (eg copper, iron), halogens. Free radical initiators. Oxygen scavengers.

SECTION 11 : TOXICOLOGICAL INFORMATION

Methacrylic acid :

RTECS Number: OZ2975000

Skin: Unreported - Rat LD50: 1600 mg/kg [Details of toxic effects not reported other than lethal dose value]
Oral - Mouse LD50: 1250 mg/kg [Details of toxic effects not reported other than lethal dose value]
Intraperitoneal. - Mouse LD50: 48 mg/kg [Details of toxic effects not reported other than lethal dose value]
Unreported - Mouse LD50: 1250 mg/kg [Details of toxic effects not reported other than lethal dose value]
Oral - Rabbit LD50: 1200 mg/kg [Details of toxic effects not reported other than lethal dose value]
Administration onto the skin - Rabbit LD50: 500 mg/kg [Details of toxic effects not reported other than lethal dose value]
Administration onto the skin - Guinea pig LD50: 1 gm/kg [Details of toxic effects not reported other than lethal dose value]
Oral - Rat LD50: 1060 mg/kg [Details of toxic effects not reported other than lethal dose value]

Ingestion: Oral - Mouse LD50: 1250 mg/kg [Details of toxic effects not reported other than lethal dose value]
Oral - Rat LD50: 1060 mg/kg [Details of toxic effects not reported other than lethal dose value]

Methyl Methacrylate Monomer :

RTECS Number: OZ5075000

Eye: Eye - Rabbit Standard Draize test.: 150 mg

Skin: Intraperitoneal. - Guinea pig LD50: 1890 mg/kg [Behavioral - Somnolence (general depressed activity)]
Subcutaneous - Guinea pig LD50: 5954 mg/kg [Behavioral - Somnolence (general depressed activity)]
Oral - Rat LD50: 7872 mg/kg [Behavioral - Muscle weakness Behavioral - Coma Lungs, Thorax, or Respiration - Respiratory depression]
Intraperitoneal. - Rat LD50: 1328 mg/kg [Details of toxic effects not reported other than lethal dose value]
Subcutaneous - Rat LD50: 7088 mg/kg [Behavioral - Somnolence (general depressed activity)]
Oral - Mouse LD50: 3625 mg/kg [Details of toxic effects not reported other than lethal dose value]
Intraperitoneal. - Mouse LD50: 945 mg/kg [Behavioral - Somnolence (general depressed activity)]
Subcutaneous - Mouse LD50: 5954 mg/kg [Behavioral - Somnolence (general depressed activity)]

Oral - Rabbit LD50: 8700 mg/kg [Details of toxic effects not reported other than lethal dose value]
Administration onto the skin - Rabbit LD50: >5 gm/kg [Skin and Appendages - Dermatitis, other (After systemic exposure)]
Oral - Guinea pig LD50: 5954 mg/kg [Behavioral - Somnolence (general depressed activity) Behavioral - Ataxia Gastrointestinal - Changes in structure or function of salivary glands]
Administration onto the skin - Rabbit Open irritation test: 10 gm

Inhalation: Inhalation - Rat LC50: 78000 mg/m³/4H [Details of toxic effects not reported other than lethal dose value]
Inhalation - Mouse LC50: 18500 mg/m³/2H [Details of toxic effects not reported other than lethal dose value]

Ingestion: Oral - Rat LD50: 7872 mg/kg [Behavioral - Muscle weakness Behavioral - Coma Lungs, Thorax, or Respiration - Respiratory depression]
Oral - Mouse LD50: 3625 mg/kg [Details of toxic effects not reported other than lethal dose value]

SECTION 12 : ECOLOGICAL INFORMATION

Ecotoxicity: No ecotoxicity data was found for the product.

Environmental Fate: No environmental information found for this product.

SECTION 13 : DISPOSAL CONSIDERATIONS

Methacrylate phosphate ester :

Waste Disposal: Disposal should be done in accordance with Federal (40 CFR Part 261), State and local environmental control regulations. If waste is determined to be hazardous, use licensed hazardous waste transporter and disposal facility.

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.

RCRA Number: D001

Important Disposal Information: DANGER! Rags, steel wool and waste soaked with this product may spontaneously catch fire if improperly discarded or stored. To avoid a spontaneous combustion fire, immediately after use, place rags, steel wool or waste in a sealed, water-filled, metal container.

SECTION 14 : TRANSPORT INFORMATION

DOT Shipping Name: Adhesives

DOT UN Number: 1133

DOT Hazard Class: 3

DOT Packing Group: II

DOT Exemption: ORM-D Small quantity exemption

Notes : Emergency Response Guide Number: 128

SECTION 15 : REGULATORY INFORMATION

Methacrylic acid :

TSCA Inventory Status: Listed

Massachusetts: Listed: Massachusetts Oil and Hazardous List

Pennsylvania: Listed

Canada DSL: Listed

EC Number: 607-088-00-5

Methyl Methacrylate Monomer :

TSCA Inventory Status: Listed

SARA: EPCRA - 40 CFR Part 372 - (SARA Title III) Section 313 Listed Chemical.

New Jersey: Listed: NJ Hazardous List; Substance Number: 1277

Massachusetts: Listed: Massachusetts Oil and Hazardous List

Pennsylvania: Listed

Canada DSL: Listed

EC Number: 607-035-00-6

Canada WHMIS: WHMIS Hazard Class(es): B2; D2B
This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by the Controlled Products Regulations.

SECTION 16 : ADDITIONAL INFORMATION**HMIS Ratings:**

HMIS Health Hazard: 2

HMIS Fire Hazard: 3

HMIS Reactivity: 1

HMIS Personal Protection: 1

SDS Creation Date: October 12, 2010

SDS Revision Date: July 01, 2013

SDS Author: Actio Corporation

Copyright© 1996-2018 Enviance. All Rights Reserved.

SECTION 1 : PRODUCT AND COMPANY IDENTIFICATION

Product Name: **Metal Bonding Adhesive (Part 2)**

Product Code: 06419B

Synonyms: SpeedGrip Metal Door Skin Bonding Adhesive (45 minutes)

Manufacturer Name: Saint-Gobain Abrasives, Inc.

Address: One New Bond Street
Worcester, MA 01615


Website: www.Nortonabrasives.com

General Phone Number: 800-551-4413

Emergency Phone Number: 508-795-5000

CHEMTREC: For emergencies in the US, call CHEMTREC: 800-424-9300

Canutec: In Canada, call CANUTEC: (613) 996-6666 (call collect)



HMIS	
Health Hazard	2
Fire Hazard	1
Reactivity	1
Personal Protection	1

SECTION 2 : COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent	EC Num.
Benzoyl peroxide	94-36-0	5 - 10 by weight	617-008-00-0
Dibutyl phthalate	84-74-2	5 - 10 by weight	
Epoxy resin	Proprietary	30 - 60 by weight	

SECTION 3 : HAZARDS IDENTIFICATION

Emergency Overview:	WARNING! Potential Sensitizer Irritant.
Route of Exposure:	Eyes. Skin. Inhalation. Ingestion.
Potential Health Effects:	
Eye:	Can cause moderate irritation, burning sensation, tearing, redness, and swelling. Overexposure may cause lacrimation, conjunctivitis, corneal damage and permanent injury.
Skin:	Can cause skin irritation; itching, redness, rashes, hives, burning, and swelling. Allergic reactions are possible. May cause skin sensitization, an allergic reaction, which becomes evident on reexposure to this material.
Inhalation:	Respiratory tract irritant. High concentration may cause dizziness, headache, and anesthetic effects. May cause respiratory sensitization with asthma-like symptoms in susceptible individuals.
Ingestion:	Causes irritation, a burning sensation of the mouth, throat and gastrointestinal tract and abdominal pain.
Chronic Health Effects:	Prolonged skin contact may lead to burning associated with severe reddening, swelling, and possible tissue destruction.
Signs/Symptoms:	Overexposure can cause headaches, dizziness, nausea, and vomiting.
Target Organs:	Eyes. Skin. Respiratory system. Digestive system.
Aggravation of Pre-Existing Conditions:	Individuals with pre-existing skin disorders, asthma, allergies or known sensitization may be more susceptible to the effects of this product.

SECTION 4 : FIRST AID MEASURES

Eye Contact:	Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Get immediate medical attention.
Skin Contact:	Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.
Inhalation:	If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.
Ingestion:	If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

SECTION 5 : FIRE FIGHTING MEASURES

Flash Point:	201°F (93.3°C)
Flash Point Method:	Setaflash Closed Cup
Auto Ignition Temperature:	Not determined.
Lower Flammable/Explosive Limit:	Not determined.
Upper Flammable/Explosive Limit:	Not determined.
Fire Fighting Instructions:	Evacuate area of unprotected personnel. Use cold water spray to cool fire exposed containers to minimize risk of rupture. Do not enter confined fire space without full protective gear. If possible, contain fire run-off water.
Extinguishing Media:	Use foam, water fog, carbon dioxide (CO2) or dry chemical when fighting fires involving this material.
Protective Equipment:	As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear.
Unusual Fire Hazards:	Organic peroxides can decompose violently if heated strongly while confined. Sudden reaction and fire may result if product is mixed with an oxidizing agent. Sealed containers at elevated temperatures may rupture explosively and spread fire due to polymerization.
NFPA Ratings:	
NFPA Health:	2
NFPA Flammability:	1
NFPA Reactivity:	1

SECTION 6 : ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Avoid breathing vapors. Notify appropriate authorities if necessary. Avoid contact. Evacuate area and keep unnecessary and unprotected personnel from entering the spill area.
Environmental Precautions:	Avoid runoff into storm sewers, ditches, and waterways.
Spill Cleanup Measures:	Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Provide ventilation. Clean up spills immediately observing precautions in the protective equipment section. After removal, flush spill area with soap and water to remove trace residue. Avoid personal contact and breathing vapors or mists. Ventilate area. Use proper personal protective equipment as listed in Section 8.

SECTION 7 : HANDLING and STORAGE

Handling:	Use with adequate ventilation. Avoid breathing vapor, aerosol or mist.
Storage:	Store in a cool, dry, well ventilated area away from sources of heat and incompatible materials. Keep container tightly closed when not in use. Do not store in temperatures above 100 °F.
Hygiene Practices:	Wash thoroughly after handling.

SECTION 8 : EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

Engineering Controls:	Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.
Eye/Face Protection:	Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.
Skin Protection Description:	Use neoprene, nitrile or rubber gloves and other protective apparel to prevent skin contact. Consult manufacturer's data for permeability data.
Respiratory Protection:	A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.
Other Protective:	Facilities storing or utilizing this material should be equipped with an eyewash and a deluge shower safety station.

EXPOSURE GUIDELINES

Benzoyl peroxide :

Guideline ACGIH: ACGIH TLV-TWA 5 mg/m³

Guideline OSHA: OSHA PEL-TWA 5 mg/m³

Dibutyl phthalate :

Guideline ACGIH: ACGIH TLV-TWA 5 mg/m³

Guideline OSHA: OSHA PEL-TWA 5 mg/m³

Notes : Only established PEL and TLV values for the ingredients are listed.

SECTION 9 : PHYSICAL and CHEMICAL PROPERTIES

Physical State Appearance:	Paste.
Color:	Black.
Odor:	Mild.
Boiling Point:	642°F (339°C)
Melting Point:	Not determined.
Density:	15.07 lb/gal
Solubility:	Insoluble in water.
Vapor Density:	> 1 (air = 1)
Vapor Pressure:	Not determined.
Percent Volatile:	By Weight: 0.00% By Volume: 0.00%
Evaporation Rate:	Slower than butyl acetate.
pH:	Not determined.
Flash Point:	201°F (93.3°C)
Flash Point Method:	Setaflash Closed Cup
Auto Ignition Temperature:	Not determined.
VOC Content:	0 lb/gal, 0 g/L

SECTION 10 : STABILITY and REACTIVITY

Chemical Stability:	Product is stable under normal conditions.
Hazardous Polymerization:	Will not occur under normal conditions.
Conditions to Avoid:	High temperatures.
Incompatible Materials:	Strong acids, bases and strong oxidizers.

SECTION 11 : TOXICOLOGICAL INFORMATION

Benzoyl peroxide :

Eye:	Eye - Rabbit Standard Draize test. : 500 mg/24H - [mild](RTECS)
Skin:	Skin - Human Standard Draize test. : 5%/8W-I - [severe](RTECS) Skin - Mammal species unspecified LD50: >1 gm/kg - [Details of toxic effects not reported other than lethal dose value](RTECS)
Ingestion:	Oral - Rat LD50: 6400 mg/kg - [Details of toxic effects not reported other than lethal dose value] (RTECS) Oral - Mouse LD50: 1200 mg/kg - [Details of toxic effects not reported other than lethal dose value] (RTECS)

Dibutyl phthalate :

Skin:	Skin - Rabbit LD50: >20 mL/kg - [Details of toxic effects not reported other than lethal dose value] (RTECS) Skin - Rat LDLo: 6 gm/kg - [Details of toxic effects not reported other than lethal dose value](RTECS)
Inhalation:	Inhalation - Rat LC50: 4250 mg/m3 - [Details of toxic effects not reported other than lethal dose value] (RTECS) Inhalation - Mouse LC50: 25 gm/m3/2H - [Details of toxic effects not reported other than lethal dose value] (RTECS)
Ingestion:	Oral - Rat LD50: 7499 mg/kg - [Details of toxic effects not reported other than lethal dose value] (RTECS) Oral - Mouse LD50: 3474 mg/kg - [Details of toxic effects not reported other than lethal dose value] (RTECS)

SECTION 12 : ECOLOGICAL INFORMATION

Ecotoxicity:	No ecotoxicity data was found for the product.
Environmental Fate:	No environmental information found for this product.

SECTION 13 : DISPOSAL CONSIDERATIONS

Epoxy resin :

Waste Disposal:	Disposal should be done in accordance with Federal (40 CFR Part 261), State and local environmental control regulations. If waste is determined to be hazardous, use licensed hazardous waste transporter and disposal facility.
Waste Disposal:	Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.

SECTION 14 : TRANSPORT INFORMATION

DOT Shipping Name:	Non regulated.
DOT UN Number:	Non regulated.
DOT Exemption:	Not regulated in non bulk packages per CFR 49 173.150 (f) (2).

SECTION 15 : REGULATORY INFORMATION

Benzoyl peroxide :

TSCA Inventory Status:	Listed
SARA:	EPCRA - 40 CFR Part 372 - (SARA Title III) Section 313 Listed Chemical.
State Regulations:	Listed in the State of Massachusetts Hazardous Substance List. Listed in the New Jersey State Right to Know List. Listed in the Pennsylvania State Hazardous Substances List.
New Jersey:	Listed: NJ Hazardous List; Substance Number: 0215
Massachusetts:	Listed: Massachusetts Oil and Hazardous List
Pennsylvania:	Listed
EC Number:	617-008-00-0

Dibutyl phthalate :

TSCA Inventory Status:	Listed
------------------------	--------

SARA: EPCRA - 40 CFR Part 372 - (SARA Title III) Section 313 Listed Chemical.

State Regulations: Listed in the State of Massachusetts Hazardous Substance List.
Listed in the New Jersey State Right to Know List.
Listed in the Pennsylvania State Hazardous Substances List.

New Jersey: Listed: NJ Hazardous List; Substance Number: 0773

Massachusetts: Listed: Massachusetts Oil and Hazardous List

Pennsylvania: Listed

Canada WHMIS: WHMIS Hazard Class(es): D2B
This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by the Controlled Products Regulations.

SECTION 16 : ADDITIONAL INFORMATION

HMIS Ratings:

HMIS Health Hazard: 2
HMIS Fire Hazard: 1
HMIS Reactivity: 1
HMIS Personal Protection: 1

SDS Creation Date: October 12, 2010
SDS Revision Date: July 01, 2013
SDS Author: Actio Corporation

Copyright© 1996-2018 Enviance. All Rights Reserved.