

# **SAFETY DATA SHEET**

## SECTION 1: IDENTIFICATION

Product identifier used on

the label:

**Resin Bonded WHEEL** Product Name: Product Code: **Bonded Abrasives** UPC Number: 61463670735

Other means of identification:

Recommended use of the chemical and restrictions on use:

Product Use/Restriction: Abrasive Product.

Chemical manufacturer address and telephone number:

**United States** <u>Canada</u>

Manufacturer Name: Saint-Gobain Abrasives, Inc. Saint-Gobain Canada, Inc. Address: 1 New Bond Street 28 Albert Street, W. Worcester, MA 01615 Plattsville, ON NOJ 1S0 Website:

www.Nortonabrasives.com www.Nortonabrasives.com

800-551-4413 519-684-7441 General Phone Number:

Emergency phone number:

**Emergency Phone** 

Number:

508-795-5000

CHEMTREC: For emergencies in the US, call

For emergencies in Canada, call CHEMTREC: 800-424-9300 CHEMTREC: 800-424-9300

508-795-5000

## SECTION 2: HAZARD(S) IDENTIFICATION

### Classification of the chemical in accordance with CFR 1910.1200(d)(f):

Signal Word: Not applicable.

GHS Class: Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Hazard Statements: Not applicable. Precautionary Statements: Not applicable.

Hazards not otherwise classified that have been identified during the classification process:

Route of Exposure: Eyes. Skin. Inhalation. Ingestion.

Eye: Causes eye irritation. Skin: Causes skin irritation.

Inhalation: Prolonged or excessive inhalation may cause respiratory tract irritation.

Resin Bonded WHEEL 61463670735 Ingestion: May be harmful if swallowed. May cause vomiting.

Chronic Health Effects: Prolonged or repeated contact may cause skin irritation.

Signs/Symptoms: Overexposure may cause headaches and dizziness.

Target Organs: Eyes. Skin. Respiratory system. Digestive system.

Aggravation of Pre-Existing

Conditions:

None generally recognized.

#### **Fiberglass**

Inhalation: Fiberglass contained in wheels have fiber diameters greater than 10 um, therefore considered

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### Mixtures:

Chemical Name	CAS#	Ingredient Percent	EC Num.
bisphenol A/F epoxy resin	40216-08-8	5 - 10 by weight	
Sulfates/Sulfides	No Data	10 - 30 by weight	
Calcium carbonate	1317-65-3	1 - 5 by weight	215-279-6
Zirconium dioxide	1314-23-4	5 - 10 by weight	215-227-2
Resin	9003-35-4	1 - 5 by weight	
Fiberglass	65997-17-3	1 - 5 by weight	266-046-0
Aluminum Oxide, Non-fibrous	1344-28-1	30 - 60 by weight	215-691-6
Natas	Actual arinding tosts with who	la known to contain Coustalling Cilian did no	at produce any detectable amount

Actual grinding tests with wheels known to contain Crystalline Silica did not produce any detectable amount Notes:

of respirable free Crystalline Silica.

## SECTION 4: FIRST AID MEASURES

#### Description of necessary measures:

Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the Eye Contact:

eyes by separating the eyelids with fingers. Remove contacts if present and easy to do. Continue rinsing.

Get medical attention, if irritation or symptoms of overexposure persists.

Skin Contact: Immediately wash skin with soap and plenty of water.

Get medical attention if irritation develops or persists.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained

personnel. Seek immediate medical attention.

Ingestion: If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give

anything by mouth to an unconscious person.

### Most important symptoms/effects, acute and delayed:

Other First Aid: Not applicable.

Resin Bonded WHEEL 61463670735

## <u>Indication of immediate medical attention and special treatment needed:</u>

Note to Physicians: Not applicable.

## SECTION 5: FIRE FIGHTING MEASURES

#### Suitable and unsuitable extinguishing media:

Suitable Extinguishing Media: Use alcohol resistant foam, carbon dioxide, dry chemical, or water fog or spray when fighting fires

involving this material.

Unsuitable extinguishing media: Not applicable.

#### Specific hazards arising from the chemical:

Hazardous Combustion Not applicable.

Byproducts:

Unusual Fire Hazards: Not applicable.

#### Special protective equipment and precautions for fire-fighters:

Protective Equipment: As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent)

and full protective gear.

Fire Fighting Instructions: Not applicable.

**NFPA Ratings**:

NFPA Health: 1 NFPA Flammability: 1 NFPA Reactivity: 0



#### SECTION 6: ACCIDENTAL RELEASE MEASURES

## Personal precautions, protective equipment and emergency procedures:

Personal Precautions: Evacuate area and keep unnecessary and unprotected personnel from entering the spill area. Use proper

personal protective equipment as listed in Section 8.

**Environmental precautions:** 

**Environmental Precautions:** Avoid runoff into storm sewers, ditches, and waterways.

Methods and materials for containment and cleaning up:

Spill Cleanup Measures: Not applicable.

Methods and materials for containment and cleaning up:

Methods for containment: Contain spills with an inert absorbent material such as soil or sand. Prevent from spreading by covering,

diking or other means. Provide ventilation.

Methods for cleanup: Clean up spills immediately observing precautions in the protective equipment section. Place into a

suitable container for disposal. Provide ventilation. After removal, flush spill area with soap and water to

remove trace residue.

Reference to other sections:

Other Precautions: Not applicable.

Resin Bonded WHEEL 61463670735 Revison Date: 06/03/2018

## SECTION 7: HANDLING and STORAGE

Precautions for safe handling:

Handling: Use with adequate ventilation. Avoid breathing vapor and contact with eyes, skin and clothing.

Hygiene Practices: Wash thoroughly after handling. Avoid contact with eyes and skin. Avoid inhaling vapor or mist.

Conditions for safe storage, including any incompatibilities:

Storage: Store in a cool, dry, well ventilated area away from sources of heat, combustible materials, and

incompatible substances. Keep container tightly closed when not in use.

## SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

#### **EXPOSURE GUIDELINES:**

Ingredient	Guideline OSHA	Guideline ACGIH	Quebec Canada	Ontario Canada	Alberta Canada
Calcium carbonate			VEMP-TWA: 10 mg/m3 Total particulate/dust (T)		OEL-TWA: 10 mg/m3
Zirconium dioxide		TLV-TWA: 10 mg/m3 as zirconium compounds			
Fiberglass	PEL-TWA: 1 f/cc as Continuous filament glass	TLV-TWA: 1 f/cc as Continuous filament glass TLV-TWA: 5 mg/m3 as Continuous filament glass			
Aluminum Oxide, Non-fibrous	PEL-TWA: 5 mg/m3 Respirable fraction (R) PEL-TWA: 15 mg/m3 Total particulate/dust (T)	TLV-TWA: 10 mg/m3	VEMP-TWA: 10 mg/m3 Total particulate/dust (T)	OEL-TWAEV: 10 mg/m3 Total particulate/dust (T)	OEL-TWA: 10 mg/m3
Ingredient	Mexico	British Columbia			
		Canada			
Calcium carbonate		Canada  OEL-TWA: 10 mg/m3 Total particulate/dust (T) OEL-TWA: 3 mg/m3 Respirable fraction (R) OEL-STEL: 20 mg/m3 Total particulate/dust (T)			

#### Appropriate engineering controls:

Engineering Controls:

Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general

ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of

the personal protective equipment.

Individual protection measures:

Eye/Face Protection: Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and

face protection regulation, or the European standard EN 166.

Skin Protection Description: Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be

used to prevent contact with eyes, skin or clothing.

 Resin Bonded WHEEL
 61463670735

 Revison Date: 06/03/2018
 4 of 8

Respiratory Protection: A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible

under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if

there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

Other Protective: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

PPE Pictograms:



Not determined.

Not determined.

Not determined.

## SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

#### PHYSICAL AND CHEMICAL PROPERTIES:

Physical State Appearance: Solid article.

Color: Not determined.

Odor: Odorless.

Odor Threshold: Not determined.

**Boiling Point:** Not determined.

Melting Point: Density: Not determined.

Solubility: Not determined.

Vapor Density:

Not determined. Vapor Pressure:

**Evaporation Rate:** Not determined.

pH: Not determined.

Viscosity: Not determined.

Coefficient of Water/Oil Distribution:

Flammability:

Not determined.

Flash Point: None.

Lower Flammable/Explosive Limit: Not applicable. Upper Flammable/Explosive Limit: Not applicable.

Auto Ignition Temperature: Not applicable.

**Explosive Properties:** Excessive dust accumulation could present a potential combustible dust hazard.

VOC Content: Not determined.

## SECTION 10: STABILITY and REACTIVITY

Reactivity:

Reactivity: Not applicable.

Chemical Stability:

Chemical Stability: Stable under normal temperatures and pressures.

Possibility of hazardous reactions:

Hazardous Polymerization: Not reported.

Resin Bonded WHEEL 61463670735 5 of 8 Revison Date: 06/03/2018

Conditions To Avoid:

Conditions to Avoid: Heat, flames, incompatible materials, and freezing or temperatures below 32 deg. F.

Incompatible Materials:

Incompatible Materials: Oxidizing agents. Strong acids and alkalis.

<u>Hazardous Decomposition Products:</u>

Special Decomposition Products: Not applicable.

## SECTION 11: TOXICOLOGICAL INFORMATION

#### TOXICOLOGICAL INFORMATION:

Acute Toxicity: This product has not been tested for its toxicity.

Carcinogens:							
	ACGIH	NIOSH	OSHA	IARC	NTP		MEXICO
Aluminum Oxide, Non-fibrous	A4 Not Classifiable as a Human Carcinogen	No Data	No Data	No Data	No Data		A4 Not Classifiable as a Human Carcinogen

**Calcium carbonate:** 

RTECS Number: EV9580000

**Zirconium dioxide:** 

RTECS Number: ZH8800000

Resin:

RTECS Number: SM8542500

Skin: Administration onto the skin - Rat LD50 : >2 gm/kg [Details of toxic effects not reported other than

lethal dose value ] (RTECS)

Ingestion: Oral - Rat LD50 : >5 gm/kg [Details of toxic effects not reported other than lethal dose value ] (RTECS)

Fiberglass:

RTECS Number: LK3651000

Aluminum Oxide, Non-fibrous:

RTECS Number: BD1200000

Inhalation: Inhalation - Rat TCLo: 200 mg/m3/5H/28W (Intermittent) [Lungs, Thorax, or Respiration - Structural or

functional change in trachea or bronchi; Lungs, Thorax, or Respiration - Chronic pulmonary edema;

Related to Chronic Data - death] (RTECS)

## SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:

Ecotoxicity: Please contact the phone number or address of the manufacturer listed in Section 1 for information on

ecotoxicity.

## **SECTION 13: DISPOSAL CONSIDERATIONS**

 Resin Bonded WHEEL
 61463670735

 Revison Date: 06/03/2018
 6 of 8

#### Description of waste:

Waste Disposal:

Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.

## **SECTION 14: TRANSPORT INFORMATION**

UN number:

Not regulated as hazardous material for transportation.

UN proper shipping name:

Not regulated as hazardous material for transportation.

Transport hazard class(es):

Not regulated as hazardous material for transportation.

Packing group:

Not regulated as hazardous material for transportation.

Environmental hazards:

Not regulated as hazardous material for transportation.

Special precautions for user:

Not regulated as hazardous material for transportation.

#### **SECTION 15: REGULATORY INFORMATION**

Safety, health and environmental regulations specific for the product:

## **Inventory Status**

	Japan ENCS	EINECS Number	South Korea KECL	Australia AICS	Canada NDSL
Calcium carbonate					Listed
Aluminum Oxide, Non-fibrous	(1) -23	262-373-8	KE-01012	Listed	

	Canada DSL	TSCA Inventory Status		
Calcium carbonate		Listed		
Zirconium dioxide	Listed	Listed		
Resin	Listed	Listed		
Fiberglass	Listed	Listed		
Aluminum Oxide, Non-fibrous	Listed	Listed		

#### **Aluminum Oxide, Non-fibrous:**

Canada IDL: Identified under the Canadian Hazardous Products Act Ingredient Disclosure List: 0.1%.50(1298)

<u>Calcium carbonate</u>:

EC Number: 215-279-6

Zirconium dioxide:

EC Number: 215-227-2

Fiberglass:

 Resin Bonded WHEEL
 61463670735

 Revison Date: 06/03/2018
 7 of 8

EC Number: 266-046-0

**Aluminum Oxide, Non-fibrous:** 

EC Number: 215-691-6

# **State Right To Know**

	RI	MN	IL	PA	MA
Calcium carbonate				Listed	Listed
Zirconium dioxide					Listed
Aluminum Oxide, Non-fibrous	Listed	Listed	No Data	Listed	Listed

	NJ		
Aluminum Oxide, Non-fibrous	Listed: NJ Hazardous List; Substance Number: 2891		

# SECTION 16: ADDITIONAL INFORMATION

## **HMIS Ratings**:

HMIS Health Hazard: 1
HMIS Fire Hazard: 1
HMIS Reactivity: 0

Health Hazard	1
Fire Hazard	1
Reactivity	0
Personal Protection	

SDS Creation Date:

SDS Revision Date:

June 03, 2018

SDS Revision Notes:

GHS Update

 $\label{lem:copyright} \mbox{Copyright} \mbox{$\stackrel{\frown}{$}$} \mbox{1996-2018 Enviance. All Rights Reserved.}$ 

 Resin Bonded WHEEL
 61463670735

 Revison Date: 06/03/2018
 8 of 8