



# Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

## STP Octane Booster

Version number: 9.0  
Replaces version of: 2021-12-16 (8)

Revision: 2022-07-13

### SECTION 1: Identification

#### 1.1 Product identifier

Trade name

**STP Octane Booster**

Alternative number(s)

071153785922, 071153175624, 071153785748,  
067788171124, 067788171209, 071153785748

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

General use

#### 1.3 Details of the supplier of the safety data sheet

Energizer Manufacturing, Inc.  
25225 Detroit Rd.  
Westlake OH 44145  
United States

Telephone: 800-383-7323; 314-985-2000 (USA / CANADA)  
e-mail: Autocare.regulatory@energizer.com  
Website: <http://data.energizer.com>

Energizer Trading Ltd.  
Sword House, Totteridge Road, High Wycombe, HP13 6DG, UK

Telephone: +44(0)8000353376  
e-mail: ConsumerServiceEU@energizer.com

#### 1.4 Emergency telephone number

Emergency information service

1-314-985-1511 Int'l: 1-800-526-4727  
This number is only available during the following  
office hours: Mon-Fri 09:00 AM - 05:00 PM

### SECTION 2: Hazard identification

#### 2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Category	Hazard class and category	Hazard statement
2.6	flammable liquid	3	Flam. Liq. 3	H226
3.1I	acute toxicity (inhal.)	3	Acute Tox. 3	H331
3.2	skin corrosion/irritation	2	Skin Irrit. 2	H315
3.5	germ cell mutagenicity	1B	Muta. 1B	H340
3.6	carcinogenicity	1A	Carc. 1A	H350

## STP Octane Booster

Version number: 9.0  
Replaces version of: 2021-12-16 (8)

Revision: 2022-07-13

Section	Hazard class	Category	Hazard class and category	Hazard statement
3.7	reproductive toxicity	2	Repr. 2	H361d
3.8D	specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336
3.9	specific target organ toxicity - repeated exposure	2	STOT RE 2	H373
3.10	aspiration hazard	1	Asp. Tox. 1	H304

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources.

## 2.2 Label elements

Labeling

- Signal word                      danger

- Pictograms

GHS02, GHS06, GHS07,  
GHS08



- Hazard statements

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs (nervous system) through prolonged or repeated exposure.

- Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves.



# Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

## STP Octane Booster

Version number: 9.0  
Replaces version of: 2021-12-16 (8)

Revision: 2022-07-13

### - Precautionary statements

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P302+P352	IF ON SKIN: Wash with plenty of water.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P311	Call a POISON CENTER/doctor.
P321	Specific treatment (see on this label).
P331	Do NOT induce vomiting.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with national regulations.

### - Hazardous ingredients for labelling

Distillates (petroleum), hydrodesulfurized middle, Naphthalene, Benzene, Jet A-1, toluene, Heavy aromatic naphtha

### 2.3 Other hazards

of no significance













## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not relevant (mixture)

### 3.2 Mixtures



























Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
Straight-run Kerosene	CAS No 64741-44-2	10 – < 25	Flam. Liq. 3 / H226 Acute Tox. 4 / H332	 
Distillates (petroleum), hydrodesulfurized middle	CAS No 64742-80-9	10 – < 25	Flam. Liq. 3 / H226 Acute Tox. 4 / H332 Carc. 1B / H350	  
Distillates (petroleum), hydrodesulfurized light catalytic cracked	CAS No 68333-25-5	10 – < 25	Flam. Liq. 3 / H226 Acute Tox. 4 / H332 Carc. 1B / H350 Asp. Tox. 1 / H304	  
Jet A-1	CAS No 8008-20-6	10 – < 25	Flam. Liq. 3 / H226 Acute Tox. 3 / H331 Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304	   

## STP Octane Booster

Version number: 9.0  
Replaces version of: 2021-12-16 (8)

Revision: 2022-07-13

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
Kerosine (petroleum), hydrodesulfurized	CAS No 64742-81-0	5 – < 10	Flam. Liq. 3 / H226 Acute Tox. 3 / H331 Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304	   
Distillates (petroleum), light hydrocracked	CAS No 64741-77-1	1 – < 5	Flam. Liq. 3 / H226 Acute Tox. 3 / H331 Carc. 2 / H351	  
Solvent naphtha (petroleum), light arom.	CAS No 64742-95-6	1 – < 5	Flam. Liq. 1 / H224 Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304	  
Tricarbonyl(methylcyclopentadienyl)manganese	CAS No 12108-13-3	1 – < 5	Acute Tox. 3 / H301 Acute Tox. 2 / H310 Acute Tox. 1 / H330	
1,2,4 trimethylbenzene	CAS No 95-63-6	1 – < 5	Flam. Liq. 3 / H226 Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 STOT SE 3 / H335 Asp. Tox. 1 / H304	  
Heavy aromatic naphtha	CAS No Proprietary	1 – < 5	Flam. Liq. 3 / H226 STOT SE 3 / H335 STOT SE 3 / H336 STOT RE 2 / H373 Asp. Tox. 1 / H304	  
Naphthalene	CAS No 91-20-3	< 1	Acute Tox. 4 / H302 Acute Tox. 1 / H330 Carc. 2 / H351 STOT SE 2 / H371 STOT RE 2 / H373	 
Cumene	CAS No 98-82-8	< 1	Flam. Liq. 3 / H226 Carc. 2 / H351 STOT SE 3 / H335 Asp. Tox. 1 / H304	  
2-ethylhexan-1-ol	CAS No 104-76-7	< 1	Flam. Liq. 4 / H227 Acute Tox. 2 / H330	
Benzene	CAS No 71-43-2	< 1	Flam. Liq. 2 / H225 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Muta. 1B / H340 Carc. 1A / H350 STOT RE 1 / H372 Asp. Tox. 1 / H304	  







# Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

## STP Octane Booster

Version number: 9.0  
Replaces version of: 2021-12-16 (8)

Revision: 2022-07-13

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
toluene	CAS No 108-88-3	< 1	Flam. Liq. 2 / H225 Acute Tox. 1 / H330 Skin Irrit. 2 / H315 Repr. 2 / H361d STOT SE 3 / H336 STOT RE 2 / H373 Asp. Tox. 1 / H304	   

For full text of abbreviations: see SECTION 16.

### SECTION 4: First-aid measures

#### 4.1 Description of first-aid measures

##### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

##### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

##### Following skin contact

Wash with plenty of soap and water.

##### Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

##### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed

Narcotic effects.

#### 4.3 Indication of any immediate medical attention and special treatment needed

none

### SECTION 5: Fire-fighting measures

#### 5.1 Extinguishing media

##### Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO<sub>2</sub>)

##### Unsuitable extinguishing media

Water jet



# Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

## STP Octane Booster

Version number: 9.0  
Replaces version of: 2021-12-16 (8)

Revision: 2022-07-13

### 5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

### 6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.



# Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

## STP Octane Booster

Version number: 9.0  
Replaces version of: 2021-12-16 (8)

Revision: 2022-07-13

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

##### Recommendations

##### - Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

##### - Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

##### Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedings.

#### 7.2 Conditions for safe storage, including any incompatibilities

##### Managing of associated risks

##### - Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

##### - Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

##### - Ventilation requirements

Keep any substance that emits harmful vapors or gases in a place that allows these to be permanently extracted. Use local and general ventilation. Ground/bond container and receiving equipment.

##### - Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

#### 7.3 Specific end use(s)

See section 16 for a general overview.



# Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

## STP Octane Booster

Version number: 9.0  
Replaces version of: 2021-12-16 (8)

Revision: 2022-07-13

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
CA	toluene	108-88-3	OEL (BC)	20							"BC Regulation"
CA	toluene	108-88-3	OEL (ON-MoL)	20							MoL
CA	toluene	108-88-3	PEV/VEA	50	188					H	Regulation OHS
CA	toluene (toluol)	108-88-3	OEL (AB)	50	188					H	OHS Code
CA	2-methylcyclopentadienyl manganese tricarbonyl	12108-13-3	OEL (AB)		0.2					Mn, H	OHS Code
CA	2-methylcyclopentadienyl manganese tricarbonyl	12108-13-3	OEL (BC)		0.2					Mn, H	"BC Regulation"
CA	2-methylcyclopentadienyl manganese tricarbonyl	12108-13-3	OEL (ON-MoL)		0.2					Mn, H	MoL
CA	manganese-methylcyclopentadienyltricarbonyl	12108-13-3	PEV/VEA		0.2					Mn, H	Regulation OHS
CA	Kerosine (petroleum), hydrodesulfurized	64742-81-0	OEL (AB)		200					Hy-Carb, vap, i, H	OHS Code
CA	Kerosine - unspecified	64742-81-0	OEL (ON-MoL)		200					Hy-Carb, vap, H	MoL





# Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

## STP Octane Booster

Version number: 9.0  
Replaces version of: 2021-12-16 (8)

Revision: 2022-07-13

### Occupational exposure limit values (Workplace Exposure Limits)

Coun try	Name of agent	CAS No	Iden- tifier	TWA [ppm]	TWA [mg/ m <sup>3</sup> ]	STEL [ppm]	STEL [mg/ m <sup>3</sup> ]	Ceil- ing-C [ppm]	Ceil- ing-C [mg/ m <sup>3</sup> ]	Nota tion	Sourc e
CA	benzene	71-43-2	PEV/ VEA	1	3	5	15.5				Regu- lation OHS
CA	benzene	71-43-2	OEL (AB)	0.5	1.6	2.5	8			H	OHS Code
CA	benzene	71-43-2	OEL (BC)	0.5		2.5				H	"BC Regu- lation"
CA	benzene	71-43-2	OEL (ON)	0.5		2.5				H	Regu- lation 833
CA	benzene	71-43-2	OEL (ON- MoL)	0.5		2.5				H	MoL
CA	jet fuels, JP 5	8008-20- 6	OEL (AB)		200					Hy- Carb, vap, i, H	OHS Code
CA	Kerosine (petro- leum)	8008-20- 6	OEL (BC)		200					Hy- Carb, i, vap, H	"BC Regu- lation"
CA	Kerosine (petro- leum) (jet fuels, JP 5)	8008-20- 6	OEL (ON- MoL)		200					Hy- Carb, vap, H	MoL
CA	naphthalene	91-20-3	OEL (AB)	10	52	15	79			H	OHS Code
CA	naphthalene	91-20-3	OEL (BC)	10						H	"BC Regu- lation"
CA	naphthalene	91-20-3	OEL (ON- MoL)	10						H	MoL
CA	naphthalene	91-20-3	PEV/ VEA	10						H	Regu- lation OHS
CA	cumene	98-82-8	OEL (AB)	50	246						OHS Code



# Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

## STP Octane Booster

Version number: 9.0  
Replaces version of: 2021-12-16 (8)

Revision: 2022-07-13

### Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
CA	cumene	98-82-8	OEL (BC)	25		75					"BC Regulation"
CA	cumene	98-82-8	OEL (ON-MoL)	50							MoL
CA	cumene	98-82-8	PEV/VEA	50	246						Regulation OHS

#### Notation

Ceiling-C	ceiling value is a limit value above which exposure should not occur
H	absorbed through the skin
HyCarb	calculated as hydrocarbons
i	inhalable fraction
Mn	calculated as Mn (manganese)
STEL	short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
TWA	time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)
vap	as vapors

### Relevant DNELs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Straight-run Kerosene	64741-44-2	DNEL	16.4 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
Straight-run Kerosene	64741-44-2	DNEL	1,501 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - systemic effects
Straight-run Kerosene	64741-44-2	DNEL	2.91 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Distillates (petroleum), hydrosulfurized light catalytic cracked	68333-25-5	DNEL	27.3 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
Distillates (petroleum), hydrosulfurized light catalytic cracked	68333-25-5	DNEL	2,230 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - systemic effects



# Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

## STP Octane Booster

Version number: 9.0  
Replaces version of: 2021-12-16 (8)

Revision: 2022-07-13

### Relevant DNELs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Distillates (petroleum), hydrosulfurized light catalytic cracked	68333-25-5	DNEL	2.4 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Distillates (petroleum), light hydrocracked	64741-77-1	DNEL	68.34 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
Distillates (petroleum), light hydrocracked	64741-77-1	DNEL	4,288 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - systemic effects
Distillates (petroleum), light hydrocracked	64741-77-1	DNEL	2.91 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Tricarbonyl(methylcyclopentadienyl)manganese	12108-13-3	DNEL	0.6 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
Tricarbonyl(methylcyclopentadienyl)manganese	12108-13-3	DNEL	0.11 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
1,2,4 trimethylbenzene	95-63-6	DNEL	100 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
1,2,4 trimethylbenzene	95-63-6	DNEL	100 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - systemic effects
1,2,4 trimethylbenzene	95-63-6	DNEL	100 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
1,2,4 trimethylbenzene	95-63-6	DNEL	100 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
1,2,4 trimethylbenzene	95-63-6	DNEL	16,171 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Naphthalene	91-20-3	DNEL	25 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
Naphthalene	91-20-3	DNEL	25 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
Naphthalene	91-20-3	DNEL	3.57 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Cumene	98-82-8	DNEL	100 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
Cumene	98-82-8	DNEL	250 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects

## STP Octane Booster

Version number: 9.0  
Replaces version of: 2021-12-16 (8)

Revision: 2022-07-13

### Relevant DNELs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Cumene	98-82-8	DNEL	15.4 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
2-ethylhexan-1-ol	104-76-7	DNEL	12.8 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
2-ethylhexan-1-ol	104-76-7	DNEL	53.2 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
2-ethylhexan-1-ol	104-76-7	DNEL	53.2 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
2-ethylhexan-1-ol	104-76-7	DNEL	23 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
toluene	108-88-3	DNEL	192 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
toluene	108-88-3	DNEL	384 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - systemic effects
toluene	108-88-3	DNEL	192 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
toluene	108-88-3	DNEL	384 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
toluene	108-88-3	DNEL	384 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

### Relevant PNECs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
Tricarbonyl(methylcyclopentadienyl)manganese	12108-13-3	PNEC	0.21 µg/l	aquatic organisms	freshwater	short-term (single instance)
Tricarbonyl(methylcyclopentadienyl)manganese	12108-13-3	PNEC	0.021 µg/l	aquatic organisms	marine water	short-term (single instance)
Tricarbonyl(methylcyclopentadienyl)manganese	12108-13-3	PNEC	16 µg/kg	terrestrial organisms	soil	short-term (single instance)
1,2,4 trimethylbenzene	95-63-6	PNEC	0.12 mg/l	aquatic organisms	freshwater	short-term (single instance)
1,2,4 trimethylbenzene	95-63-6	PNEC	0.12 mg/l	aquatic organisms	marine water	short-term (single instance)

## STP Octane Booster

Version number: 9.0  
Replaces version of: 2021-12-16 (8)

Revision: 2022-07-13

### Relevant PNECs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
1,2,4 trimethybenzene	95-63-6	PNEC	2.41 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
1,2,4 trimethybenzene	95-63-6	PNEC	13.56 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
1,2,4 trimethybenzene	95-63-6	PNEC	13.56 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
1,2,4 trimethybenzene	95-63-6	PNEC	2.34 mg/kg	terrestrial organisms	soil	short-term (single instance)
Cumene	98-82-8	PNEC	0.035 mg/l	aquatic organisms	freshwater	short-term (single instance)
Cumene	98-82-8	PNEC	0.004 mg/l	aquatic organisms	marine water	short-term (single instance)
Cumene	98-82-8	PNEC	200 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Cumene	98-82-8	PNEC	3.22 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Cumene	98-82-8	PNEC	0.322 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Cumene	98-82-8	PNEC	0.624 mg/kg	terrestrial organisms	soil	short-term (single instance)
2-ethylhexan-1-ol	104-76-7	PNEC	0.017 mg/l	aquatic organisms	freshwater	short-term (single instance)
2-ethylhexan-1-ol	104-76-7	PNEC	0.002 mg/l	aquatic organisms	marine water	short-term (single instance)
2-ethylhexan-1-ol	104-76-7	PNEC	10 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
2-ethylhexan-1-ol	104-76-7	PNEC	0.284 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
2-ethylhexan-1-ol	104-76-7	PNEC	0.028 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
2-ethylhexan-1-ol	104-76-7	PNEC	0.047 mg/kg	terrestrial organisms	soil	short-term (single instance)
Benzene	71-43-2	PNEC	1.9 mg/l	aquatic organisms	freshwater	short-term (single instance)
Benzene	71-43-2	PNEC	1.9 mg/l	aquatic organisms	marine water	short-term (single instance)

## STP Octane Booster

Version number: 9.0  
Replaces version of: 2021-12-16 (8)

Revision: 2022-07-13

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
Benzene	71-43-2	PNEC	39 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Benzene	71-43-2	PNEC	33 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Benzene	71-43-2	PNEC	33 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Benzene	71-43-2	PNEC	4.8 mg/kg	terrestrial organisms	soil	short-term (single instance)
toluene	108-88-3	PNEC	0.68 mg/l	aquatic organisms	freshwater	short-term (single instance)
toluene	108-88-3	PNEC	0.68 mg/l	aquatic organisms	marine water	short-term (single instance)
toluene	108-88-3	PNEC	13.61 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
toluene	108-88-3	PNEC	16.39 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
toluene	108-88-3	PNEC	16.39 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
toluene	108-88-3	PNEC	2.89 mg/kg	terrestrial organisms	soil	short-term (single instance)

### 8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.



# Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

## STP Octane Booster

Version number: 9.0  
Replaces version of: 2021-12-16 (8)

Revision: 2022-07-13

### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

### Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

Physical state	liquid
Color	not determined
Particle	not relevant (liquid)
Odor	characteristic

#### Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	not determined
Flash point	38 °C
Evaporation rate	Not determined
Flammability (solid, gas)	not relevant, (fluid)

#### Explosive limits

- Lower explosion limit (LEL)	1.4 vol%
- Upper explosion limit (UEL)	7.6 vol%
Vapor pressure	≤240 kPa at 37.8 °C
Density	not determined
Vapor density	this information is not available



# Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

## STP Octane Booster

Version number: 9.0  
Replaces version of: 2021-12-16 (8)

Revision: 2022-07-13

Relative density	Information on this property is not available
Solubility(ies)	not determined
Partition coefficient	
- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	220 °C (auto-ignition temperature (liquids and gases))
Viscosity	not determined
Explosive properties	not explosive (GHS of the United Nations, annex 4)
Oxidizing properties	none

### 9.2 Other information

Temperature class (USA, acc. to NEC 500)	T2D (maximum permissible surface temperature on the equipment: 215°C)
--	---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

### 10.2 Chemical stability

See below "Conditions to avoid".

### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

### 10.5 Incompatible materials

Oxidizers





# Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

## STP Octane Booster

Version number: 9.0  
Replaces version of: 2021-12-16 (8)

Revision: 2022-07-13

### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

#### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### Classification acc. to GHS

##### Acute toxicity

Toxic if inhaled.

GHS of the United Nations, annex 4: May be harmful if swallowed.

##### - Acute toxicity estimate (ATE)

Inhalation: gas 4,187 ppmV/4h  
Inhalation: vapour 3.219 mg/l/4h

#### Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
Straight-run Kerosene	64741-44-2	inhalation: vapour	11 mg/l/4h
Straight-run Kerosene	64741-44-2	inhalation: dust/mist	>2.53 mg/l/4h
Distillates (petroleum), hydrodesulfurized middle	64742-80-9	inhalation: vapour	11 mg/l/4h
Distillates (petroleum), hydrodesulfurized middle	64742-80-9	inhalation: dust/mist	4.6 mg/l/4h
Jet A-1	8008-20-6	inhalation: vapour	>5.28 mg/l/4h
Distillates (petroleum), hydrodesulfurized light catalytic cracked	68333-25-5	inhalation: vapour	11 mg/l/4h
Distillates (petroleum), hydrodesulfurized light catalytic cracked	68333-25-5	inhalation: dust/mist	4.65 mg/l/4h
Kerosine (petroleum), hydrodesulfurized	64742-81-0	inhalation: vapour	>5.28 mg/l/4h
Distillates (petroleum), light hydrocracked	64741-77-1	inhalation: vapour	3.6 mg/l/4h
Tricarbonyl(methylcyclopentadienyl)manganese	12108-13-3	oral	51.8 mg/kg
Tricarbonyl(methylcyclopentadienyl)manganese	12108-13-3	dermal	140 mg/kg
Tricarbonyl(methylcyclopentadienyl)manganese	12108-13-3	inhalation: vapour	0.1235 mg/l/4h



# Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

## STP Octane Booster

Version number: 9.0  
Replaces version of: 2021-12-16 (8)

Revision: 2022-07-13

### Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
1,2,4 trimethybenzene	95-63-6	inhalation: vapour	11 mg/l/4h
Naphthalene	91-20-3	oral	710 mg/kg
Naphthalene	91-20-3	inhalation: vapour	>0.4 mg/l/4h
Naphthalene	91-20-3	inhalation: dust/mist	0.005 mg/l/4h
2-ethylhexan-1-ol	104-76-7	inhalation: vapour	>0.89 mg/l/4h
toluene	108-88-3	inhalation: gas	7.6 ppmV/4h

### Skin corrosion/irritation

Causes skin irritation.

### Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

### Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

### Germ cell mutagenicity

May cause genetic defects.

### Carcinogenicity

May cause cancer.

### Reproductive toxicity

Suspected of damaging the unborn child.

### Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

### Specific target organ toxicity - repeated exposure

May cause damage to organs (nervous system) through prolonged or repeated exposure.

Hazard category	Target organ	Exposure route
2	nervous system	if exposed

### Aspiration hazard

May be fatal if swallowed and enters airways.



# Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

## STP Octane Booster

Version number: 9.0  
Replaces version of: 2021-12-16 (8)

Revision: 2022-07-13

### SECTION 12: Ecological information

#### 12.1 Toxicity

Toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Straight-run Kerosene	64741-44-2	LL50	>100 mg/l	fish	24 h
Straight-run Kerosene	64741-44-2	EL50	>1,000 mg/l	aquatic invertebrates	24 h
Distillates (petroleum), hydrodesulfurized middle	64742-80-9	LL50	>100 mg/l	fish	24 h
Distillates (petroleum), hydrodesulfurized middle	64742-80-9	EL50	>1,000 mg/l	aquatic invertebrates	24 h
Jet A-1	8008-20-6	LL50	5 mg/l	fish	96 h
Jet A-1	8008-20-6	EL50	1.4 mg/l	aquatic invertebrates	48 h
Distillates (petroleum), hydrodesulfurized light catalytic cracked	68333-25-5	LL50	>0.3 mg/l	fish	96 h
Distillates (petroleum), hydrodesulfurized light catalytic cracked	68333-25-5	LC50	>0.21 mg/l	fish	96 h
Distillates (petroleum), hydrodesulfurized light catalytic cracked	68333-25-5	EL50	0.32 mg/l	aquatic invertebrates	48 h
Kerosine (petroleum), hydrodesulfurized	64742-81-0	LL50	5 mg/l	fish	96 h
Kerosine (petroleum), hydrodesulfurized	64742-81-0	EL50	1.4 mg/l	aquatic invertebrates	48 h
Distillates (petroleum), light hydrocracked	64741-77-1	LL50	>100 mg/l	fish	24 h
Distillates (petroleum), light hydrocracked	64741-77-1	EL50	180 mg/l	aquatic invertebrates	24 h
Solvent naphtha (petroleum), light arom.	64742-95-6	LL50	8.2 mg/l	fish	96 h
Solvent naphtha (petroleum), light arom.	64742-95-6	EL50	4.5 mg/l	aquatic invertebrates	48 h



# Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

## STP Octane Booster

Version number: 9.0  
Replaces version of: 2021-12-16 (8)

Revision: 2022-07-13

### Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Tricarbonyl(methylcyclopentadienyl)manganese	12108-13-3	LC50	0.21 mg/l	fish	96 h
Tricarbonyl(methylcyclopentadienyl)manganese	12108-13-3	EC50	0.94 mg/l	aquatic invertebrates	24 h
Tricarbonyl(methylcyclopentadienyl)manganese	12108-13-3	ErC50	1.7 mg/l	algae	48 h
1,2,4 trimethylbenzene	95-63-6	LC50	7.72 mg/l	fish	96 h
1,2,4 trimethylbenzene	95-63-6	EC50	2.356 mg/l	algae	96 h
Heavy aromatic naphtha	Proprietary	LC50	2 mg/l	rainbow trout (Oncorhynchus mykiss)	96 h
Heavy aromatic naphtha	Proprietary	LC50	3 mg/l	fathead minnow	72 h
Heavy aromatic naphtha	Proprietary	EC50	1.1 mg/l	water flea (Daphnia)	48 h
Heavy aromatic naphtha	Proprietary	EC50	1.1 mg/l	algae	96 h
Heavy aromatic naphtha	Proprietary	LL50	5 mg/l	fish	96 h
Heavy aromatic naphtha	Proprietary	EL50	1.4 mg/l	aquatic invertebrates	48 h
Naphthalene	91-20-3	LC50	1.6 mg/l	fish	96 h
Naphthalene	91-20-3	EC50	2.16 mg/l	aquatic invertebrates	48 h
Cumene	98-82-8	LC50	4.7 mg/l	fish	96 h
Cumene	98-82-8	EC50	2.14 mg/l	aquatic invertebrates	48 h
Cumene	98-82-8	ErC50	2.01 mg/l	algae	72 h
2-ethylhexan-1-ol	104-76-7	LC50	17.1 mg/l	fish	96 h
2-ethylhexan-1-ol	104-76-7	EC50	39 mg/l	aquatic invertebrates	48 h
2-ethylhexan-1-ol	104-76-7	ErC50	16.6 mg/l	algae	72 h
Benzene	71-43-2	LC50	5.3 mg/l	fish	96 h



# Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

## STP Octane Booster

Version number: 9.0  
Replaces version of: 2021-12-16 (8)

Revision: 2022-07-13

### Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Benzene	71-43-2	EC50	10 mg/l	aquatic invertebrates	24 h
Benzene	71-43-2	ErC50	100 mg/l	algae	72 h
toluene	108-88-3	LC50	5.5 mg/l	fish	96 h
toluene	108-88-3	EC50	84 mg/l	microorganisms	24 h

### Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Straight-run Kerosene	64741-44-2	EL50	>1,000 mg/l	microorganisms	40 h
Distillates (petroleum), hydrodesulfurized middle	64742-80-9	EL50	>1,000 mg/l	microorganisms	40 h
Jet A-1	8008-20-6	EL50	0.89 mg/l	aquatic invertebrates	21 d
Distillates (petroleum), hydrodesulfurized light catalytic cracked	68333-25-5	EL50	0.22 mg/l	aquatic invertebrates	21 d
Distillates (petroleum), hydrodesulfurized light catalytic cracked	68333-25-5	EC50	0.17 mg/l	aquatic invertebrates	21 d
Kerosine (petroleum), hydrodesulfurized	64742-81-0	EL50	0.89 mg/l	aquatic invertebrates	21 d
Distillates (petroleum), light hydrocracked	64741-77-1	EL50	>1,000 mg/l	microorganisms	40 h
Solvent naphtha (petroleum), light arom.	64742-95-6	EL50	10 mg/l	fish	21 d
Solvent naphtha (petroleum), light arom.	64742-95-6	EC50	15.41 mg/l	microorganisms	40 h
Heavy aromatic naphtha	Proprietary	EL50	0.89 mg/l	aquatic invertebrates	21 d
Naphthalene	91-20-3	EC50	2.96 mg/l	algae	4 h
Cumene	98-82-8	EC50	1.5 mg/l	aquatic invertebrates	21 d
Cumene	98-82-8	LC50	>3 mg/l	aquatic invertebrates	21 d



# Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

## STP Octane Booster

Version number: 9.0  
Replaces version of: 2021-12-16 (8)

Revision: 2022-07-13

Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
toluene	108-88-3	LC50	3.78 mg/l	aquatic invertebrates	2 d
toluene	108-88-3	EC50	3.23 mg/l	aquatic invertebrates	7 d

### 12.2 Persistence and degradability

Data are not available.

### 12.3 Bioaccumulative potential

Data are not available.

### 12.4 Mobility in soil

Data are not available.

### 12.5 Results of PBT and vPvB assessment

Data are not available.

### 12.6 Endocrine disrupting properties

None of the ingredients are listed.

### 12.7 Other adverse effects

Data are not available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

#### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.



# Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

## STP Octane Booster

Version number: 9.0  
Replaces version of: 2021-12-16 (8)

Revision: 2022-07-13

### SECTION 14: Transport information

#### 14.1 UN number

UN RTDG	UN 1268
IMDG-Code	UN 1268
ICAO-TI	UN 1268

#### 14.2 UN proper shipping name

UN RTDG	PETROLEUM DISTILLATES, N.O.S.
IMDG-Code	PETROLEUM DISTILLATES, N.O.S.
ICAO-TI	Petroleum distillates, n.o.s.

#### 14.3 Transport hazard class(es)

UN RTDG	3
IMDG-Code	3
ICAO-TI	3

#### 14.4 Packing group

UN RTDG	III
IMDG-Code	III
ICAO-TI	III

#### 14.5 Environmental hazards

hazardous to the aquatic environment

##### 14.5.1 Additional information

LTD QTY

Environmentally hazardous substance (aquatic environment)	Jet A-1
---	---------

#### 14.6 Special precautions for user

There is no additional information.

#### 14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

### Information for each of the UN Model Regulations

#### Transport information - National regulations - Additional information (UN RTDG)

UN number	1268
Class	3
Environmental hazards	yes (hazardous to the aquatic environment)
Packing group	III

## STP Octane Booster

Version number: 9.0  
Replaces version of: 2021-12-16 (8)

Revision: 2022-07-13

Danger label(s)

3, fish and tree



Special provisions (SP)

223 (UN RTDG)

Excepted quantities (EQ)

E1 (UN RTDG)

Limited quantities (LQ)

5 L (UN RTDG)

### International Maritime Dangerous Goods Code (IMDG) - Additional information

Particulars in the shipper's declaration

UN1268, PETROLEUM DISTILLATES, N.O.S., (contains: Straight-run Kerosene, Distillates (petroleum), hydrodesulfurized middle), 3, III, 38°C c.c., MARINE POLLUTANT

Marine pollutant

yes (hazardous to the aquatic environment)

Danger label(s)

3, fish and tree



Special provisions (SP)

223, 955

Excepted quantities (EQ)

E1

Limited quantities (LQ)

5 L

EmS

F-E, S-E

Stowage category

A

### International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Particulars in the shipper's declaration

UN1268, Petroleum distillates, n.o.s., (contains: Straight-run Kerosene, Distillates (petroleum), hydrodesulfurized middle), 3, III

Environmental hazards

yes (hazardous to the aquatic environment)

Danger label(s)

3



Special provisions (SP)

A3

Excepted quantities (EQ)

E1

Limited quantities (LQ)

10 L





# Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

## STP Octane Booster

Version number: 9.0  
Replaces version of: 2021-12-16 (8)

Revision: 2022-07-13

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations specific for the product in question

##### National regulations (United States)

**Toxic Substance Control Act (TSCA)** all ingredients are listed

##### Superfund Amendment and Reauthorization Act (SARA TITLE III )

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

The List of Extremely Hazardous Substances and Their Threshold Planning Quantities

Name of substance	CAS No	Notes	Reportable quantity (pounds)	Threshold planning quantity (pounds)
Tricarbonyl(methylcyclopentadienyl)manganese	12108-13-3	d	100	100

##### Legend

d Revised TPQ based on new or re-evaluated toxicity data, April 22, 1987.

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings

Name of substance	CAS No	Remarks	Effective date
Benzene	71-43-2		1987-01-01
Cumene	98-82-8		1987-01-01
1,2,4 trimethylbenzene	95-63-6		1987-01-01
Naphthalene	91-20-3		1987-01-01
toluene	108-88-3		1987-01-01

##### Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
Benzene	71-43-2	a	1 2 3 4	10 (4,54)
Cumene	98-82-8		3 4	5000 (2270)



# Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

## STP Octane Booster

Version number: 9.0  
Replaces version of: 2021-12-16 (8)

Revision: 2022-07-13

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
Naphthalene	91-20-3		1 2 3 4	100 (45,4)
toluene	108-88-3		1 2 3 4	1000 (454)

### Legend

- 1 "1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act
- 2 "2" indicates that the source is section 307(a) of the Clean Water Act
- 3 "3" indicates that the source is section 112 of the Clean Air Act
- 4 "4" indicates that the source is section 3001 of the Resource Conservation and Recovery Act (RCRA)
- a Benzene was already a CERCLA hazardous substance prior to the CAA Amendments of 1990 and received an adjusted 10-pound RQ based on potential carcinogenicity in an August 14, 1989, final rule (54 FR 33418). The CAA Amendments specify that "benzene (including benzene from gasoline)" is a hazardous air pollutant and, thus, a CERCLA hazardous substance.

### Clean Air Act

none of the ingredients are listed

### California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals			
Name acc. to inventory	CAS No	Remarks	Type of the toxicity
benzene	71-43-2		cancer
benzene	71-43-2		developmental, male
ethylbenzene	100-41-4		cancer
cumene	98-82-8		cancer
naphthalene	91-20-3		cancer
toluene	108-88-3		developmental

### Drug precursors, Chemicals designated within the Controlled Substances Act, 21 U.S.C. § 802, paragraphs 34 (list I) and 35 (list II)

Name of substance	CAS No	Listed in	Special conditions	Excluded transactions	DEA - code	Concentration limit
toluene	108-88-3	List II chemicals	SC-6594	excl-trans-12	6594	35% by Weight or Volume



# Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

## STP Octane Booster

Version number: 9.0  
Replaces version of: 2021-12-16 (8)

Revision: 2022-07-13

### Legend

excl-trans-12 List II chemicals SC-6594 Excluded transactions: Domestic and import transactions in chemical mixtures that contain acetone, ethyl ether, 2-butanone, and/or toluene, unless regulated because of being formulated with other List I or List II chemical(s) above the concentration limit. The term "list II chemical" means a chemical (other than a list I chemical) specified by regulation of the Attorney General as a chemical that is used in manufacturing a controlled substance in violation of this subchapter. Exports only; Limit applies to toluene or any combination of acetone, ethyl ether, 2-butanone, methyl isobutyl ketone, and toluene if present in the mixture by summing the concentrations for each chemical.

### Industry or sector specific available guidance(s)

#### NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

#### NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

### National regulations (Canada)

#### Domestic Substances List (DSL)/Non-domestic Substances List (NDSL)

all ingredients are listed



# Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

## STP Octane Booster

Version number: 9.0  
Replaces version of: 2021-12-16 (8)

Revision: 2022-07-13

### National inventories

Country	Inventory	Status
AU	AIIC	not all ingredients are listed
CA	DSL	not all ingredients are listed
CA	NDSL	not all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	not all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	not all ingredients are listed
US	TSCA	all ingredients are listed

#### Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NDSL	Non-domestic Substances List (NDSL)
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

### 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.



# Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

## STP Octane Booster

Version number: 9.0  
Replaces version of: 2021-12-16 (8)

Revision: 2022-07-13

### SECTION 16: Other information

#### Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.1		Classification acc. to GHS: change in the listing (table)	yes
2.2		- Pictograms: change in the listing (table)	yes
2.2		- Hazard statements: change in the listing (table)	yes
2.2		- Precautionary statements: change in the listing (table)	yes
2.2	- Hazardous ingredients for labelling: Distillates (petroleum), hydrodesulfurized middle, Naphthalene, Benzene, Kerosene, toluene, Heavy aromatic naphtha	- Hazardous ingredients for labelling: Distillates (petroleum), hydrodesulfurized middle, Naphthalene, Benzene, Jet A-1, toluene, Heavy aromatic naphtha	yes
3.2		Description of the mixture: change in the listing (table)	yes
4.1	Following inhalation: If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.	Following inhalation: If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.	yes
4.2	Most important symptoms and effects, both acute and delayed: Symptoms and effects are not known to date.	Most important symptoms and effects, both acute and delayed: Narcotic effects.	yes
11.1		Acute toxicity estimate (ATE) of components of the mixture: change in the listing (table)	yes
11.1	Skin corrosion/irritation: Shall not be classified as corrosive/irritant to skin.	Skin corrosion/irritation: Causes skin irritation.	yes
11.1	Specific target organ toxicity - single exposure: Shall not be classified as a specific target organ toxicant (single exposure).	Specific target organ toxicity - single exposure: May cause drowsiness or dizziness.	yes
12.1		Aquatic toxicity (acute) of components of the mixture: change in the listing (table)	yes
12.1		Aquatic toxicity (chronic) of components of the mixture: change in the listing (table)	yes



# Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

## STP Octane Booster

Version number: 9.0  
Replaces version of: 2021-12-16 (8)

Revision: 2022-07-13

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
14.5.1	Environmentally hazardous substance (aquatic environment): Kerosene	Environmentally hazardous substance (aquatic environment): Jet A-1	yes
15.1		NPCA-HMIS® III: change in the listing (table)	yes
15.1		National inventories: change in the listing (table)	yes

### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
"BC Regulation"	OHS Regulation: Section 5.48 (British Columbia)
Acute Tox.	Acute toxicity
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
Carc.	Carcinogenicity
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DEA	Drug Enforcement Administration
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EINECS	European Inventory of Existing Commercial Chemical Substances
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid



# Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

## STP Octane Booster

Version number: 9.0  
Replaces version of: 2021-12-16 (8)

Revision: 2022-07-13

Abbr.	Descriptions of used abbreviations
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LL50	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality
MoL	Ministry of Labor: Current Occupational Exposure Limits for Ontario Workplaces Required under Regulation 833
Muta.	Germ cell mutagenicity
NLP	No-Longer Polymer
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OHS Code	Occupational Health and Safety Code: Occupational exposure limits for chemical substances (Alberta)
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
Regulation 833	R.R.O. 1990, Reg. 833: Control of exposure to biological or chemical agents (Ontario)
Regulation OHS	Regulation respecting occupational health and safety: Permissible exposure values for airborne contaminants (Quebec)
Repr.	Reproductive toxicity
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average



# Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

## STP Octane Booster

Version number: 9.0  
Replaces version of: 2021-12-16 (8)

Revision: 2022-07-13

Abbr.	Descriptions of used abbreviations
UN RTDG	UN Recommendations on the Transport of Dangerous Good
vPvB	Very Persistent and very Bioaccumulative

### Key literature references and sources for data

Hazardous Products Regulations (HPR).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H224	Extremely flammable liquid and vapour.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H227	Combustible liquid.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H310	Fatal in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
H351	Suspected of causing cancer.





# Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

## STP Octane Booster

Version number: 9.0  
Replaces version of: 2021-12-16 (8)

Revision: 2022-07-13

Code	Text
H361d	Suspected of damaging the unborn child.
H371	May cause damage to organs.
H372	Causes damage to organs (nervous system) through prolonged or repeated exposure.
H373	May cause damage to organs (nervous system) through prolonged or repeated exposure.

### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.