# **Permatex**

# SAFETY DATA SHEET

Revision Date 21-Oct-2016 Version 4

# 1. IDENTIFICATION

**Product identifier** 

Product Name PC DISC BRAKE QUIET 255G AE

Other means of identification

Product Code 80557 Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Adhesive

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufactured and Distributed by:May Also Be Distributed by:ITW PermatexITW Permatex Canada6875 Parkland Blvd.35 Brownridge Road, Unit 1Solon, OH 44139 USAHalton Hills, ON Canada L7G 0C6

Telephone: (800) 924-6994

Company Phone Number 1-87-Permatex

(877) 376-2839

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

E-mail address mail@permatex.com

# 2. HAZARDS IDENTIFICATION

# Classification

# **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Liquefied gas

### Label elements

### **Emergency Overview**

Danger	
Causes skin irritation	

Causes serious eye irritation

Suspected of damaging fertility or the unborn child

May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways

Extremely flammable aerosol

Contains gas under pressure; may explode if heated



Appearance Blue Physical state Liquid Odor Solvent

### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Wear eye/face protection

Do not breathe dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Do not spray on an open flame or other ignition source

Pressurized container: Do not pierce or burn, even after use

### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

Specific treatment (see supplemental first aid instructions on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eve irritation persists: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

If skin irritation occurs: Get medical advice/attention

Take off contaminated clothing and wash before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

In case of fire: Use CO2, dry chemical, or foam for extinction

# **Precautionary Statements - Storage**

Store locked up

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

### Hazards not otherwise classified (HNOC)

Not applicable

# Other Information

- The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0.1 % w/w 1,3-butadiene (EINECS No. 203-450-8). If the substance is not classified as a carcinogen or mutagen, at least the S-phrases (2-)9-16 (Table 3.2) should apply. This note applies only to certain complex oil-derived substances in Part 3
- The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7).

Unknown acute toxicity 15 % of the mixture consists of ingredient(s) of unknown toxicity

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

### Substance(s)

Chemical Name	CAS No	Weight-%	Trade Secret
ACETONE	67-64-1	15 - 40	*
PETROLEUM GASES, LIQUEFIED, SWEETENED	68476-86-8	10 - 30	*
N-HEXANE	110-54-3	10 - 30	*
SOLVENT NAPHTHA (PETROLEUM), LIGHT	64742-89-8	3 - 7	*
ALIPH.			
ETHYL ACETATE	141-78-6	3 - 7	*

### 4. FIRST AID MEASURES

**Description of first aid measures** 

General advice Get medical advice/attention if you feel unwell.

**Eve contact** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Skin contact IF ON SKIN:. Wash skin with soap and water. If skin irritation persists, call a physician.

Wash contaminated clothing before reuse.

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion IF SWALLOWED:. Call a physician or poison control center immediately. Do NOT induce

vomiting.

Self-protection of the first aider Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

See section 2 for more information. **Symptoms** 

Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Note to physicians

# 5. FIRE-FIGHTING MEASURES

<u>Suitable extinguishing media</u> Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

Extremely flammable. Contains gas under pressure; may explode if heated.

**Explosion data** 

**Sensitivity to Mechanical Impact** None. Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas. Avoid contact with skin, eyes or

clothing. Use personal protective equipment as required. Wash thoroughly after handling. Remove all sources of ignition. Contents under pressure. Do not puncture or incinerate

cans.

**Environmental precautions** 

Environmental precautions Do not flush into surface water or sanitary sewer system. See Section 12 for additional

ecological Information.

Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Soak up with

inert absorbent material. Sweep up and shovel into suitable containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

# 7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Avoid contact with skin, eyes or clothing. Avoid breathing vapors or mists. Ensure adequate

ventilation, especially in confined areas. Do not puncture or incinerate cans. Use personal

protective equipment as required.

Conditions for safe storage, including any incompatibilities

**Storage Conditions** Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Incompatible materials Strong oxidizing agents, Alkalis, Chlorinated compounds, Acids

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
ACETONE	STEL: 500 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 250 ppm	TWA: 2400 mg/m <sup>3</sup>	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m <sup>3</sup>
		(vacated) TWA: 1800 mg/m <sup>3</sup>	_
		(vacated) STEL: 2400 mg/m <sup>3</sup> The	
		acetone STEL does not apply to the	
		cellulose acetate fiber industry. It is	
		in effect for all other sectors	
		(vacated) STEL: 1000 ppm	
N-HEXANE	TWA: 50 ppm	TWA: 500 ppm	IDLH: 1100 ppm
110-54-3	S*	TWA: 1800 mg/m <sup>3</sup>	TWA: 50 ppm
		(vacated) TWA: 50 ppm	TWA: 180 mg/m <sup>3</sup>
		(vacated) TWA: 180 mg/m <sup>3</sup>	
ETHYL ACETATE	TWA: 400 ppm	TWA: 400 ppm	IDLH: 2000 ppm
141-78-6		TWA: 1400 mg/m <sup>3</sup>	TWA: 400 ppm
		(vacated) TWA: 400 ppm	TWA: 1400 mg/m <sup>3</sup>
		(vacated) TWA: 1400 mg/m <sup>3</sup>	_

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

**Engineering Controls** Showers

> Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves. Skin and body protection

Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as Respiratory protection

appropriate.

**General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of

equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid Blue **Appearance** Odor Solvent

No information available **Odor threshold** 

Property Values Remarks • Method

No information available Melting point / freezing point No information available > 38 °C / >100 °F Boiling point / boiling range

Flash point No information available Gives a flame projection at full valve opening or

Air = 1

flashback at any degree of valve opening

**Evaporation rate** > 1 Butyl acetate = 1

Flammability (solid, gas) No information available

Flammability Limit in Air Upper flammability limit: No information available

Lower flammability limit: No information available Vapor pressure No information available

Vapor density >1

0.795-0.805 Relative density Water solubility Insoluble in water Solubility in other solvents No information available Partition coefficient No information available **Autoignition temperature** No information available **Decomposition temperature** No information available Kinematic viscosity No information available No information available

Dynamic viscosity No information available **Explosive properties Oxidizing properties** No information available

**Other Information** 

Softening point No information available Molecular weight No information available

**VOC Content (%)** 61.65%

No information available **Density Bulk density** No information available

# 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions

### Possibility of Hazardous Reactions

None under normal processing.

### Conditions to avoid

Heat, flames and sparks.

### Incompatible materials

Strong oxidizing agents, Alkalis, Chlorinated compounds, Acids

### **Hazardous Decomposition Products**

Carbon oxides

# 11. TOXICOLOGICAL INFORMATION

# Information on likely routes of exposure

**Inhalation** Harmful by inhalation. May cause drowsiness or dizziness.

**Eye contact** Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

**Skin contact** May cause skin irritation and/or dermatitis.

Ingestion Harmful if swallowed. Potential for aspiration if swallowed. Aspiration may cause pulmonary

edema and pneumonitis.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
ACETONE	= 5800 mg/kg (Rat)	-	= 50100 mg/m <sup>3</sup> (Rat) 8 h
67-64-1			
N-HEXANE	= 25 g/kg (Rat)	= 3000 mg/kg (Rabbit)	= 48000 ppm (Rat) 4 h
110-54-3			
SOLVENT NAPHTHA	-	= 3000 mg/kg ( Rabbit )	-
(PETROLEUM), LIGHT ALIPH.			
64742-89-8			
ETHYL ACETATE	= 5620 mg/kg (Rat)	> 18000 mg/kg (Rabbit) > 20	-
141-78-6		mL/kg (Rabbit)	

# Information on toxicological effects

**Symptoms** No information available.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

SensitizationNo information available.Germ cell mutagenicityNo information available.CarcinogenicityNo information available.

Target Organ Effects Central nervous system, Eyes, Peripheral Nervous System (PNS), Respiratory system,

Skin.

# The following values are calculated based on chapter 3.1 of the GHS document .

 ATEmix (oral)
 12387 mg/kg

 ATEmix (dermal)
 9871 mg/kg

 ATEmix (inhalation-gas)
 962077 mg/l

 ATEmix (inhalation-dust/mist)
 283.9 mg/l

 ATEmix (inhalation-vapor)
 204000 mg/l

# 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

40 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

### Persistence and degradability

No information available.

### **Bioaccumulation**

No information available.

### **Mobility**

No information available.

Chemical Name	Partition coefficient
ACETONE	-0.24
67-64-1	
PETROLEUM GASES, LIQUEFIED, SWEETENED	<=2.8
68476-86-8	
ETHYL ACETATE	0.6
141-78-6	

### Other adverse effects

No information available

# 13. DISPOSAL CONSIDERATIONS

# Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

**Contaminated packaging** Do not reuse container.

US EPA Waste Number D001

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status	
ACETONE	Ignitable	
67-64-1	-	
N-HEXANE	Toxic	
110-54-3	Ignitable	
ETHYL ACETATE	Toxic	
141-78-6	Ignitable	

# 14. TRANSPORT INFORMATION

DOT

**UN/ID** no 1950

Proper shipping name: Aerosols, Limited Quantity (LQ)

Hazard Class 2.1 Emergency Response Guide 126

Number

IATA

UN/ID no ID 8000

Proper shipping name: Consumer commodity

Hazard Class 9 ERG Code 9L

**IMDG** 

**UN/ID** no 1950

Proper shipping name: Aerosols, Limited Quantity (LQ)

Hazard Class 2.1 EmS-No F-D, S-U

# 15. REGULATORY INFORMATION

**International Inventories** 

Complies **TSCA DSL/NDSL** Complies **EINECS/ELINCS** Complies Not determined **ENCS** Complies **IECSC** Complies **KECL** Complies **PICCS AICS** Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

### **US Federal Regulations**

### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
N-HEXANE - 110-54-3	1.0
SARA 311/312 Hazard Categories	
Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

### **CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
ACETONE	5000 lb	-	RQ 5000 lb final RQ
67-64-1			RQ 2270 kg final RQ
N-HEXANE	5000 lb	-	RQ 5000 lb final RQ
110-54-3			RQ 2270 kg final RQ
ETHYL ACETATE	5000 lb	-	RQ 5000 lb final RQ
141-78-6			RQ 2270 kg final RQ

# **US State Regulations**

# **California Proposition 65**

This product does not contain any Proposition 65 chemicals

# **U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
ACETONE	X	X	X
67-64-1			
N-HEXANE	X	X	X
110-54-3			
ETHYL ACETATE	X	X	X
141-78-6			

### **U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

### **WHMIS Hazard Class**

A Compressed gases, B5 - Flammable aerosol, D2B - Toxic materials

# 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 4 Instability 0 -

HMIS Health hazards 2 Flammability 4 Physical hazards 0 Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date 21-Oct-2016

### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**