Page 1 of 10

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

Product identifier used on the label

: DIESEL FUEL DE-GEL

Product Code(s) : M7532C

Recommended use of the chemical and restrictions on use

Diesel fuel additive.

No restrictions on use known.

Chemical family : Mixture of: Petroleum solvent; Glycol ethers; Diesel fuel additive

Name, address, and telephone number of

the supplier:

Name, address, and telephone number of the manufacturer:

Refer to supplier

Radiator Specialty Co., of Canada

3-3055 Dundas St West, Suite 50 Mississauga, ON, Canada

L5L 3R8

Supplier's Telephone # : (905) 625-9117 (Mon. - Fri., 8 am - 4 pm)

24 Hr. Emergency Tel # : No information available.

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical

Clear yellow liquid. Aromatic odour.

Most important hazards:

Flammable liquid and vapour. May be ignited by open flame.

Aspiration hazard. Can enter the lungs and cause damage. Irritating to skin. May cause irritation of respiratory tract. Inhalation may cause central nervous system depression. Contains material which can cause birth defects based on animal data. Occupational exposure to the substance or mixture may cause adverse effects. For further information, please refer to section 11 of the SDS.

Toxic to aquatic life with long lasting effects. Avoid release to the environment. See Section 12 for more environmental information.

This product is packaged and sold as a consumer product. The Hazardous Products Act (HPA) does not apply to consumer products [Hazardous Products Act Section 12(j)]. The below WHMIS 2015 classification and labeling information is being provided for informational purposes.

This material is classified as hazardous under Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification:

Flammable liquid - Category 3

Aspiration toxicity - Category 1

Skin corrosion/irritation - Category 2

Reproductive toxicity - Category 2

Specific target organ toxicity, single exposure - Category 3 (Narcotic effects; Respiratory irritation)

Label elements

Hazard pictogram(s)



Signal Word

DANGER!

Hazard statement(s)

Flammable liquid and vapour.

May be fatal if swallowed and enters airways.

Causes skin irritation.

May cause respiratory irritation.

May cause drowsiness or dizziness.

Suspected of damaging the unborn child.

Precautionary statement(s)

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources - No smoking.

Keep container tightly closed.

Ground/Bond container and receiving equipment.

Use explosion-proof electrical and ventilating equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing mist or vapours.

Wash exposed skin thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/clothing and eye/face protection.

IF exposed or concerned: Get medical advice/attention.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

In case of fire: Use carbon dioxide, dry chemical or foam to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Keep cool.

Store locked up.

Dispose of contents/container in accordance with local regulation.

Other hazards

Other hazards which do not result in classification:

Toxic fumes may be released during a fire. Direct eye contact may cause slight or mild, transient irritation. May cause gastrointestinal irritation. Prolonged overexposure may cause slight liver and kidney effects, such as increased organ weights.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Chemical name	Common name and synonyms	CAS#	Concentration (% by weight)
Solvent naphtha (petroleum), light aromatic	Aromatic naphtha	64742-95-6	65.0 - 85.0
Diethylene glycol monomethyl ether	Methoxydiglycol DEGME	111-77-3	7.0 - 13.0
Solvent naphtha (petroleum), heavy aromatic	Heavy Aromatic Naphtha	64742-94-5	3.0 - 7.0

Note: The exact concentrations of the above listed chemicals are being withheld as a trade secret.

This product is packaged and sold as a consumer product. The Hazardous Products Act (HPA) does not apply to consumer products [Hazardous Products Act Section 12(j)].

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

Ingestion

: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.

DIESEL FUEL DE-GEL M7532C Page 3 of 10

SDS Preparation Date (mm/dd/yyyy): 01/24/2019

SAFETY DATA SHEET

Inhalation : IF INHALED: Remove person to fresh air and keep comfortable for breathing. If breathing is

difficult, give oxygen by qualified medical personnel only. If breathing stops, provide artificial

respiration. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact : IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical

advice/attention. Take off contaminated clothing and wash it before reuse.

Eve contact Rinse immediately with plenty of water, also under the eyelids. IF exposed or concerned:

Get medical advice/attention.

Most important symptoms and effects, both acute and delayed

: May be fatal if swallowed and enters airways. Aspiration hazard Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be

May cause respiratory irritation. Symptoms may include upper respiratory irritation, coughing and breathing difficulties. Inhalation may cause headache, nausea and central nervous effects such as dizziness, coordination difficulties and unconsciousness.

Causes skin irritation. Contact may cause redness, swelling and a painful sensation. Suspected of damaging the unborn child. Symptoms may include decreased fetal and pup body weight, delayed ossification, skeletal malformations and increased fetal and pup mortality.

Direct eye contact may cause slight or mild, transient irritation. Direct eye contact may cause slight redness.

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Prolonged overexposure may cause slight liver and kidney effects, such as increased organ weights.

Indication of any immediate medical attention and special treatment needed

: Immediate medical attention is required. Product may present an aspiration hazard, if ingested in large amounts, causing life-threatening lung injury. Provide general supportive measures and treat symptomatically.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media

: Carbon dioxide (CO2); Dry chemical; Alcohol resistant foam

Unsuitable extinguishing media

: Do not use a solid water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture / Conditions of flammability

Flammable liquid and vapour. This material may be ignited by heat, sparks and direct flame. Vapours may be heavier than air and may collect in confined and low-lying areas. Product may float, and be re-ignited at the water's surface. Toxic fumes, gases or vapours may evolve on burning.

Hazardous combustion products

Carbon oxides; Hydrocarbons; Other unidentified organic compounds.

Special protective equipment and precautions for firefighters

Protective equipment for fire-fighters

: Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Special fire-fighting procedures

Move containers from fire area if safe to do so. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or water courses. Dike for water control.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Keep people away from and upwind of spill/leak. Restrict access to area until completion of clean-up. Wear appropriate protective equipment. Refer to protective measures listed in sections 7 and 8.

DIESEL FUEL DE-GEL M7532C Page 4 of 10

SDS Preparation Date (mm/dd/yyyy): 01/24/2019

SAFETY DATA SHEET

Environmental precautions

: Prevent product from entering drains, sewers, waterways and soil. Avoid release to the environment.

Methods and material for containment and cleaning up

: Ventilate the area. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. Use only non-sparking tools. For spilled liquids: absorb spill with inert, non-combustible material such as sand, then place into suitable containers. Do not use combustible absorbents, such as sawdust. Pick up and transfer to properly labeled containers. Contaminated absorbent material may pose the same hazards as the spilled product. Contact the proper local authorities. Refer to Section 13 for disposal of contaminated material.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Use only outdoors or in a well-ventilated area. Wear suitable protective equipment during handling. Wear protective gloves/clothing and eye/face protection. Avoid breathing mist or vapours. Avoid contact with skin, eyes and clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources - No smoking. Ground/Bond container and receiving equipment. Use explosion-proof electrical and ventilating equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep away from incompatibles. Wash thoroughly after handling. Keep container tightly closed when not in use. Keep out of reach of children.

Conditions for safe storage

Store in cool/well-ventilated place. Store locked up. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking. Have appropriate fire extinguishers and spill clean-up equipment in or near storage area. Keep away from incompatibles.

Incompatible materials

: Strong oxidizing agents; Strong bases; Reducing agents; Strong acids

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Chemical Name	ACGIH TLV OSHA PEL			<u>PEL</u>
	<u>TWA</u>	<u>STEL</u>	<u>PEL</u>	STEL
Solvent naphtha (petroleum), light aromatic	N/Av	N/Av	N/Av	N/Av
Diethylene glycol monomethyl ether	N/Av	N/Av	N/Av	N/Av
Solvent naphtha (petroleum), heavy aromatic	N/Av	N/Av	500 ppm (2000 mg/m³) (as petroleum distillates, naphtha)	N/Av

Exposure controls

Ventilation and engineering measures

- : Use only outdoors or in a well-ventilated area. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. In case of insufficient ventilation wear suitable respiratory equipment.
- Respiratory protection
- If airbourne concentrations are above the permissible exposure limit or are not known, use NIOSH-approved respirators. Refer to CSA Z94.3 or other appropriate standards. Advice should be sought from respiratory protection specialists.
- Skin protection
- Wear protective gloves/clothing. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Wear resistant clothing and boots. Depending on conditions of use, an impervious apron should be worn.

Eye / face protection

: Wear eye/face protection. Wear as appropriate: Tightly fitting safety goggles; Safety glasses with side shields. A full face shield may also be necessary.

DIESEL FUEL DE-GEL M7532C Page 5 of 10

SDS Preparation Date (mm/dd/yyyy): 01/24/2019

SAFETY DATA SHEET

Other protective equipment Ensure that eyewash stations and safety showers are close to the workstation location.

Other equipment may be required depending on workplace standards.

General hygiene considerations

: Avoid breathing mist or vapours. Avoid contact with skin, eyes and clothing. Wash

thoroughly after handling. Remove and wash contaminated clothing before re-use. Handle in

accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Clear yellow liquid.

Odour aromatic **Odour threshold** : N/Av : N/Av рН

Melting/Freezing point : - 84°C (- 119.2°F) (estimation)

Initial boiling point and boiling range

: 193°C (379.4°F) (estimation)

40.6°C (105°F) Flash point Flashpoint (Method) closed cup Evaporation rate (BuAe = 1) : N/Av

Flammability (solid, gas) Not applicable.

Lower flammable limit (% by vol.)

0.7% (estimation)

Upper flammable limit (% by vol.)

: 5.7% (estimation)

Oxidizing properties : None known. **Explosive properties** : Not explosive

Vapour pressure : 0.22 hPa (estimation)

Vapour density Relative density / Specific gravity

Specific Gravity: 0.89

Solubility in water : N/Av Other solubility(ies) N/Av

Partition coefficient: n-octanol/water or Coefficient of water/oil distribution

: N/Av

Auto-ignition temperature 450°C (842°F) (estimation)

Decomposition temperature

: < 15 cSt @ 40°C (104°F) **Viscosity** Volatiles (% by weight) : 10.17% (estimated)

Volatile organic Compounds (VOC's)

: N/Av

Absolute pressure of container

: N/Ap : N/Ap

Flame projection length Other physical/chemical comments

: No additional information.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not normally reactive.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions

: Hazardous polymerization does not occur.

Keep away from heat, sparks and open flames. Do not use in areas without adequate Conditions to avoid

ventilation. Avoid contact with incompatible materials.

Incompatible materials Strong oxidizing agents; Strong bases; Reducing agents; Strong acids

Hazardous decomposition products

: None known, refer to hazardous combustion products in Section 5.

Page 6 of 10

SAFETY DATA SHEET

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Routes of entry inhalation : YES Routes of entry skin & eye : YES **Routes of entry Ingestion** : YES Routes of exposure skin absorption

: NO

Potential Health Effects:

Signs and symptoms of short-term (acute) exposure

Sign and symptoms Inhalation

May cause respiratory irritation. Symptoms may include upper respiratory irritation, coughing and breathing difficulties. Inhalation of high concentrations may cause dizziness, disorientation, incoordination, narcosis, nausea or narcotic effects.

Sign and symptoms ingestion

: May be fatal if swallowed and enters airways. Aspiration hazard. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Sign and symptoms skin

: Causes skin irritation. Contact may cause redness, swelling and a painful sensation.

Sign and symptoms eyes

Direct eye contact may cause slight or mild, transient irritation. Direct eye contact may cause

slight redness.

Potential Chronic Health Effects

Prolonged or repeated skin exposure may cause redness, a burning sensation, drying and cracking of the skin (dermatitis). Prolonged overexposure may cause slight kidney effects, such as increased organ weight.

Mutagenicity

: No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity

Not classifiable as a human carcinogen. No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP.

Reproductive effects & Teratogenicity

: This material is classified as hazardous under Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification:

Reproductive toxicity - Category 2. Suspected of damaging the unborn child. Symptoms may include decreased fetal and pup body weight, delayed ossification, skeletal malformations and increased fetal and pup mortality. Contains: Diethylene glycol monomethyl ether.

Sensitization to material

No data available to indicate product or components may be skin sensitizers. No data available to indicate product or components may be respiratory sensitizers.

Specific target organ effects

This material is classified as hazardous under Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification:

Specific target organ toxicity, single exposure - Category 3. May cause drowsiness or dizziness. May cause respiratory irritation.

According to the classification criteria of Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015), this product is not expected to cause specific target organ toxicity (STOT) through repeated exposures.

Medical conditions aggravated by overexposure

: Pre-existing skin, eye, respiratory and central nervous system disorders.

DIESEL FUEL DE-GEL M7532C Page 7 of 10

SDS Preparation Date (mm/dd/yyyy): 01/24/2019

SAFETY DATA SHEET

Synergistic materials : None known or reported by the manufacturer.

Toxicological data : Not classified for acute toxicity based on available data. No data is available on the product

itself. The calculated ATE values for this mixture are:

ATE dermal = > 3692 mg/kg

ATE inhalation (vapours) = > 22.2 mg/L/4H ATE inhalation (mists) = > 284.5 mg/L/4H

See below for individual ingredient acute toxicity data.

	LC₅₀ (4hr)	LD ₅₀	
Chemical name	<u>inh, rat</u>	(Oral, rat)	(Rabbit, dermal)
Solvent naphtha (petroleum), light aromatic	> 17.7 mg/L (vapour)	8400 mg/kg	> 3160 mg/kg
Diethylene glycol monomethyl ether	> 50 mg/L (aerosol)	6830 mg/kg	9404 mg/kg
Solvent naphtha (petroleum), heavy aromatic	> 17.1 mg/L (mist)	> 6000 mg/kg	> 3160 mg/kg

Other important toxicological hazards

: None known or reported by the manufacturer.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

: Toxic to aquatic life with long lasting effects. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters. The product contains the following substances which are hazardous for the environment: Solvent naphtha (petroleum), light aromatic; Solvent naphtha (petroleum), heavy aromatic.

See the following tables for individual ingredient ecotoxicity data.

Ecotoxicity data:

<u>Ingredients</u>	0.10.11	Toxicity to Fish			
	CAS No	LC50 / 96h	NOEC / 21 day	M Factor	
Solvent naphtha (petroleum), light aromatic	64742-95-6	9.2 mg/L (Rainbow trout)	N/Av	None.	
Diethylene glycol monomethyl ether	111-77-3	5700 mg/L (Fathead minnow)	N/Av	None.	
Solvent naphtha (petroleum), heavy aromatic	64742-94-5	3.6 mg/L (Rainbow trout)	N/Av	None.	

<u>Ingredients</u>	CAS No	lo Toxicity to Daphnia				
		EC50 / 48h	NOEC / 21 day	M Factor		
Solvent naphtha (petroleum), light aromatic	64742-95-6	6.16 mg/L (Daphnia magna)	N/Av	None.		
Diethylene glycol monomethyl ether	111-77-3	1192 mg/L (Daphnia magna)	N/Av	None.		
Solvent naphtha (petroleum), heavy aromatic	64742-94-5	1.1 mg/L (Daphnia magna)	N/Av	None.		

<u>Ingredients</u>	CAS No	Toxicity to Algae					Toxicity to Algae		
		EC50 / 96h or 72h	NOEC / 96h or 72h	M Factor					
Solvent naphtha (petroleum), light aromatic	64742-95-6	N/Av	N/Av	None.					

Diethylene glycol monomethyl ether	111-77-3	> 500 mg/L/72hr (Green algae)	N/Av	None.
Solvent naphtha (petroleum), heavy aromatic	64742-94-5	7.2 mg/L/72hr (Green algae)	0.22 mg/L/72hr	None.

Persistence and degradability

The product itself has not been tested.

The following ingredients are considered to be readily biodegradable: Diethylene glycol monomethyl ether.

Contains the following chemicals which are considered to be inherently biodegradable: Solvent naphtha (petroleum), light aromatic.

Contains the following chemicals which are not readily biodegradable: Solvent naphtha (petroleum), heavy aromatic.

Bioaccumulation potential

The product itself has not been tested. See the following data for ingredient information.

<u>Components</u>	Partition coefficient n-octanol/water (log Kow)	Bioconcentration factor (BCF)
Solvent naphtha (petroleum), light aromatic (CAS 64742-95-6)	2.1 - 6 (calculated)	10 - 2500 (calculated)
Diethylene glycol monomethyl ether (CAS 111-77-3)	- 1.18	3.0
Solvent naphtha (petroleum), heavy aromatic (CAS 64742-94-5)	> 3, < 6.5	N/Av

Mobility in soil

: The product itself has not been tested.

Other Adverse Environmental effects

: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13. DISPOSAL CONSIDERATIONS

Handling for Disposal

: Handle in accordance with good industrial hygiene and safety practice. Refer to protective measures listed in sections 7 and 8. This material and its container must be disposed of in a safe way. Empty containers retain residue and can be dangerous. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

Methods of Disposal

Dispose of in accordance with federal, provincial and local hazardous waste laws.

SECTION 14. TRANSPORT INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
TDG	UN1993	FLAMMABLE LIQUID, N.O.S. (Aromatic naphtha)	3	III	3
TDG Additional information	'Flammable Liqu	r road or rail shipment if packaged in non-bulk containers (450 uids General Exemption' may apply. Section 1.33 of the Regu f this product in small means of containment as not regulated.			

Special precautions for user

Appropriate advice on safety must accompany the package. Keep away from heat, sparks and open flame. - No smoking.

Environmental hazards

This product meets the criteria for an environmentally hazardous material according to the IMDG Code. See Section 12 for more environmental information.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: Not applicable.

SECTION 15 - REGULATORY INFORMATION

Canadian Information:

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

Canadian National Pollutant Release Inventory (NPRI): This product contains the following substances listed on the NPRI:

Solvent naphtha (petroleum), light aromatic (Part 5: Other groups and mixtures)

Diethylene glycol monomethyl ether (Part 1, Group A Substance)

Solvent naphtha (petroleum), heavy aromatic (Part 5: Other groups and mixtures)

WHMIS information: Refer to Section 2 for a WHMIS Classification for this product.

US Federal Information:

TSCA: All listed ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

International Information:

Components listed below are present on the following International Inventory list:

<u>Ingredients</u>	CAS#	European EINECs	Australia AICS	Philippines PICCS	Japan ENCS	Korea KECI/KECL	China IECSC	New Zealand IOC
Solvent naphtha (petroleum), light aromatic	64742-95-6	265-199-0	Present	Present	(9)-1698	KE-31662	Present	May be used as a single component chemical under an appropriate group standard.
Diethylene glycol monomethyl ether	111-77-3	203-906-6	Present	Present	(7)-97; (2)-422; (2)-2979	KE-23278	Present	HSR002752
Solvent naphtha (petroleum), heavy aromatic	64742-94-5	265-198-5	Present	Present	(9)-2578	KE-31656	Present	May be used as a single component chemical under an appropriate group standard.

SECTION 16. OTHER INFORMATION

Legend

: ACGIH: American Conference of Governmental Industrial Hygienists

AICS: Australian Inventory of Chemical Substances

CAS: Chemical Abstract Services CSA: Canadian Standards Association EC50: Effective Concentration 50%

EINECS: European Inventory of Existing Commercial chemical Substances

ENCS: Existing and New Chemical Substances HSDB: Hazardous Substances Data Bank

IARC: International Agency for Research on Cancer

IBC: Intermediate Bulk Container

IECSC: Inventory of Existing Chemical Substances IMDG: International Maritime Dangerous Goods

IOC: Inventory of Chemicals

KECI: Korean Existing Chemicals Inventory KECL: Korean Existing Chemicals List

LC: Lethal Concentration

LD: Lethal Dose N/Ap: Not Applicable N/Av: Not Available

NIOSH: National Institute of Occupational Safety and Health

NOEC: No observable effect concentration

NTP: National Toxicology Program

OECD: Organisation for Economic Co-operation and Development

OSHA: Occupational Safety and Health Administration

PEL: Permissible exposure limit

PICCS: Philippine Inventory of Chemicals and Chemical Substances

RTECS: Registry of Toxic Effects of Chemical Substances

SDS: Safety Data Sheet

STEL: Short Term Exposure Limit

TDG: Canadian Transportation of Dangerous Goods Act & Regulations

TLV: Threshold Limit Values TSCA: Toxic Substance Control Act TWA: Time Weighted Average

WHMIS: Workplace Hazardous Materials Identification System

References

- 1. ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices for 2018.
- 2. International Agency for Research on Cancer Monographs, searched 2018.
- 3. Canadian Centre for Occupational Health and Safety, CCInfoWeb databases, 2018 (Chempendium, HSDB and RTECs).
- 4. Material Safety Data Sheets from manufacturer.
- 5. OECD The Global Portal to Information on Chemical Substances eChemPortal, 2018.

Preparation Date (mm/dd/yyyy)

: 01/24/2019

Other special considerations for handling

: Provide adequate information, instruction and training for operators.

Prepared for:

Radiator Specialty Co. of Canada 3-3055 Dundas St West, Suite 50 Mississauga, ON, Canada, L5L 3R8

Telephone: 905-625-9117 (Mon. - Fri., 8 AM - 4 PM) Please direct all enquiries to Radiator Specialty.

Prepared by:

ICC The Compliance Center Inc.

Telephone: (888) 442-9628 (U.S.): (888) 977-4834 (Canada)

http://www.thecompliancecenter.com



DISCLAIMER

This Safety Data Sheet was prepared by ICC The Compliance Center Inc. using information provided by Radiator Specialty Co. of Canada and CCOHS' Web Information Service. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and Radiator Specialty Co. of Canada expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other process.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc. and Radiator Specialty Co. of Canada.

END OF DOCUMENT