SECTION 1. IDENTIFICATION

Product identifier used on the label

: SILICONE SPRAY

Product Code(s) : M914C, M914/6C

Recommended use of the chemical and restrictions on use

: Lubricant.

Restrictions on use: Not available.

Chemical family : Mixture of: Mineral spirits; Solvent; Base oil; Silicone oil.; Corrosion inhibitor; Lubricity

improver; Fragrances

Name, address, and telephone number of

the supplier:

Name, address, and telephone number of

Page 1 of 12

the manufacturer:

Refer to supplier

Radiator Specialty Co., of Canada

3-3055 Dundas St West, Suite 50 Mississauga, ON, Canada

L5L 3R8

Supplier's Telephone # : (905) 625-9117 (Mon. - Fri., 8 am - 4 pm)

24 Hr. Emergency Tel # : Not available.

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical

Hazy yellow liquid, contained in pressurized aerosol can. Floral odour.

Most important hazards.

Flammable aerosol. May be ignited by open flames and sparks. Contents under pressure. Container may explode if heated. Aspiration hazard. Can enter the lungs and cause damage. Irritating to eyes and skin. Inhalation may cause central nervous system depression. Causes damage to organs through prolonged or repeated exposure. Occupational exposure to the substance or mixture may cause adverse effects. For further information, please refer to section 11 of the SDS. Toxic to aquatic life with long lasting effects. Avoid release to the environment. See Section 12 for more environmental information.

This product is packaged and sold as a consumer product. The Hazardous Products Act (HPA) does not apply to consumer products [Hazardous Products Act Section 12(j)]. The below WHMIS 2015 classification and labeling information is being provided for informational purposes.

This material is classified as hazardous under Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification:

Flammable aerosol - Category 2

Gases under pressure - Compressed gas

Aspiration toxicity -Category 1

Skin corrosion/irritation - Category 2

Eye damage/irritation - Category 2A

Specific target organ toxicity, single exposure - Category 3(Narcotic effects)

Specific target organ toxicity, repeated exposure -Category 1

Label elements

Hazard pictogram(s)



Signal Word

DANGER!

SDS Preparation Date (mm/dd/yyyy): 03/13/2019

SAFETY DATA SHEET

Hazard statement(s)

Flammable aerosol.

Contains gas under pressure; may explode if heated.

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Causes damage to organs through prolonged or repeated exposure.

Precautionary statement(s)

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources - No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Do not breathe mist or vapor.

Wash exposed skin thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves and eye/face protection.

Get medical advice/attention if you feel unwell.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local regulation.

Other hazards

Other hazards which do not result in classification:

Toxic fumes may be released during a fire. Mild respiratory irritant. Ingestion of larger amounts may cause defects to the central nervous system (e.g. dizziness, headache). Prolonged overexposure may cause slight liver and kidney effects, such as increased organ weights.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Chemical name	Common name and synonyms	CAS#	Concentration (% by weight)
Mineral spirits			45.0 - 70.0
This material is a mixture of the following cl			
stoddard solvent	Mineral spirits White spirit	8052-41-3	
Solvent naphtha (petroleum), medium aliphatic	White spirit stoddard solvent	64742-88-7	-
Naphtha (petroleum), hydrotreated heavy	Odorless mineral spirits Hydrotreated heavy naphtha	64742-48-9	-
Petroleum hydrocarbon			15.0 - 40.0
This material is a mixture of the following cl	nemicals:		
Distillates (petroleum), hydrotreated light	Hydrotreated kerosene	64742-47-8	
Solvent naphtha (petroleum) heavy aliphatic	Heavy aliphatic solvent naphtha	64742-96-7	-
Solvent naphtha (petroleum) heavy aliphatic	Heavy aliphatic solvent naphtha	64742-96-7	-

SILICONE SPRAY M914/C, M914/6C

SDS Preparation Date (mm/dd/yyyy): 03/13/2019

SAFETY DATA SHEET

Distillates (petroleum), hydrotreated heavy naphthenic	Mineral oil	64742-52-5	5.0 - 10.0
Carbon dioxide	Carbonic anhydride	124-38-9	1.0 - 5.0

The exact concentrations of the above listed chemicals are being withheld as a trade secret.

Note: This product is packaged and sold as a consumer product. The Hazardous Products Act (HPA) does not apply to consumer products [Hazardous Products Act Section 12(j)].

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

Ingestion

: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.

Page 3 of 12

Inhalation

: IF INHALED: Remove person to fresh air and keep comfortable for breathing. If breathing is difficult, give oxygen by qualified medical personnel only. If breathing stops, provide artificial respiration. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact

: IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs, get medical

advice/attention. Take off contaminated clothing and wash it before reuse.

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Flush eyes with water for at least 15 minutes. If eye irritation persists: get medical advice/attention.

Most important symptoms and effects, both acute and delayed

: May be fatal if swallowed and enters airways. Aspiration hazard. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal

Causes skin irritation. Contact may cause redness, swelling and a painful sensation. Causes serious eye irritation. Symptoms may include stinging, tearing, redness and swelling.

Inhalation may cause headache, nausea and central nervous effects such as dizziness, coordination difficulties and unconsciousness.

Causes damage to organs through prolonged or repeated exposure. May result in irreversible neurological symptoms such as problems with memory, visuospatial skills (e.g. depth perception), fatigue, muscle control, peripheral nerves (e.g. tingling in the hands and feet), and seizures.

Mild respiratory irritant. May cause coughing and breathing difficulties.

Ingestion of larger amounts may cause defects to the central nervous system (e.g. dizziness, headache).

Prolonged overexposure may cause slight liver and kidney effects, such as increased organ weights.

Indication of any immediate medical attention and special treatment needed

: Immediate medical attention is required. Aspiration hazard. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal. Provide general supportive measures and treat symptomatically.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media

: Carbon dioxide (CO2); Dry chemical; Alcohol resistant foam; Water fog.

Unsuitable extinguishing media

: Do not use a solid water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture / Conditions of flammability

Extremely flammable aerosol. May be ignited by open flames and sparks. This product is contained under pressure, and could explode when exposed to heat and flame. Material will float on water and can be re-ignited at the water's surface. Toxic fumes, gases or vapours may evolve on burning.

SILICONE SPRAY M914C, M914/6C Page 4 of 12

SDS Preparation Date (mm/dd/yyyy): 03/13/2019

SAFETY DATA SHEET

Hazardous combustion products

Carbon oxides; Aldehydes; Hydrocarbons; Nitrogen oxides (NOx); Polycyclic aromatic hydrocarbons; Silicon oxides; Phosphorus compounds; Sulphur oxides; Other unidentified organic compounds.

Special protective equipment and precautions for firefighters

Protective equipment for fire-fighters

: Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Special fire-fighting procedures

Move containers from fire area if safe to do so. Cool closed containers exposed to fire with water spray. Shield personnel to protect from venting or rupturing containers. Do not allow run-off from fire fighting to enter drains or water courses. Dike for water control.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: All persons dealing with the clean-up should wear the appropriate personal protective equipment. Keep people away from and upwind of spill/leak. Restrict access to area until completion of clean-up. Refer to protective measures listed in sections 7 and 8.

Environmental precautions

Ensure spilled product does not enter drains, sewers, waterways, or confined spaces. For large spills, dike the area to prevent spreading.

Methods and material for containment and cleaning up

: Ventilate the area. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. Use only non-sparking tools and equipment in the clean-up process. For spilled liquids: absorb spill with inert, non-combustible material such as sand, then place into suitable containers. Do not use combustible absorbents, such as sawdust. Keep in properly labelled containers. Refer to Section 13 for disposal of contaminated material. Notify the appropriate authorities as required.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

: Use only outdoors or in a well-ventilated area. Wear suitable protective equipment during handling. Wear protective gloves and eye/face protection. Do not breathe mist or vapor. Avoid contact with skin, eyes and clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Keep away from incompatibles. Always replace cap after use. Wash thoroughly after handling.

Conditions for safe storage

Store in cool/well-ventilated place. Store locked up. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking. Have appropriate fire extinguishers and spill clean-up equipment in or near storage area. Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F. Keep away from incompatibles.

Incompatible materials : Strong oxidizing agents; Acids; Halogenated compounds

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:				
Chemical Name	ACGIH	TLV	OSHA F	<u>PEL</u>
	<u>TWA</u>	STEL	<u>PEL</u>	STEL
stoddard solvent	100 ppm	N/Av	500 ppm (2900 mg/m³)	N/Av

Page 5 of 12

SAFETY DATA SHEET

Solvent naphtha (petroleum), medium aliphatic	N/Av	N/Av	500 ppm (2000 mg/m³) (as petroleum distillates, naphtha)	N/Av
Naphtha (petroleum), hydrotreated heavy	N/Av	N/Av	N/Av	N/Av
Distillates (petroleum), hydrotreated light	200 mg/m³ (as total hydrocarbon vapour) (skin)	N/Av	N/Av	N/Av
Solvent naphtha (petroleum) heavy aliphatic	N/Av	N/Av	500 ppm (2000 mg/m³) (as petroleum distillates, naphtha)	N/Av
Distillates (petroleum), hydrotreated heavy naphthenic	5 mg/m³ (As 'Oil mist, mineral') (inhalable)	N/Av	5 mg/m³ (As 'Oil mist, mineral')	N/Av
Carbon dioxide	5000 ppm	30 000 ppm	5000 ppm (9000 mg/m³)	N/Av

Exposure controls

Ventilation and engineering measures

: Use only outdoors or in a well-ventilated area. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. In case of insufficient

ventilation wear suitable respiratory equipment.

Respiratory protection : If airbourne concentrations are above the permissible exposure limit or are not known, use

NIOSH-approved respirators. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with CSA Z94.4-02. Advice should

be sought from respiratory protection specialists.

Skin protection: Wear protective gloves. The suitability for a specific workplace should be discussed with the

producers of the protective gloves. Depending on conditions of use, an impervious apron

should be worn. Wear sufficient clothing to prevent skin contact.

Eye / face protection : Wear eye/face protection. Wear as appropriate: Safety glasses with side shields; Tightly

fitting safety goggles. A full face shield may also be necessary.

Other protective equipment : Ensure that eyewash stations and safety showers are close to the workstation location.

Other equipment may be required depending on workplace standards.

General hygiene considerations

Do not breathe mist or vapor. Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Remove and wash contaminated clothing before re-use. Handle in accordance with good industrial hygiene and

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Hazy yellow liquid, contained in pressurized aerosol can.

safety practice.

Odour threshold : Floral odour.

Odour threshold : N/Av
pH : N/Av

Melting/Freezing point : Melting point: N/Av

Freezing point: - 70°C (- 94°F) (estimation)

Initial boiling point and boiling range

: 157°C (314.6°F) (estimation)

Flash point : $47.2^{\circ}\text{C} (114^{\circ}\text{F})$

Flashpoint (Method) : N/AvEvaporation rate (BuAe = 1) : N/Av

Flammability (solid, gas) : Not applicable.

Lower flammable limit (% by vol.)

: 0.7% (estimation)

Upper flammable limit (% by vol.)

: 6.0% (estimation)

SILICONE SPRAY M914/C, M914/6C

SDS Preparation Date (mm/dd/yyyy): 03/13/2019

SAFETY DATA SHEET

Oxidizing properties : No oxidizing properties.

Explosive properties : Aerosols are sensitive to mechanical impact. Closed containers are contained under

pressure and may explode if exposed to excess heat for a prolonged period of time.

Page 6 of 12

Vapour pressure : 0.41 hPa (estimated)

Vapour density : N/Av

Relative density / Specific gravity

Relative density: 815 kg/m³

Specific Gravity: 0.82

Solubility in water : Insoluble.

Other solubility(ies) : N/Av

Partition coefficient: n-octanol/water or Coefficient of water/oil distribution

: N/Av

Auto-ignition temperature : 109.44°C (229°F) (estimation)

Decomposition temperature : N/A

Viscosity : 16 cP @ 40°C (104°F) (concentrate)

Volatiles (% by weight) : 58.5% Volatile organic Compounds (VOC's)

: N/Av

Absolute pressure of container

: N/Av

Flame projection length : 63.5 cm (25")

Other physical/chemical comments

: Flashback Observed: NO

Chemical heat of combustion: 27.36 kJ/g (estimated)

SECTION 10. STABILITY AND REACTIVITY

Reactivity: Not normally reactive.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions

: Hazardous polymerization does not occur.

Conditions to avoid : Direct sources of heat. Do not use in areas without adequate ventilation. Avoid contact with

incompatible materials. Protect from sunlight and do not expose to temperatures exceeding

50 °C/122 °F.

Incompatible materials : Strong oxidizing agents; Acids; Halogenated compounds

Hazardous decomposition products

: Not available.

Refer also to hazardous combustion products, Section 5.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

 $\begin{tabular}{lll} Routes of entry inhalation & : YES \\ Routes of entry skin & eye & : YES \\ Routes of entry Ingestion & : YES \\ Routes of exposure skin absorption \\ \end{tabular}$

: NO

Potential Health Effects:

Signs and symptoms of short-term (acute) exposure

Sign and symptoms Inhalation

• Mild respiratory irritant. May cause coughing and breathing difficulties. Inhalation may cause headache, nausea and central nervous effects such as dizziness, coordination difficulties and unconsciousness. In extremely high concentrations, product may act as an asphyxiant and cause increased breathing and pulse rates, fatigue and unconsciousness. SILICONE SPRAY M914C, M914/6C Page 7 of 12

SDS Preparation Date (mm/dd/yyyy): 03/13/2019

SAFETY DATA SHEET

Sign and symptoms ingestion

: May be fatal if swallowed and enters airways. Aspiration hazard. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal. Ingestion of larger amounts may cause defects to the central nervous system (e.g. dizziness, headache).

Sign and symptoms skin

May cause moderate to severe skin irritation. Contact may cause redness, swelling and a painful sensation.

Sign and symptoms eyes

Causes serious eye irritation. Symptoms may include stinging, tearing, redness and swelling. If product is sprayed directly into the eyes, could cause freezing of the eye.

Potential Chronic Health Effects

Prolonged overexposure may cause slight liver and kidney effects, such as increased organ

Mutagenicity

No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity

Not classifiable as a human carcinogen. No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP.

Reproductive effects & Teratogenicity

: This product is not expected to cause reproductive or developmental effects.

Sensitization to material

No data available to indicate product or components may be respiratory sensitizers. No data available to indicate product or components may be skin sensitizers.

Specific target organ effects

This material is classified as hazardous under Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015), Classification: Specific target organ toxicity, single exposure - Category 3. May cause drowsiness or dizziness.

Specific target organ toxicity, repeated exposure - Category 1. Causes damage to organs through prolonged or repeated exposure. Contains: stoddard solvent. May result in irreversible neurological symptoms such as problems with memory, visuospatial skills (e.g. depth perception), fatigue, muscle control, peripheral nerves (e.g. tingling in the hands and feet), and seizures.

Medical conditions aggravated by overexposure

: Pre-existing skin, eye, respiratory and central nervous system disorders.

Synergistic materials Toxicological data

: None known or reported by the manufacturer.

Not classified for acute toxicity based on available data. No data is available on the product itself. The calculated ATE values for this mixture are:

ATE inhalation (vapours) = 38 - 42.23 mg/L/4H

See below for individual ingredient acute toxicity data.

	LC ₅₀ (4hr)	LD	150
Chemical name	inh, rat	(Oral, rat)	(Rabbit, dermal)
Mineral spirits			+
This material is a mixture of	f the following chemicals:		
stoddard solvent	> 5.5 mg/L (vapour)	> 5000 mg/kg	> 3000 mg/kg
Solvent naphtha (petroleum), medium aliphatic	> 5.5 mg/L (vapour)	> 5000 mg/kg (No mortality)	> 2000 mg/kg (No mortality)
Naphtha (petroleum), hydrotreated heavy	> 5.04 mg/L (vapour)	> 7000 mg/kg	> 2000 mg/kg (No mortality)
Petroleum hydrocarbon			
This material is a mixture of	f the following chemicals:		
Distillates (petroleum), hydrotreated light	> 5.2 mg/L (aerosol) (No mortality)	> 5000 mg/kg	> 2000 mg/kg (No mortality)
Solvent naphtha (petroleum) heavy aliphatic	> 5.2 mg/L (mist) (No mortality) (Read-across)	> 5000 mg/kg	> 2000 mg/kg (No mortality)

Distillates (petroleum), hydrotreated heavy naphthenic	> 5 mg/L (mist)	> 5000 mg/kg	> 2000 mg/kg
Carbon dioxide	200 000 ppm/2H (141 421	N/Ap(gas)	N/Ap(gas)

Other important toxicological hazards

: None known or reported by the manufacturer.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

: Toxic to aquatic life with long lasting effects. The ecological characteristics of this product have not been fully investigated. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters. The product contains the following substances which are hazardous for the environment: Mineral spirits.

See the following tables for individual ingredient ecotoxicity data.

Ecotoxicity data:

			Toxicity to Fish	
<u>Ingredients</u>	CAS No	LC50 / 96h	NOEC / 21 day	M Factor
stoddard solvent	8052-41-3	2.1 - 4.2 mg/L (Bluegill sunfish)	N/Av	None.
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	2 - 5 mg/L (Rainbow trout)	0.098 mg/L/28-day (QSAR) (NOEL)	None.
Naphtha (petroleum), hydrotreated heavy	64742-48-9	8.2 mg/L (Fathead minnow)	N/Av	None.
Distillates (petroleum), hydrotreated light	64742-47-8	20 mg/L (Rainbow trout) (Read-across)	N/Av	None.
Solvent naphtha (petroleum) heavy aliphatic	64742-96-7	2 - 5mg/L (Rainbow trout)	0.098 mg/L/28-day (QSAR)	None.
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	> 100 mg/L (Fathead minnow)	N/Av	None.
Carbon dioxide	124-38-9	N/Ap	N/Ap	N/Ap

<u>Ingredients</u>	CAS No	Tox	cicity to Daphnia	
		EC50 / 48h	NOEC / 21 day	M Factor
stoddard solvent	8052-41-3	0.42 - 2.3 mg/L (Daphnia magna)	0.1 - 0.37 mg/L	None.
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	1.4 mg/L (Daphnia magna)	0.48 mg/L (QSAR) (NOEL)	None.
Naphtha (petroleum), hydrotreated heavy	64742-48-9	32 mg/L (Daphnia magna)	6.3 mg/L	None.
Distillates (petroleum), hydrotreated light	64742-47-8	40 - 89 mg/L (Daphnia magna) (Read-across)	0.48 mg/L (Read-across)	None.
Solvent naphtha (petroleum) heavy aliphatic	64742-96-7	1.4 mg/L (Daphnia magna)	0.48 mg/L	None.
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	> 10 000 mg/L (Daphnia magna)	10 mg/L	None.
Carbon dioxide	124-38-9	N/Ap	N/Ap	N/Ap

Ingredients	CAS No	To	oxicity to Algae	
		EC50 / 96h or 72h	NOEC / 96h or 72h	M Factor
stoddard solvent	8052-41-3	0.58 - 1.2 mg/L/72hr (Green algae)	0.16 mg/L/72hr	None.
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	1 - 3 mg/L/72hr (Green algae)	1 mg/L/72hr (Green algae) (NOEL)	None.
Naphtha (petroleum), hydrotreated heavy	64742-48-9	45 mg/L/96hr (Green algae)	18 mg/L/96hr	None.
Distillates (petroleum), hydrotreated light	64742-47-8	6.2 mg/L/96hr (Green algae) (Read-across)	0.4 mg/L/96hr (Read-across)	None.
Solvent naphtha (petroleum) heavy aliphatic	64742-96-7	5 - 6.2 mg/L/96hr (Green algae)	0.4 - 6.2 mg/L/96hr	None.
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	> 1000 mg/L/96hr (Green algae)	≥ 100 mg/L/72hr	None.
Carbon dioxide	124-38-9	N/Ap	N/Ap	N/Ap

Persistence and degradability

: The product itself has not been tested.

The following ingredients are considered to be readily biodegradable: Petroleum hydrocarbon.

Contains the following chemicals which are considered to be inherently biodegradable:

Mineral spirits

Contains the following chemicals which are not readily biodegradable:

Distillates (petroleum), hydrotreated heavy naphthenic

Bioaccumulation potential

: The product itself has not been tested. See the following data for ingredient information.

<u>Components</u>	Partition coefficient n-octanol/water (log Kow)	Bioconcentration factor (BCF)
stoddard solvent (CAS 8052-41-3)) 3.16 - 7.06	N/Av
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	3.7 - 6.7	142 - 11,430 (Fish) (calculated)
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)	2.1 - 6 (calculated)	10 - 2500 (calculated)
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	5.1 - 8.8	N/Av
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	3.9 - 6 (calculated)	N/Av

Mobility in soil

: The product itself has not been tested.

Other Adverse Environmental effects

: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13. DISPOSAL CONSIDERATIONS

Handling for Disposal

: Handle in accordance with good industrial hygiene and safety practice. Refer to protective measures listed in sections 7 and 8. This material and its container must be disposed of in a safe way.

Empty containers retain residue and can be dangerous. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

Methods of Disposal

: Dispose of in accordance with federal, provincial and local hazardous waste laws.

Page 10 of 12

SAFETY DATA SHEET

SECTION 14. TRANSPORT INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
TDG	UN1950	AEROSOLS	2.1	None	2
TDG Additional information		as LIMITED QUANTITY when transported in containers no lar ss. Under the TDG, refer to Section 1.17 for additional exemption.			

Special precautions for user

: Appropriate advice on safety must accompany the package. Keep away from heat, sparks and open flame. - No smoking.

Environmental hazards

: This product meets the criteria for an environmentally hazardous material according to the

IMDG Code. See Section 12 for more environmental information.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: Not applicable.

SECTION 15 - REGULATORY INFORMATION

Canadian Information:

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

Canadian National Pollutant Release Inventory (NPRI): This product contains the following substances listed on the NPRI:

Distillates (petroleum), hydrotreated light (Part 5: Other groups and mixtures)

stoddard solvent (Part 5: Other groups and mixtures)

Naphtha (petroleum), hydrotreated heavy (Part 5: Other groups and mixtures)

Solvent naphtha (petroleum), medium aliphatic (Part 5: Other groups and mixtures)

WHMIS information: Refer to Section 2 for a WHMIS Classification for this product.

US Federal Information:

TSCA: All listed ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

International Information:

Components listed below are present on the following International Inventory list:

<u>Ingredients</u>	CAS#	European EINECs	Australia AICS	Philippines PICCS	Japan ENCS	Korea KECI/KECL	China IECSC	New Zealand IOC
stoddard solvent	8052-41-3	232-489-3	Present	Present	(9)-1702; (9)-1702	KE-32199	Present	HSR001498
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	265-191-7	Present	Present	(9)-1700	KE-31664	Present	May be used as a single component chemical under an appropriate group standard.
Naphtha (petroleum), hydrotreated heavy	64742-48-9	265-150-3	Present	Present	(9)-1690	KE-25622	Present	May be used as a single component chemical under an appropriate group standard.

Distillates (petroleum), hydrotreated light	64742-47-8	265-149-8	Present	Present	(9)-1700	KE-12550	Present	May be used as a single component chemical under an appropriate group standard.
Solvent naphtha (petroleum) heavy aliphatic	64742-96-7	265-200-4	Present	Present	Not listed	KE-31655	Present	May be used as a single component chemical under an appropriate group standard.
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	265-155-0	Present	Present	(9)-1689	KE-12543	Present	May be used as a single component chemical under an appropriate group standard.
Carbon dioxide	124-38-9	204-696-9	Present	Present	(1)-310; (1)-169	KE-04683	Present	HSR001018

SECTION 16. OTHER INFORMATION

Legend : ACGIH: American Conference of Governmental Industrial Hygienists

AICS: Australian Inventory of Chemical Substances

CAS: Chemical Abstract Services CSA: Canadian Standards Association EC50: Effective Concentration 50%

EINECS: European Inventory of Existing Commercial chemical Substances

ENCS: Existing and New Chemical Substances HSDB: Hazardous Substances Data Bank

IARC: International Agency for Research on Cancer

IBC: Intermediate Bulk Container

IECSC: Inventory of Existing Chemical Substances IMDG: International Maritime Dangerous Goods

IOC: Inventory of Chemicals

KECI: Korean Existing Chemicals Inventory KECL: Korean Existing Chemicals List

LC: Lethal Concentration

LD: Lethal Dose N/Ap: Not Applicable N/Av: Not Available

NIOSH: National Institute of Occupational Safety and Health

NOEC: No observable effect concentration NTP: National Toxicology Program

OECD: Organisation for Economic Co-operation and Development

OSHA: Occupational Safety and Health Administration

PEL: Permissible exposure limit

PICCS: Philippine Inventory of Chemicals and Chemical Substances

QSAR: Quantitative structure-activity relationship

RTECS: Registry of Toxic Effects of Chemical Substances

SCBA: Self-Contained Breathing Apparatus

SDS: Safety Data Sheet

STEL: Short Term Exposure Limit

TDG: Canadian Transportation of Dangerous Goods Act & Regulations

TLV: Threshold Limit Values TWA: Time Weighted Average

WHMIS: Workplace Hazardous Materials Identification System

SILICONE SPRAY M914/6C

SDS Preparation Date (mm/dd/yyyy): 03/13/2019

SAFETY DATA SHEET

References : 1. ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents &

Biological Exposure Indices for 2018.

2. International Agency for Research on Cancer Monographs, searched 2019.

 Canadian Centre for Occupational Health and Safety, CCInfoWeb databases, 2019 (Chempendium, HSDB and RTECs).

4. Material Safety Data Sheets from manufacturer.

5. OECD - The Global Portal to Information on Chemical Substances - eChemPortal, 2019.

Preparation Date (mm/dd/yyyy)

: 03/13/2019

Other special considerations for handling

: Provide adequate information, instruction and training for operators.

Prepared for:

Radiator Specialty Co. of Canada 3-3055 Dundas St West, Suite 50 Mississauga, ON, Canada, L5L 3R8

Telephone: 905-625-9117 (Mon. - Fri., 8 AM - 4 PM) Please direct all enquiries to Radiator Specialty.

Prepared by:

ICC The Compliance Center Inc.

Telephone: (888) 442-9628 (U.S.): (888) 977-4834 (Canada)

http://www.thecompliancecenter.com



Page 12 of 12

DISCLAIMER

This Safety Data Sheet was prepared by ICC The Compliance Center Inc. using information provided by Radiator Specialty Co. of Canada and CCOHS' Web Information Service. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and Radiator Specialty Co. of Canada expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other process.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc. and Radiator Specialty Co. of Canada.

END OF DOCUMENT