## SAFETY DATA SHEET

Valvoline™ VR1 Racing™ SAE 20W-50 Racing Oil

Version: 1.5 Revision Date: 04/30/2020 Print Date: 09/09/2022

GHS classification in accordance with the Hazardous Products Regulations

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION** 

**Product identifier** 

Trade name Valvoline™ VR1 Racing™ SAE 20W-50

Racing Oil

Product code 3094

Details of the supplier of the safety data sheet

Valvoline Canada Corp 905 Winston Churchill Blvd Mississauga ON L5J 4P2

Canada

1-800-TEAMVAL (1-800-832-6825)

SDS@valvoline.com

**Emergency telephone number** 

1-800-VALVOLINE (1-800-825-8654)

**Regulatory Information Number** 1-800-TEAMVAL (1-800-832-6825)

**Product Information** 

1-800-TEAMVAL (1-800-832-6825)

## **SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification** 

Eye irritation : Category 2A

**GHS** label elements

Hazard pictograms

Signal word : Warning

Hazard statements : H319 Causes serious eye irritation.

Precautionary statements : Prevention:

P280 Wear eye protection/ face protection. P264 Wash skin thoroughly after handling.

Response:

P337 + P313 If eye irritation persists: Get medical advice/

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

## SAFETY DATA SHEET

Valvoline™ VR1 Racing™ SAE 20W-50 Racing Oil

Version: 1.5 Revision Date: 04/30/2020 Print Date: 09/09/2022

### Other hazards

None known.

### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

Chemical nature : Defatter

**Hazardous components** 

a_a. a c a c c c p c c c			
Chemical name	CAS-No.	Classification	Concentration (%)
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	Not a hazardous substance or mixture.	>=60.00 - < 80.00
Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate		Skin Irrit. 2; H315 Eye Dam. 1; H318	>=1.00 - < 5.00
bis(priosprioroditificate		Eye Dam. 1, 11316	

Actual concentration or concentration range is withheld as a trade secret

## **SECTION 4. FIRST AID MEASURES**

General advice : Do not leave the victim unattended.

Show this safety data sheet to the doctor in attendance.

Move out of dangerous area.

If inhaled : If breathed in, move person into fresh air.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Wash contaminated clothing before re-use.

If on skin, rinse well with water.

Remove contaminated clothing. If irritation develops, get

medical attention.

In case of eye contact : Protect unharmed eye.

Remove contact lenses.

Immediately flush eye(s) with plenty of water.

If swallowed : Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

: No symptoms known or expected. Causes serious eye irritation.

### SAFETY DATA SHEET

Valvoline™ VR1 Racing™ SAE 20W-50 Racing Oil

Version: 1.5 Revision Date: 04/30/2020 Print Date: 09/09/2022

delayed

Notes to physician : No hazards which require special first aid measures.

### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray Foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: carbon dioxide and carbon monoxide

Specific extinguishing

methods

Product is compatible with standard fire-fighting agents.

Further information : Standard procedure for chemical fires.

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Use personal protective equipment.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

## SAFETY DATA SHEET

Valvoline™ VR1 Racing™ SAE 20W-50 Racing Oil

Version: 1.5 Revision Date: 04/30/2020 Print Date: 09/09/2022

### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Dispose of rinse water in accordance with local and national

regulations.

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Avoid contact with skin and eyes. Container hazardous when empty.

Do not smoke.

Do not breathe vapours/dust.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	TWA	5 mg/m3 Mist	CA AB OEL
		STEL	10 mg/m3 Mist	CA AB OEL
		TWAEV	5 mg/m3 Mist	CA QC OEL
		STEV	10 mg/m3 Mist	CA QC OEL
		TWA	1 mg/m3 Mist	CA BC OEL

**Engineering measures** : Provide sufficient mechanical (general and/or local exhaust)

ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or

apparent adverse effects.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally

required.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Wear chemical splash goggles when there is the potential for

## SAFETY DATA SHEET

Valvoline™ VR1 Racing™ SAE 20W-50 Racing
Oil

Version: 1.5 Revision Date: 04/30/2020 Print Date: 09/09/2022

exposure of the eyes to liquid, vapor or mist.

Skin and body protection : Wear resistant gloves (consult your safety equipment

supplier).

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Safety shoes Impervious clothing Wear as appropriate:

Hygiene measures : When using do not smoke.

When using do not eat or drink.

Wash hands before breaks and at the end of workday.

### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Colour : amber

Odour : mild

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : 315.56 °C

(1,013.333333 hPa)

Calculated Phase Transition Liquid/Gas

Flash point : 201 - 249 °C

Method: closed cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Self-ignition : No data available

Upper explosion limit / Upper

7 %(V)

flammability limit

GLP: Calculated Explosive Limit

Lower explosion limit / Lower

flammability limit

0.9 %(V)

GLP: Calculated Explosive Limit

## **SAFETY DATA SHEET**

Valvoline™ VR1 Racing™ SAE 20W-50 Racing Oil

Version: 1.5 Revision Date: 04/30/2020 Print Date: 09/09/2022

Vapour pressure : 0.1 hPa (20 °C)

Calculated Vapor Pressure

Relative vapour density : No data available

Relative density : 0.8880 (15.56 °C)

Density : 0.8816 g/cm3 (15.56 °C)

Solubility(ies)

Water solubility : negligible

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 182 mm2/s (40 °C)

Oxidizing properties : No data available

## **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Product will not undergo hazardous polymerization.

Conditions to avoid : None known.

Incompatible materials : Strong oxidizing agents

Acids

Hazardous decomposition

products No hazardous decomposition products are known.

### **SECTION 11. TOXICOLOGICAL INFORMATION**

## **SAFETY DATA SHEET**

Valvoline™ VR1 Racing™ SAE 20W-50 Racing Oil

Version: 1.5 Revision Date: 04/30/2020 Print Date: 09/09/2022

### Information on likely routes of exposure

Inhalation
Skin contact
Eye Contact
Ingestion
Acute toxicity

Not classified based on available information.

**Product:** 

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

**Components:** 

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate:

Acute oral toxicity : LD50 (Rat): 2,230 mg/kg

GLP: no

Acute inhalation toxicity : LC50 (Rat): > 2.3 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: Not classified as acutely toxic by inhalation

under GHS.

Remarks: Information given is based on data obtained from

similar substances.

Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg

Method: OECD Test Guideline 402

Assessment: Not classified as acutely toxic by dermal

absorption under GHS.

Skin corrosion/irritation

Not classified based on available information.

**Product:** 

Remarks : May cause skin irritation in susceptible persons.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Assessment : Slight, transient irritation Result : Slight, transient irritation

Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Irritating to skin.

### SAFETY DATA SHEET

Valvoline™ VR1 Racing™ SAE 20W-50 Racing Oil

Version: 1.5 Revision Date: 04/30/2020 Print Date: 09/09/2022

GLP : yes

### Serious eye damage/eye irritation

Causes serious eve irritation.

**Product:** 

Remarks : Causes serious eye irritation.

Vapours may cause irritation to the eyes, respiratory system

and the skin.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Result : No eye irritation
Assessment : No eye irritation

Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate:

Result : Corrosive

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

**Components:** 

Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate:

Species : Guinea pig

Assessment : Did not cause sensitisation on laboratory animals.

Method : OECD Test Guideline 406

Result : Did not cause sensitisation on laboratory animals.

GLP : yes

Germ cell mutagenicity

Not classified based on available information.

Components:

Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate:

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

Carcinogenicity

Not classified based on available information.

**Components:** 

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:** 

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

## **SAFETY DATA SHEET**

Valvoline™ VR1 Racing™ SAE 20W-50 Racing Oil

Version: 1.5 Revision Date: 04/30/2020 Print Date: 09/09/2022

STOT - repeated exposure

Not classified based on available information.

**Aspiration toxicity** 

Not classified based on available information.

**Product:** 

No aspiration toxicity classification

Components:

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:** 

No aspiration toxicity classification

**Further information** 

Product:

Remarks : No data available

**SECTION 12. ECOLOGICAL INFORMATION** 

**Ecotoxicity** 

Product:

Ecotoxicology Assessment

Short-term (acute) aquatic

hazard

: Not classified based on available information.

Long-term (chronic) aquatic

hazard

: Not classified based on available information.

**Components:** 

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Toxicity to fish : LL50 (Fish): > 100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: EL50 (Aquatic invertebrates): > 10,000 mg/l

Exposure time: 48 h

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l

Exposure time: 72 h

Toxicity to fish (Chronic

toxicity)

: NOEC (Fish): 10 mg/l

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEC (Aquatic invertebrates): 10 mg/l

Ecotoxicology Assessment

Short-term (acute) aquatic

hazard

: Not classified based on available information.

Long-term (chronic) aquatic : Not classified based on available information.

## SAFETY DATA SHEET

Valvoline™ VR1 Racing™ SAE 20W-50 Racing Oil

Version: 1.5 Revision Date: 04/30/2020 Print Date: 09/09/2022

hazard

Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 4.5 mg/l

> Exposure time: 96 h Test Type: semi-static test

Method: OECD Test Guideline 203

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to daphnia and other

aquatic invertebrates

: EL50 (Daphnia magna (Water flea)): 23 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

GLP: yes

Toxicity to algae : NOEL (Desmodesmus subspicatus (green algae)): 10 mg/l

End point: Growth inhibition

Exposure time: 72 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 201

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEC (Daphnia magna (Water flea)): 0.4 mg/l

Exposure time: 21 d Test substance: WAF

Method: OECD Test Guideline 211

Remarks: Information given is based on data obtained from

similar substances.

## Persistence and degradability

Components:

Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate: Biodegradability : Result: Not readily biodegradable.

> Biodegradation: 1.5 % Exposure time: 28 d

Method: OECD Test Guideline 301B

Remarks: Information given is based on data obtained from

similar substances.

No data available

Bioaccumulative potential

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

octanol/water

Partition coefficient: n- : log Pow: Expected > 7

No data available Mobility in soil

**Components:** 

## SAFETY DATA SHEET

Valvoline™ VR1 Racing™ SAE 20W-50 Racing
Oil

Version: 1.5 Revision Date: 04/30/2020 Print Date: 09/09/2022

No data available
Other adverse effects
No data available
Product:

Additional ecological

information

: No data available

**Components:** 

### **SECTION 13. DISPOSAL CONSIDERATIONS**

### **Disposal methods**

General advice : Dispose of in accordance with all applicable local, state and

federal regulations.

Send to a licensed waste management company. Do not contaminate ponds, waterways or ditches with

chemical or used container.

Do not dispose of waste into sewer.

Contaminated packaging : Do not re-use empty containers.

Empty containers should be taken to an approved waste

handling site for recycling or disposal.

Dispose of as unused product. Empty remaining contents.

### **SECTION 14. TRANSPORT INFORMATION**

### International Regulations

### **UNRTDG**

Not regulated as a dangerous good

### IATA-DGR

Not regulated as a dangerous good

## **IMDG-Code**

Not regulated as a dangerous good

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### **National Regulations**

### **TDG**

Not regulated as a dangerous good

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

## **SAFETY DATA SHEET**

Valvoline™ VR1 Racing™ SAE 20W-50 Racing Oil

Version: 1.5 Revision Date: 04/30/2020 Print Date: 09/09/2022

### **SECTION 15. REGULATORY INFORMATION**

Canadian PBT Chemicals : This product contains the following components on the DSL

that are classified as Persistent, Bioaccumulative and/or Toxic

(PBT) under CEPA:

Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl)

bis(phosphorodithioate

NPRI Components : Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl)

bis(phosphorodithioate

Zinc, bis[O,O-bis(2-ethylhexyl) phosphorodithioato-S,S']-, (T-

4)-

ETHYL BENZENE

TOLUENE BENZENE NAPHTHALENE 1,4-DIOXANE

### The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : Not in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

TSCA : On TSCA Inventory

### **Inventories**

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

## **SECTION 16. OTHER INFORMATION**

**Further information** 

Internal information: R0173128


NFPA:	HMIS III:
NFPA:	I HIVIIƏ III:

# Valvoline<sub>2</sub>

## SAFETY DATA SHEET

Valvoline™ VR1 Racing™ SAE 20W-50 Racing Oil

Version: 1.5 Revision Date: 04/30/2020 Print Date: 09/09/2022



NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

### **Full text of H-Statements**

H315 Causes skin irritation.

H318 Causes serious eye damage.

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet:

ACGIH: American Conference of Industrial Hygienists

BEI: Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization



## **SAFETY DATA SHEET**

Valvoline™ VR1 Racing™ SAE 20W-50 Racing Oil

Version: 1.5 Revision Date: 04/30/2020 Print Date: 09/09/2022

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV: Threshold Limit Value TWA: Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

**DOT**: Department of Transportation

FIFRA: Federal Insecticide, Fungicide, and Rodenticide Act HMIRC: Hazardous Materials Information Review Commission

HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety and Health Administration

PMRA: Health Canada Pest Management Regulatory Agency

RTK: Right to Know

WHMIS: Workplace Hazardous Materials Information System