



SAFETY DATA SHEET

Valvoline™ Durablend™ SAE 10W-30 Motor Oil

Version: 1.3

Revision Date: 03/06/2020

Print Date:
09/09/2022

GHS classification in accordance with the Hazardous Products Regulations

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Valvoline™ Durablend™ SAE 10W-30 Motor Oil

Product code : 3469

Details of the supplier of the safety data sheet

Valvoline Canada Corp
905 Winston Churchill Blvd
Mississauga ON L5J 4P2
Canada
1-800-TEAMVAL (1-800-832-6825)

SDS@valvoline.com

Emergency telephone number

1-800-VALVOLINE (1-800-825-8654)

Regulatory Information Number

1-800-TEAMVAL (1-800-832-6825)

Product Information

1-800-TEAMVAL (1-800-832-6825)

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	Not a hazardous substance or mixture.	>=30.00 - < 60.00
Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based	72623-87-1	Asp. Tox. 1; H304	>=10.00 - < 30.00
Distillates, petroleum, solvent-refined heavy paraffinic	64741-88-4	Not a hazardous substance or mixture.	>=5.00 - < 10.00



SAFETY DATA SHEET

Valvoline™ Durablend™ SAE 10W-30 Motor Oil

Version: 1.3

Revision Date: 03/06/2020

Print Date:
09/09/2022

--	--	--	--

Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- | | |
|---|--|
| General advice | : No hazards which require special first aid measures. |
| If inhaled | : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician. |
| In case of skin contact | : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water. |
| In case of eye contact | : Remove contact lenses.
Protect unharmed eye. |
| If swallowed | : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician. |
| Most important symptoms and effects, both acute and delayed | : No symptoms known or expected. |
| Notes to physician | : No hazards which require special first aid measures. |

SECTION 5. FIREFIGHTING MEASURES

- | | |
|--------------------------------------|--|
| Suitable extinguishing media | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Carbon dioxide (CO ₂)
Dry chemical |
| Specific hazards during firefighting | : Do not allow run-off from fire fighting to enter drains or water courses.
If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release. |
| Hazardous combustion | : carbon dioxide and carbon monoxide |



SAFETY DATA SHEET

Valvoline™ Durablend™ SAE 10W-30 Motor Oil

Version: 1.3

Revision Date: 03/06/2020

Print Date:
09/09/2022

products

Specific extinguishing
methods

:

Product is compatible with standard fire-fighting agents.

Further information

:

Standard procedure for chemical fires.

Special protective equipment
for firefighters

:

In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions,
protective equipment and
emergency procedures

:

Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions

:

Prevent further leakage or spillage if safe to do so.

Methods and materials for
containment and cleaning up

:

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

Other information

:

Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling

:

Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.

Materials to avoid

:

No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	TWA	5 mg/m3 Mist	CA AB OEL
		STEL	10 mg/m3	CA AB OEL



SAFETY DATA SHEET

Valvoline™ Durablend™ SAE 10W-30 Motor Oil

Version: 1.3

Revision Date: 03/06/2020

Print Date:
09/09/2022

			Mist	
		TWAEV	5 mg/m3 Mist	CA QC OEL
		STEV	10 mg/m3 Mist	CA QC OEL
		TWA	1 mg/m3 Mist	CA BC OEL
Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based	72623-87-1	TWA	5 mg/m3 Mist	CA AB OEL
		STEL	10 mg/m3 Mist	CA AB OEL
		TWAEV	5 mg/m3 Mist	CA QC OEL
		STEV	10 mg/m3 Mist	CA QC OEL
		TWA	1 mg/m3 Mist	CA BC OEL
		PEL	5 mg/m3 particulate	CAL PEL
Distillates, petroleum, solvent- refined heavy paraffinic	64741-88-4	TWA	5 mg/m3 Mist	CA AB OEL
		STEL	10 mg/m3 Mist	CA AB OEL
		TWAEV	5 mg/m3 Mist	CA QC OEL
		STEV	10 mg/m3 Mist	CA QC OEL
		TWA	0.2 mg/m3 Mist	CA BC OEL
		TWA	1 mg/m3 Mist	CA BC OEL

Engineering measures : General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Wear as appropriate:



SAFETY DATA SHEET

Valvoline™ Durablend™ SAE 10W-30 Motor Oil

Version: 1.3

Revision Date: 03/06/2020

Print Date:
09/09/2022

Safety shoes
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures : General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: amber
Odour	: No data available
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Boiling point/boiling range	: > 425 °C
Flash point	: > 199 °C
	Method: Cleveland open cup
Evaporation rate	: < 1 Ethyl Ether
Flammability (solid, gas)	: No data available
Self-ignition	: No data available
Upper explosion limit / Upper flammability limit	: 6 %(V) Calculated Explosive Limit
Lower explosion limit / Lower flammability limit	: 1 %(V) Calculated Explosive Limit
Vapour pressure	: 0.0133333 hPa (21.11 °C) Calculated Vapor Pressure
Relative vapour density	: No data available
Relative density	: 0.870 (20 °C)
Density	: 0.8678 g/cm ³ (15.56 °C)
Solubility(ies) Water solubility	: negligible



SAFETY DATA SHEET

Valvoline™ Durablend™ SAE 10W-30 Motor Oil

Version: 1.3

Revision Date: 03/06/2020

Print Date:
09/09/2022

Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: < 3,400.000 mPa.s (-20 °C)
Viscosity, kinematic	: > 20.5 mm ² /s (40 °C)
Oxidizing properties	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Product will not undergo hazardous polymerization.
Conditions to avoid	: None known.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:



SAFETY DATA SHEET

Valvoline™ Durablend™ SAE 10W-30 Motor Oil

Version: 1.3

Revision Date: 03/06/2020

Print Date:
09/09/2022

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: Not classified as acutely toxic by inhalation under GHS.
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Remarks: No mortality observed at this dose.

Distillates, petroleum, solvent-refined heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: Not classified as acutely toxic by inhalation under GHS.
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Remarks: No mortality observed at this dose.

Skin corrosion/irritation

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Species : Rabbit
Result : No skin irritation

Distillates, petroleum, solvent-refined heavy paraffinic:

Species : Rabbit
Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks : Unlikely to cause eye irritation or injury.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Result : No eye irritation
Assessment : No eye irritation



SAFETY DATA SHEET

Valvoline™ Durablend™ SAE 10W-30 Motor Oil

Version: 1.3

Revision Date: 03/06/2020

Print Date:
09/09/2022

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Species : Rabbit
Result : No eye irritation

Distillates, petroleum, solvent-refined heavy paraffinic:

Species : Rabbit
Result : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Test Type : Buehler Test
Species : Guinea pig
Assessment : Does not cause skin sensitisation.

Distillates, petroleum, solvent-refined heavy paraffinic:

Test Type : Buehler Test
Species : Guinea pig
Assessment : Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

No aspiration toxicity classification



SAFETY DATA SHEET

Valvoline™ Durablend™ SAE 10W-30 Motor Oil

Version: 1.3

Revision Date: 03/06/2020

Print Date:
09/09/2022

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

May be fatal if swallowed and enters airways.

Distillates, petroleum, solvent-refined heavy paraffinic:

No aspiration toxicity classification

Further information

Product:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Not classified based on available information.

Long-term (chronic) aquatic hazard : Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Toxicity to fish : LL50 (Fish): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10,000 mg/l
Exposure time: 48 h

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Fish): 10 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 10 mg/l

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Not classified based on available information.

Long-term (chronic) aquatic hazard : Not classified based on available information.

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test Type: static test



SAFETY DATA SHEET

Valvoline™ Durablend™ SAE 10W-30 Motor Oil

Version: 1.3

Revision Date: 03/06/2020

Print Date:
09/09/2022

	Test substance: WAF Method: OECD Test Guideline 203 Remarks: No toxicity at the limit of solubility
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202
Toxicity to algae	: NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201
Toxicity to fish (Chronic toxicity)	: NOELR (Oncorhynchus mykiss (rainbow trout)): >= 1,000 mg/l Exposure time: 14 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEL (Daphnia (water flea)): 10 mg/l Exposure time: 21 d Test substance: WAF Method: OECD Test Guideline 211
Distillates, petroleum, solvent-refined heavy paraffinic:	
Toxicity to fish	: LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 203 Remarks: No toxicity at the limit of solubility
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202
Toxicity to algae	: NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201
Toxicity to fish (Chronic toxicity)	: NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated >= 1,000 mg/l Exposure time: 14 d



SAFETY DATA SHEET

Valvoline™ Durablend™ SAE 10W-30 Motor Oil

Version: 1.3

Revision Date: 03/06/2020

Print Date:
09/09/2022

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Daphnia (water flea)): 10 mg/l
Exposure time: 21 d
Test substance: WAF
Method: OECD Test Guideline 211

Persistence and degradability

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Distillates, petroleum, solvent-refined heavy paraffinic:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

No data available

Bioaccumulative potential

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Partition coefficient: n-octanol/water : log Pow: Expected > 7

No data available

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

Additional ecological information : No data available

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.

SECTION 14. TRANSPORT INFORMATION



SAFETY DATA SHEET

Valvoline™ Durablend™ SAE 10W-30 Motor Oil

Version: 1.3

Revision Date: 03/06/2020

Print Date:
09/09/2022

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

TDG

Not regulated as a dangerous good

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

The components of this product are reported in the following inventories:

DSL	: All components of this product are on the Canadian DSL
AICS	: On the inventory, or in compliance with the inventory
ENCS	: On the inventory, or in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: Not in compliance with the inventory
TCSI	: On the inventory, or in compliance with the inventory
TSCA	: On TSCA Inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION



SAFETY DATA SHEET

Valvoline™ Durablend™ SAE 10W-30 Motor Oil


Version: 1.3

Revision Date: 03/06/2020

Print Date:
09/09/2022

Further information

Internal information : R0289372

NFPA:	HMIS III:						
Flammability Health Instability Special hazard 	<table><tr><td>HEALTH</td><td>0</td></tr><tr><td>FLAMMABILITY</td><td>1</td></tr><tr><td>PHYSICAL HAZARD</td><td>0</td></tr></table> 0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic	HEALTH	0	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	0						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements

H304 May be fatal if swallowed and enters airways.

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.



SAFETY DATA SHEET

Valvoline™ Durablend™ SAE 10W-30 Motor Oil

Version: 1.3

Revision Date: 03/06/2020

Print Date:
09/09/2022

IATA-DGR : Dangerous Goods Regulation by the “International Air Transport Association” (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the “International Civil Aviation Organization”

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System