Cerulean™ #2 GREASE



Version: 1.2 Revision Date: 03/08/2021 Print Date: 09/09/2022

GHS classification in accordance with the Hazardous Products Regulations

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Cerulean™ #2

GREASE

Product code : 3474

Details of the supplier of the safety data sheet

Valvoline Canada Corp 905 Winston Churchill Blvd Mississauga ON L5J 4P2

Canada

1-800-TEAMVAL (1-800-832-6825)

1 000 12/11/17/12 (1 000 002 0020

SDS@valvoline.com

Emergency telephone number

1-800-VALVOLINE (1-800-825-8654)

Regulatory Information Number

1-800-TEAMVAL (1-800-832-6825)

Product Information

1-800-TEAMVAL (1-800-832-6825)

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Skin sensitisation : Sub-category 1A

GHS label elements

Hazard pictograms



Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.

Precautionary statements : **Prevention:**

P280 Wear protective gloves.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

Response:

P362 + P364 Take off contaminated clothing and wash it before

euse.

P333 + P313 If skin irritation or rash occurs: Get medical advice/

Valvoline.

Cerulean™ #2 GREASE

Version: 1.2 Revision Date: 03/08/2021 Print Date: 09/09/2022

attention.

P302 + P352 IF ON SKIN: Wash with plenty of water.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
NONANEDIOIC ACID,	38900-29-7	1;	>=10.00 - < 30.00
DILITHIUM SALT		Acute Tox. 4; H302	
2,5-BIS(OCTYLDITHIO)-1,3,4- THIADIAZOLE	13539-13-4	Acute Tox. 4; H332	>=0.10 - < 1.00
		Skin Irrit. 2; H315	
		Eye Irrit. 2A; H319	
		Skin Sens. 1; H317	
Pentene, 2,4,4-trimethyl-, sulfurized	68515-88-8	Skin Irrit. 2; H315	>=0.10 - < 1.00
		Skin Sens. 1A; H317	

Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If breathed in, move person into fresh air.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Remove contaminated clothing. If irritation develops, get

medical attention.

Valvoline

Cerulean™ #2 GREASE

Version: 1.2 Revision Date: 03/08/2021 Print Date: 09/09/2022

If on skin, rinse well with water.

First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

Wash contaminated clothing before re-use.

In case of eye contact : Flush eyes with water as a precaution.

> Remove contact lenses. Protect unharmed eye.

If eye irritation persists, consult a specialist.

If swallowed : If symptoms persist, call a physician.

Never give anything by mouth to an unconscious person.

Do not give milk or alcoholic beverages.

IF SWALLOWED: Call a POISON CENTER/ doctor if you feel

unwell.

Most important symptoms and effects, both acute and

delayed

: No symptoms known or expected.

May cause an allergic skin reaction.

: No hazards which require special first aid measures. Notes to physician

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray Foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

Hazardous combustion

products

: carbon dioxide and carbon monoxide

Specific extinguishing

methods

: Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Valvoline

Cerulean™ #2 GREASE

Version: 1.2 Revision Date: 03/08/2021 Print Date: 09/09/2022

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Use personal protective equipment.

Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions : If the product contaminates rivers and lakes or drains inform

respective authorities.

Prevent further leakage or spillage if safe to do so.

Prevent product from entering drains.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours/dust.

Do not smoke.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Container hazardous when empty.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes.

Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Keep container tightly closed in a dry and well-ventilated

place.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Valvoline.

Cerulean™ #2 GREASE

Version: 1.2 Revision Date: 03/08/2021 Print Date: 09/09/2022

Contains no substances with occupational exposure limit values.

Engineering measures : Provide sufficient mechanical (general and/or local exhaust)

ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or

apparent adverse effects.

Personal protective equipment

Respiratory protection : Respiratory protection is not required under normal conditions

of use.

No personal respiratory protective equipment normally

required.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Not required under normal conditions of use. Wear splash-

proof safety goggles if material could be misted or splashed

into eyes.

Skin and body protection : Wear resistant gloves (consult your safety equipment

supplier).

Wear as appropriate: Impervious clothing Safety shoes

Choose body protection according to the amount and concentration of the dangerous substance at the work place. Discard gloves that show tears, pinholes, or signs of wear.

Hygiene measures : When using do not smoke.

When using do not eat or drink.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Colour : blue green

Odour : hydrocarbon-like

Odour Threshold : No data available

pH : No data available

Valvoline.

Cerulean™ #2 GREASE

Version: 1.2 Revision Date: 03/08/2021 Print Date: 09/09/2022

Melting point/freezing point : No data available

Boiling point/boiling range : > 371 °C

Flash point : > 204 °C

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Self-ignition : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapour pressure : < 0.1 hPa (20 °C)

Relative vapour density

No data available

Relative density

No data available

Density : 0.9 g/cm3 (20 °C)

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 1000 mm2/s (40 °C)

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Valvoline.

Cerulean™ #2 GREASE

Version: 1.2 Revision Date: 03/08/2021 Print Date: 09/09/2022

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Product will not undergo hazardous polymerization.

Conditions to avoid : None known.

Incompatible materials : None known.

Hazardous decomposition

products No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Eye Contact Ingestion

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: 3,334 mg/kg

Method: Calculation method

Components:

NONANEDIOIC ACID, DILITHIUM SALT:

Acute oral toxicity : LD50 (Rat, female): > 300 - < 2,000 mg/kg

Remarks: Information given is based on data obtained from

similar substances.

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Assessment: Not classified as acutely toxic by dermal

absorption under GHS.

Remarks: Information given is based on data obtained from

similar substances.

2,5-BIS(OCTYLDITHIO)-1,3,4-THIADIAZOLE:

Acute inhalation toxicity : Assessment: The component/mixture is classified as acute

inhalation toxicity, category 4.

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks : May cause skin irritation in susceptible persons.

Valvoline.

Cerulean™ #2 GREASE

Version: 1.2 Revision Date: 03/08/2021 Print Date: 09/09/2022

Components:

NONANEDIOIC ACID, DILITHIUM SALT:

Method : Regulation (EC) No. 440/2008, Annex, B.40

Result : No skin irritation

2,5-BIS(OCTYLDITHIO)-1,3,4-THIADIAZOLE:Result : Irritating to skin.

-

Result : Severe skin irritation

Serious eye damage/eye irritation

Pentene, 2,4,4-trimethyl-, sulfurized:

Not classified based on available information.

Product:

Remarks : Unlikely to cause eye irritation or injury.

Components:

NONANEDIOIC ACID, DILITHIUM SALT:
Species : Rabbit

Result : Slight, transient irritation

2,5-BIS(OCTYLDITHIO)-1,3,4-THIADIAZOLE:

Result : Irritating to eyes.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Product:

Remarks : May cause allergic skin reaction.

Components:

NONANEDIOIC ACID, DILITHIUM SALT:

Test Type : Local lymph node assay

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 429

2,5-BIS(OCTYLDITHIO)-1,3,4-THIADIAZOLE:

Assessment : May cause sensitisation by skin contact.

Pentene, 2,4,4-trimethyl-, sulfurized:

Test Type : Open epicutaneous test

Species : Guinea pig

Assessment : The product is a skin sensitiser, sub-category 1A.

Method : OECD Test Guideline 406

Germ cell mutagenicity

Not classified based on available information.

Components:

NONANEDIOIC ACID, DILITHIUM SALT:

Valvoline.

Cerulean™ #2 GREASE

Version: 1.2 Revision Date: 03/08/2021 Print Date: 09/09/2022

Genotoxicity in vitro : Test Type: Ames test

Metabolic activation: with and without metabolic activation

Result: negative

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Short-term (acute) aquatic

hazard

: Acute aquatic toxicity Category 3; Harmful to aquatic life.

Long-term (chronic) aquatic

hazard

: Chronic aquatic toxicity Category 3; Harmful to aquatic life

with long lasting effects.

Components:

NONANEDIOIC ACID, DILITHIUM SALT:

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 100 mg/l

Exposure time: 96 h Test Type: static test

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Test Type: static test

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 23 mg/l

End point: Growth inhibition

Exposure time: 72 h Test Type: static test

Pentene, 2,4,4-trimethyl-, sulfurized:

Toxicity to fish : LC50 (Fish): 0.494 mg/l

Exposure time: 96 h Test Type: static test

Valvoline

Cerulean™ #2 GREASE

Version: 1.2 Revision Date: 03/08/2021 Print Date: 09/09/2022

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: EC50 (Aquatic invertebrates): 0.004 mg/l

Exposure time: 96 h Test Type: static test

Ecotoxicology Assessment

Short-term (acute) aquatic

hazard

: Acute aquatic toxicity Category 1; Very toxic to aquatic life.

Long-term (chronic) aquatic

hazard

: Chronic aquatic toxicity Category 1; Very toxic to aquatic life

with long lasting effects.

Persistence and degradability

Components:

NONANEDIOIC ACID, DILITHIUM SALT:

Biodegradability : Result: Readily biodegradable.

Remarks: Information given is based on data obtained from

similar substances.

No data available

Bioaccumulative potential

Components:

NONANEDIOIC ACID, DILITHIUM SALT: Partition coefficient: n-

octanol/water

: log Pow: -3.5

No data available Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

Additional ecological : Harmful to aquatic life with long lasting effects., An information

environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Dispose of in accordance with all applicable local, state and

federal regulations.

Send to a licensed waste management company. Do not contaminate ponds, waterways or ditches with

chemical or used container.

The product should not be allowed to enter drains, water

courses or the soil.

Contaminated packaging : Empty remaining contents.

Valvoline.

Cerulean™ #2 GREASE

Version: 1.2 Revision Date: 03/08/2021 Print Date: 09/09/2022

Dispose of as unused product.

Empty containers should be taken to an approved waste

handling site for recycling or disposal. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

TDG

Not regulated as a dangerous good

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : Not in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

TSCA : On the inventory, or in compliance with the inventory

Inventories



Cerulean™ #2 GREASE


Version: 1.2 Revision Date: 03/08/2021 Print Date: 09/09/2022

AICS (Australia), AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Internal information: R0290465



NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the

Valvoline.

Cerulean™ #2 GREASE

Version: 1.2 Revision Date: 03/08/2021 Print Date: 09/09/2022

information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet:

ACGIH: American Conference of Industrial Hygienists

BEI: Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement: Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx: Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV : Threshold Limit Value TWA : Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA: Federal Insecticide, Fungicide, and Rodenticide Act HMIRC: Hazardous Materials Information Review Commission

HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety and Health Administration

PMRA: Health Canada Pest Management Regulatory Agency

RTK: Right to Know

WHMIS: Workplace Hazardous Materials Information System



Cerulean™ #2 GREASE

Version: 1.2 Revision Date: 03/08/2021 Print Date: 09/09/2022