Valvoline:	Page: 1
SAFETY DATA SHEET	Revision Date: 05/19/2017
	Print Date: 9/22/2022
	SDS Number: R0163802
All Fleet™ SAE 30 Engine Oil	Version: 1.0
822564	

GHS classification in accordance with the Hazardous Products Regulations

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : All Fleet™ SAE 30

Engine Oil

Details of the supplier of the safety data	Emergency telephone number
sheet	1-800-VALVOLINE (1-800-825-8654)
Valvoline Canada Corp	
905 Winston Churchill Blvd	
Mississauga ON L5J 4P2	Regulatory Information Number
Canada	1-800-TEAMVAL
1-800-TEAMVAL	
	Product Information
	1-800-TEAMVAL

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

nazaraoao componento			
Chemical name	CAS-No.	Classification	Concentration (%)
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0	Asp. Tox. 1; H304	>=1.00 - < 5.00
ZINC BIS[O-(6-	93819-94-4	Skin Irrit. 2; H315	>=1.00 - < 3.00
METHYLHELPTYL)]BIS[O-SEC-BUTYL)]BIS(DITHIOPHOSPATE)		Eye Dam. 1; H318	

SECTION 4. FIRST AID MEASURES

Valvoline:	Page: 2
SAFETY DATA SHEET	Revision Date: 05/19/2017
	Print Date: 9/22/2022
	SDS Number: R0163802
All Fleet™ SAE 30 Engine Oil	Version: 1.0
822564	

General advice : No hazards which require special first aid measures.

If inhaled : If breathed in, move person into fresh air.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

If swallowed : Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

: Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary

abnormalities.

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through

the skin may include:

stomach or intestinal upset (nausea, vomiting, diarrhea)

irritation (nose, throat, airways)

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray Foam

Carbon dioxide (CO2)

Dry chemical

Valvoline:	Page: 3
SAFETY DATA SHEET	Revision Date: 05/19/2017
	Print Date: 9/22/2022
	SDS Number: R0163802
All Fleet™ SAE 30 Engine Oil	Version: 1.0
822564	

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: carbon dioxide and carbon monoxide

Hydrocarbons zinc oxide Sulphur oxides hydrogen sulfide mercaptans

Specific extinguishing

methods

.

Product is compatible with standard fire-fighting agents.

Further information : Standard procedure for chemical fires.

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Materials to avoid : No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Valvoline:	Page: 4
SAFETY DATA SHEET	Revision Date: 05/19/2017
	Print Date: 9/22/2022
	SDS Number: R0163802
All Fleet™ SAE 30 Engine Oil	Version: 1.0
822564	

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Engineering measures : General room ventilation should be adequate for normal

conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known,

suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : Respiratory protection is not required under normal conditions

of use.

No personal respiratory protective equipment normally

required.

Eye protection : Not required under normal conditions of use. Wear splash-

proof safety goggles if material could be misted or splashed

into eves.

Skin and body protection : Wear resistant gloves (consult your safety equipment

supplier).

Wear as appropriate:

Safety shoes

Hygiene measures : General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Colour : amber

Odour : hydrocarbon-like

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : 424.99 °F / 218.33 °C

(1,013.333333 hPa)

Calculated Phase Transition Liquid/Gas

Flash point : $> 390 \, ^{\circ}\text{F} \, / > 199 \, ^{\circ}\text{C}$

Method: Cleveland open cup

Valvoline:	Page: 5
SAFETY DATA SHEET	Revision Date: 05/19/2017
	Print Date: 9/22/2022
	SDS Number: R0163802
All Fleet™ SAE 30 Engine Oil	Version: 1.0
822564	

Evaporation rate : > 1

Ethyl Ether

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : 0.0133333 hPa (37.78 °C)

Calculated Vapor Pressure

Relative vapour density : No data available

Relative density : 0.89 (15.6 °C)

Density : 0.8781 g/cm3 (15.6 °C)

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Thermal decomposition :

No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Product will not undergo hazardous polymerization.

Valvoline:	Page: 6
SAFETY DATA SHEET	Revision Date: 05/19/2017
	Print Date: 9/22/2022
	SDS Number: R0163802
All Fleet™ SAE 30 Engine Oil	Version: 1.0
822564	

Conditions to avoid : excessive heat

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products carbon dioxide and carbon monoxide

hydrogen sulfide Sulphur oxides zinc oxide fumes mercaptans

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of : Inhalation

exposure Skin contact

Eye Contact Ingestion

Acute toxicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

ZINC BIS[O-(6-METHYLHELPTYL)]BIS[O-SEC-BUTYL)]BIS(DITHIOPHOSPATE):

Acute oral toxicity : LD50 (Rat): 2,600 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg

Method: OECD Test Guideline 402

Assessment: Not classified as acutely toxic by dermal

absorption under GHS.

Skin corrosion/irritation

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Result: Slight, transient irritation

ZINC BIS[O-(6-METHYLHELPTYL)]BIS[O-SEC-BUTYL)]BIS(DITHIOPHOSPATE):

Species: Guinea pig

Method: OECD Test Guideline 404

Result: Irritating to skin.

Remarks: Information given is based on data obtained from similar substances.

Serious eye damage/eye irritation

Valvoline:	Page: 7
SAFETY DATA SHEET	Revision Date: 05/19/2017
	Print Date: 9/22/2022
	SDS Number: R0163802
All Fleet™ SAE 30 Engine Oil	Version: 1.0
822564	

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Result: Slight, transient irritation

ZINC BIS[O-(6-METHYLHELPTYL)]BIS[O-SEC-BUTYL)]BIS(DITHIOPHOSPATE):

Species: Rabbit Result: Corrosive

Remarks: Information given is based on data obtained from similar substances.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Components:

ZINC BIS[O-(6-METHYLHELPTYL)]BIS[O-SEC-BUTYL)]BIS(DITHIOPHOSPATE):

Genotoxicity in vitro : Test Type: Ames test

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Remarks: Information given is based on data obtained from

similar substances.

Genotoxicity in vivo : Test Type: Micronucleus test

Test species: Mouse

Method: OECD Test Guideline 474

Result: negative

Remarks: Information given is based on data obtained from

similar substances.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

May be fatal if swallowed and enters airways.

Further information

Valvoline ₂	P	age: 8
SAFETY DATA SHEET	Revision Date: 05/19	/2017
	Print Date: 9/22	/2022
	SDS Number: R01	63802
All Fleet™ SAE 30 Engine Oil	Versio	n: 1.0
822564		

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Components:

ZINC BIS[O-(6-METHYLHELPTYL)]BIS[O-SEC-BUTYL)]BIS(DITHIOPHOSPATE):

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 4.5 mg/l

Exposure time: 96 h Test Type: semi-static test

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Water flea (Daphnia magna)): 5.4 mg/l

Exposure time: 48 h Test Type: static test

Toxicity to algae : EC50 (Selenastrum capricornutum (green algae)): 2.1 mg/l

End point: Growth inhibition

Exposure time: 72 h
Test Type: static test

Persistence and degradability

ZINC BIS[O-(6-METHYLHELPTYL)]BIS[O-SEC-BUTYL)]BIS(DITHIOPHOSPATE):

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 1.5 % Exposure time: 28 d

Method: OECD Test Guideline 301B

No data available

Bioaccumulative potential

ZINC BIS[O-(6-METHYLHELPTYL)]BIS[O-SEC-BUTYL)]BIS(DITHIOPHOSPATE):

Partition coefficient: n- : log Pow: 0.59 - 1.2 (23 °C)

octanol/water

No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Additional ecological

information

: No data available

Valvoline:	Page: 9
SAFETY DATA SHEET	Revision Date: 05/19/2017
	Print Date: 9/22/2022
	SDS Number: R0163802
All Fleet™ SAE 30 Engine Oil	Version: 1.0
822564	

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging : Empty remaining contents.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD	SUBSIDIARY	PACKING	MARINE
		CLASS	HAZARDS	GROUP	POLLUTANT /
					LTD. QTY.

U.S. DOT - ROAD

0.0.20.
Not dangerous goods

CFR_RAIL_C

Not dangerous goods	

U.S. DOT - INLAND WATERWAYS

Not dangerous goods	

TDG_ROAD_C

Not dangerous goods

TDG RAIL C

	Not dangerous goods

TDG_INWT_C

Not dangerous goods	

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods	

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Valvoline:	Page: 10
SAFETY DATA SHEET	Revision Date: 05/19/2017
	Print Date: 9/22/2022
	SDS Number: R0163802
All Fleet™ SAE 30 Engine Oil	Version: 1.0
822564	

Not dangerous goods	

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods	

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no	

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TSCA : On TSCA Inventory

Inventories


AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 05/19/2017

Valvoline:	Page: 11
SAFETY DATA SHEET	Revision Date: 05/19/2017
	Print Date: 9/22/2022
	SDS Number: R0163802
All Fleet™ SAE 30 Engine Oil	Version: 1.0
822564	



NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H318 Causes serious eye damage.

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH: American Conference of Industrial Hygienists

BEI: Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

Valvoline:	Page: 12
SAFETY DATA SHEET	Revision Date: 05/19/2017
	Print Date: 9/22/2022
	SDS Number: R0163802
All Fleet™ SAE 30 Engine Oil	Version: 1.0
822564	

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL: Occupational Exposure Limit
P-Statement: Precautionary Statement
PBT: Persistent, Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV: Threshold Limit Value TWA: Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

DOT: Department of Transportation

FIFRA: Federal Insecticide, Fungicide, and Rodenticide Act HMIRC: Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety and Health Administration

PMRA: Health Canada Pest Management Regulatory Agency

RTK: Right to Know

WHMIS: Workplace Hazardous Materials Information System