

Valvoline™ High Mileage with MaxLife™ Technology SAE 10W-30 Motor Oil

Version: 1.10 Revision Date: 10/23/2020 Print Date: 09/22/2022

GHS classification in accordance with the Hazardous Products Regulations

## **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

**Product identifier** 

Trade name : Valvoline™ High Mileage with MaxLife™ Technology SAE

10W-30 Motor Oil

Product code : 822567

Details of the supplier of the safety data sheet

Valvoline Canada Corp 905 Winston Churchill Blvd Mississauga ON L5J 4P2

Canada

1-800-TEAMVAL (1-800-832-6825)

Emergency telephone number 1-800-VALVOLINE (1-800-825-8654)

**Regulatory Information Number** 1-800-TEAMVAL (1-800-832-6825)

**Product Information** 

1-800-TEAMVAL (1-800-832-6825)

SDS@valvoline.com

#### **SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification** 

Not a hazardous substance or mixture.

**GHS** label elements

Not a hazardous substance or mixture.

Other hazards

None known.

### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

Chemical nature : Defatter

**Hazardous components** 

Chemical name	CAS-No.	Classification	Concentration (%)
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC		Not a hazardous substance or mixture.	>=30.00 - < 60.00
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY	• · · · - • · ·	Not a hazardous substance or mixture.	>=30.00 - < 60.00



Valvoline™ High Mileage with MaxLife™ Technology SAE 10W-30 Motor Oil

Version: 1.10 Revision Date: 10/23/2020 Print Date: 09/22/2022

PARAFFINIC			
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	Asp. Tox. 1; H304	>=1.00 - < 5.00

Actual concentration or concentration range is withheld as a trade secret

#### **SECTION 4. FIRST AID MEASURES**

General advice : No hazards which require special first aid measures.

If inhaled : If breathed in, move person into fresh air.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

If swallowed : Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

: No symptoms known or expected.

Notes to physician : No hazards which require special first aid measures.

# **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray

Foam

Carbon dioxide (CO2)

Dry chemical

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the

### SAFETY DATA SHEET

Valvoline™ High Mileage with MaxLife™ Technology SAE 10W-30 Motor Oil

Version: 1.10 Revision Date: 10/23/2020 Print Date: 09/22/2022

point of release.

Hazardous combustion

products

: carbon dioxide and carbon monoxide

Specific extinguishing

methods

:

Product is compatible with standard fire-fighting agents.

Further information : Standard procedure for chemical fires.

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

#### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Materials to avoid : No materials to be especially mentioned.

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components		(Form of exposure)	Control parameters / Permissible concentration	Basis
DISTULATES (DETROLEUM)	C4740 E4 7			
DISTILLATES (PETROLEUM),	64742-54-7	TWA	5 mg/m3	CA AB OEL



Valvoline™ High Mileage with MaxLife™ Technology SAE 10W-30 Motor Oil

Version: 1.10 Revision Date: 10/23/2020 Print Date: 09/22/2022

HYDROTREATED HEAVY PARAFFINIC			Mist	
		STEL	10 mg/m3 Mist	CA AB OEL
		TWAEV	5 mg/m3 Mist	CA QC OEL
		STEV	10 mg/m3 Mist	CA QC OEL
-		TWA	1 mg/m3 Mist	CA BC OEL
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	TWA	5 mg/m3 Mist	CA AB OEL
		STEL	10 mg/m3 Mist	CA AB OEL
		TWAEV	5 mg/m3 Mist	CA QC OEL
		STEV	10 mg/m3 Mist	CA QC OEL
		TWA	1 mg/m3 Mist	CA BC OEL
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	TWA	5 mg/m3 Mist	CA AB OEL
		STEL	10 mg/m3 Mist	CA AB OEL
		TWAEV	5 mg/m3 Mist	CA QC OEL
		STEV	10 mg/m3 Mist	CA QC OEL
		TWA	1 mg/m3 Mist	CA BC OEL

**Engineering measures** 

: General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

# Personal protective equipment

Respiratory protection

No personal respiratory protective equipment normally

required.

No personal respiratory protective equipment normally

required.

Eye protection : Not required under normal conditions of use. Wear splash-

proof safety goggles if material could be misted or splashed

into eyes.

# SAFETY DATA SHEET

Valvoline™ High Mileage with MaxLife™ Technology SAE 10W-30 Motor Oil

Version: 1.10 Revision Date: 10/23/2020 Print Date: 09/22/2022

Skin and body protection : Wear resistant gloves (consult your safety equipment

supplier).

Wear as appropriate:

Safety shoes

Hygiene measures : General industrial hygiene practice.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Colour : amber

Odour : mild

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : > 218 °C

(1013 hPa)

Flash point : > 199 °C

Method: Cleveland open cup

Evaporation rate : < 1

Flammability (solid, gas) : No data available

Self-ignition : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapour pressure : < 1.0 mmHg (20 °C)

Relative vapour density : > 1

AIR=1

Relative density : No data available



Valvoline™ High Mileage with MaxLife™ Technology SAE 10W-30 Motor Oil

Version: 1.10 Revision Date: 10/23/2020 Print Date: 09/22/2022

Density : 0.8687 g/cm3 (15.6 °C)

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : ca. 70 mm2/s (40 °C)

Oxidizing properties : No data available

### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Product will not undergo hazardous polymerization.

Conditions to avoid : excessive heat

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products No hazardous decomposition products are known.

# **SECTION 11. TOXICOLOGICAL INFORMATION**

# Information on likely routes of exposure

Inhalation

Skin contact

**Eye Contact** 

Ingestion

#### **Acute toxicity**

Not classified based on available information.

#### Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

# SAFETY DATA SHEET

Valvoline™ High Mileage with MaxLife™ Technology SAE 10W-30 Motor Oil

Version: 1.10 Revision Date: 10/23/2020 Print Date: 09/22/2022

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:** 

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Skin corrosion/irritation

Not classified based on available information.

Product:

Result : Slight, transient irritation

**Components:** 

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:** 

Assessment : Slight, transient irritation Result : Slight, transient irritation

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:** 

Assessment : Slight, transient irritation Result : Slight, transient irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Assessment : Slight, transient irritation Result : Slight, transient irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Result : Slight, transient irritation

Remarks : Expected based on components.

Remarks : Unlikely to cause eye irritation or injury.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Result : No eye irritation
Assessment : No eye irritation

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:** 

Result : No eye irritation
Assessment : No eye irritation

**HYDROTREATED LIGHT PARAFFINIC DISTILLATE:** 

Result : Slight, transient irritation
Assessment : Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.



Valvoline™ High Mileage with MaxLife™ Technology SAE 10W-30 Motor Oil

Version: 1.10 Revision Date: 10/23/2020 Print Date: 09/22/2022

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

**Components:** 

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

**HYDROTREATED LIGHT PARAFFINIC DISTILLATE:** 

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

**Aspiration toxicity** 

Not classified based on available information.

**Product:** 

No aspiration toxicity classification

**Components:** 

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:** 

No aspiration toxicity classification

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

**Further information** 

Product:

Remarks : No data available

# **SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity** 

**Product:** 

Ecotoxicology Assessment

Short-term (acute) aquatic : Not classified based on available information.

hazard

# SAFETY DATA SHEET

Valvoline™ High Mileage with MaxLife™ Technology SAE 10W-30 Motor Oil

Version: 1.10 Revision Date: 10/23/2020 Print Date: 09/22/2022

Long-term (chronic) aquatic

hazard

: Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Toxicity to fish : LL50 (Fish): > 100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: EL50 (Aquatic invertebrates): > 10,000 mg/l

Exposure time: 48 h

: EL50 (Algae, algal mat (Algae)): > 100 mg/l Toxicity to algae

Exposure time: 72 h

Toxicity to fish (Chronic

toxicity)

: NOEC (Fish): 10 mg/l

aquatic invertebrates (Chronic toxicity)

Toxicity to daphnia and other : NOEC (Aquatic invertebrates): 10 mg/l

**Ecotoxicology Assessment** 

Short-term (acute) aquatic

hazard

: Not classified based on available information.

Long-term (chronic) aquatic

hazard

: Not classified based on available information.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

**Ecotoxicology Assessment** 

Short-term (acute) aquatic

hazard

: Not classified based on available information.

Long-term (chronic) aquatic

hazard

: Not classified based on available information.

Persistence and degradability

**Components:** 

No data available

Bioaccumulative potential

**Components:** 

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Partition coefficient: n-: log Pow: Expected > 7

octanol/water

No data available

Mobility in soil

Components:

No data available

Other adverse effects

No data available

# **SAFETY DATA SHEET**

Valvoline™ High Mileage with MaxLife™ Technology SAE 10W-30 Motor Oil

Version: 1.10 Revision Date: 10/23/2020 Print Date: 09/22/2022

**Product:** 

Additional ecological

information

: No data available

Components:

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

General advice : Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging : Empty remaining contents.

#### **SECTION 14. TRANSPORT INFORMATION**

#### International Regulations

#### **UNRTDG**

Not regulated as a dangerous good

### IATA-DGR

Not regulated as a dangerous good

#### **IMDG-Code**

Not regulated as a dangerous good

# Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### **National Regulations**

#### **TDG**

Not regulated as a dangerous good

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

#### **SECTION 15. REGULATORY INFORMATION**

Canadian PBT Chemicals : This product contains the following components on the DSL

that are classified as Persistent, Bioaccumulative and/or Toxic

(PBT) under CEPA:

Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl)

bis(phosphorodithioate

NPRI Components : Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl)

bis(phosphorodithioate



Valvoline™ High Mileage with MaxLife™ Technology SAE 10W-30 Motor Oil

Version: 1.10 Revision Date: 10/23/2020 Print Date: 09/22/2022

Zinc, bis[O,O-bis(2-ethylhexyl) phosphorodithioato-S,S']-, (T-

4)-

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS

ETHYL BENZENE

TOLUENE BENZENE NAPHTHALENE 1,4-DIOXANE

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

TSCA : On TSCA Inventory

#### **Inventories**

AICS (Australia), AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

#### **SECTION 16. OTHER INFORMATION**

**Further information** 


Internal information: R0355563

NFPA: HM	MIS III:
----------	----------



Valvoline™ High Mileage with MaxLife™ Technology SAE 10W-30 Motor Oil

Version: 1.10 Revision Date: 10/23/2020 Print Date: 09/22/2022



NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

#### **Full text of H-Statements**

H304 May be fatal if swallowed and enters airways.

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH: American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"



Valvoline™ High Mileage with MaxLife™ Technology SAE 10W-30 Motor Oil

Version: 1.10 Revision Date: 10/23/2020 Print Date: 09/22/2022

IMDG: International Maritime Code for Dangerous Goods ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit P-Statement : Precautionary Statement PBT : Persistent , Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV: Threshold Limit Value TWA: Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

DOT: Department of Transportation

FIFRA: Federal Insecticide, Fungicide, and Rodenticide Act HMIRC: Hazardous Materials Information Review Commission

HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety and Health Administration

PMRA: Health Canada Pest Management Regulatory Agency

RTK: Right to Know

WHMIS: Workplace Hazardous Materials Information System