



SAFETY DATA SHEET
All Fleet™ Plus Heavy Duty Diesel SAE 10W-30
Motor Oil

Version: 1.6

Revision Date: 05/03/2021

Print Date:
09/22/2022

GHS classification in accordance with the Hazardous Products Regulations

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : All Fleet™ Plus Heavy Duty Diesel SAE 10W-30 Motor Oil
Product code : 822569

Details of the supplier of the safety data sheet

Valvoline Canada Corp
905 Winston Churchill Blvd
Mississauga ON L5J 4P2
Canada
1-800-TEAMVAL (1-800-832-6825)

SDS@valvoline.com

Emergency telephone number

1-800-VALVOLINE (1-800-825-8654)

Regulatory Information Number

1-800-TEAMVAL (1-800-832-6825)

Product Information

1-800-TEAMVAL (1-800-832-6825)

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity:
10.7572 %

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
Distillates, petroleum, solvent-refined heavy paraffinic	64741-88-4	Not a hazardous substance or mixture.	>=30.00 - < 60.00
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	Not a hazardous substance or mixture.	>=10.00 - < 30.00
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY	64742-65-0	Asp. Tox. 1; H304	>=1.00 - < 5.00



SAFETY DATA SHEET

All Fleet™ Plus Heavy Duty Diesel SAE 10W-30
Motor Oil

Version: 1.6

Revision Date: 05/03/2021

Print Date:
09/22/2022

PARAFFINIC			
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts	85940-28-9	Skin Irrit. 2; H315 Eye Irrit. 2A; H319	≥ 1.00 - < 5.00

Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : No hazards which require special first aid measures.
- If inhaled : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Wash contaminated clothing before re-use.
If on skin, rinse well with water.
Remove contaminated clothing. If irritation develops, get medical attention.
- In case of eye contact : If eye irritation persists, consult a specialist.
Protect unharmed eye.
Remove contact lenses.
Flush eyes with water as a precaution.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : No symptoms known or expected.
- Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing : High volume water jet



SAFETY DATA SHEET

All Fleet™ Plus Heavy Duty Diesel SAE 10W-30
Motor Oil

Version: 1.6

Revision Date: 05/03/2021

Print Date:
09/22/2022

media

- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release.
- Hazardous combustion products : Oxides of phosphorus
carbon dioxide and carbon monoxide
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Standard procedure for chemical fires.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Use personal protective equipment.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.
- Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Dispose of rinse water in accordance with local and national regulations.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Avoid contact with skin and eyes.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated



SAFETY DATA SHEET

All Fleet™ Plus Heavy Duty Diesel SAE 10W-30
Motor Oil

Version: 1.6

Revision Date: 05/03/2021

Print Date:
09/22/2022

place.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates, petroleum, solvent-refined heavy paraffinic	64741-88-4	TWA	5 mg/m3 Mist	CA AB OEL
		STEL	10 mg/m3 Mist	CA AB OEL
		TWAEV	5 mg/m3 Mist	CA QC OEL
		STEV	10 mg/m3 Mist	CA QC OEL
		TWA	0.2 mg/m3 Mist	CA BC OEL
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	TWA	1 mg/m3 Mist	CA BC OEL
		TWA	5 mg/m3 Mist	CA AB OEL
		STEL	10 mg/m3 Mist	CA AB OEL
		TWAEV	5 mg/m3 Mist	CA QC OEL
		STEV	10 mg/m3 Mist	CA QC OEL
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0	TWA	1 mg/m3 Mist	CA BC OEL
		TWA	5 mg/m3 Mist	CA AB OEL
		STEL	10 mg/m3 Mist	CA AB OEL
		TWAEV	5 mg/m3 Mist	CA QC OEL
		STEV	10 mg/m3 Mist	CA QC OEL
		TWA	0.2 mg/m3 Mist	CA BC OEL
		TWA	1 mg/m3 Mist	CA BC OEL

Engineering measures

: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if



SAFETY DATA SHEET

All Fleet™ Plus Heavy Duty Diesel SAE 10W-30
Motor Oil

Version: 1.6

Revision Date: 05/03/2021

Print Date:
09/22/2022

applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection	: No personal respiratory protective equipment normally required.
Hand protection	
Remarks	: The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	: Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.
Skin and body protection	: Wear resistant gloves (consult your safety equipment supplier). Choose body protection according to the amount and concentration of the dangerous substance at the work place. Safety shoes Impervious clothing Wear as appropriate:
Hygiene measures	: When using do not smoke. When using do not eat or drink. Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: amber
Odour	: oily
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Boiling point/boiling range	: 271.1 °C (1,013.333333 hPa) Calculated Phase Transition Liquid/Gas
Flash point	: > 199 °C



SAFETY DATA SHEET
All Fleet™ Plus Heavy Duty Diesel SAE 10W-30
Motor Oil

Version: 1.6

Revision Date: 05/03/2021

Print Date:
09/22/2022

Method: Cleveland open cup

Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Self-ignition	:	No data available
Upper explosion limit / Upper flammability limit	:	6 %(V) Calculated Explosive Limit
Lower explosion limit / Lower flammability limit	:	1 %(V) Calculated Explosive Limit
Vapour pressure	:	1.3333333 hPa (20 °C) Calculated Vapor Pressure
Relative vapour density	:	No data available
Relative density	:	0.88 (15.6 °C)
Density	:	0.87 g/cm3 (15.56 °C)
Solubility(ies)		
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Oxidizing properties	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	Stable under recommended storage conditions.
Possibility of hazardous reactions	:	Product will not undergo hazardous polymerization.



SAFETY DATA SHEET
All Fleet™ Plus Heavy Duty Diesel SAE 10W-30
Motor Oil

Version: 1.6

Revision Date: 05/03/2021

Print Date:
09/22/2022

Conditions to avoid : None known.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Components:

Distillates, petroleum, solvent-refined heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: Not classified as acutely toxic by inhalation under GHS.
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Remarks: No mortality observed at this dose.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts:

Acute oral toxicity : LD50 (Rat): 2,570 - 3,700 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 2.3 mg/l



SAFETY DATA SHEET

All Fleet™ Plus Heavy Duty Diesel SAE 10W-30
Motor Oil

Version: 1.6

Revision Date: 05/03/2021

Print Date:
09/22/2022

Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: Not classified as acutely toxic by inhalation
under GHS.
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 20,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

Distillates, petroleum, solvent-refined heavy paraffinic:

Species : Rabbit
Result : No skin irritation

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts:

Species : Rabbit
Result : Irritating to skin.

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks : Vapours may cause irritation to the eyes, respiratory system
and the skin.

Components:

Distillates, petroleum, solvent-refined heavy paraffinic:

Species : Rabbit
Result : No eye irritation

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Result : No eye irritation
Assessment : No eye irritation

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Result : Slight, transient irritation
Assessment : Slight, transient irritation

Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts:

Species : Rabbit
Result : Irritating to eyes.



SAFETY DATA SHEET

All Fleet™ Plus Heavy Duty Diesel SAE 10W-30
Motor Oil

Version: 1.6

Revision Date: 05/03/2021

Print Date:
09/22/2022

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Distillates, petroleum, solvent-refined heavy paraffinic:

Test Type	: Buehler Test
Species	: Guinea pig
Assessment	: Does not cause skin sensitisation.

Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts:

Test Type	: Buehler Test
Species	: Guinea pig
Assessment	: Does not cause skin sensitisation.
Method	: OECD Test Guideline 406

Germ cell mutagenicity

Not classified based on available information.

Components:

Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts:

Genotoxicity in vitro	: Test Type: Ames test
	Test system: Salmonella typhimurium
	Metabolic activation: with and without metabolic activation
	Result: negative

Carcinogenicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity -	: Classified based on DMSO extract content < 3% (Regulation
Assessment	(EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Components:

Distillates, petroleum, solvent-refined heavy paraffinic:

No aspiration toxicity classification



SAFETY DATA SHEET
All Fleet™ Plus Heavy Duty Diesel SAE 10W-30
Motor Oil

Version: 1.6

Revision Date: 05/03/2021

Print Date:
09/22/2022

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

No aspiration toxicity classification

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Not classified based on available information.

Long-term (chronic) aquatic hazard : Not classified based on available information.

Components:

Distillates, petroleum, solvent-refined heavy paraffinic:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 203
Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 202

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l
End point: Growth inhibition
Exposure time: 72 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated >= 1,000 mg/l
Exposure time: 14 d

Toxicity to daphnia and other : NOEL (Daphnia (water flea)): 10 mg/l



SAFETY DATA SHEET

All Fleet™ Plus Heavy Duty Diesel SAE 10W-30
Motor Oil

Version: 1.6

Revision Date: 05/03/2021

Print Date:
09/22/2022

aquatic invertebrates
(Chronic toxicity)

Exposure time: 21 d
Test substance: WAF
Method: OECD Test Guideline 211

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Toxicity to fish : LL50 (Fish): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10,000 mg/l
Exposure time: 48 h

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Fish): 10 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 10 mg/l

Ecotoxicology Assessment
Short-term (acute) aquatic hazard : Not classified based on available information.

Long-term (chronic) aquatic hazard : Not classified based on available information.

Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts:
Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 4.5 mg/l
Exposure time: 96 h
Test Type: semi-static test
Remarks: Information given is based on data obtained from similar substances.

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 5.4 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: WAF

Toxicity to algae : (Selenastrum capricornutum (green algae)): 2.1 mg/l
End point: Growth inhibition
Exposure time: 96 h
Test Type: static test
Test substance: WAF

Persistence and degradability

Components:

Distillates, petroleum, solvent-refined heavy paraffinic:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 4 %



SAFETY DATA SHEET
All Fleet™ Plus Heavy Duty Diesel SAE 10W-30
Motor Oil

Version: 1.6

Revision Date: 05/03/2021

Print Date:
09/22/2022

Exposure time: 28 d
Method: OECD Test Guideline 301B

Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts:
Biodegradability : Result: Not readily biodegradable.
Biodegradation: 1.5 %
Exposure time: 28 d
Method: OECD Test Guideline 301B
Remarks: Information given is based on data obtained from similar substances.

No data available

Bioaccumulative potential

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Partition coefficient: n- : log Pow: Expected > 7
octanol/water

Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts:
Partition coefficient: n- : log Pow: 8.8
octanol/water Remarks: QSAR

No data available

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

Additional ecological : No data available
information

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Dispose of in accordance with all applicable local, state and federal regulations.

Send to a licensed waste management company.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Do not dispose of waste into sewer.

Contaminated packaging : Do not re-use empty containers.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Dispose of as unused product.
Empty remaining contents.



SAFETY DATA SHEET

All Fleet™ Plus Heavy Duty Diesel SAE 10W-30
Motor Oil

Version: 1.6

Revision Date: 05/03/2021

Print Date:
09/22/2022

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

TDG

Not regulated as a dangerous good

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

NPRI Components : Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : Not in compliance with the inventory

ENCS : Not in compliance with the inventory

KECI : Not in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

TSCA : On TSCA Inventory

Inventories



SAFETY DATA SHEET

All Fleet™ Plus Heavy Duty Diesel SAE 10W-30
Motor Oil

Version: 1.6

Revision Date: 05/03/2021


Print Date:
09/22/2022

AICS (Australia), AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Internal information : R0229763

NFPA:	HMIS III:						
<p>Flammability</p> <p>Health</p> <p>Instability</p> <p>Special hazard</p> 	<table><tr><td>HEALTH</td><td>0</td></tr><tr><td>FLAMMABILITY</td><td>1</td></tr><tr><td>PHYSICAL HAZARD</td><td>0</td></tr></table> <p>0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	0	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	0						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements

H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).



SAFETY DATA SHEET

All Fleet™ Plus Heavy Duty Diesel SAE 10W-30
Motor Oil

Version: 1.6

Revision Date: 05/03/2021

Print Date:
09/22/2022

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System