		Page: 1
SAFETY DATA SHEET		Revision Date: 02/01/2019
		Print Date: 9/22/2022
		SDS Number: 000000255327
Valvoline Professional Series VPS POWER STEERING FLUID Power Steering Fluid ™ Trademark, Valvoline or its subsidiaries, registered in various countries 860343		Version: 1.2

GHS classification in accordance with the Hazardous Products Regulations

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Valvoline Professional Series VPS POWER STEERING FLUID
Power Steering Fluid
™ Trademark, Valvoline or its subsidiaries, registered in various countries

Details of the supplier of the safety data sheet

Valvoline Canada Corp
905 Winston Churchill Blvd
Mississauga ON L5J 4P2
Canada
1-800-TEAMVAL (1-800-832-6825)

SDS@valvoline.com

Emergency telephone number

1-800-VALVOLINE (1-800-825-8654)

Regulatory Information Number

1-800-TEAMVAL (1-800-832-6825)

Product Information

1-800-TEAMVAL (1-800-832-6825)

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	Asp. Tox. 1; H304	>=30.00 - < 50.00
HYDROTREATED LIGHT	64742-55-8	Asp. Tox. 1; H304	>=1.00 - < 5.00

**SAFETY DATA SHEET**

Revision Date: 02/01/2019

Print Date: 9/22/2022

SDS Number: 000000255327

Version: 1.2

Valvoline Professional Series VPS POWER
STEERING FLUID Power Steering Fluid
™ Trademark, Valvoline or its subsidiaries,
registered in various countries
860343

PARAFFINIC DISTILLATE			
DODECYL HYDROXYPROPYL SULFIDE	67124-09-8	Skin Sens. 1; H317	>=0.10 - < 1.00

SECTION 4. FIRST AID MEASURES

General advice	: No hazards which require special first aid measures.
If inhaled	: If breathed in, move person into fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
In case of eye contact	: Remove contact lenses. Protect unharmed eye.
If swallowed	: Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	: No symptoms known or expected.
Notes to physician	: No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO2) Dry chemical
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion	: carbon dioxide and carbon monoxide

**SAFETY DATA SHEET**

Revision Date: 02/01/2019

Print Date: 9/22/2022

SDS Number: 000000255327

Version: 1.2

Valvoline Professional Series VPS POWER
STEERING FLUID Power Steering Fluid
™ Trademark, Valvoline or its subsidiaries,
registered in various countries
860343

products

Hydrocarbons

Specific extinguishing
methods

: Product is compatible with standard fire-fighting agents.

Further information

: Fire residues and contaminated fire extinguishing water must
be disposed of in accordance with local regulations.Special protective equipment
for firefighters

: In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURESPersonal precautions,
protective equipment and
emergency procedures: Persons not wearing protective equipment should be excluded
from area of spill until clean-up has been completed.

Environmental precautions

: Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform
respective authorities.Methods and materials for
containment and cleaning up: Soak up with inert absorbent material (e.g. sand, silica gel,
acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

Other information

: Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling

: Smoking, eating and drinking should be prohibited in the
application area.
For personal protection see section 8.

Conditions for safe storage

: Containers which are opened must be carefully resealed and
kept upright to prevent leakage.

Materials to avoid

: No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION



SAFETY DATA SHEET

Revision Date: 02/01/2019

Print Date: 9/22/2022

SDS Number: 000000255327

Version: 1.2

Valvoline Professional Series VPS POWER STEERING FLUID Power Steering Fluid
TM Trademark, Valvoline or its subsidiaries, registered in various countries
860343

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	TWA	5 mg/m3 Mist	CA AB OEL
		STEL	10 mg/m3 Mist	CA AB OEL
		TWAEV	5 mg/m3 Mist	CA QC OEL
		STEV	10 mg/m3 Mist	CA QC OEL
		TWA	1 mg/m3 Mist	CA BC OEL
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	TWA	5 mg/m3 Mist	CA AB OEL
		STEL	10 mg/m3 Mist	CA AB OEL
		TWAEV	5 mg/m3 Mist	CA QC OEL
		STEV	10 mg/m3 Mist	CA QC OEL
		TWA	1 mg/m3 Mist	CA BC OEL

Engineering measures

: General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection

: No personal respiratory protective equipment normally required.

Eye protection

: Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection

: Wear as appropriate:
Safety shoes
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures

: General industrial hygiene practice.

**SAFETY DATA SHEET**

Revision Date: 02/01/2019

Print Date: 9/22/2022

SDS Number: 000000255327

Version: 1.2

Valvoline Professional Series VPS POWER
STEERING FLUID Power Steering Fluid
™ Trademark, Valvoline or its subsidiaries,
registered in various countries
860343

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Odour	: No data available
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: > 199 °C
	Method: Cleveland open cup
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Self-ignition	: No data available
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: No data available
Density	: No data available
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available

**SAFETY DATA SHEET**

Revision Date: 02/01/2019

Print Date: 9/22/2022

SDS Number: 000000255327

Version: 1.2

Valvoline Professional Series VPS POWER
STEERING FLUID Power Steering Fluid
™ Trademark, Valvoline or its subsidiaries,
registered in various countries
860343

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Product will not undergo hazardous polymerization.

Conditions to avoid : excessive heat
heat

Incompatible materials : Alkali metals
aluminum
Ammonia
Combustible material
halogens
Metals
metal oxides
Oxidizing agents
peroxides
reducing agents
sodium
Strong acids
strong bases
water

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation

Skin contact

**SAFETY DATA SHEET**

Revision Date: 02/01/2019

Print Date: 9/22/2022

SDS Number: 000000255327

Version: 1.2

Valvoline Professional Series VPS POWER
STEERING FLUID Power Steering Fluid
™ Trademark, Valvoline or its subsidiaries,
registered in various countries
860343

Eye Contact

Ingestion

Acute toxicity

Not classified based on available information.

Components:**Distillates (Petroleum), Hydrotreated Heavy Paraffinic:**

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

DODECYL HYDROXYPROPYL SULFIDE:Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
GLP: yesAcute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: Not classified as acutely toxic by dermal
absorption under GHS.**Skin corrosion/irritation**

Not classified based on available information.

Components:**Distillates (Petroleum), Hydrotreated Heavy Paraffinic:**

Assessment : Slight, transient irritation

Result : Slight, transient irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Assessment : Slight, transient irritation

Result : Slight, transient irritation

DODECYL HYDROXYPROPYL SULFIDE:

Species : Rabbit

Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks : Unlikely to cause eye irritation or injury.

Components:**Distillates (Petroleum), Hydrotreated Heavy Paraffinic:**


Result : No eye irritation

Assessment : No eye irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result : Slight, transient irritation

Assessment : Slight, transient irritation

		Page: 8
SAFETY DATA SHEET		Revision Date: 02/01/2019
		Print Date: 9/22/2022
		SDS Number: 000000255327
Valvoline Professional Series VPS POWER STEERING FLUID Power Steering Fluid ™ Trademark, Valvoline or its subsidiaries, registered in various countries 860343		Version: 1.2

DODECYL HYDROXYPROPYL SULFIDE:

Species : Rabbit
Result : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

DODECYL HYDROXYPROPYL SULFIDE:

Test Type : Local lymph node assay
Species : Guinea pig
Assessment : May cause sensitisation by skin contact.
Method : OECD Test Guideline 429

Germ cell mutagenicity

Not classified based on available information.

Components:

DODECYL HYDROXYPROPYL SULFIDE:

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

May be fatal if swallowed and enters airways.

**SAFETY DATA SHEET**

Revision Date: 02/01/2019

Print Date: 9/22/2022

SDS Number: 000000255327

Version: 1.2

Valvoline Professional Series VPS POWER
STEERING FLUID Power Steering Fluid
™ Trademark, Valvoline or its subsidiaries,
registered in various countries
860343

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

Further information**Product:**

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Product:**

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Acute aquatic toxicity Category 3; Harmful to aquatic life.

Long-term (chronic) aquatic hazard : Chronic aquatic toxicity Category 3; Harmful to aquatic life with long lasting effects.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Toxicity to fish : LL50 (Fish): > 100 mg/l
Exposure time: 96 hToxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10,000 mg/l
Exposure time: 48 hToxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Fish): 10 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 10 mg/l

Ecotoxicology Assessment
Short-term (acute) aquatic hazard : Not classified based on available information.

Long-term (chronic) aquatic hazard : Not classified based on available information.

DODECYL HYDROXYPROPYL SULFIDE:Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.75 mg/l
Exposure time: 96 h
Test Type: semi-static test

**SAFETY DATA SHEET**

Revision Date: 02/01/2019

Print Date: 9/22/2022

SDS Number: 000000255327

Version: 1.2

Valvoline Professional Series VPS POWER
STEERING FLUID Power Steering Fluid
™ Trademark, Valvoline or its subsidiaries,
registered in various countries
860343

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 0.58 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: WAF

Toxicity to algae : EL50 (Desmodesmus subspicatus (green algae)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: WAF

M-Factor (Short-term (acute) aquatic hazard) : 1

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Daphnia magna (Water flea)): 0.32 mg/l
Exposure time: 21 d
Test Type: semi-static test
Method: OECD Test Guideline 211
GLP: yes

M-Factor (Long-term (chronic) aquatic hazard) : 1

Persistence and degradability**Components:****DODECYL HYDROXYPROPYL SULFIDE:**

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 5 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

No data available

Bioaccumulative potential**Components:****DODECYL HYDROXYPROPYL SULFIDE:**

Partition coefficient: n-octanol/water : log Pow: 4.7 - 6.5

No data available

Mobility in soil**Components:**

No data available

Other adverse effects

No data available

Product:

Additional ecological : An environmental hazard cannot be excluded in the event of

**SAFETY DATA SHEET**

Revision Date: 02/01/2019

Print Date: 9/22/2022

SDS Number: 000000255327

Version: 1.2

Valvoline Professional Series VPS POWER
STEERING FLUID Power Steering Fluid
™ Trademark, Valvoline or its subsidiaries,
registered in various countries
860343

information

unprofessional handling or disposal., May cause long lasting
harmful effects to aquatic life.

Components:**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

General advice

: Dispose of in accordance with all applicable local, state and
federal regulations.

The product should not be allowed to enter drains, water
courses or the soil.

Contaminated packaging

: Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste
handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION**International transport regulations****REGULATION**

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS


Not dangerous goods

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

		Page: 12
SAFETY DATA SHEET		Revision Date: 02/01/2019
		Print Date: 9/22/2022
		SDS Number: 000000255327
Valvoline Professional Series VPS POWER STEERING FLUID Power Steering Fluid ™ Trademark, Valvoline or its subsidiaries, registered in various countries 860343		Version: 1.2

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

The components of this product are reported in the following inventories:

- DSL : All components of this product are on the Canadian DSL
- AICS : Not in compliance with the inventory
- ENCS : On the inventory, or in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : Not in compliance with the inventory
- TCSI : On the inventory, or in compliance with the inventory

**SAFETY DATA SHEET**

Revision Date: 02/01/2019

Print Date: 9/22/2022

SDS Number: 000000255327


Version: 1.2

Valvoline Professional Series VPS POWER
STEERING FLUID Power Steering Fluid
™ Trademark, Valvoline or its subsidiaries,
registered in various countries
860343

TSCA : On TSCA Inventory

SECTION 16. OTHER INFORMATION**Further information**

Revision Date: 02/01/2019

NFPA:	HMIS III:						
<p>Flammability</p> <p>Health</p> <p>Instability</p> <p>Special hazard.</p> 	<table><tr><td>HEALTH</td><td>0</td></tr><tr><td>FLAMMABILITY</td><td>1</td></tr><tr><td>PHYSICAL HAZARD</td><td>0</td></tr></table> <p>0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	0	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	0						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements


H304 May be fatal if swallowed and enters airways.
H317 May cause an allergic skin reaction.

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

		Page: 14
SAFETY DATA SHEET		Revision Date: 02/01/2019
		Print Date: 9/22/2022
		SDS Number: 000000255327
Valvoline Professional Series VPS POWER STEERING FLUID Power Steering Fluid ™ Trademark, Valvoline or its subsidiaries, registered in various countries 860343		Version: 1.2

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association


NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System

		Page: 15
SAFETY DATA SHEET		Revision Date: 02/01/2019
		Print Date: 9/22/2022
		SDS Number: 000000255327
Valvoline Professional Series VPS POWER STEERING FLUID Power Steering Fluid ™ Trademark, Valvoline or its subsidiaries, registered in various countries 860343		Version: 1.2