



SAFETY DATA SHEET

ZEREX™ G40® Antifreeze Coolant

Version: 1.1

Revision Date: 10/27/2021

Print Date:
09/22/2022

GHS classification in accordance with the Hazardous Products Regulations

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : ZEREX™ G40®
Antifreeze Coolant

Product code : 875535

Details of the supplier of the safety data sheet

Valvoline Canada Corp
905 Winston Churchill Blvd
Mississauga ON L5J 4P2
Canada
1-800-TEAMVAL (1-800-832-6825)

SDS@valvoline.com

Emergency telephone number

1-800-VALVOLUME (1-800-825-8654)

Regulatory Information Number

1-800-TEAMVAL (1-800-832-6825)

Product Information

1-800-TEAMVAL (1-800-832-6825)

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Acute toxicity (Oral) : Category 4

Specific target organ toxicity
- repeated exposure (Oral) : Category 2 (Kidney, Liver)

GHS label elements

Hazard pictograms



Signal word : Warning

Hazard statements : H302 Harmful if swallowed.
H373 May cause damage to organs (Kidney, Liver) through prolonged or repeated exposure if swallowed.

Precautionary statements : **Prevention:**
P260 Do not breathe mist or vapours.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.



SAFETY DATA SHEET

ZEREX™ G40® Antifreeze Coolant

Version: 1.1

Revision Date: 10/27/2021

Print Date:
09/22/2022

Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.

P314 Get medical advice/ attention if you feel unwell.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
ETHYLENE GLYCOL	107-21-1	Acute Tox. 4; H302 STOT RE 2; H373	92.6533
2,2'-oxybis-Ethanol	111-46-6	Acute Tox. 4; H302 STOT RE 2; H373	4.6355
SEBACIC ACID	111-20-6	Not a hazardous substance or mixture.	2.6822
SODIUM HYDROXIDE	1310-73-2	Met. Corr. 1; H290 Skin Corr. 1A; H314 Eye Dam. 1; H318	1.3929
ETHYLENE GLYCOL	107-21-1	Acute Tox. 4; H302 STOT RE 2; H373	>=80.00 - <= 100.00

Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.



SAFETY DATA SHEET

ZEREX™ G40® Antifreeze Coolant

Version: 1.1

Revision Date: 10/27/2021

Print Date:
09/22/2022

	Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of eye contact	: Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Induce vomiting immediately and call a physician. Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.
Most important symptoms and effects, both acute and delayed	: No symptoms known or expected. Harmful if swallowed. May cause damage to organs through prolonged or repeated exposure if swallowed.
Notes to physician	: No hazards which require special first aid measures. Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Unsuitable extinguishing media	: High volume water jet
Hazardous combustion products	: No hazardous combustion products are known
Specific extinguishing methods	:
Further information	: Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.



SAFETY DATA SHEET

ZEREX™ G40® Antifreeze Coolant

Version: 1.1

Revision Date: 10/27/2021

Print Date:
09/22/2022

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Do not breathe vapours/dust.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ETHYLENE GLYCOL	107-21-1	(c)	100 mg/m ³	CA AB OEL
		TWA	10 mg/m ³ particulate	CA BC OEL
		STEL	20 mg/m ³ particulate	CA BC OEL
		C	100 mg/m ³ aerosol	CA BC OEL
		C	50 ppm Vapour	CA BC OEL
		C	50 ppm 127 mg/m ³ Vapour and mist	CA QC OEL

Personal protective equipment

- Respiratory protection : A NIOSH-approved air-purifying respirator with an appropriate



SAFETY DATA SHEET

ZEREX™ G40® Antifreeze Coolant

Version: 1.1

Revision Date: 10/27/2021

Print Date:
09/22/2022

cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

No personal respiratory protective equipment normally required.

Hand protection	
Remarks	: The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	: Eye wash bottle with pure water Tightly fitting safety goggles
Skin and body protection	: Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: violet
Odour	: No data available
Odour Threshold	: No data available
pH	: 8.4
Melting point/freezing point	: No data available
Boiling point/boiling range	: 145 °C (1,013.33 hPa) Calculated Phase Transition Liquid/Gas
Flash point	: > 121 °C



SAFETY DATA SHEET

ZEREX™ G40® Antifreeze Coolant

Version: 1.1

Revision Date: 10/27/2021

Print Date:
09/22/2022

Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Self-ignition	:	No data available
Upper explosion limit / Upper flammability limit	:	15.1 %(V) Method: DIN 51649
Lower explosion limit / Lower flammability limit	:	3.4 %(V) Method: DIN 51649
Vapour pressure	:	2 hPa (20 °C) Calculated Vapor Pressure
Relative vapour density	:	No data available
Relative density	:	1.1231 (15.6 °C)
Density	:	1.1231 g/cm3 (15.6 °C)
Solubility(ies)		
Water solubility	:	soluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Oxidizing properties	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed.
Conditions to avoid	:	excessive heat



SAFETY DATA SHEET

ZEREX™ G40® Antifreeze Coolant

Version: 1.1

Revision Date: 10/27/2021

Print Date:
09/22/2022

	No data available
Incompatible materials	: Aldehydes Alkali metals Alkaline earth metals Strong acids strong alkalis Strong bases Strong oxidizing agents Sulphur compounds
	Not applicable
Hazardous decomposition products	No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if swallowed.

Product:

Acute oral toxicity : Acute toxicity estimate: 538.15 mg/kg
Method: Calculation method

Components:

ETHYLENE GLYCOL:

Acute oral toxicity : LD0 (Human): estimated 1.56 g/kg

Assessment: The component/mixture is moderately toxic after single ingestion.

Acute inhalation toxicity : LC50 (Rat): 10.9 mg/l
Exposure time: 1 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): 9,530 mg/kg

Acute toxicity (other routes of administration) : LD50 (Rat): 5,010 mg/kg
Application Route: Intraperitoneal

LD50 (Rat): 3,260 mg/kg
Application Route: Intravenous

2,2'-oxybis-Ethanol:

Acute oral toxicity : LD50 (Human): Expected 1,120 mg/kg
Target Organs: Kidney



SAFETY DATA SHEET

ZEREX™ G40® Antifreeze Coolant

Version: 1.1

Revision Date: 10/27/2021

Print Date:
09/22/2022

- Acute inhalation toxicity : LC50 (Rat): > 4.6 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity
- Acute dermal toxicity : LD50 (Rabbit): 13,300 mg/kg
- SEBACIC ACID:**
- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: The toxicological data has been taken from products of similar composition.
- Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: No mortality observed at this dose.
- SODIUM HYDROXIDE:**
- Acute oral toxicity : LDLo (Rabbit): 500 mg/kg
- Acute inhalation toxicity : Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Moderate respiratory irritant
- Acute dermal toxicity : Symptoms: Corrosion
Assessment: The substance or mixture has no acute dermal toxicity
- ETHYLENE GLYCOL:**
- Acute oral toxicity : LD0 (Human): estimated 1.56 g/kg
Assessment: The component/mixture is moderately toxic after single ingestion.
- Acute inhalation toxicity : LC50 (Rat): 10.9 mg/l
Exposure time: 1 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity
- Acute dermal toxicity : LD50 (Rabbit): 9,530 mg/kg
- Acute toxicity (other routes of administration) : LD50 (Rat): 5,010 mg/kg
Application Route: Intraperitoneal
LD50 (Rat): 3,260 mg/kg
Application Route: Intravenous



SAFETY DATA SHEET

ZEREX™ G40® Antifreeze Coolant

Version: 1.1

Revision Date: 10/27/2021

Print Date:
09/22/2022

Skin corrosion/irritation

Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Species : Rabbit
Result : No skin irritation

2,2'-oxybis-Ethanol:

Species : Human
Result : Slight, transient irritation

SEBACIC ACID:

Species : Rabbit
Result : No skin irritation

SODIUM HYDROXIDE:

Result : Corrosive after 3 minutes or less of exposure

ETHYLENE GLYCOL:

Species : Rabbit
Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Result : Slight, transient irritation

2,2'-oxybis-Ethanol:

Species : Rabbit
Result : Slight, transient irritation

SEBACIC ACID:

Species : Rabbit
Remarks : Mild eye irritation

SODIUM HYDROXIDE:

Result : Corrosive
Assessment : Corrosive

ETHYLENE GLYCOL:

Result : Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Test Type : Maximisation Test



SAFETY DATA SHEET

ZEREX™ G40® Antifreeze Coolant

Version: 1.1

Revision Date: 10/27/2021

Print Date:
09/22/2022

Species : Guinea pig
Assessment : Does not cause skin sensitisation.

2,2'-oxybis-Ethanol:

Test Type : Maximisation Test
Species : Guinea pig
Method : Directive 67/548/EEC, Annex V, B.6.
Result : Did not cause sensitisation on laboratory animals.

SEBACIC ACID:

Assessment : Does not cause skin sensitisation.

SODIUM HYDROXIDE:

Exposure routes : Skin contact
Species : Humans
Result : negative

ETHYLENE GLYCOL:

Test Type : Maximisation Test
Species : Guinea pig
Assessment : Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

2,2'-oxybis-Ethanol:

Genotoxicity in vitro : Test Type: Ames test
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative
GLP: yes

Test system: Chinese hamster ovary cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 479
Result: negative
GLP: yes

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Mouse
Method: OECD Test Guideline 474
Result: negative
GLP: yes

SEBACIC ACID:



SAFETY DATA SHEET

ZEREX™ G40® Antifreeze Coolant

Version: 1.1

Revision Date: 10/27/2021

Print Date:
09/22/2022

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

ETHYLENE GLYCOL:

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

May cause damage to organs (Kidney, Liver) through prolonged or repeated exposure if swallowed.

Components:

ETHYLENE GLYCOL:

Exposure routes : Ingestion
Target Organs : Kidney, Liver
Assessment : May cause damage to organs through prolonged or repeated exposure.

2,2'-oxybis-Ethanol:

Exposure routes : Ingestion
Target Organs : Kidney
Assessment : May cause damage to organs through prolonged or repeated exposure.

ETHYLENE GLYCOL:

Exposure routes : Ingestion
Target Organs : Kidney, Liver
Assessment : May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Experience with human exposure

Components:

ETHYLENE GLYCOL:

Ingestion : Target Organs: Kidney

2,2'-oxybis-Ethanol:

General Information : Liver
Kidney



SAFETY DATA SHEET

ZEREX™ G40® Antifreeze Coolant

Version: 1.1

Revision Date: 10/27/2021

Print Date:
09/22/2022

ETHYLENE GLYCOL:

Ingestion : Target Organs: Kidney

Further information

Product:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Not classified based on available information.

Not classified based on available information.

Long-term (chronic) aquatic hazard : Not classified based on available information.

Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 27,540 mg/l
Exposure time: 96 h
Test Type: static test

LC50 (Pimephales promelas (fathead minnow)): 8,050 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test Type: static test

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 6,500 - 13,000 mg/l
End point: Growth inhibition
Exposure time: 7 Days

Toxicity to fish (Chronic toxicity) : NOEC (Pimephales promelas (fathead minnow)): 32,000 mg/l
Exposure time: 7 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 24,000 mg/l
Exposure time: 7 d

Ecotoxicology Assessment
Short-term (acute) aquatic hazard : Not classified based on available information.



SAFETY DATA SHEET

ZEREX™ G40® Antifreeze Coolant

Version: 1.1

Revision Date: 10/27/2021

Print Date:
09/22/2022

Long-term (chronic) aquatic hazard	: Not classified based on available information.
2,2'-oxybis-Ethanol: Toxicity to daphnia and other aquatic invertebrates	: LC50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 24 h Test Type: static test Method: DIN 38412
SEBACIC ACID: Toxicity to fish	: LC50 (Danio rerio (zebra fish)): > 100 mg/l Exposure time: 96 h Test Type: semi-static test
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test
Toxicity to algae	: NOEC (Skeletonema costatum (marine diatom)): > 3 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Remarks: No toxicity at the limit of solubility
SODIUM HYDROXIDE: Toxicity to fish	: LC50 (Gambusia affinis (Mosquito fish)): 125 mg/l Exposure time: 96 h Method: Static Remarks: Mortality
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 34.59 - 47.13 mg/l Exposure time: 48 h Remarks: Intoxication
Toxicity to bacteria	: Remarks: Not applicable
Ecotoxicology Assessment Short-term (acute) aquatic hazard	: Neutralisation will reduce ecotoxic effects.
Long-term (chronic) aquatic hazard	: This product has no known ecotoxicological effects.
ETHYLENE GLYCOL: Toxicity to fish	: LC50 (Lepomis macrochirus (Bluegill sunfish)): 27,540 mg/l Exposure time: 96 h Test Type: static test LC50 (Pimephales promelas (fathead minnow)): 8,050 mg/l



SAFETY DATA SHEET

ZEREX™ G40® Antifreeze Coolant

Version: 1.1

Revision Date: 10/27/2021

Print Date:
09/22/2022

Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test Type: static test

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 6,500 - 13,000 mg/l
End point: Growth inhibition
Exposure time: 7 Days

Toxicity to fish (Chronic toxicity) : NOEC (Pimephales promelas (fathead minnow)): 32,000 mg/l
Exposure time: 7 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 24,000 mg/l
Exposure time: 7 d

Ecotoxicology Assessment Short-term (acute) aquatic hazard : Not classified based on available information.

Long-term (chronic) aquatic hazard : Not classified based on available information.

Persistence and degradability

Components:

ETHYLENE GLYCOL:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 90 - 100 %
Exposure time: 10 d
Method: OECD Test Guideline 301

2,2'-oxybis-Ethanol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 70 - 80 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

SEBACIC ACID:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 98 %
Exposure time: 28 d

ETHYLENE GLYCOL:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 90 - 100 %
Exposure time: 10 d
Method: OECD Test Guideline 301

No data available



SAFETY DATA SHEET

ZEREX™ G40® Antifreeze Coolant

Version: 1.1

Revision Date: 10/27/2021

Print Date:
09/22/2022

Bioaccumulative potential

Components:

ETHYLENE GLYCOL:

Bioaccumulation

: Species: Crayfish (Procambarus)
Bioconcentration factor (BCF): 0.27
Exposure time: 61 d
Concentration: 1000 mg/l
Method: Flow through

Partition coefficient: n-octanol/water

: log Pow: -1.36

2,2'-oxybis-Ethanol:

Bioaccumulation

: Species: Leuciscus idus (Golden orfe)
Bioconcentration factor (BCF): 100

Partition coefficient: n-octanol/water

: log Pow: -1.47

SEBACIC ACID:

Partition coefficient: n-octanol/water

: log Pow: 1.5

ETHYLENE GLYCOL:

Bioaccumulation

: Species: Crayfish (Procambarus)
Bioconcentration factor (BCF): 0.27
Exposure time: 61 d
Concentration: 1000 mg/l
Method: Flow through

Partition coefficient: n-octanol/water

: log Pow: -1.36

No data available

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

Additional ecological information

: No data available

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice

: Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with



SAFETY DATA SHEET

ZEREX™ G40® Antifreeze Coolant

Version: 1.1

Revision Date: 10/27/2021

Print Date:
09/22/2022

chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

TDG

Not regulated as a dangerous good

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

Canadian PBT Chemicals : This product contains the following components on the DSL that are classified as Persistent, Bioaccumulative and/or Toxic (PBT) under CEPA:

NPRI Components : OCTAMETHYLCYCLOTETRASILOXANE
ETHYLENE GLYCOL
METHANOL
COPPER
TOLUENE
NICKEL
COBALT

The components of this product are reported in the following inventories:

TCSI : Not in compliance with the inventory

TSCA : All substances listed as active on the TSCA inventory



SAFETY DATA SHEET

ZEREX™ G40® Antifreeze Coolant

Version: 1.1

Revision Date: 10/27/2021

Print Date:
09/22/2022

AIIC	: Not in compliance with the inventory
DSL	: All components of this product are on the Canadian DSL
ENCS	: Not in compliance with the inventory
ISHL	: Not in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
NZIoC	: Not in compliance with the inventory
TECI	: Not in compliance with the inventory

Canadian lists

No substances are subject to a Significant New Activity Notification.

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Internal information : 000000098616

NFPA:	HMIS III:						
<p>Flammability</p> <p>Health</p> <p>Instability</p> <p>Special hazard</p>	<table> <tr> <td>HEALTH</td><td>2*</td></tr> <tr> <td>FLAMMABILITY</td><td>1</td></tr> <tr> <td>PHYSICAL HAZARD</td><td>0</td></tr> </table> <p>0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	2*	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	2*						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification



SAFETY DATA SHEET

ZEREX™ G40® Antifreeze Coolant

Version: 1.1

Revision Date: 10/27/2021

Print Date:
09/22/2022

Combustible Liquid Class IIIB

Full text of H-Statements

H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H373	May cause damage to organs through prolonged or repeated exposure if swallowed.

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit



SAFETY DATA SHEET

ZEREX™ G40® Antifreeze Coolant

Version: 1.1

Revision Date: 10/27/2021

Print Date:
09/22/2022

P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic
PPE : Personal Protective Equipment
STEL : Short-term exposure limit
STOT : Specific Target Organ Toxicity
TLV : Threshold Limit Value
TWA : Time-weighted average
vPvB : Very Persistent and Very Bioaccumulative
WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
DOT : Department of Transportation
FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
HMIRC : Hazardous Materials Information Review Commission
HMIS : Hazardous Materials Identification System
NFPA : National Fire Protection Association
NIOSH : National Institute for Occupational Safety and Health
OSHA : Occupational Safety and Health Administration
PMRA : Health Canada Pest Management Regulatory Agency
RTK : Right to Know
WHMIS : Workplace Hazardous Materials Information System