



# SAFETY DATA SHEET

Valvoline™ MULTI-VEHICLE TRANSFER CASE  
FLUID

Version: 1.17

Revision Date: 01/24/2022

Print Date:  
09/22/2022

GHS classification in accordance with the Hazardous Products Regulations

## SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

### Product identifier

Trade name : Valvoline™ MULTI-VEHICLE TRANSFER CASE FLUID

Product code : 880392

### Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Lubricant

#### Details of the supplier of the safety data sheet

Valvoline Canada Corp  
905 Winston Churchill Blvd  
Mississauga ON L5J 4P2  
Canada  
1-800-TEAMVAL (1-800-832-6825)

SDS@valvoline.com

#### Emergency telephone number

1-800-VALVOLINE (1-800-825-8654)

#### Regulatory Information Number

1-800-TEAMVAL (1-800-832-6825)

#### Product Information

1-800-TEAMVAL (1-800-832-6825)

## SECTION 2. HAZARDS IDENTIFICATION

### GHS Classification

Physical hazards not otherwise classified : Category 1

### GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : May become electrostatically charged. Sparks may ignite liquid and vapor.

Precautionary statements : P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P103 Read label before use.

### Prevention:



# SAFETY DATA SHEET

Valvoline™ MULTI-VEHICLE TRANSFER CASE  
FLUID

Version: 1.17

Revision Date: 01/24/2022

Print Date:  
09/22/2022

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

## Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	Asp. Tox. 1; H304	$\geq 80.00$ - $\leq 100.00$
Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based	72623-87-1	Asp. Tox. 1; H304	$\geq 5.00$ - $< 10.00$
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	Not a hazardous substance or mixture.	$\geq 1.00$ - $< 5.00$
LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED	72623-86-0	Asp. Tox. 1; H304	$\geq 1.00$ - $< 5.00$
Short-, medium- and long-chain alkyl methacrylates and short-chain alkyl methacrylamide copolymer		Eye Irrit. 2A; H319	$\geq 1.00$ - $< 5.00$
PETROLEUM DISTILLATES	64742-55-8	Asp. Tox. 1; H304 PHNOC 1;	$\geq 1.00$ - $< 5.00$
distillates (petroleum), hydrotreated light paraffinic	64742-55-8	PHNOC 1;	$\geq 1.00$ - $< 5.00$

Actual concentration or concentration range is withheld as a trade secret

## SECTION 4. FIRST AID MEASURES

- General advice : Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.  
Protect unharmed eye.  
If eye irritation persists, consult a specialist.



## SAFETY DATA SHEET

Valvoline™ MULTI-VEHICLE TRANSFER CASE  
FLUID

Version: 1.17

Revision Date: 01/24/2022

Print Date:  
09/22/2022

---

If swallowed	: Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	: No symptoms known or expected.
Notes to physician	: No hazards which require special first aid measures.  Treat symptomatically.

---

### SECTION 5. FIREFIGHTING MEASURES

Hazardous combustion products	: carbon dioxide and carbon monoxide
Specific extinguishing methods	:
Further information	: Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Environmental precautions	: If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	: Wipe up with absorbent material (e.g. cloth, fleece). Keep in suitable, closed containers for disposal.

---

### SECTION 7. HANDLING AND STORAGE

Advice on safe handling	: For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area.
Conditions for safe storage	: Electrical installations / working materials must comply with the technological safety standards.



# SAFETY DATA SHEET

Valvoline™ MULTI-VEHICLE TRANSFER CASE  
FLUID

Version: 1.17

Revision Date: 01/24/2022

Print Date:  
09/22/2022

Materials to avoid : No materials to be especially mentioned.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	TWA	1 mg/m3 Mist	CA BC OEL
Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based	72623-87-1	TWA	1 mg/m3 Mist	CA BC OEL
		TWA	5 mg/m3 Mist	CA AB OEL
		STEL	10 mg/m3 Mist	CA AB OEL
		TWAEV	5 mg/m3 Mist	CA QC OEL
		STEV	10 mg/m3 Mist	CA QC OEL
		TWA	1 mg/m3 Mist	CA BC OEL
		PEL	5 mg/m3 particulate	CAL PEL
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	TWA	1 mg/m3 Mist	CA BC OEL
PETROLEUM DISTILLATES	64742-55-8	TWA	1 mg/m3 Mist	CA BC OEL
distillates (petroleum), hydrotreated light paraffinic	64742-55-8	TWA	1 mg/m3 Mist	CA BC OEL

### Personal protective equipment

Respiratory protection : Respiratory protection is not required under normal conditions of use.

No personal respiratory protective equipment normally required.

Eye protection : Safety glasses

Skin and body protection : Protective suit

Hygiene measures : General industrial hygiene practice.



# SAFETY DATA SHEET

Valvoline™ MULTI-VEHICLE TRANSFER CASE  
FLUID

Version: 1.17

Revision Date: 01/24/2022

Print Date:  
09/22/2022

---

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: red
Odour	: mild
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Boiling point/boiling range	: > 218 °C (1013 hPa)
Flash point	: 201 - 249 °C  Method: Cleveland open cup
Evaporation rate	: < 1 Ethyl Ether
Flammability (solid, gas)	: No data available
Flammability (liquids)	: Static-accumulating flammable liquid.  Static-accumulating flammable liquid.
Self-ignition	: No data available
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapour pressure	: 1 hPa Calculated Vapor Pressure
Relative vapour density	: > 1 AIR=1
Relative density	: No data available
Density	: 0.844 g/cm <sup>3</sup> (15.56 °C)



## SAFETY DATA SHEET

Valvoline™ MULTI-VEHICLE TRANSFER CASE  
FLUID

Version: 1.17

Revision Date: 01/24/2022

Print Date:  
09/22/2022

Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: 28.8 mm <sup>2</sup> /s ( 40 °C)
Oxidizing properties	: No data available

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: Stable under recommended storage conditions. No hazards to be specially mentioned.
Conditions to avoid	: None known.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	No hazardous decomposition products are known.

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified based on available information.

#### Components:

##### **Distillates (Petroleum), Hydrotreated Heavy Paraffinic:**

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

##### **Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg



**SAFETY DATA SHEET**  
Valvoline™ MULTI-VEHICLE TRANSFER CASE  
FLUID

Version: 1.17

Revision Date: 01/24/2022

Print Date:  
09/22/2022

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Remarks: No mortality observed at this dose.

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

**LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Remarks: No mortality observed at this dose.

**HYDROTREATED LIGHT PARAFFINIC DISTILLATE:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Remarks: No mortality observed at this dose.

**distillates (petroleum), hydrotreated light paraffinic:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: No mortality observed at this dose.



# SAFETY DATA SHEET

Valvoline™ MULTI-VEHICLE TRANSFER CASE  
FLUID

Version: 1.17

Revision Date: 01/24/2022

Print Date:  
09/22/2022

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Remarks: No mortality observed at this dose.

## Skin corrosion/irritation

Not classified based on available information.

### Components:

#### **Distillates (Petroleum), Hydrotreated Heavy Paraffinic:**

Assessment : Slight, transient irritation  
Result : Slight, transient irritation

#### **Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:**

Species : Rabbit  
Result : No skin irritation

#### **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Assessment : Slight, transient irritation  
Result : Slight, transient irritation

#### **LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED:**

Species : Rabbit  
Result : No skin irritation

#### **HYDROTREATED LIGHT PARAFFINIC DISTILLATE:**

Species : Rabbit  
Result : No skin irritation

#### **distillates (petroleum), hydrotreated light paraffinic:**

Species : Rabbit  
Result : No skin irritation

## Serious eye damage/eye irritation

Not classified based on available information.

### Product:

Result : Slight, transient irritation  
Remarks : Expected based on components.

### Components:

#### **Distillates (Petroleum), Hydrotreated Heavy Paraffinic:**

Result : No eye irritation  
Assessment : No eye irritation

#### **Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:**

Species : Rabbit  
Result : No eye irritation

#### **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Result : No eye irritation  
Assessment : No eye irritation

#### **LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED:**

Species : Rabbit





# SAFETY DATA SHEET

Valvoline™ MULTI-VEHICLE TRANSFER CASE  
FLUID

Version: 1.17

Revision Date: 01/24/2022

Print Date:  
09/22/2022

Result : No eye irritation

**Short-, medium- and long-chain alkyl methacrylates and short-chain alkyl methacrylamide copolymer:**

Result : Eye irritation

**HYDROTREATED LIGHT PARAFFINIC DISTILLATE:**

Species : Rabbit

Result : No eye irritation

**distillates (petroleum), hydrotreated light paraffinic:**

Species : Rabbit

Result : No eye irritation

**Respiratory or skin sensitisation**

**Skin sensitisation**

Not classified based on available information.

**Respiratory sensitisation**

Not classified based on available information.

**Components:**

**Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:**

Test Type : Buehler Test

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

**LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED:**

Test Type : Buehler Test

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

**HYDROTREATED LIGHT PARAFFINIC DISTILLATE:**

Test Type : Buehler Test

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

**distillates (petroleum), hydrotreated light paraffinic:**

Test Type : Buehler Test

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**Components:**

**Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:**

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation  
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation



**SAFETY DATA SHEET**  
Valvoline™ MULTI-VEHICLE TRANSFER CASE  
FLUID

Version: 1.17

Revision Date: 01/24/2022

Print Date:  
09/22/2022

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

**HYDROTREATED LIGHT PARAFFINIC DISTILLATE:**

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation  
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

**distillates (petroleum), hydrotreated light paraffinic:**

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation  
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

Not classified based on available information.

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**Product:**

No aspiration toxicity classification

**Components:**

**Distillates (Petroleum), Hydrotreated Heavy Paraffinic:**

May be fatal if swallowed and enters airways.

**Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:**

May be fatal if swallowed and enters airways.

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

No aspiration toxicity classification

**LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

May be fatal if swallowed and enters airways.

**HYDROTREATED LIGHT PARAFFINIC DISTILLATE:**

May be fatal if swallowed and enters airways.

**distillates (petroleum), hydrotreated light paraffinic:**

No aspiration toxicity classification

**Further information**

**Product:**

Remarks : No data available

---

**SECTION 12. ECOLOGICAL INFORMATION**



# SAFETY DATA SHEET

Valvoline™ MULTI-VEHICLE TRANSFER CASE  
FLUID

Version: 1.17

Revision Date: 01/24/2022

Print Date:  
09/22/2022

## Ecotoxicity

### Product:

#### Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Not classified based on available information.

Long-term (chronic) aquatic hazard : Not classified based on available information.

### Components:

#### Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Toxicity to fish : LL50 (Fish): > 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10,000 mg/l  
Exposure time: 48 h

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l  
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Fish): 10 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 10 mg/l

#### Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Not classified based on available information.

Long-term (chronic) aquatic hazard : Not classified based on available information.

#### Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
Exposure time: 96 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 203  
Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 48 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 202

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l  
End point: Growth inhibition



# SAFETY DATA SHEET

Valvoline™ MULTI-VEHICLE TRANSFER CASE  
FLUID

Version: 1.17

Revision Date: 01/24/2022

Print Date:  
09/22/2022

	Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201
Toxicity to fish (Chronic toxicity)	: NOELR (Oncorhynchus mykiss (rainbow trout)): >= 1,000 mg/l Exposure time: 14 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEL (Daphnia (water flea)): 10 mg/l Exposure time: 21 d Test substance: WAF Method: OECD Test Guideline 211
Ecotoxicology Assessment Short-term (acute) aquatic hazard	: Not classified based on available information.
Long-term (chronic) aquatic hazard	: Not classified based on available information.
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:	
Toxicity to fish	: LL50 (Fish): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Aquatic invertebrates): > 10,000 mg/l Exposure time: 48 h
Toxicity to algae	: EL50 (Algae, algal mat (Algae)): > 100 mg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	: NOEC (Fish): 10 mg/l
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Aquatic invertebrates): 10 mg/l
Ecotoxicology Assessment Short-term (acute) aquatic hazard	: Not classified based on available information.
Long-term (chronic) aquatic hazard	: Not classified based on available information.
LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED:	
Toxicity to fish	: LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 203 Remarks: No toxicity at the limit of solubility



**SAFETY DATA SHEET**  
Valvoline™ MULTI-VEHICLE TRANSFER CASE  
FLUID

Version: 1.17

Revision Date: 01/24/2022

Print Date:  
09/22/2022

- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 48 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 202
- Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l  
End point: Growth inhibition  
Exposure time: 72 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 201
- Toxicity to fish (Chronic toxicity) : NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated >= 1,000 mg/l  
Exposure time: 14 d
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Daphnia (water flea)): 10 mg/l  
Exposure time: 21 d  
Test substance: WAF  
Method: OECD Test Guideline 211
- Short-, medium- and long-chain alkyl methacrylates and short-chain alkyl methacrylamide copolymer:  
Ecotoxicology Assessment  
Short-term (acute) aquatic hazard : Not classified based on available information.
- Long-term (chronic) aquatic hazard : Not classified based on available information.
- PETROLEUM DISTILLATES:**  
Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
Exposure time: 96 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 203  
Remarks: No toxicity at the limit of solubility
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 48 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 202
- Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l  
End point: Growth inhibition  
Exposure time: 72 h



**SAFETY DATA SHEET**  
Valvoline™ MULTI-VEHICLE TRANSFER CASE  
FLUID

Version: 1.17

Revision Date: 01/24/2022

Print Date:  
09/22/2022

	Test Type: static test Test substance: WAF Method: OECD Test Guideline 201
Toxicity to fish (Chronic toxicity)	: NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated $\geq$ 1,000 mg/l Exposure time: 14 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEL (Daphnia (water flea)): 10 mg/l Exposure time: 21 d Test substance: WAF Method: OECD Test Guideline 211
distillates (petroleum), hydrotreated light paraffinic:	
Toxicity to fish	: LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 203 Remarks: No toxicity at the limit of solubility
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202
Toxicity to algae	: NOEL (Pseudokirchneriella subcapitata (green algae)): $\geq$ 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201
Toxicity to fish (Chronic toxicity)	: NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated $\geq$ 1,000 mg/l Exposure time: 14 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEL (Daphnia (water flea)): 10 mg/l Exposure time: 21 d Test substance: WAF Method: OECD Test Guideline 211
Ecotoxicology Assessment Short-term (acute) aquatic hazard	: Not classified based on available information.
Long-term (chronic) aquatic hazard	: Not classified based on available information.



# SAFETY DATA SHEET

Valvoline™ MULTI-VEHICLE TRANSFER CASE  
FLUID

Version: 1.17

Revision Date: 01/24/2022

Print Date:  
09/22/2022

## Persistence and degradability

### Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 2 - 4 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED:

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 2 - 4 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

PETROLEUM DISTILLATES:

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 2 - 4 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

distillates (petroleum), hydrotreated light paraffinic:

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 2 - 4 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

No data available

### **Bioaccumulative potential**

#### Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Partition coefficient: n- : log Pow: Expected > 7  
octanol/water

No data available

### **Mobility in soil**

#### Components:

No data available

### **Other adverse effects**

No data available

#### Product:

Additional ecological : No data available  
information

#### Components:

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### **Disposal methods**

Contaminated packaging : Empty containers should be taken to an approved waste  
handling site for recycling or disposal.



# SAFETY DATA SHEET

Valvoline™ MULTI-VEHICLE TRANSFER CASE  
FLUID

Version: 1.17

Revision Date: 01/24/2022

Print Date:  
09/22/2022

---

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### UNRTDG

Not regulated as a dangerous good

#### IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### National Regulations

#### TDG

Not regulated as a dangerous good

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

---

## SECTION 15. REGULATORY INFORMATION

### The components of this product are reported in the following inventories:

TCSI	: Not in compliance with the inventory
TSCA	: All substances listed as active on the TSCA inventory
AIIC	: Not in compliance with the inventory
DSL	: All components of this product are on the Canadian DSL
ENCS	: Not in compliance with the inventory
ISHL	: Not in compliance with the inventory
KECI	: Not in compliance with the inventory
PICCS	: Not in compliance with the inventory
IECSC	: Not in compliance with the inventory
NZIoC	: On the inventory, or in compliance with the inventory





# SAFETY DATA SHEET

Valvoline™ MULTI-VEHICLE TRANSFER CASE  
FLUID

Version: 1.17

Revision Date: 01/24/2022

Print Date:  
09/22/2022

TECI : Not in compliance with the inventory

## Canadian lists

No substances are subject to a Significant New Activity Notification.

## Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

## SECTION 16. OTHER INFORMATION

### Further information

Internal information : R0367943

NFPA:	HMIS III:						
<p>Flammability</p> <p>Health</p> <p>Instability</p> <p>Special hazard</p>	<table><tr><td>HEALTH</td><td>1/</td></tr><tr><td>FLAMMABILITY</td><td>1</td></tr><tr><td>PHYSICAL HAZARD</td><td>0</td></tr></table> <p>0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	1/	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	1/						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

### NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

### Full text of H-Statements

H304 May be fatal if swallowed and enters airways.  
H319 Causes serious eye irritation.

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.



## SAFETY DATA SHEET

Valvoline™ MULTI-VEHICLE TRANSFER CASE  
FLUID

Version: 1.17

Revision Date: 01/24/2022

Print Date:  
09/22/2022

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

RTK : Right to Know



**SAFETY DATA SHEET**  
Valvoline™ MULTI-VEHICLE TRANSFER CASE  
FLUID

Version: 1.17

Revision Date: 01/24/2022

Print Date:  
09/22/2022

---

WHMIS : Workplace Hazardous Materials Information System