

## SAFETY DATA SHEET

Issuing Date 27-Oct-2014 Revision Date 15-Oct-2014 Revision Number 2

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

**Product identifier** 

Product SDS Name Epoxy Putty Stick – High Heat

J-B Weld FG SKU Part Numbers Covered

8297, 8297F

J-B Weld Product Names Covered

HighHeat™ (all sizes)

**J-B Weld Product Type** 

**Epoxy Putty Stick** 

Recommended use of the chemical and restrictions on use

Recommended Use Adhesive & Repair

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name J-B WELD COMPANY, LLC

Supplier Address 1130 COMO ST

SULPHUR SPRINGS, TX 75482

USA

**Emergency Telephone Numbers** Transportation Emergencies: Chemtrec (24 hour transportation emergency response info):

800-424-9300 or 703-527-3887

Poison/Medical Emergencies: Poison Control Centers (24 hour emergency poison / medical

response info): 800-222-1222

Supplier Email <a href="mailto:info@jbweld.com">info@jbweld.com</a>

Supplier Phone Number 903-885-7696

## 2. HAZARDS IDENTIFICATION

OSHA/HCS status This material is considered hazardous by the OSHA Hazard Communication

Standard (29-CFR 1910.1200).



Classification of the substance or mixture

SKIN SENSITIZATION - Category 1

## **GHS label elements**

Hazard pictograms



Signal word Warning!

Hazard statements

Causes skin and eye irritation.

May cause an allergic skin reaction.

**Precautionary statements** 

General Read label before use. Keep out of reach of children. If medical advice is needed,

have product container or label at hand.

Prevention Wear protective gloves. Wear eye or face protection. Avoid breathing dust. Wash

hands thoroughly after handling. Contaminated work clothing should not be allowed

out of the workplace.

Response IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing.

Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation

persists: Get medical attention.

Storage Not applicable.

Disposal Dispose of contents and container in accordance with all local, regional, national and

international regulations.

Hazards not otherwise classified None known.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance/mixture Mixture

Ingredient name	% by weight	CAS number
Cristobalite	10-30	14464-46-1
crystalline silica non-respirable	10-30	14808-60-7

#### Canada

Name	CAS number	%
Talc, not containing asbestiform fibres	14807-96-6	10-30
Cristobalite	14464-46-1	10-30
glass, oxide, chemicals	65997-17-3	10-30
crystalline silica non-respirable	14808-60-7	10-30
3,6-diazaoctanethylenediamin	112-24-3	0.1-1

Occupational exposure limits, if available, are listed in Section 8.



Epoxy Putty Stick – High Heat Revision Date 15-Oct-2014

## 4. FIRST AID MEASURES

## **Description of necessary first aid measure**

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing,

if breathing is regular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under

medical surveillance for 48 hours.

Skin contact Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash

contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid

further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Eye contact Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check

for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention

if irritation occurs.

Ingestion Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest

in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or

waistband.

## Most important symptoms/effects, acute and delayed Potential acute health effects

Inhalation Exposure to decomposition products may cause a health hazard. Serious effects may be delayed

following exposure.

Skin contact May cause an allergic skin reaction.

Eye contact No known significant effects or critical hazards.

Ingestion No known significant effects or critical hazards.

### Over-exposure signs/symptoms

Inhalation No specific data.

Skin contact Adverse symptoms may include the following:

irritation redness

Eye contact No specific data



Ingestion No specific data

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed

person may need to be kept under medical surveillance for 48 hours.

Specific treatments No specific treatment.

See toxicological information (Section 11)

## 5. FIRE-FIGHTING MEASURES

#### Extinguishing media

Suitable extinguishing media Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media None known.

Specific hazards arising from the

chemical

No specific fire or explosion hazard.

## National Fire Protection Associationg (U.S.A.)

**Flammability** 

Health



## **Special**

Hazardous thermal decomposition products Decomposition products may include the following materials:

Carbon dioxide Carbon monoxide Nitrogen oxides

Halogenated compounds Metal oxide/oxides

Special protective actions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in a positive pressure mode.

## 6. ACCIDENTAL RELEASE MEASURES

## Personal precautions, protective equipment and emergency procedures

**Personal Precautions** Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal

protective equipment as required. Avoid generation of dust. Do not breathe dust. Evacuate

personnel to safe areas.

Other Information Refer to protective measures listed in Sections 7 and 8.



**Environmental Precautions** 

Environmental Precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage

if safe to do so.

Methods and material for containment and cleaning up

**Methods for Containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Pick up and transfer to properly labeled containers.

## 7. HANDLING AND STORAGE

Conditions for safe storage, including any incompatibilities

Do not store above the following temperature: 35°C (95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Precautions for safe handling

Protective measure

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measure.



## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Control parameters

## Occupational exposure limits

Ingredient name	CAS#	Exposure limits
cristobalite	14464-46-1	OSHA PEL Z3 (United States, 9/2005). Notes: 1/2[250/(%SiO2+5)]  TWA: 250 MPPCF / 2 x (%SiO2+5) 8 hours. Form: Respirable OSHA PEL Z3 (United States, 9/2005). Notes: 1/2[10/(%SiO2+2)]  TWA: 10 MG/M3 / 2 x (%SiO2+2) 8 hours. Form: Respirable OSHA PEL 1989 (United States, 3/1989).  TWA: 0.05 mg/m³, (as quartz) 8 hours. Form: Respirable dust ACGIH TLV (United States, 3/2012).  TWA: 0.025 mg/m³ 8 hours. Form: Respirable fraction NIOSH REL (United States, 1/2013).  TWA: 0.05 mg/m³ 10 hours. Form: respirable dust OSHA PEL Z3 (United States, 9/2005). Notes: 1/2[30/(%SiO2+2)]  TWA: 30 MG/M3 / 2 x (%SiO2+2) 8 hours. Form: Total dust.
crystalline silica non-respirable	14808-60-7	OSHA PEL Z3 (United States, 9/2005). Notes: 250/(%SiO2+5) TWA: 250 MPPCF / (%SiO2+5) 8 hours. Form: Respirable OSHA PEL Z3 (United States, 9/2005). Notes: 10/(SiO2+2) TWA: 10 MG/M3 / (%SiO2+2) 8 hours. Form: Respirable ACGIH TLV (United States, 3/2012). TWA: 0.025 mg/m³ 8 hours. Form: Respirable fraction NIOSH REL (United States, 1/2013). TWA: 0.05 mg/m³ 10 hours. Form: respirable dust OSHA PEL Z3 (United States, 9/2005). Notes: 30/(%SiO2+2) TWA: 30 MG/M3 / (%SiO2+2) 8 hours. Form: Total dust.

## **Canada**

Occupational exposure limits TWA (8 hours) STEL (15 mins) Ceiling
---



Ingredient	List name	ppm	mg/ m³	Other	ppm	mg/ m³	Other	ppm	mg/ m³	Other	Notations
crystalline silica non-respirable	US ACGIH 3/2012	-	0.025	-	-	-	-	-	-	_	[a]
'	BC 4/2012	_	0.025	-	-	-	-	-	-	-	[b]
	ON 1/2013	-	0.1	-	-	-	-	-	-	-	[c]
	QC 12/2012	-	0.1	-	-	-	-	-	-	-	[d]
cristobalite	US ACGIH 3/2012	-	0.025	-	-	-	-	-	-	-	[a]
	AB 4/2009	-	0.025	-	-	-	-	-	-	-	[e]
	BC 4/2012	-	0.025	-	-	-	-	-	-	-	[b]
	ON 1/2013	-	0.05	-	-	-	-	-	-	-	[c]
	QC 12/2012	-	0.05	-	-	-	-	-	-	-	[d]
glass, oxide, chemicals	US ACGIH 3/2012	-	5	-	-	-	-	-	-	-	[f]
	US ACGIH 3/2012	-	-	1 f/cc	-	-	-	-	-	-	[g]
	AB 4/2009	-	5	1 f/cc	-	-	-	-	-	-	[h]
		-	5	-	-	-	-	-	-	-	[i]
	BC 4/2012	-	5	-	-	-	-	-	-	-	ÜĴ
		-	-	1 f/cc	-	-	-	-	-	-	
	ON 1/2013	-	10	-	-	-	-	-	-	-	[k]
		-	5	-	-	-	-	-	-	-	[1]
		-	-	1 f/cc	-	-	-	-	-	-	[m]
	QC 12/2012	-	-	1 f/cc	-	-	-	-	-	-	[n]
		-	10	-	-	-	-	-	-	-	[o]
Talc , not containing asbestiform fibres	AB 4/2009	-	2	-	-	-	-	-	-	-	[e]
	BC 4/2012	_	2	-	-	-	-	-	-	-	[b]
		_	-	0.1 f/cc	-	-	-	-	-	-	
	ON 1/2013	_	2	-	-	-	-	-	-	-	[c]
		-	2	-	-	-	-	-	-	_	[p]
		-	-	2 f/cc	-	-	-	-	-	_	
	QC 12/2012	-	3	-	-	-	-	-	-	-	[d]
3,6-diazaoctanethylenediamin	ON 1/2013	0.5	3	-	-	-	-	-	-	-	[1]
	US AIHA 10/2011	1	-	_	-	-	-	-	-	-	[1]

Form: [a]Respirable particulate [b]Respirable [c]Respirable fraction: means that size fraction of the airborne particulate deposited in the gas-exchange region of the respiratory tract and collected during air sampling with a particle size-selective device that, (a) meets the ACGIH particle size–selective sampling criteria for airborne particulate matter; and (b) has the cut point of 4 μm at 50 per cent collection efficiency. [d]The value is for particulate matter containing no asbestos and < 1 per cent crystalline silica. [e]Respirable dust. [f]Inhalable fraction [g]Respirable fibers: length greater than 5 uM; aspect ratio equal to or greater than 3:1 as determined by the membrane filter method at 400-450X magnification (4-mm objective) phase contrast illumination. [h]Fibres [i]Fibres, total particulate [j]Inhalable [k]Fiber [l]Inhalable fraction: means that size fraction of the airborne particulate deposited anywhere in the respiratory tract and collected during air sampling with a particle size-selective device that, (a) meets the ACGIH particle size-selective sampling criteria for airborne particulate matter; and (b) has the cut point of 100 μm at 50 per cent collection efficiency. [m]Respirable fibres: length > 5μm; aspect ratio ≥3:1, as determined by the membrane filter method at 400-450 times magnification (4-mm objective), using phase-contrast illumination. [n]RESPIRABLE FIBRES (other than respirable asbestos fibres): Objects, other than respirable asbestos fibres, longer than 5 μm, having a diameter of less than 3 μm and a ratio of length to diameter of more than 3:1. [o]Total dust. [p]Respirable fraction [g]Total dust

## Appropriate engineering controls

No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

## **Environmental exposure controls**

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.



**Epoxy Putty Stick – High Heat**Revision Date 15-Oct-2014

Individual protection measures

Hygiene measures Wash hands, forearms and face thoroughly after handling chemical products, before

eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety

showers are close to the workstation location.

**Respiratory protection**Use a properly fitted, particulate filter respirator complying with an approved standard if

a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working

limits of the selected respirator.

Skin Protection

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is

necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the

protection time of the gloves cannot be accurately estimated.

**Body protection** Personal protective equipment for the body should be selected based on the task being

performed and the risks involved and should be approved by a specialist before

handling this product.

Other skin protection Appropriate footwear and any additional skin protection measures should be selected

based on the task being performed and the risks involved and should be approved by a

specialist before handling this product.

**Eye/face protection** Safety eyewear complying with an approved standard should be used when a risk

assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless

the assessment indicates a higher degree of protection: safety glasses with

sideshields.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical and Chemical Properties** 

Physical State Solid

AppearanceMetallic. Gray-BeigeOdorEthereal

ColorMetallic. Gray-BeigeOdor ThresholdNo information available

<u>Property</u> <u>Values</u> <u>Remarks/ Method</u>

No data available pН None known Melting / freezing point No data available None known Boiling point / boiling range No data available None known **Flash Point** Closed cup: >93° C None known **Evaporation Rate** No data available None known Flammability (solid, gas) Flammable in the presence of the None known

Flammability (solid, gas)

Flammable in the presence of the None k
following materials or conditions: open

flames, sparks and static discharge.

Upper flammability limit No data available

Lower flammability limit No data available

Vapor pressureNo data availableNone knownVapor densityNo data availableNone known



Revision Date 15-Oct-2014

**Specific Gravity** 1.741 None known **Water Solubility** Insoluble in water None known Solubility in other solvents No data available None known Partition coefficient: n-octanol/waterNo data available None known None known **Autoignition temperature** No data available **Decomposition temperature** >200° C None known Kinematic viscosity No data available None known **Dynamic viscosity** No data available None known

Explosive properties

Oxidizing Properties

No data available
No data available
No data available

**Other Information** 

Softening Point No data available

VOC Content (%)

Particle Size No data available

**Particle Size Distribution** 

## 10. STABILITY AND REACTIVITY

#### Reactivity

No data available.

## **Chemical stability**

Stable under recommended storage conditions.

#### Possibility of Hazardous Reactions

None under normal processing.

#### **Hazardous Polymerization**

Hazardous polymerization does not occur.

#### **Conditions to avoid**

Excessive heat.

#### Incompatible materials

Strong acids. Strong oxidizing agents. Strong bases.

#### **Hazardous Decomposition Products**

Carbon oxides.

## 11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Acute toxicity No specific data.

<u>Irritation/Corrosion</u> No specific data

SensitizationNo specific data.MutagenicityNo specific data.CarcinogenicityNo specific data.

-



Classification

<u>Oldooniloatioii</u>			
Product/ingredient name	OSHA	IARC	NTP
cristobalite	-	1	Known to be a human carcinogen.
Crystalline silica non-respirable	-	1	Known to be a human carcinogen.

Reproductive toxicityNo specific dataTeratogenicityNo specific data.Specific target organ toxicity (single exposure)No specific data.Specific target organ toxicity (repeated exposure)No specific data.Aspiration hazardNo specific data.Information on the likely routes of exposureNot available

Potential acute health effects

**Eye contact** No known significant effects or critical hazards.

**Inhalation** Exposure to decomposition products may cause a health hazard. Serious effects may be

delayed following exposure.

**Skin contact** May cause an allergic skin reaction.

**Ingestion** No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact No specific data

Inhalation No specific data.

**Skin contact** Adverse symptoms may include the following:

irritation redness

**Ingestion** No specific data

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects

Not available
Potential delayed effects

Not available

Long term exposure

Potential immediate effects

Not available
Potential delayed effects

Not available

Potential chronic health

<u>effects</u>

No specific data.

General Once sensitized, a severe allergic reaction may occur when subsequently exposed to very

low levels.

CarcinogenicityNo known significant effects or critical hazards.MutagenicityNo known significant effects or critical hazards.TeratogenicityNo known significant effects or critical hazards.Developmental effectsNo known significant effects or critical hazards.Fertility effectsNo known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates No specific data.



12. ECOLOGICAL INFORMATION

Toxicity No specific data.

Persistence and degradability No specific data.

Bioaccumulative potential No specific data.

**Mobility in soil** 

Soil/water partition coefficient (Koc) Not available

Other adverse effects No known significant effects or critical hazards.

## 13. DISPOSAL CONSIDERATIONS

Waste treatment methods

**Disposal methods** 

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional,

or local regulations for additional requirements.

**Contaminated Packaging** 

Dispose of contents/containers in accordance with local regulations.

## 14. TRANSPORT INFORMATION

 DOT
 NOT REGULATED

 Proper Shipping Name
 NON REGULATED

Hazard Class N/A

Marine Pollutant This product contains a chemical which is listed as a marine pollutant according to DOT

TDG Not regulated

MEX Not regulated

ICAO Not regulated

Not regulated

Not regulated

Proper Shipping Name NON REGULATED

Hazard Class N/A

IMDG/IMO Not regulated

Hazard Class N/A

Marine Pollutant Product is a marine pollutant according to the criteria set by IMDG/IMO

ADR Not regulated
ADN Not regulated
Not regulated



15. REGULATORY INFORMATION

**United States** 

U.S. Federal regulations TSCA 8(a) PAIR: Siloxanes and Silicones, di-Me, reaction products with silica

TSCA 8(a) CDR Exempt/Partial exemption: Not determined

United States inventory (TSCA 8b): All components are listed or exempted.

Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs) Not listed

Clean Air Act Section 602 Class I

**Substances** 

Not listed

Clean Air Act Section 602 Class II

**Substances** 

Not listed

SARA 302/304

Composition/information on ingredients No products were found

SARA 304 RQ Not applicable

**SARA 311/312** 

Classification Immediate (acute) health hazard

Composition/information on ingredients

Name	%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
Cristobalite	10-30	No.	No.	No.	No.	Yes
crystalline silica non-respirable	10-30	No.	No.	No.	No.	Yes

State regulations

Massachusetts The following components are listed: SOAPSTONE; MINERAL WOOL FIBER

**New York** None of the components are listed.

New Jersey The following components are listed: SOAPSTONE, SILICA, QUARTZ; QUARTZ (SiO2);

FERROSILICON; FERROCERIUM

Pennsylvania The following components are listed: SOAPSTONE DUST, QUARTZ (SiO2)

Minnesota Hazardous

**Substances** 

None of the components are listed.

<u>California Prop. 65</u> WARNING: This product contains a chemical known to the State of California to cause

cancer

Ingredient Name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
Talc, not containing asbestiform fibres	Yes.	No.	No.	No.
cristobalite	Yes.	No.	No.	No.
Crystalline silica non-respirable	Yes.	No.	No	No



Epoxy Putty Stick – High Heat Revision Date 15-Oct-2014

\_\_\_\_\_

Canada

WHMIS (Canada) Class D-2A: Material causing other toxic effects (Very toxic).

Canadian lists

Canadian NPRI None of the components are listed.

**CEPA Toxic substances**None of the components are listed.

Canada inventory All components are listed or exempted.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

International regulations

International lists Australia inventory (AICS): All components are listed or exempted.

China inventory (IECSC): Not determined.

Japan inventory: Not determined.

Korea inventory: All components are listed or exempted.

Malaysia Inventory (EHS Register): Not determined.

New Zealand Inventory of Chemicals (NZIoC): All components are listed or exempted.

Philippines inventory (PICCS): All components are listed or exempted.

Taiwan inventory (CSNN): Not determined.

**Substances of very high concern** None of the components are listed.

## **16. OTHER INFORMATION**

Key to abbreviations ATE = Acute Toxicity Estimate

**BCF** = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

**UN = United Nations** 

## Notice to reader

NON-WARRANTY: The information presented in this publication is based upon the research and experience of J-B Weld Company. No representation or warranty is made, however, concerning the accuracy or completeness of the information presented in this publication. J-B Weld Company makes no warranty or representation of any kind, express or implied, including without limitation any warranty of merchantability or fitness for any particular purpose, and no warranty or representation shall be implied by law or otherwise. Any products sold by J-B Weld Company are not warranted as suitable for any particular purpose to the buyer. The suitability of any products for any purpose particular to the buyers is for the buyer to determine. J-B Weld Company assumed no responsibility for the selection of products suitable to the particular purposes of any particular buyer. J-B Weld Company shall in no event be liable for any special, incidental, or consequential damages.

**End of Safety Data Sheet** 

