



Comet Chemical Company Ltd.
3463 Thomas Street
Innisfill, ON, Canada, L9S 3W4
Telephone: (705) 436 5580

Comsol 140 (High Flash Mineral Spirits)

SDS Preparation Date (mm/dd/yyyy): 10/24/2016

Page 1 of 10

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

Product identifier used on the label

: **Comsol 140 (High Flash Mineral Spirits)**

Product Code(s) : None reported.

Recommended use of the chemical and restrictions on use

: Industrial solvent.
Use pattern: Professional Use Only
Restriction on use: None known

Chemical family : Petroleum distillates

Name, address, and telephone number
of the supplier:

Comet Chemical Company Ltd.

3463 Thomas Street
Innisfill, ON, Canada L9S 3W4

Supplier's Telephone # : 705-436-5580

24 Hr. Emergency Tel # : TERRRAPURE ENVIRONMENTAL : 800-567-7455

Name, address, and telephone number of
the manufacturer:

Refer to supplier

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical

Clear blue liquid. Petroleum hydrocarbon odour.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Hazard classification:

Flammable Liquid - Category 4

Aspiration toxicity: Category 1

Label elements

Hazard pictogram(s)



Signal Word

DANGER!

Hazard statement(s)

Combustible liquid.

May be fatal if swallowed and enters airways.



Comsol 140 (High Flash Mineral Spirits)

SDS Preparation Date (mm/dd/yyyy): 10/24/2016

Page 2 of 10

SAFETY DATA SHEET

Precautionary statement(s)

Keep away from flames and hot surfaces. - No smoking.
Wear protective gloves and eye/face protection.

If swallowed: Immediately call a poison center/doctor.
Do NOT induce vomiting.
In case of fire: Use water fog, dry chemical, CO₂ or 'alcohol' foam to extinguish.

Store locked up.
Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

Other hazards which do not result in classification:

Ingestion may cause irritation of the mouth, throat and stomach. May cause respiratory irritation. Contact with eyes may cause irritation.

Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

Environmental precautions :
Avoid release to the environment. See ECOLOGICAL INFORMATION, Section 12.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Pure substance

<u>Chemical name</u>	<u>Common name and synonyms</u>	<u>CAS #</u>	<u>Concentration (% by weight)</u>
Hydrotreated light distillate	Distillates (petroleum), hydrotreated light	64742-47-8	100.00

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

- Ingestion* : If swallowed: Immediately call a poison center/doctor. Do not induce vomiting. Rinse mouth thoroughly. Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.
- Inhalation* : Immediately remove person to fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only. Call a POISON CENTER or doctor/physician if you feel unwell.
- Skin contact* : Wash affected areas with soap and water. Take off contaminated clothing and wash before re-use. Get medical attention if irritation develops and persists.
- Eye contact* : Flush with large amounts of water for 15 minutes. Remove contact lenses, if present and easy to do. If irritation or symptoms develop, seek medical attention.

Most important symptoms and effects, both acute and delayed

- : Aspiration hazard - material may cause lung inflammation or damage if it enters lungs through vomiting or swallowing. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal. Inhalation of high concentrations may cause dizziness, disorientation, incoordination, narcosis, nausea or narcotic effects. Direct eye contact may cause temporary redness. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May have laxative effects.

Indication of any immediate medical attention and special treatment needed

- : Treat symptomatically. Aspiration hazard.

Comsol 140 (High Flash Mineral Spirits)

SDS Preparation Date (mm/dd/yyyy): 10/24/2016

Page 3 of 10

SAFETY DATA SHEET

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media

- : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media

- : Do not use a solid water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture / Conditions of flammability

- : Combustible liquid. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure. Vapour can travel considerable distance and flashback to a source of ignition. Vapours are heavier than air and collect in confined and low-lying areas.

Flammability classification (OSHA 29 CFR 1910.106)

- : Flammable Liquid - Category 4

Hazardous combustion products

- : Carbon dioxide and carbon monoxide. Other unidentified organic compounds.

Special protective equipment and precautions for firefighters

Protective equipment for fire-fighters

- : Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. A full-body chemical resistant suit should be worn.

Special fire-fighting procedures

- : Evacuate personnel to safe areas. Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame. Dike for water control. Avoid release to the environment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

- : All persons dealing with clean-up should wear the appropriate protective equipment including self-contained breathing apparatus. Keep all other personnel upwind and away from the spill/release. Restrict access to area until completion of clean-up. Refer to Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION, for additional information on acceptable personal protective equipment.

Environmental precautions

- : Ensure spilled product does not enter drains, sewers, waterways, or confined spaces. For large spills, dike the area to prevent spreading.

Methods and material for containment and cleaning up

- : Ventilate the area. Prevent further leakage or spillage if safe to do so. Dike for water control. Use only non-sparking tools and equipment in the clean-up process. Spilled material will create slippery surfaces. Clean up promptly. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13). Contact the proper local authorities.

Special spill response procedures

- : In case of transportation accident, contact TERRAPURE ENVIRONMENTAL at 1-800-567-7455.
US CERCLA Reportable quantity (RQ): None reportable.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

Comsol 140 (High Flash Mineral Spirits)

SDS Preparation Date (mm/dd/yyyy): 10/24/2016

Page 4 of 10

SAFETY DATA SHEET

- : Use only outdoors or in a well-ventilated area. Wear suitable protective equipment. Avoid breathing mist or vapours. Avoid contact with skin, eyes and clothing. Keep away from heat and open flames. - No smoking. Use only non-sparking tools. Use explosion-proof electrical/ventilating/lighting/equipment. Take precautionary measures against static discharges. Bond and ground transfer containers and equipment to avoid static accumulation. Label containers appropriately. Wash thoroughly after handling. Keep containers closed when not in use.
- Conditions for safe storage** : Store locked up. Store in a cool, dry, well-ventilated area. Keep container tightly closed. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks.
- Incompatible materials** : Strong oxidizers (e.g. Chlorine, Peroxides, etc.).

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

<u>Exposure Limits:</u>			
<u>Chemical Name</u>	<u>ACGIH TLV</u>		<u>OSHA PEL</u>
	<u>TWA</u>	<u>STEL</u>	<u>PEL</u> <u>STEL</u>
Hydrotreated light distillate	200 mg/m ³ (as total hydrocarbon vapour)	N/Av	N/Av N/Av

Exposure controls

Ventilation and engineering measures

- : Provide exhaust ventilation or other engineering controls to keep the airborne concentration of vapours below their respective threshold limit value. Use explosion-proof electrical and ventilating equipment.

- Respiratory protection** : Respiratory protection is required if the concentrations exceed the TLV. Use a NIOSH approved dust respirator if dust levels exceed exposure limits. Seek advice from respiratory protection specialists.

- Skin protection** : Wear protective gloves. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

- Eye / face protection** : Wear eye/face protection. Chemical goggles must be worn to prevent dusts from entering the eyes.

- Other protective equipment** : Wear appropriate protective clothing to prevent skin contact, such as coveralls or long sleeved shirt, long pants, and shoes and socks. An eyewash station and safety shower should be made available in the immediate working area. Other equipment may be required depending on workplace standards.

General hygiene considerations

- : Avoid breathing mist or vapours. Avoid contact with skin, eyes and clothing. Do not eat, drink, smoke or use cosmetics while working with this product. Upon completion of work, wash hands before eating, drinking, smoking or use of toilet facilities. Remove soiled clothing and wash it thoroughly before reuse.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance** : Clear blue liquid.
Odour : Mild petroleum odour.
Odour threshold : No information available.
pH : No information available.
Melting/Freezing point : -54°C
Initial boiling point and boiling range : 188-208°C
Flash point : 264-67°C

Comsol 140 (High Flash Mineral Spirits)

SDS Preparation Date (mm/dd/yyyy): 10/24/2016

Page 5 of 10

SAFETY DATA SHEET

Flashpoint (Method) : Tag closed cup
Evaporation rate (BuAe = 1) : Not available.
Flammability (solid, gas) : The product is not flammable.
Lower flammable limit (% by vol.)
: 1.5%
Upper flammable limit (% by vol.)
: 10.5%
Oxidizing properties : None known.
Explosive properties : Not explosive
Vapour pressure : 17 mmHg
Vapour density : 4.5(Air = 1)
Relative density / Specific gravity
: 0.80
Solubility in water : Insoluble.
Other solubility(ies) : No information available.
Partition coefficient: n-octanol/water or Coefficient of water/oil distribution
: 0.2
Auto-ignition temperature : 227°C
Decomposition temperature : No information available.
Viscosity : 0.4 mm²/s
Volatiles (% by weight) : Not available.
Volatile organic Compounds (VOC's)
: No information available.
Absolute pressure of container
: N/Ap
Flame projection length : N/Ap
Other physical/chemical comments
: None known or reported by the manufacturer.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not normally reactive.
Chemical stability : Stable under normal conditions.
Possibility of hazardous reactions
: Hazardous polymerization does not occur.
Conditions to avoid : Ensure adequate ventilation, especially in confined areas. Avoid contact with incompatible materials.
Incompatible materials : See Section 7 (Handling and Storage) for further details.
Hazardous decomposition products
: None known, refer to hazardous combustion products in Section 5.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Routes of entry inhalation : YES
Routes of entry skin & eye : YES
Routes of entry Ingestion : YES
Routes of exposure skin absorption
: NO

Comsol 140 (High Flash Mineral Spirits)

SDS Preparation Date (mm/dd/yyyy): 10/24/2016

Page 6 of 10

SAFETY DATA SHEET

Potential Health Effects:

Signs and symptoms of short-term (acute) exposure

Sign and symptoms Inhalation

- : May cause respiratory tract irritation. Symptoms may include coughing, choking and wheezing.

Sign and symptoms ingestion

- : Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration hazard if swallowed - can enter lungs and cause damage. Aspiration may cause pulmonary oedema and pneumonitis.

Sign and symptoms skin

- : Causes skin irritation. Symptoms may include redness, edema, drying defatting and cracking of the skin.

Sign and symptoms eyes

- : Direct eye contact may cause slight redness.

Potential Chronic Health Effects

- : Prolonged exposure can cause redness, swelling, itching, cracking of the skin, dermatitis and sensitization.

Mutagenicity

- : Not expected to be mutagenic in humans.

Carcinogenicity

- : No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP.

Reproductive effects & Teratogenicity

- : Not expected to have other reproductive effects.

Sensitization to material

- : Not expected to be a skin or respiratory sensitizer.

Specific target organ effects

- : This material is not classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Medical conditions aggravated by overexposure

- : Pre-existing skin, eye and respiratory disorders.

Synergistic materials

- : No information available.

Toxicological data

- : See below for toxicological data on the substance.

<u>Chemical name</u>	<u>LC₅₀(4hr)</u>	<u>LD₅₀</u>	
	<u>inh, rat</u>	<u>(Oral, rat)</u>	<u>(Rabbit, dermal)</u>
Hydrotreated light distillate	>6.03 mg/L (aerosol)	>5000 mg/kg	>2000 mg/kg

Other important toxicological hazards

- : See Section 2 for additional information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

- : Not expected to be harmful to aquatic organisms. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment. See the following tables for the substance's ecotoxicity data. Do not allow this material to drain into sewers/water supplies.

Ecotoxicity data:

<u>Ingredients</u>	<u>CAS No</u>	<u>Toxicity to Fish</u>		
		<u>LC50 / 96h</u>	<u>NOEC / 21 day</u>	<u>M Factor</u>
Hydrotreated light distillate	64742-47-8	45 mg/L (Fathead minnow)	N/Av	None.



Comet Chemical Company Ltd.
3463 Thomas Street
Innisfill, ON, Canada, L9S 3W4
Telephone: (705) 436 5580

Comsol 140 (High Flash Mineral Spirits)

SDS Preparation Date (mm/dd/yyyy): 10/24/2016

Page 7 of 10

SAFETY DATA SHEET

<u>Ingredients</u>	CAS No	Toxicity to Daphnia		
		EC50 / 48h	NOEC / 21 day	M Factor
Hydrotreated light distillate	64742-47-8	N/Av	N/Av	N/Av

<u>Ingredients</u>	CAS No	Toxicity to Algae		
		EC50 / 96h or 72h	NOEC / 96h or 72h	M Factor
Hydrotreated light distillate	64742-47-8	N/Av	N/Av	N/Av

Persistence and degradability

: Not readily biodegradable.

Bioaccumulation potential

: No data is available on the product itself.

<u>Components</u>	<u>Partition coefficient n-octanol/water (log Kow)</u>	<u>Bioconcentration factor (BCF)</u>
Hydrotreated light distillate (CAS 64742-47-8)	5.1-8.8	N/Av

Mobility in soil

: This material has low solubility and floats, and is expected to migrate from water to the land.

Other Adverse Environmental effects

: No data is available on the product itself.

SECTION 13. DISPOSAL CONSIDERATIONS

Handling for Disposal

: Handle waste according to recommendations in Section 7. Empty containers may contain hazardous residues.

Methods of Disposal

: Dispose in accordance with all applicable federal, state, provincial and local regulations.

RCRA

: If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method.

Comsol 140 (High Flash Mineral Spirits)

SDS Preparation Date (mm/dd/yyyy): 10/24/2016

Page 8 of 10

SAFETY DATA SHEET

SECTION 14. TRANSPORTATION INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
TDG	None.	Not regulated.	not regulated	none	
TDG Additional information	None.				
49CFR/DOT	NA1993	Combustible liquid, n.o.s. (Distillates Petroleum hydrotreated light)	Combustible.	III	
49CFR/DOT Additional information	Not regulated for road or rail shipment if packaged in non-bulk containers (450 Litres or less each).				
IMDG	None.	Not regulated.	not regulated	none	
IMDG Additional information	None.				
ICAO/IATA	None.	Not regulated.	not regulated	none	
ICAO/IATA Additional information	None.				

Special precautions for user : Appropriate advice on safety must accompany the package.

Environmental hazards : This substance does not meet the criteria for an environmentally hazardous substance according to the IMDG Code. See Section 12 for more environmental information.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: This information is not available.

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

Components listed below are present on the following U.S. Federal chemical lists:

<u>Ingredients</u>	CAS #	TSCA Inventory	CERCLA Reportable Quantity(RQ) (40 CFR 117.302):	SARA TITLE III: Sec. 302, Extremely Hazardous Substance, 40 CFR 355:	SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical	de minimus Concentration
Hydrotreated light distillate	64742-47-8	Yes	N/Ap	N/Av	Toxic Chemical No	No

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes: Fire Hazard, Acute Health Hazard Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds or the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.



Comsol 140 (High Flash Mineral Spirits)

SDS Preparation Date (mm/dd/yyyy): 10/24/2016

Page 9 of 10

SAFETY DATA SHEET

US State Right to Know Laws:

The following chemicals are specifically listed by individual States:

<u>Ingredients</u>	CAS #	California Proposition 65		State "Right to Know" Lists					
		Listed	Type of Toxicity	CA	MA	MN	NJ	PA	RI
Hydrotreated light distillate	64742-47-8	No	N/Ap	No	No	No	No	No	No

Canadian Information:

All ingredients are present on the DSL.
WHMIS Classification: See Section 2.

International Information:

Components listed below are present on the following International Inventory list:

<u>Ingredients</u>	CAS #	European EINECS	Australia AICS	Philippines PICCS	Japan ENCS	Korea KECI/KECL	China IECSC	NewZealand IOC
Hydrotreated light distillate	64742-47-8	265-149-8	Present	Present	(9)-1700	KE-12550	Present	No information available.

SECTION 16. OTHER INFORMATION

Legend

: ACGIH: American Conference of Governmental Industrial Hygienists
CAS: Chemical Abstract Services
CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980
CFR: Code of Federal Regulations
CNS: Central Nervous System
DOT: Department of Transportation
EPA: Environmental Protection Agency
EINECS: European Inventory of Existing Commercial chemical Substances
IARC: International Agency for Research on Cancer
IBC: Intermediate Bulk Container
IMDG: International Maritime Dangerous Goods
Inh: Inhalation
LC: Lethal Concentration
LD: Lethal Dose
N/Ap: Not Applicable
N/Av: Not Available
NIOSH: National Institute of Occupational Safety and Health
NTP: National Toxicology Program
OSHA: Occupational Safety and Health Administration
PEL: Permissible exposure limit
RCRA: Resource Conservation and Recovery Act
RTECS: Registry of Toxic Effects of Chemical Substances
SARA: Superfund Amendments and Reauthorization Act
STEL: Short Term Exposure Limit
TDG: Canadian Transportation of Dangerous Goods Act & Regulations
TLV: Threshold Limit Values
TWA: Time Weighted Average
WHMIS: Workplace Hazardous Materials Identification System

Comsol 140 (High Flash Mineral Spirits)

SDS Preparation Date (mm/dd/yyyy): 10/24/2016

Page 10 of 10

SAFETY DATA SHEET

References :

1. ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices for 2016
2. International Agency for Research on Cancer Monographs, searched 2016
3. Canadian Centre for Occupational Health and Safety, CCInfoWeb databases, 2016(Chempendium, HSDB and RTECs).
4. Material Safety Data Sheets from manufacturer.
5. US EPA Title III List of Lists - 2016 version.
6. California Proposition 65 List - 2016 version.
7. OECD - The Global Portal to Information on Chemical Substances - eChemPortal, 2016.

Preparation Date (mm/dd/yyyy)

: 10/24/2016

Other special considerations for handling

: Provide adequate information, instruction and training for operators.

<u>Prepared for:</u> Comet Chemical Company Ltd. 3463 Thomas Street Innisfill, ON L9S 3W4 Information (M-F 8:00-5:00): 705-436-5580 www.cometchemical.com	 COMET COMET CHEMICAL COMPANY LTD.
<u>Prepared by:</u> ICC The Compliance Center Inc. Telephone: (888) 442-9628 (U.S.): (888) 977-4834 (Canada) http://www.thecompliancecenter.com	 icc ComplianceCenter

DISCLAIMER

This Safety Data Sheet was prepared by ICC The Compliance Center Inc. using information provided by Comet Chemical Company Ltd. and CCOHS' Web Information Service. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and Comet Chemical Company Ltd. expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other process.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc. and Comet Chemical Company Ltd.

END OF DOCUMENT