

# SAFETY DATA SHEET

According to Canadian Hazardous Products Regulations (HPR) (SOR/2015/17)

SDS #: 087495 FLUID H3

**Date of the previous version:** not applicable **Revision Date:** 2018-03-28 **Version** 1

1. IDENTIFICATION

**Product identifier** 

Product name FLUID H3

Other means of identification

Product Code(s) 087495

Number 5WS Substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Identified uses Transmission fluid

**Uses advised against**Do not use for any purpose other than the one for which it is intended.

Details of the supplier of the safety data sheet

Supplier TOTAL CANADA INC.

220, LAFLEUR LASALLE, QUEBEC

H8R 4C9

Tel: (514) 595-7579 Fax: (514) 595-5950

Contact Point service HSE

E-mail Address info@total-lub.ca

Emergency telephone number

Emergency telephone 1-800-463-3955

Company Phone Number +1 866 928 0789 (24h/24, 7d/7) +1 215 207 0061 (24h/24, 7d/7)

# 2. HAZARDS IDENTIFICATION

#### Classification

The product is not classified as hazardous according to WHMIS

### Label elements

The product is not classified as hazardous according to WHMIS



Date of the previous version: not applicable Revision Date: 2018-03-28 Version 1

Hazard Statements

None

Other information

Other hazards Harmful to aquatic life

**Physical-Chemical Properties** Contaminated surfaces will be extremely slippery.

**Environmental properties**The product may form an oil film on the water surface that may stop the oxygen exchange.

Should not be released into the environment.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Chemical nature Mineral oil of petroleum origin.

Chemical Name	EC-No	CAS-No	Weight %
Methacrylate copolymer	-	^	1<3
Alkoxylated long chain	-	^	0.25<1
alkylamine			

Additional information Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

# 4. FIRST AID MEASURES

### First aid measures for different exposure routes

General advice IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR

EMERGENCY MEDICAL CARE.

Eye contact Rinse thoroughly with plenty of water, also under the eyelids. Keep eye wide open while

rinsing.

**Skin contact**Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. Wash contaminated clothing before reuse. High pressure jets may cause skin damage. Take victim immediately to hospital. Remove contaminated clothing

and shoes. Wash off with soap and water.

**Inhalation** Remove casualty to fresh air and keep at rest in a position comfortable for breathing. If not

breathing, give artificial respiration. Inhalation of high concentrations of vapor or aerosols

may cause irritation of the upper respiratory tract.

Ingestion Clean mouth with water. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician or Poison Control Center immediately. If swallowed,



Date of the previous version:not applicableRevision Date: 2018-03-28Version 1

do not induce vomiting - seek medical advice.

Protection of First-aiders First aider needs to protect himself. See Section 8 for more detail. Do not use

mouth-to-mouth method if victim ingested or inhaled the substance; induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper

respiratory medical device. Use personal protective equipment.

Most important symptoms/effects, acute and delayed

**Skin contact** Not classified based on available data. May produce an allergic reaction. High pressure

injection of the products under the skin may have very serious consequences even though

no symptom or injury may be apparent.

**Eye contact** Not classified based on available data.

**Inhalation** Not classified based on available data. Inhalation of vapors in high concentration may

cause irritation of respiratory system.

Ingestion Not classified based on available data. Ingestion may cause gastrointestinal irritation,

nausea, vomiting and diarrhea.

**Symptoms** No information available.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Carbon dioxide (CO<sub>2</sub>). ABC powder. Foam. Water spray or fog.

**Unsuitable Extinguishing Media**Do not use a solid water stream as it may scatter and spread fire.

Special Hazard Incomplete combustion and thermolysis may produce gases of varying toxicity such as

carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration. Combustion products include sulphur oxides ( SO2 and SO3 ) and Hydrogen sulphide H2S. Nitrogen

oxides (NOx). Mercaptans.

**Explosion Data** 

Sensitivity to Mechanical Impact Sensitivity to Static Discharge None. None.

Special protective equipment for

fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Evacuate non-essential personnel.

# **6. ACCIDENTAL RELEASE MEASURES**



Date of the previous version: not applicable Revision Date: 2018-03-28 Version 1

Personal precautions, protective equipment and emergency procedures

**General Information**Do not touch or walk through spilled material. Contaminated surfaces will be extremely

slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all

sources of ignition.

**Other information** See Section 12 for additional information.

Environmental precautions

General Information Do not allow material to contaminate ground water system. Prevent entry into waterways,

sewers, basements or confined areas. Local authorities should be advised if significant spillages cannot be contained. Try to prevent the material from entering drains or water

courses.

Methods and material for containment and cleaning up

Methods for containment Dike to collect large liquid spills. If necessary dike the product with dry earth, sand or

similar non-combustible materials.

**Methods for cleaning up**Dam up. Soak up with inert absorbent material. Keep in suitable, closed containers for

disposal. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according

to local / national regulations (see section 13).

### 7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling For personal protection see section 8. Use only in well-ventilated areas. Do not breathe

vapors or spray mist. Avoid contact with skin, eyes and clothing. When using, do not eat,

drink or smoke.

**Prevention of fire and explosion** Take precautionary measures against static discharges.

**Hygiene measures** Ensure the application of strict rules of hygiene by the personnel exposed to the risk of

contact with the product. When using, do not eat, drink or smoke. Wash hands before breaks and immediately after handling the product. Regular cleaning of equipment, work area and clothing is recommended. Do not use abrasives, solvents or fuels. Do not dry

hands with rags that have been contaminated with product. Do not put product

contaminated rags into workwear pockets. Use personal protective equipment as required. Wash hands before breaks and at the end of workday. Wash hands with water as a precaution. Avoid breathing vapors, mist or gas. Do not wash off with:. Fuel. Solvent. Abrasive. Avoid extended and repeated contact with the skin as this may cause skin conditions, which may also be aggravated by minor injuries or by contact with soiled clothing. Avoid prolonged and repeated contact with the skin, especially with used or waste

product.

Conditions for safe storage, including any incompatibilities



Date of the previous version: not applicable Revision Date: 2018-03-28 Version 1

**Technical measures/Storage** 

conditions

Keep away from food, drink and animal feedingstuffs. Keep in a bunded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Store at room temperature. Protect from moisture. Keep in a bunded area. Protect from frost, heat and sunlight. Store in original container. Keep in properly labeled

containers.

Materials to Avoid Strong oxidizing agents.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

**Exposure limits** Mineral oil mist:

USA: OSHA (PEL) TWA 5 mg/m³, NIOSH (REL) TWA 5 mg/m³, STEL 10 mg/m³, ACGIH

(TLV) TWA 5 mg/m3 (highly refined). .

**Legend** See section 16

**Exposure controls** 

**Engineering Measures** Apply technical measures to comply with the occupational exposure limits. Ensure

adequate ventilation, especially in confined areas. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the

recommended equipment.

Individual protection measures, such as personal protective equipment

**General Information** Protective engineering solutions should be implemented and in use before personal

protective equipment is considered. The personal protective equipment (PPE) recommendations apply to the product ITSELF. In case of mixtures or formulations, it is

suggested that you contact the relevant PPE suppliers.

**Eye/face protection** If splashes are likely to occur, wear safety glasses with side-shields.

**Skin and body protection** Wear suitable protective clothing. Protective shoes or boots.

Hand Protection Hydrocarbon-proof gloves: Fluorinated rubber. Nitrile rubber. Please observe the

instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which

the product is used, such as the danger of cuts, abrasion, and the contact time.



Date of the previous version: not applicable **Revision Date: 2018-03-28** Version 1

Respiratory protection

None under normal use conditions. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Respirator with combination filter for vapor/particulate. Warning ! filters have a limited use duration. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Physical and chemical properties

**Appearance** limpid

Color No information available Physical State @20°C liquid

Odor Characteristic

**Odor Threshold** No information available

Values\_ **Property** Remarks Method

Not applicable рΗ

Melting point/range No information available

No information available Boiling point/boiling range

Flash point 220 °C ASTM D 93 ASTM D 93.

428 °F **Evaporation rate** 

No information available Flammability Limits in Air

No information available upper Lower No information available

Vapor Pressure No information available Vapor density No information available

Relative density 0.865 @ 15 °C **ASTM D 1298** @ 15 °C **Density** 865 kg/m<sup>3</sup> **ASTM D 1298** 

Water solubility Not applicable

Solubility in other solvents No information available

logPow No information available Not applicable **Autoignition temperature** 

**Decomposition temperature** No information available

35.10 mm2/s Viscosity, kinematic @ 40 °C ASTM D 445 @ 100 °C 7.2 mm2/s ASTM D 445

**Explosive properties** Not explosive Not applicable **Oxidizing Properties** 

Possibility of hazardous reactions None under normal processing

Other information

**Freezing Point** No information available



Date of the previous version: not applicable Revision Date: 2018-03-28 Version 1

Pour point -48 °C ASTM D 97

10. STABILITY AND REACTIVITY

**Reactivity** None under normal processing.

<u>Chemical stability</u> Stable under recommended storage conditions.

Possibility of hazardous reactions 
No dangerous reaction known under conditions of normal use. None under normal

processing.

Conditions to avoid Keep away from open flames, hot surfaces and sources of ignition. Keep away from heat

and sparks. Heat, flames and sparks. Take precautionary measures against static discharges. Heat (temperatures above flash point), sparks, ignition points, flames, static

electricity. Strong oxidizing agents.

<u>Incompatible materials</u> Strong oxidizing agents.

Hazardous Decomposition Products Incomplete combustion and thermolysis may produce gases of varying toxicity such as

carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. Nitrogen oxides (NOx). Mercaptans. Combustion products include sulphur oxides ( SO2 and SO3 )

and Hydrogen sulphide H2S.

# 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

**Symptoms** No information available.

**Skin contact** Not classified based on available data. May produce an allergic reaction. High pressure

injection of the products under the skin may have very serious consequences even though

no symptom or injury may be apparent.

**Eye contact** Not classified based on available data.

**Inhalation** Not classified based on available data. Inhalation of vapors in high concentration may

cause irritation of respiratory system.

**Ingestion** Not classified based on available data. Ingestion may cause gastrointestinal irritation,

nausea, vomiting and diarrhea.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Acute toxicity - Product Information

**Oral**Not classified based on available data 0 % of the mixture consists of ingredient(s) of unknown acute oral toxicity



Date of the previous version: not applicable Revision Date: 2018-03-28 Version 1

**Dermal**Not classified based on available data 0 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

**Inhalation** Not classified based on available data

ATEmix (inhalation-dust/mist) 7.70 mg/l ATEmix (inhalation-vapor) 30.50 mg/l

0 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity

### **Acute toxicity - Component Information**

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methacrylate copolymer	LD50 >2000 mg/kg (rat)	LD50 >2000 mg/kg (rabbit)	LC50 >5.2 mg/l
Alkoxylated long chain alkylamine	LD50 1350 mg/kg (Rat)		LC50 (1h) 220 ppm (Rat - Vapor)

Skin corrosion/irritation Not classified based on available data.

Serious eye damage/eye irritation Not classified based on available data.

Respiratory or skin sensitization Not classified based on available data. Contains sensitizer(s). May produce an allergic

reaction. The supplier of one or more of the components contained within this formulation has indicated that he has data on the components and/or similar mixtures, which confirms

that at the concentration used, classification is not required.

**Germ cell mutagenicity**Not classified based on available data.
Carcinogenicity
Not classified based on available data.

**Reproductive toxicity** Not classified based on available data.

Target Organ Effects (STOT) None known.

STOT - single exposure
STOT - repeated exposure
Aspiration hazard

Not classified based on available data.
Not classified based on available data.
Not classified based on available data.

# 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

Acute aquatic toxicity - Product Information

No information available

# Acute aquatic toxicity - Component Information

No information available

#### **Chronic aquatic toxicity - Product Information**

No information available



Date of the previous version:not applicableRevision Date: 2018-03-28Version 1

**Chronic aquatic toxicity - Component Information** 

No information available

Effects on terrestrial organisms No information available.

Persistence and degradability

No information available

Bioaccumulative potential

Product Information No information available.

logPow No information available

**Component Information** No information available.

**Mobility** 

Soil Given its physical and chemical characteristics, the product generally shows low soil

mobility

Air Loss by evaporation is limited

Water The product is insoluble and floats on water

Other adverse effects

General Information No information available

### 13. DISPOSAL CONSIDERATIONS

# Waste treatment

Waste from residues/unused products

Should not be released into the environment. Do not empty into drains. Dispose of in accordance with all applicable national environmental laws and regulations. Where possible recycling is preferred to disposal or incineration. Other Regulatory Status: No Canadian federal standard; however, for general discharge guidance, federal installations limited to 15 mg/L for total oil and grease. Provincial criteria are likely and should be requested when notifying provincial authorities.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or

disposal.



Date of the previous version: not applicable Revision Date: 2018-03-28 Version 1

# 14. TRANSPORT INFORMATION

TDG Not regulated

**DOT** Not regulated

MEX Not regulated

ICAO/IATA Not regulated

IMDG/IMO Not regulated

ADR/RID Not regulated

ADN Not regulated

### 15. REGULATORY INFORMATION

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) (SOR/2015/17) and the Safety Data Sheet (SDS) contains all the information required by the HPR

following inventories: Canada (DSL/NDSL) U.S.A. (TSCA)

# 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPAHealth Hazard0Flammability1Instability0Special hazardsHMISHealth Hazard0Flammability1Physical Hazard0Personal protectionX

Revision Date: 2018-03-28
Revision Note Initial Release

### Abbreviations, acronyms

ACGIH = American Conference of Governmental Industrial Hygienists

bw = body weight

bw/day = body weight/day

EC x = Effect Concentration associated with x% response

GLP = Good Laboratory Practice

IARC = International Agency for Research of Cancer

LC50 = 50% Lethal concentration - Concentration of a chemical in air or a chemical in water which causes the death of 50% (one



**Date of the previous version:** not applicable **Revision Date:** 2018-03-28 **Version** 1

half) of a group of test animals

LD50 = 50% Lethal Dose - Chemical amount, given at once, which causes the death of 50% (one half) of a group of test animals LL = Lethal Loading

NIOSH = National Institute of Occupational Safety and Health

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

NOEL = No Observed Effect Level

OECD = Organization for Economic Co-operation and Development

OSHA = Occupational Safety and Health Administration

UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material

NTP = National Toxicology Program

Section 8

TWA - Time Weight Average

STEL - Short Term Exposure Limits

+ Sensitizer \* Skin designation
C: Carcinogen R: Toxic to reproduction

Ceiling: Ceiling Limit Value

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

**End of the Safety Data Sheet**