



SAFETY DATA SHEET

According to Canadian Hazardous Products Regulations (HPR) (SOR/2015/17)

SDS # : 088399

QUARTZ 7000 FUTURE XT 5W-20

Date of the previous version: 2018-02-23

Revision Date: 2018-10-30

Version 2

1. IDENTIFICATION

Product identifier

Product name QUARTZ 7000 FUTURE XT 5W-20

Other means of identification

Product Code(s) 088399

Number DTR
Substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Identified uses Engine oil***

Uses advised against Do not use for any purpose other than the one for which it is intended.

Details of the supplier of the safety data sheet

Supplier TOTAL CANADA INC.
220, LAFLEUR
LASALLE, QUEBEC
H8R 4C9
Tel: (514) 595-7579
Fax: (514) 595-5950

Contact Point service HSE

E-mail Address ProductSafety@total.com***

Emergency telephone number

Emergency telephone 1-800-463-3955
Company Phone Number +1 866 928 0789 (24h/24, 7d/7)
+1 215 207 0061 (24h/24, 7d/7)

2. HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation - Category 3***
Serious eye damage/eye irritation - Category 2A***

Label elements

Version HGHS



SDS # : 088399

QUARTZ 7000 FUTURE XT 5W-20

Date of the previous version: 2018-02-23

Revision Date: 2018-10-30

Version 2

**WARNING*******Hazard Statements**

Causes serious eye irritation

Causes mild skin irritation***

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves/protective clothing/eye protection/face protection***

Precautionary Statements - Response *****Eyes**IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention*****Skin**

If skin irritation occurs: Get medical advice/attention***

Other information**Physical-Chemical Properties**

Contaminated surfaces will be extremely slippery.***

Environmental propertiesThe product may form an oil film on the water surface that may stop the oxygen exchange.
Should not be released into the environment.*****3. COMPOSITION/INFORMATION ON INGREDIENTS****Mixture****Chemical nature**

Mineral oil of petroleum origin.

Chemical Name	EC-No	CAS-No	Weight %
Distillates (petroleum), hydrotreated heavy paraffinic***	265-157-1	64742-54-7	50<60
Distillates (petroleum), solvent-dewaxed heavy paraffinic***	265-169-7	64742-65-0	3<5
zinc O,O,O',O'-tetrakis(1,3-dimethylb utyl) bis(phosphorodithioate)***	218-679-9	2215-35-2	1<2.5
bis(nonylphenyl)amine***	253-249-4	36878-20-3	1<2.5

Version HGHS



SDS # : 088399

QUARTZ 7000 FUTURE XT 5W-20

Date of the previous version: 2018-02-23

Revision Date: 2018-10-30

Version 2

Molybdenum polysulphide long chain alkyl dithiocarbamate complex***	457-320-2***	^	0.1<0.25
---	--------------	---	----------

Additional information

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

4. FIRST AID MEASURES**First aid measures for different exposure routes**

General advice	IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.***
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing.***
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash contaminated clothing before reuse.***
Inhalation	Remove casualty to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration.***
Ingestion	Clean mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.***
Protection of First-aiders	First aider needs to protect himself. See Section 8 for more detail. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.***

Most important symptoms/effects, acute and delayed

Skin contact	Causes mild skin irritation. May produce an allergic reaction.***
Eye contact	Causes serious eye irritation.***
Inhalation	Not classified based on available data. Inhalation of vapors in high concentration may cause irritation of respiratory system.***
Ingestion	Not classified based on available data. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.***
Symptoms	No information available.***

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	Treat symptomatically.***
---------------------------	---------------------------

Version HGHS



SDS # : 088399

QUARTZ 7000 FUTURE XT 5W-20

Date of the previous version: 2018-02-23

Revision Date: 2018-10-30

Version 2

5. FIRE-FIGHTING MEASURES

<u>Suitable Extinguishing Media</u>	Carbon dioxide (CO ₂). ABC powder. Foam. Water spray or fog.***
<u>Unsuitable Extinguishing Media</u>	Do not use a solid water stream as it may scatter and spread fire.
<u>Special Hazard</u>	Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration. Combustion products include sulphur oxides (SO ₂ and SO ₃) and Hydrogen sulphide H ₂ S, Mercaptans, Nitrogen oxides (NO _x), Phosphorous oxides, Zinc oxides.***
<u>Explosion Data</u>	
<u>Sensitivity to Mechanical Impact</u>	None.
<u>Sensitivity to Static Discharge</u>	None.
<u>Special protective equipment for fire-fighters</u>	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Evacuate non-essential personnel.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

<u>General Information</u>	Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.***
<u>Other information</u>	See Section 12 for additional information.

Environmental precautions

<u>General Information</u>	Do not allow material to contaminate ground water system. Prevent entry into waterways, sewers, basements or confined areas. Local authorities should be advised if significant spillages cannot be contained.***
-----------------------------------	---

Methods and material for containment and cleaning up

<u>Methods for containment</u>	Dike to collect large liquid spills. If necessary dike the product with dry earth, sand or similar non-combustible materials.***
<u>Methods for cleaning up</u>	Dispose of contents/container in accordance with local regulation. In case of soil contamination, remove contaminated soil for remediation or disposal, in accordance with local regulations.***

7. HANDLING AND STORAGE

Precautions for safe handling

Version HGHS



SDS # : 088399

QUARTZ 7000 FUTURE XT 5W-20

Date of the previous version: 2018-02-23

Revision Date: 2018-10-30

Version 2

Advice on safe handling For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing.***

Prevention of fire and explosion Take precautionary measures against static discharges.***

Hygiene measures Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. When using, do not eat, drink or smoke. Wash hands before breaks and immediately after handling the product. Regular cleaning of equipment, work area and clothing is recommended. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.***

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions Keep away from food, drink and animal feedingstuffs. Keep in a banded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Store at room temperature. Protect from moisture.***

Materials to Avoid Strong oxidizing agents.***

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits Mineral oil mist:
USA: OSHA (PEL) TWA 5 mg/m³, NIOSH (REL) TWA 5 mg/m³, STEL 10 mg/m³, ACGIH (TLV) TWA 5 mg/m³ (highly refined).***

Legend See section 16

Exposure controls

Engineering Measures Apply technical measures to comply with the occupational exposure limits. Ensure adequate ventilation, especially in confined areas. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.***

Individual protection measures, such as personal protective equipment

General Information Protective engineering solutions should be implemented and in use before personal protective equipment is considered. The personal protective equipment (PPE) recommendations apply to the product ITSELF. In case of mixtures or formulations, it is suggested that you contact the relevant PPE suppliers.***

Version HGHS



SDS # : 088399

QUARTZ 7000 FUTURE XT 5W-20

Date of the previous version: 2018-02-23

Revision Date: 2018-10-30

Version 2

Eye/face protection	Safety glasses with side-shields.***
Skin and body protection	Wear suitable protective clothing. Protective shoes or boots.
Hand Protection	Hydrocarbon-proof gloves: Fluorinated rubber. Nitrile rubber. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.***
Respiratory protection	None under normal use conditions. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Respirator with combination filter for vapor/particulate. Warning ! filters have a limited use duration. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.***

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Appearance		limpid	
Color		No information available	
Physical State @20°C		liquid	
Odor		Characteristic	
Odor Threshold		No information available	
<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>Method</u>
pH		No information available	
Melting point/range		No information available	
Boiling point/boiling range		No information available	
Flash point	222 °C 392 °F		ASTM D 92 ASTM D 92.
Evaporation rate		No information available	
Flammability Limits in Air		No information available	
Vapor Pressure		No information available	
Vapor density		No information available	
Relative density	0.855***	@ 15 °C	
Density	855*** kg/m ³	@ 15 °C	
Water solubility		Not applicable	
Solubility in other solvents		Not applicable	
logPow		No information available***	
Autoignition temperature		No information available	
Decomposition temperature		No information available	

Version HGHS



SDS # : 088399

QUARTZ 7000 FUTURE XT 5W-20

Date of the previous version: 2018-02-23

Revision Date: 2018-10-30

Version 2

Viscosity, kinematic ***	53*** mm2/s	@ 40 °C	ASTM D 445***
	*** 8.77*** mm2/s***	@ 100 °C***	ASTM D 445
Explosive properties	Not explosive		
Oxidizing Properties	Not applicable		
Possibility of hazardous reactions	No information available		
Other information			
Freezing Point		No information available	
Pour point ***	*** -46*** °C***	***	ASTM D 97***

10. STABILITY AND REACTIVITY

<u>Reactivity</u>	None under normal processing.***
<u>Chemical stability</u>	Stable under recommended storage conditions.
<u>Possibility of hazardous reactions</u>	No dangerous reaction known under conditions of normal use.***
<u>Conditions to avoid</u>	Keep away from open flames, hot surfaces and sources of ignition. Keep away from heat and sparks.***
<u>Incompatible materials</u>	Strong oxidizing agents.***
<u>Hazardous Decomposition Products</u>	Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. Combustion products include sulphur oxides (SO2 and SO3) and Hydrogen sulphide H2S, Mercaptans, Nitrogen oxides (NOx), Zinc oxides. Phosphorous oxides.***

11. TOXICOLOGICAL INFORMATIONInformation on likely routes of exposure

Symptoms	No information available.***
Skin contact	Causes mild skin irritation. May produce an allergic reaction.***
Eye contact	Causes serious eye irritation.***
Inhalation	Not classified based on available data. Inhalation of vapors in high concentration may cause irritation of respiratory system.***
Ingestion	Not classified based on available data. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.***

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Acute toxicity - Product Information**

Version HGHS



SDS # : 088399

QUARTZ 7000 FUTURE XT 5W-20

Date of the previous version: 2018-02-23

Revision Date: 2018-10-30

Version 2

Oral Not classified based on available data***

Dermal Not classified based on available data***

Inhalation Not classified based on available data***

Acute toxicity - Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Distillates (petroleum), hydrotreated heavy paraffinic*** 64742-54-7	LD50 > 5000 mg/kg bw (rat - OECD 420)	LD50 > 5000 mg/kg bw (rabbit - OECD 402)	LC50 (4h) > 5 mg/l (aerosol) (rat - OECD 403)
Distillates (petroleum), solvent-dewaxed heavy paraffinic*** 64742-65-0	LD50 > 5000 mg/kg bw (rat - OECD 420)	LD50 > 5000 mg/kg bw (rabbit - OECD 402)	LC50 (4h) > 5.53 mg/l (aerosol) (rat - OECD 403)
zinc O,O',O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate)*** 2215-35-2	LD50 2230 mg/kg (Rat - OECD 401)	LD50 > 25000 mg/kg (Rabbit - OECD 402)	
bis(nonylphenyl)amine*** 36878-20-3	LD50 > 5000 mg/kg (rat)	LD50 > 2000 mg/kg (Rat - OECD 402)	
Molybdenum polysulphide long chain alkyl dithiocarbamate complex*** ^	LD50 > 2000 mg/kg (Rat - OECD 425)	LD50 > 2000 mg/kg (Rat - OECD 402)	

Skin corrosion/irritation

Serious eye damage/eye irritation

Respiratory or skin sensitization

Germ cell mutagenicity

Carcinogenicity

Irritating to skin.***

Irritating to eyes.***

Not classified based on available data. Contains sensitizer(s). May produce an allergic reaction.***

Not classified based on available data.***

Not classified based on available data. During use in engines, contamination of oil with low levels of combustion products occurs. Used motor oils have been shown to cause skin cancer in mice following repeated application and continuous exposure. Brief or intermittent skin contact with used motor oil is not expected to have serious effects in humans if the oil is thoroughly removed by washing with soap and water.***

Reproductive toxicity

Target Organ Effects (STOT)

STOT - single exposure

STOT - repeated exposure

Aspiration hazard

Not classified based on available data.***

None known.***

Not classified based on available data.***

Not classified based on available data.***

Not classified based on available data.***

12. ECOLOGICAL INFORMATION**Ecotoxicity**Acute aquatic toxicity - **Product Information*****

No information available***

Version HGHS



SDS # : 088399

QUARTZ 7000 FUTURE XT 5W-20

Date of the previous version: 2018-02-23

Revision Date: 2018-10-30

Version 2

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates	Toxicity to microorganisms
Distillates (petroleum), hydrotreated heavy paraffinic*** 64742-54-7	EL50 (48h) > 100 mg/l (Pseudokirchnerella subcapitata - OECD 201)	LL50 (96h) > 100 mg/l (Oncorhynchus mykiss - OECD 203)	EL50 (48h) > 10000 mg/l (Daphnia magna - OECD 202)	
Distillates (petroleum), solvent-dewaxed heavy paraffinic*** 64742-65-0		LL50 (96h) > 100 mg/l (Oncorhynchus mykiss - OECD 203)	EL50 (48h) > 10000 mg/l (Daphnia magna - OECD 202)	
zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate)*** 2215-35-2	EL50 (72h) 21 mg/l (Desmodesmus subspicatus - Static - OECD 201)	LL50 (96h) 4.5 mg/l (Oncorhynchus mykiss - semi static - OECD203)	EL50 (48h) 23 mg/l (Daphnia magna - static - OECD 202)	
bis(nonylphenyl)amine*** 36878-20-3			EC50(48h) > 100 mg/l (daphnia magna - OECD 202)	
Molybdenum polysulphide long chain alkyl dithiocarbamate complex*** ^	EC50 (72h) 14 mg/l (Selenastrum capricornutum - OECD 201)	LL50 (96h) 94.8 mg/l (Oncorhynchus mykiss - OECD 203)	EL50 (48h) 50 mg/l (Daphnia magna - OECD 202)	

Chronic aquatic toxicity - Product Information

No information available***

Chronic aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
Distillates (petroleum), hydrotreated heavy paraffinic*** 64742-54-7		NOEL (21d) 10 mg/l (Daphnia magna - QSAR Petrotox)	NOEL (14/28d) > 1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox)	
Distillates (petroleum), solvent-dewaxed heavy paraffinic*** 64742-65-0		NOEL (21d) 10 mg/l (Daphnia magna - OECD 211)	NOEL (14/28d) > 1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox)	
zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate)*** 2215-35-2		NOEC (21d) 0.4 mg/l (Daphnia magna - OECD 211)		

Version HGHS



SDS # : 088399

QUARTZ 7000 FUTURE XT 5W-20

Date of the previous version: 2018-02-23

Revision Date: 2018-10-30

Version 2

Effects on terrestrial organisms No information available.***

Persistence and degradability

No information available

Bioaccumulative potential

Product Information No information available.***

logPow No information available***

Component Information

Chemical Name	log Pow
Distillates (petroleum), hydrotreated heavy paraffinic*** 64742-54-7	-
zinc O,O',O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate)*** 2215-35-2	2.21
Molybdenum polysulphide long chain alkyl dithiocarbamate complex*** ^	5.1

Mobility

Soil Given its physical and chemical characteristics, the product generally shows low soil mobility.***

Air Loss by evaporation is limited.***

Water The product is insoluble and floats on water.***

Other adverse effects

General Information No information available.***

13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste from residues/unused products

Should not be released into the environment. Do not empty into drains. Dispose of in accordance with all applicable national environmental laws and regulations. Where possible recycling is preferred to disposal or incineration. Other Regulatory Status: No Canadian federal standard; however, for general discharge guidance, federal installations limited to 15 mg/L for total oil and grease. Provincial criteria are likely and should be requested when notifying provincial authorities.***

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal.***

Version HGHS



SDS # : 088399

QUARTZ 7000 FUTURE XT 5W-20

Date of the previous version: 2018-02-23

Revision Date: 2018-10-30

Version 2

14. TRANSPORT INFORMATIONTDG Not regulatedICAO/IATA Not regulatedIMDG/IMO Not regulatedADR/RID Not regulated**15. REGULATORY INFORMATION**

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) (SOR/2015/17) and the Safety Data Sheet (SDS) contains all the information required by the HPR

International Inventories All the substances contained in this product are listed or exempted from listing in the following inventories:
Canada (DSL/NDSL)
U.S.A. (TSCA)

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

<u>NFPA</u>	Health Hazard 1***	Flammability 1***	Instability 0	Special hazards -
<u>HMIS</u>	Health Hazard 1***	Flammability 1***	Physical Hazard 0	Personal protection X

Revision Date: 2018-10-30
Revision Note: *** Indicates updated section***

Abbreviations, acronyms

ACGIH = American Conference of Governmental Industrial Hygienists

bw = body weight

bw/day = body weight/day

EC x = Effect Concentration associated with x% response

GLP = Good Laboratory Practice

IARC = International Agency for Research of Cancer

LC50 = 50% Lethal concentration - Concentration of a chemical in air or a chemical in water which causes the death of 50% (one half) of a group of test animals

LD50 = 50% Lethal Dose - Chemical amount, given at once, which causes the death of 50% (one half) of a group of test animals

LL = Lethal Loading

NIOSH = National Institute of Occupational Safety and Health

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

Version HGHS



SDS # : 088399

QUARTZ 7000 FUTURE XT 5W-20

Date of the previous version: 2018-02-23

Revision Date: 2018-10-30

Version 2

NOEL = No Observed Effect Level

OECD = Organization for Economic Co-operation and Development

OSHA = Occupational Safety and Health Administration

UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material

NTP = National Toxicology Program

Section 8

TWA - Time Weight Average

STEL - Short Term Exposure Limits

+ Sensitizer
 C: Carcinogen
 Ceiling: Ceiling Limit Value

* Skin designation
 R: Toxic to reproduction

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the Safety Data Sheet