



SAFETY DATA SHEET

Page: 1

Revision Date: 10/17/2012

Print Date: 3/3/2015

MSDS Number: 000000116962

Version: 3.2

Eagle One™ WET TIRE SHINE / DRESSING
667690

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Ashland	Regulatory Information Number	1-800-325-3751
P.O. Box 2219	Telephone	614-790-3333
Columbus, OH 43216	Emergency telephone number	1-800-ASHLAND (1-800-274-5263)
Product name	Eagle One™ WET TIRE SHINE / DRESSING	
Product code	667690	

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid

CAUTION! COMBUSTIBLE LIQUID AND VAPOR. MAY AFFECT THE CENTRAL NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION.

Potential Health Effects

Exposure routes

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye contact

May cause mild eye irritation. Symptoms include stinging, tearing, and redness.

Skin contact

May cause slight skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, and drying and cracking of skin, skin burns, and other skin damage.

Ingestion

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

ASHLAND®

SAFETY DATA SHEET

Page: 2

Revision Date: 10/17/2012

Print Date: 3/3/2015

MSDS Number: 000000116962

Version: 3.2

Eagle One™ WET TIRE SHINE / DRESSING
667690

Inhalation

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: Skin, lung (for example, asthma-like conditions)

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness)

Target Organs

Exposure to this material (or a component) has been found to cause kidney damage in male rats. The mechanism by which this toxicity occurs is specific to the male rat and the kidney effects are not expected to occur in humans.

Carcinogenicity

This product (or a component) is a petroleum-derived material. Similar materials and certain compounds occurring naturally in petroleum oils have been shown to cause skin cancer in laboratory animals following repeated exposure without washing or removal. This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA).

Reproductive hazard

There are no data available for assessing risk to the fetus from maternal exposure to this material.

Other information

When heated to temperatures above 150 degrees C in the presence of air, this product can form formaldehyde vapors. Formaldehyde has been identified as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP) and the Occupational Safety and Health Administration (OSHA). Formaldehyde is irritating to the eyes, nose, throat, and airways, and can cause an allergic reaction (causes narrowing of the air passages of the lungs, sweating, flushing, hives, rapid heart rate, and lowered blood pressure). In addition, formaldehyde can cause an allergic

Eagle One™ WET TIRE SHINE / DRESSING
667690

skin reaction (delayed skin rash which may be followed by blistering, scaling and other skin effects). It is harmful if inhaled, swallowed or absorbed through skin.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components	CAS-No. / Trade Secret No.	Concentration
SOLVENT NAPHTHA (PETROLEUM), HEAVY ALIPHATIC	64742-96-7	>=80-<90%
MODIFIED SILICONE COPOLYMER		>=1.5-<5%

4. FIRST AID MEASURES

Eyes

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to physician

Eagle One™ WET TIRE SHINE / DRESSING
667690

Hazards: This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 2 - Swallowing) when deciding whether to induce vomiting.

Treatment: No information available.

5. FIREFIGHTING MEASURES

Suitable extinguishing media

Dry chemical, Carbon dioxide (CO₂), Water spray

Hazardous combustion products

Aldehydes, carbon dioxide and carbon monoxide, formaldehyde, Hydrocarbons, nitrogen oxides (NO_x), silicon oxides

Precautions for fire-fighting

If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning material with water used for cooling purposes.

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIA

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Ensure adequate ventilation. Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Pay attention to the spreading of gases especially at ground level (heavier than air) and to the direction of the wind.

Environmental precautions

Prevent spreading over a wide area (e.g. by containment or oil barriers). Do not let product enter drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.

Eagle One™ WET TIRE SHINE / DRESSING
667690

Methods for cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

Other information

Comply with all applicable federal, state, and local regulations. Suppress (knock down) gases/vapours/mists with a water spray jet.

7. HANDLING AND STORAGE**Handling**

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Static ignition hazard can result from handling and use. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.

Storage

Store in a cool, dry, ventilated area, away from incompatible substances. Store in a cool, dry, ventilated area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Exposure Guidelines**

SOLVENT NAPHTHA (PETROLEUM), HEAVY ALIPHATIC	64742-96-7
---	-------------------

CAD ON OEL	time weighted average	525 mg/m3
------------	-----------------------	-----------

General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Eagle One™ WET TIRE SHINE / DRESSING
667690

Exposure controls

General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Eye protection

Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection

Wear resistant gloves (consult your safety equipment supplier).
Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.

Respiratory protection

Respiratory protection is not required under normal conditions of use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Boiling point/boiling range	347 °F / 175 °C Calculated Phase Transition Liquid/Gas
Flash point	176 °F / 80 °C Calculated Flash Point
Lower explosion limit/Upper explosion limit	0.7 %(V) / 6 %(V) Calculated Explosive Limit
Vapour pressure	6.666 hPa @ 68 °F / 20 °C Calculated Vapor Pressure
Density	0.839 g/cm3 @ 68 °F / 20 °C

10. STABILITY AND REACTIVITY**Stability**

Stable.

Eagle One™ WET TIRE SHINE / DRESSING
667690

Conditions to avoid

Heat, flames and sparks.

Incompatible products

Acids, Strong oxidizing agents, strong reducing agents, Do not use with aluminum equipment at temperatures above 49C or 120 degrees F.

Hazardous decomposition products

Aldehydes, carbon dioxide and carbon monoxide, formaldehyde, Hydrocarbons, nitrogen oxides (NOx), silicon oxides

Hazardous reactions

Product will not undergo hazardous polymerization.

11. TOXICOLOGICAL INFORMATION**Acute oral toxicity**

Acute oral toxicity - : no data available
Product

Acute oral toxicity - Components

SOLVENT NAPHTHA : LD 50: > 5 g/kg Species: Rat Remarks: Information given
(PETROLEUM), HEAVY is based on data obtained from similar substances.
ALIPHATIC

Acute inhalation toxicity

Acute inhalation toxicity - : no data available
Product

Acute inhalation toxicity - Components

SOLVENT NAPHTHA : LC 50: > 5 mg/l Exposure time: 4 h Species: Rat Remarks:
(PETROLEUM), HEAVY Information given is based on data obtained from similar
ALIPHATIC substances.

Eagle One™ WET TIRE SHINE / DRESSING
667690

Acute dermal toxicity

Acute dermal toxicity - Product : no data available

Acute dermal toxicity - Components

SOLVENT NAPHTHA (PETROLEUM), HEAVY ALIPHATIC : LD 50: > 2,000 mg/kg Species: Rat Remarks: Information given is based on data obtained from similar substances.

Acute toxicity (other routes of administration)

Acute toxicity (other routes of administration) : no data available

12. ECOLOGICAL INFORMATION

Biodegradability

Biodegradability - Product : no data available

Bioaccumulation

Bioaccumulation - Product : no data available

Ecotoxicity effects

Toxicity to fish

Toxicity to fish - Product : no data available

Toxicity to daphnia and other aquatic invertebrates

Toxicity to daphnia and other aquatic invertebrates - Product : no data available

Toxicity to algae

Toxicity to algae - Product : no data available



SAFETY DATA SHEET

Page: 9

Revision Date: 10/17/2012

Print Date: 3/3/2015

MSDS Number: 000000116962

Version: 3.2

Eagle One™ WET TIRE SHINE / DRESSING
667690

Toxicity to bacteria

Toxicity to bacteria - : no data available
Product

13. DISPOSAL CONSIDERATIONS

Waste disposal methods

Dispose of in accordance with all applicable local, state and federal regulations.

14. TRANSPORT INFORMATION

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
--------------	----------------------	------------------	-----------------------	------------------	------------------------------------

U.S. DOT - ROAD

Not dangerous goods

U.S. DOT - RAIL

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TRANSPORT CANADA - ROAD

Not dangerous goods

TRANSPORT CANADA - RAIL

Not dangerous goods

TRANSPORT CANADA - INLAND WATERWAYS

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

Eagle One™ WET TIRE SHINE / DRESSING
667690

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

Not dangerous goods

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

15. REGULATORY INFORMATION**WHMIS Classification**

B3 Combustible Liquid

WHMIS Ingredient Disclosure List IDL: No component is listed on the WHMIS ingredients disclosure list.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

Canadian National Pollutant Release Inventory (NPRI) Canadian National Pollutant Release Inventory (NPRI): No component is listed on NPRI.

Notification status

US. Toxic Substances Control Act	y (positive listing)
Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 133)	y (positive listing)
Australia. Industrial Chemical (Notification and Assessment) Act	y (positive listing)



SAFETY DATA SHEET

Page: 11

Revision Date: 10/17/2012

Print Date: 3/3/2015

MSDS Number: 000000116962

Version: 3.2

Eagle One™ WET TIRE SHINE / DRESSING
667690

New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand	n (Negative listing)
Japan. Kashin-Hou Law List	n (Negative listing)
Korea. Toxic Chemical Control Law (TCCL) List	y (positive listing)
Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act	y (positive listing)
China. Inventory of Existing Chemical Substances	y (positive listing)

	HMIS	NFPA
Health	1	1
Flammability	2	2
Physical hazards	0	
Instability		0
Specific Hazard	--	--

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).