



**MATERIAL SAFETY DATA SHEET**  
**660-008**

Canutec 1-613-996-6666 (24 hours)

**1. CHEMICAL PRODUCT AND COMPANY INFORMATION**

Product identification : 660-008  
Product name : RAIN CLEAR  
Synonyms : Autoglass wax  
Chemical family : Mixture  
Supplier / Manufacturer : Auto-Chem Inc.  
33 de Lyon  
Repentigny, QC, Canada  
J5Z 4Z3  
Tel : 450-654-9292  
Fax : 450-654-0633  
www.autochem.com  
Contact : Jean Dagenais

**2. COMPOSITION / INFORMATION ON INGREDIENTS**

Ingredient	CAS	Percentage	Exposure limits
Ethanol	64-17-5	60 – 100	LD50 13700 mg/kg, rat, oral TLV TWA 1000 ppm, ACGIH PEL TWA 1000 ppm, OSHA REL TWA 1000 ppm NIOSH
Methanol	67-56-1	10 – 30	LD50 5628 mg/kg, rat, oral TLV TWA 200 ppm, ACGIH STEL TWA 250 ppm, ACGIH, dermal PEL TWA 200 ppm, OSHA REL TWA 200 ppm, NIOSH STEL TWA 250 ppm, NIOSH, dermal IDLH 6000 ppm, NIOSH
Sulfuric acid	7664-93-9	1 – 5	LD50 2140 mg/kg, rat, oral
Polysiloxane	69430-37-1	1 – 5	No data
Silane dichloromethyl	68611-44-9	1 – 5	LD50 >5000 mg/kg, rat, oral LC50 >0.477 mg/l/4hrs, rat

**3. HAZARDS IDENTIFICATION**

Routes of entry: Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects :

Eye contact : Vapours are moderately irritating to the eyes.  
Skin contact : Not a primary skin irritant after exposure of short duration.  
Inhalation : Vapours are moderately irritating to respiratory passages. In rare case, may sensitize heart muscle causing heart arrhythmia.  
Ingestion : Liquid when accidentally aspirated into lungs can cause a severe inflammation of the lungs. Product contains methanol which can cause blindness or other severe vision problems.

Potential chronic health effects :

Eye contact : None known.  
Skin contact : Dermatitis, may defat the skin, allergic reactions.  
Inhalation : Prolonged or repeated inhalation can cause coughing, shortness of breath, dizziness and intoxication, nausea and central nervous system depression.  
Ingestion : Product contains methanol which can cause blindness or other severe vision problems.

#### **4. FIRST AID MEASURES**

Eyes : Rinse immediately with water or saline solution 15 to 20 minutes, lifting upper and lower eyelids. Remove contact lenses. Get medical attention without delay.

Skin : In case of direct contact, rinse with running water 15 to 20 minutes. Wash thoroughly with soap and water. Remove contaminated clothing and wash with soap and water. If irritation persists, obtain medical attention.

Inhalation : Remove person to fresh air. In case of respiratory failure, give artificial respiration. In case of respiratory distress, obtain medical attention.

Ingestion : In case of ingestion, obtain medical attention immediately. Do not induce vomiting, guard against aspiration into the lungs. Never give anything by mouth to an unconscious or convulsing person. In case of respiratory or cardiac arrest, start cardio-pulmonary resuscitation and obtain medical attention.

Note to physician: This product contains methanol, a toxic substance which can cause blindness and other severe vision problems and death.

#### **5. FIRE FIGHTING MEASURES**

Flash point : 13 C (Ethanol)  
Auto-ignition temperature: 363 C (Ethanol)  
Flammability limits – air (%): LEL: 3.3 UEL: 19 (Ethanol)  
Extinguishing media : Carbon dioxide (CO<sub>2</sub>), alcohol foam, dry chemical powder or water fog, according to the nature of the fire. Dry chemical powder or water can be used to cool containers. Do not use water except as a fog.  
Protective equipment : Fire fighters should wear full protective clothing, including self contained breathing equipment.  
Hazardous combustion materials : Carbon oxides, nitrogen oxides, silicon dioxide, sulfur oxides.

#### **6. ACCIDENTAL RELEASE MEASURES**

Avoid contact with spilled or released material. Remove contaminated clothing. Shut off leaks if safe to do so. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or waterways using sand, earth or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location. Take precautionary measures against static discharge. Ensure electrical continuity by grounding all equipment.

Small spill : For less than one drum, transfer by mechanical means to a labelled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

Large spill : For more than one drum, transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with

appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

## **7. HANDLING AND STORAGE**

**Handling :** Flammable. Do not cut, drill, grind, weld or perform similar operations on or near containers. Fixed equipment as well as transfer containers and equipment should be grounded to prevent accumulation of static charge. Hot surfaces may be sufficient to ignite liquid in the absence of sparks or flames. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapours are gone. Do not pressurize drum containers to empty them. Avoid breathing vapours and prolonged or repeated contact with skin. Launder contaminated clothing prior to reuse. Use good personal hygiene. Air-dry contaminated clothing in a well ventilated area before laundering.

**Storage :** Store in a cool, dry, well ventilated area, away from heat and ignition sources. Use explosion proof ventilation to prevent vapour accumulation.

## **8. EXPOSURE CONTROL / PERSONAL PROTECTION**

**Engineering controls :** Mechanical ventilation is recommended for all indoor situations to control fugitive emissions. Electrical and mechanical equipment should be explosion proof. For personnel entry into confined spaces, a proper procedure must be followed including ventilation and testing of tank atmosphere.

### Personal protection equipment for routine handling :

**Eye :** Chemical safety goggles and /or full face shield to protect eyes and face, if product is handled such that it could be splashed into eyes.

**Skin :** In confined spaces or where the risk of skin exposure is much higher, impervious clothing should be worn.

**Gloves :** Impervious gloves, Viton gloves, polyvinyl alcohol gloves.

**Inhalation :** If exposure exceeds occupational exposure limits, use appropriate NIOSH-approved respirator. Use a NIOSH-approved chemical cartridge respirator with organic vapour cartridges or use a NIOSH-approved supplied-air respirator.

### Personal protection equipment for spills :

**Eye :** Chemical safety goggles and /or full face shield to protect eyes.

**Skin :** In confined spaces or where the risk of skin exposure is much higher, impervious clothing should be worn.

**Gloves :** Impervious gloves, Viton gloves, polyvinyl alcohol gloves.

**Inhalation :** Use a NIOSH-approved chemical cartridge respirator with organic vapour cartridges or use a NIOSH-approved supplied-air respirator.

**Note :** These precautions are for room temperature handling. Use at elevated temperatures of aerosol spray applications may require added protection.

## **9. PHYSICAL AND CHEMICAL PROPERTIES**

**Physical state :** Paste.

**Colour :** Blue.

**Odour :** Alcohol.

**pH @ 10 in water% :** 1.14

**Relative density (g/cm<sup>3</sup>) :** 0.843

**Boiling point :** Not determined.

**Freezing point :** Not determined.

Vapour pressure : Not determined.  
 Volatiles (weight) : Not determined.  
 Solubility (water) : Dispersible.  
 VOC (%) : Not determined.  
 Viscosity : Not determined.

## 10. STABILITY AND REACTIVITY

Chemical stability : Stable.  
 Hazardous polymerization : None known.  
 Conditions to avoid : Heat, sparks, open flames and other ignition sources.  
 Materials to avoid : Strong oxidants, strong acids and alkalis.  
 Dangerous decomposition products : Carbon oxides, nitrogen oxides, silicon dioxide, sulfur oxides.

## 11. TOXICOLOGICAL INFORMATION

Ingredient	CAS	Percentage	Exposure limits
Ethanol	64-17-5	60 – 100	LD50 13700 mg/kg, rat, oral TLV TWA 1000 ppm, ACGIH PEL TWA 1000 ppm, OSHA REL TWA 1000 ppm NIOSH
Methanol	67-56-1	10 – 30	LD50 5628 mg/kg, rat, oral TLV TWA 200 ppm, ACGIH STEL TWA 250 ppm, ACGIH, dermal PEL TWA 200 ppm, OSHA REL TWA 200 ppm, NIOSH STEL TWA 250 ppm, NIOSH, dermal IDLH 6000 ppm, NIOSH
Sulfuric acid	7664-93-9	1 – 5	LD50 2140 mg/kg, rat, oral
Polysiloxane	69430-37-1	1 – 5	No data
Silane dichloromethyl	68611-44-9	1 – 5	LD50 >5000 mg/kg, rat, oral LC50 >0.477 mg/l/4hrs, rat

### Potential acute health effects :

Eye contact : Vapours are moderately irritating to the eyes.  
 Skin contact : Not a primary skin irritant after exposure of short duration.  
 Inhalation : Vapours are moderately irritating to respiratory passages. In rare case, may sensitize heart muscle causing heart arrhythmia..  
 Ingestion : Liquid when accidentally aspirated into lungs can cause a severe inflammation of the lungs.

### Potential chronic health effects :

Carcinogenic effects: Professional exposure to sulphuric acid (7664-93-9) as a concentrated aerosol is a potential carcinogen to humans.  
 Mutagenic effects: None known.  
 Teratogenic effects: Ingestion of ethanol during pregnancy can adversely affect the development of the foetus.

## 12. ECOLOGICAL INFORMATION

Ingredient	CAS	Test	Species
Sulphuric acid	7664-93-9	LC50 10.5 ppm / 96 hrs LC50 100-300ppm / 48hrs	Leponis macrochirus Flounder
Silane dichloromethyl	68611-44-9	LC50 >10000 mg/l/96hrs EC50 >10000 mg/l/24hrs CI50 >10000 mg/l/72hrs	Brachydanio rerio Daphnia magna scenedesmus subspicatus

Do not allow product or runoff from fire control to enter storm or sanitary sewers, lakes, rivers, streams or public waterways. Block off drains and ditches. Spill areas must be cleaned and restored to original condition or to the satisfaction of authorities. May be harmful to aquatic life.

### 13. DISPOSAL CONSIDERATIONS

Waste disposal method : Dispose according to municipal, provincial and federal regulations.  
Contaminated packaging : According to municipal, provincial and federal regulations.

### 14. TRANSPORT INFORMATION

Regulatory Information	Shipping name	UN	Class	PG
TDG Classification	Flammable, toxic, corrosive liquid n.o.s. 3286 (Ethanol, methanol, sulphuric acid)		3 (6.1)(8)	II

### 15. REGULATORY INFORMATION

WHIMS :  
B2 Flammable liquid  
D1A Material causing immediate and serious toxic effects  
D2B Materials causing other toxic effects  
E Corrosive

DSL : All components of this product are either on the Domestic Substance List (DSL), the Non-Domestic Substance List (NDSL) or exempt.

TSCA : U.S. TSCA Inventory Status : All components of this product are either on the Toxic Substances Control Act Inventory List or exempt.

### 16. OTHER INFORMATION

Prepared by : Auto-Chem Inc.

Date : Sept. 2015

Notice to reader :

All information appearing herein is based upon data obtained from the manufacturer and/or recognized technical sources. While the information is believed to be accurate, Auto-Chem makes no representations as to its accuracy or sufficiency. Conditions of use are beyond Auto-Chem's control and therefore users are responsible to verify this data under their own operation conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling and disposal of the product, or from the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.