



## SAFETY DATA SHEET

Revision date 28-Oct-2015

Version 2

### Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name	11704 TRAFFIC YELLOW	6U
Product Code	400.0011704.077	
UN/ID no	UN1950	
Recommended Use	Aerosol, Paint	

#### Details of the supplier of the safety data sheet

See section 16 for more information

The Valspar Corporation  
PO Box 1461  
Minneapolis, MN 55440

Valspar Industries, Inc.  
1915 Second St. W.  
Cornwall, Ontario K6H 5R6

E-mail address [msds@valspar.com](mailto:msds@valspar.com)

Emergency telephone number 1-888-345-5732

### Section 2: HAZARDS IDENTIFICATION

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

#### HAZARD STATEMENTS

Flammable aerosol Contains gas under pressure; may explode if heated

Suspected of causing cancer May damage fertility or the unborn child May cause damage to organs through prolonged or repeated exposure May be fatal if swallowed and enters airways May cause drowsiness or dizziness Causes skin irritation

Causes serious eye irritation

#### WHMIS Hazard Class

B5 - Flammable aerosol

A Compressed gases

D2A - Very toxic materials

D2B - Toxic materials



Signal word

DANGER

Product Code 400.0011704.077

Page 1 / 11

WPNA - CANADA WHMIS SDS

## PREVENTION

Do not breathe dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area Wear protective gloves/protective clothing/eye protection/face protection Pressurized container: Do not pierce or burn, even after use Do not spray on an open flame or other ignition source Obtain special instructions before use Do not handle until all safety precautions have been read and understood

## RESPONSE

IF exposed or concerned: Get medical advice/attention

### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

### Skin

Rinse skin with water/shower If skin irritation occurs: Get medical advice/attention

### Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing

### Ingestion

Do NOT induce vomiting IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

## STORAGE

Protect from sunlight. Store in a well-ventilated place Store locked up Store in a well-ventilated place Do not expose to temperatures exceeding 122 °F (50 °C)

## DISPOSAL

Dispose of contents/containers in accordance with local regulations

## Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	weight-%
Limestone	1317-65-3	10 - 25
Solvent naphtha, petroleum, light aliphatic	64742-89-8	10 - 25
Propane	74-98-6	10 - 25
Isopropyl alcohol	67-63-0	5 - 10
Butane	106-97-8	5 - 10
Hexane	110-54-3	5 - 10
Toluene	108-88-3	1 - 3
Barium sulfate	7727-43-7	1 - 3
Acetone	67-64-1	1 - 3
Titanium dioxide	13463-67-7	0.3 - 1
Ethylbenzene	100-41-4	0.1 - 0.3
Methyl alcohol	67-56-1	0.1 - 0.3
1-Methyl-2-pyrrolidone	872-50-4	0.1 - 0.3

## Section 4: FIRST AID MEASURES

### First Aid Measures

#### General advice

IF exposed or concerned: Get medical advice/attention

#### Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

#### Skin Contact

Rinse skin with water/shower If skin irritation occurs: Get medical advice/attention

#### Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing

#### Ingestion

Do NOT induce vomiting IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Product Code 400.0011704.077

**Most important symptoms and effects, both acute and delayed**

**Symptoms** No information available.

**Indication of any immediate medical attention and special treatment needed**

**Note to physicians** Treat symptomatically.

**Section 5: FIRE FIGHTING MEASURES**

**Flammable properties** Flammable liquid.

**flash point** -4 °F / -20 °C

**Upper flammability limit:** 10.9

**Lower flammability limit:** 1.7

**Autoignition temperature** No information available

**Explosion data**

Sensitivity to Mechanical Impact	No information available.
Sensitivity to Static Discharge	No information available.

**Suitable extinguishing media**

Dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam.

**Not to be used for safety reasons:** Strong water jet

**Hazardous combustion products** Carbon monoxide. Carbon dioxide (CO<sub>2</sub>).

**Specific hazards arising from the chemical**

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes.

**Special protective equipment for fire-fighters**

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

**Section 6: ACCIDENTAL RELEASE MEASURES****Personal precautions**

Avoid breathing vapors or mists. Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak.

**Environmental precautions**

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages cannot be contained.

**Methods for containment**

Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up**

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

**Section 7: HANDLING AND STORAGE**

### Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Use only with adequate ventilation. Do not breathe dust/fume/gas/mist/vapors/spray. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

### General Hygiene Considerations

When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Avoid contact with skin, eyes or clothing.

### Storage Conditions

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorized personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed in a dry and well-ventilated place. Protect from sunlight. Store in a well-ventilated place.

## Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure Guidelines

#### Exposure Limits

If S\* appears in the OEL table, it indicates this chemical contains a skin notation.

Chemical Name	ACGIH TLV	Alberta	British Columbia	Ontario TWA	Quebec	OSHA PEL
Limestone 1317-65-3		TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 3 mg/m <sup>3</sup> STEL: 20 mg/m <sup>3</sup>		TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction
Propane 74-98-6	TWA: 1000 ppm	TWA: 1000 ppm	TWA: 1000 ppm	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup>	TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup>
Isopropyl alcohol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 492 mg/m <sup>3</sup> STEL: 400 ppm STEL: 984 mg/m <sup>3</sup>	TWA: 200 ppm STEL: 400 ppm	TWA: 200 ppm STEL: 400 ppm	TWA: 400 ppm TWA: 985 mg/m <sup>3</sup> STEL: 500 ppm STEL: 1230 mg/m <sup>3</sup>	TWA: 400 ppm TWA: 980 mg/m <sup>3</sup>
Butane 106-97-8	STEL: 1000 ppm	TWA: 1000 ppm	TWA: 600 ppm STEL: 750 ppm	TWA: 800 ppm	TWA: 800 ppm TWA: 1900 mg/m <sup>3</sup>	
Hexane 110-54-3	TWA: 50 ppm S*	TWA: 50 ppm TWA: 176 mg/m <sup>3</sup> S*	TWA: 20 ppm S*	TWA: 50 ppm S*	TWA: 50 ppm TWA: 176 mg/m <sup>3</sup> S*	TWA: 500 ppm TWA: 1800 mg/m <sup>3</sup>
Toluene 108-88-3	TWA: 20 ppm	TWA: 50 ppm TWA: 188 mg/m <sup>3</sup> S*	TWA: 20 ppm Adverse reproductive effect	TWA: 20 ppm	TWA: 50 ppm TWA: 188 mg/m <sup>3</sup> S*	TWA: 200 ppm Ceiling: 300 ppm
Barium sulfate 7727-43-7	TWA: 5 mg/m <sup>3</sup> inhalable fraction, particulate matter containing no asbestos and <1% crystalline silica	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 3 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction
Acetone 67-64-1	STEL: 750 ppm TWA: 500 ppm	TWA: 500 ppm TWA: 1200 mg/m <sup>3</sup> STEL: 750 ppm STEL: 1800 mg/m <sup>3</sup>	TWA: 250 ppm STEL: 500 ppm	TWA: 500 ppm STEL: 750 ppm	TWA: 500 ppm TWA: 1190 mg/m <sup>3</sup> STEL: 1000 ppm STEL: 2380 mg/m <sup>3</sup>	TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup>
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 3 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 434 mg/m <sup>3</sup> STEL: 125 ppm STEL: 543 mg/m <sup>3</sup>	TWA: 20 ppm	TWA: 20 ppm	TWA: 100 ppm TWA: 434 mg/m <sup>3</sup> STEL: 125 ppm STEL: 543 mg/m <sup>3</sup>	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>
Methyl alcohol 67-56-1	STEL: 250 ppm TWA: 200 ppm S*	TWA: 200 ppm TWA: 262 mg/m <sup>3</sup> STEL: 250 ppm STEL: 328 mg/m <sup>3</sup> S*	TWA: 200 ppm STEL: 250 ppm S*	TWA: 200 ppm STEL: 250 ppm S*	TWA: 200 ppm TWA: 262 mg/m <sup>3</sup> STEL: 250 ppm STEL: 328 mg/m <sup>3</sup> S*	TWA: 200 ppm TWA: 260 mg/m <sup>3</sup>
1-Methyl-2-pyrrolidone 872-50-4				TWA: 400 mg/m <sup>3</sup>		

### Engineering Controls

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

### Personal Protective Equipment

#### Eye/face protection

Wear safety glasses with side shields (or goggles).

#### Hand Protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

#### Skin and body protection

Wear anti-static clothing made of natural fiber or of high temperature resistant synthetic fiber. Wear suitable protective clothing.

#### Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators

#### Thermal Protection

No information available

### Environmental exposure controls

Do not allow into any sewer, on the ground or into any body of water. Local authorities should be advised if significant spillages cannot be contained.

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Physical state	Aerosol
Appearance	No information available
Odor	Aromatic
Color	yellow
Odor Threshold	No information available
pH value	No information available
Melting point/freezing point	No information available
Boiling point / boiling range	No information available °C / °F
flash point	-20 °C / -4 °F
evaporation rate	No information available
Flammability (solid, gas)	No information available
Flammability Limit in Air	
Upper flammability limit:	10.9
Lower flammability limit:	1.7
Vapor Pressure	No information available
vapor density	No information available
Density (lbs per US gallon)	8
specific gravity	0.96
Solubility(ies)	Not Determined
Partition coefficient	No information available
Autoignition temperature	No information available
Decomposition temperature	No information available
Kinematic viscosity	No information available
Dynamic viscosity	No information available

### Other information

## Section 10: STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
Incompatible materials	Strong oxidizing agents. Acids.

**Conditions to avoid** Heat, flames and sparks.

**Hazardous Decomposition Products** Carbon monoxide. Carbon dioxide (CO<sub>2</sub>).

**Possibility of Hazardous Reactions** None under normal processing.

**Hazardous polymerization** None under normal processing.

## Section 11: TOXICOLOGICAL INFORMATION

### Information on toxicological effects

### Information on likely routes of exposure

#### **Eye contact**

Causes serious eye irritation

#### **Skin Contact**

Causes skin irritation

#### **Ingestion**

May be fatal if swallowed and enters airways

#### **Inhalation**

May cause drowsiness or dizziness

### Numerical measures of toxicity - Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Limestone	-	-	-
Solvent naphtha, petroleum, light aliphatic	-	= 3000 mg/kg ( Rabbit )	-
Propane	-	-	= 658 mg/L ( Rat ) 4 h
Isopropyl alcohol	= 1870 mg/kg ( Rat )	= 4059 mg/kg ( Rabbit )	= 72600 mg/m <sup>3</sup> ( Rat ) 4 h
Butane	-	-	= 658 g/m <sup>3</sup> ( Rat ) 4 h
Hexane	-	= 3000 mg/kg ( Rabbit )	= 48000 ppm ( Rat ) 4 h
Toluene	= 2600 mg/kg ( Rat )	= 12000 mg/kg ( Rabbit )	= 12.5 mg/L ( Rat ) 4 h
Barium sulfate	-	-	-
Acetone	-	-	= 50100 mg/m <sup>3</sup> ( Rat ) 8 h
Titanium dioxide	> 10000 mg/kg ( Rat )	-	-
Ethylbenzene	= 3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.2 mg/L ( Rat ) 4 h
Methyl alcohol	= 6200 mg/kg ( Rat )	-	= 22500 ppm ( Rat ) 8 h
1-Methyl-2-pyrrolidone	= 3598 mg/kg ( Rat )	= 8 g/kg ( Rabbit )	= 3.1 mg/L ( Rat ) 4 h

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

<b>Skin corrosion/irritation</b>	Causes skin irritation
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation
<b>Skin sensitization</b>	Not applicable
<b>Respiratory sensitization</b>	Not applicable
<b>Germ cell mutagenicity</b>	Not applicable
<b>Carcinogenicity</b>	Suspected of causing cancer
<b>Reproductive Toxicity</b>	May damage fertility or the unborn child
<b>Specific target organ toxicity (single exposure)</b>	May cause drowsiness or dizziness
<b>Specific target organ toxicity (repeated exposure)</b>	May cause damage to organs through prolonged or repeated exposure
<b>Aspiration hazard</b>	Not applicable

### Carcinogenicity

According to IARC, Volume 93, no significant exposure to primary particles of titanium dioxide is thought to occur from use in paints since the pigment is bound to other materials.

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide		Group 2B		X
Ethylbenzene	A3	Group 2B		X

**Product Code 400.0011704.077**

Page 6 / 11

WPNA - CANADA WHMIS SDS

**ACGIH (American Conference of Governmental Industrial Hygienists)**

A3 - Animal Carcinogen

**IARC (International Agency for Research on Cancer)**

Group 2B - Possibly Carcinogenic to Humans

**OSHA (Occupational Safety and Health Administration of the US Department of Labor)**

X - Present

**Section 12: ECOLOGICAL INFORMATION****Ecotoxicity**

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Marine pollutant

This material meets the definition of a marine pollutant

Environmental precautions

Prevent product from entering drains.

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Limestone	-	-	-
Solvent naphtha, petroleum, light aliphatic	= 4700 mg/L <i>Pseudokirchneriella subcapitata</i> 72 h EC50	-	-
Propane	-	-	-
Isopropyl alcohol	> 1000 mg/L <i>Desmodesmus subspicatus</i> 96 h EC50 > 1000 mg/L <i>Desmodesmus subspicatus</i> 72 h EC50	> 1400000 µg/L <i>Lepomis macrochirus</i> 96h LC50 = 9640 mg/L <i>Pimephales promelas</i> 96h LC50 = 11130 mg/L <i>Pimephales promelas</i> 96h LC50	= 13299 mg/L <i>Daphnia magna</i> 48h EC50
Butane	-	-	-
Hexane	-	2.1 - 2.98 mg/L <i>Pimephales promelas</i> 96h LC50	-
Toluene	= 12.5 mg/L <i>Pseudokirchneriella subcapitata</i> 72 h EC50 > 433 mg/L <i>Pseudokirchneriella subcapitata</i> 96 h EC50	15.22 - 19.05 mg/L <i>Pimephales promelas</i> 96h LC50 50.87 - 70.34 mg/L <i>Poecilia reticulata</i> 96h LC50 = 28.2 mg/L <i>Poecilia reticulata</i> 96h LC50 = 54 mg/L <i>Oryzias latipes</i> 96h LC50 11.0 - 15.0 mg/L <i>Lepomis macrochirus</i> 96h LC50 = 5.8 mg/L <i>Oncorhynchus mykiss</i> 96h LC50 14.1 - 17.16 mg/L <i>Oncorhynchus mykiss</i> 96h LC50 5.89 - 7.81 mg/L <i>Oncorhynchus mykiss</i> 96h LC50 = 12.6 mg/L <i>Pimephales promelas</i> 96h LC50	5.46 - 9.83 mg/L <i>Daphnia magna</i> 48h EC50 = 11.5 mg/L <i>Daphnia magna</i> 48h EC50
Barium sulfate	-	-	-
Acetone	-	6210 - 8120 mg/L <i>Pimephales promelas</i> 96h LC50 = 8300 mg/L <i>Lepomis macrochirus</i> 96h LC50 4.74 - 6.33 mL/L <i>Oncorhynchus mykiss</i> 96h LC50	12600 - 12700 mg/L <i>Daphnia magna</i> 48h EC50 10294 - 17704 mg/L <i>Daphnia magna</i> 48h EC50
Titanium dioxide	-	-	-

Ethylbenzene	1.7 - 7.6 mg/L Pseudokirchneriella subcapitata 96 h EC50 > 438 mg/L Pseudokirchneriella subcapitata 96 h EC50 2.6 - 11.3 mg/L Pseudokirchneriella subcapitata 72 h EC50 = 4.6 mg/L Pseudokirchneriella subcapitata 72 h EC50	9.1 - 15.6 mg/L Pimephales promelas 96h LC50 = 9.6 mg/L Poecilia reticulata 96h LC50 = 32 mg/L Lepomis macrochirus 96h LC50 7.55 - 11 mg/L Pimephales promelas 96h LC50 = 4.2 mg/L Oncorhynchus mykiss 96h LC50 11.0 - 18.0 mg/L Oncorhynchus mykiss 96h LC50	1.8 - 2.4 mg/L Daphnia magna 48h EC50
Methyl alcohol	-	13500 - 17600 mg/L Lepomis macrochirus 96h LC50 18 - 20 mL/L Oncorhynchus mykiss 96h LC50 19500 - 20700 mg/L Oncorhynchus mykiss 96h LC50 > 100 mg/L Pimephales promelas 96h LC50 = 28200 mg/L Pimephales promelas 96h LC50	-
1-Methyl-2-pyrrolidone	> 500 mg/L Desmodesmus subspicatus 72 h EC50	= 1072 mg/L Pimephales promelas 96h LC50 = 832 mg/L Lepomis macrochirus 96h LC50 = 1400 mg/L Poecilia reticulata 96h LC50	= 4897 mg/L Daphnia magna 48h EC50

**Persistence and degradability** No information available.

**Bioaccumulation** No information available.

**Mobility** No information available.

Chemical Name	Partition Coefficient (n-octanol/water)
Limestone	-
Solvent naphtha, petroleum, light aliphatic	-
Propane	2.3
Isopropyl alcohol	0.05
Butane	2.89
Hexane	-
Toluene	2.65
Barium sulfate	-
Acetone	-0.24
Titanium dioxide	-
Ethylbenzene	3.118
Methyl alcohol	-0.77
1-Methyl-2-pyrrolidone	-0.46

### Section 13: DISPOSAL CONSIDERATIONS

**Waste from residues/unused products** Disposal should be in accordance with applicable regional, national and local laws and regulations

**Contaminated packaging** Improper disposal or reuse of this container may be dangerous and illegal.

### Section 14: TRANSPORT INFORMATION

<b>UN/ID no</b>	<b>TDG</b> UN1950	<b>IMDG</b> UN1950	<b>IATA</b> UN1950
<b>Proper shipping name</b>	Aerosols	Aerosols	Aerosols
<b>Hazard Class</b>	2.1	2.1	2.1
<b>Packing Group</b>			II

**Product Code 400.0011704.077**

Page 8 / 11

WPNA - CANADA WHMIS SDS



Environmental hazard Yes

**Marine pollutant** This material meets the definition of a marine pollutant

**Marine pollutant** Solvent naphtha, petroleum, light aliphatic , Hexane

**Special Provisions**

**EmS-No**

F-D, S-U

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No information available

## Section 15: REGULATORY INFORMATION

### International Inventories

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

All components are listed or exempt from listing

**DSL** - Canadian Domestic Substances List

All components are listed or exempt from listing

**This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR**

### **WHMIS Hazard Class**

B5 - Flammable aerosol

A - Compressed gases

D2A - Very toxic materials

D2B - Toxic materials



Chemical Name	Canada - 2013 NPRI (National Pollutant Release Inventory)
Solvent naphtha, petroleum, light aliphatic	Part 5, Other Groups and Mixtures
Propane	Part 5, Individual Substances
Isopropyl alcohol	Part 1, Group A Substance Part 5, Individual Substances
Butane	Part 5, Isomer Groups Part 4 Substance
Hexane	Part 1, Group A Substance Part 5, Individual Substances
Toluene	Part 1, Group A Substance Part 5, Individual Substances
Acetone	Part 4 Substance
Ethylbenzene	Part 1, Group A Substance
Methyl alcohol	Part 1, Group A Substance Part 5, Individual Substances
1-Methyl-2-pyrrolidone	Part 1, Group A Substance

### GHS - Classification

Carcinogenicity	Category 2
Reproductive toxicity	Category 1B
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable aerosols	Category 2
Gases under pressure	Liquefied gas

### Label elements

**Product Code 400.0011704.077**

Page 9 / 11

WPNA - CANADA WHMIS SDS



Signal word

**DANGER**

#### HAZARD STATEMENTS

Flammable aerosol  
Contains gas under pressure; may explode if heated  
Suspected of causing cancer  
May damage fertility or the unborn child  
May cause drowsiness or dizziness  
May cause damage to organs through prolonged or repeated exposure  
May be fatal if swallowed and enters airways

#### PREVENTION

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

#### RESPONSE

IF exposed or concerned: Get medical advice/attention.

##### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

##### Skin

Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention.

##### Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

##### Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

#### STORAGE

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 122 °F (50 °C).

#### DISPOSAL

Dispose of contents/containers in accordance with local regulations.

#### HAZARDS NOT OTHERWISE CLASSIFIED (HNOC)

Propellant is classified as a simple asphyxiant if released in large quantities: May displace oxygen and cause rapid suffocation.

#### OTHER HAZARDS

Causes mild skin irritation. Toxic to aquatic life with long lasting effects.

**UNKNOWN ACUTE TOXICITY** 0% of the mixture consists of ingredient(s) of unknown toxicity.

### Section 16: OTHER INFORMATION

#### HMIS

Health hazards 3\*

\* = Chronic Health Hazard

Flammability 4

Physical hazards 0

Personal Protection X

Supplier Address

Product Code 400.0011704.077

Page 10 / 11

WPNA - CANADA WHMIS SDS

Valspar Consumer  
Headquarters  
8725 W. Higgins Rd. Suite  
1000  
Chicago, IL 60631  
773-628-5500

The Valspar Corporation  
4999 36th St.  
Grand Rapids, MI 49512  
800-253-3957

Valspar Plasti-Kote  
1636 Shawsone Dr.  
Mississauga, Ontario L4W 1N7  
905-671-8333

**Prepared By**

Product Stewardship

**Revision date**

28-Oct-2015

**Revision Note**

No information available

**Disclaimer**

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. **UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.**

**End of Safety Data Sheet**