



SAFETY DATA SHEET

Revision date 19-Jan-2016

Version 1

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name SECOND SKIN SMOKE 17204
Product Code 465.0017204.076
UN/ID no UN1950
Recommended Use Aerosol, Paint

Details of the supplier of the safety data sheet

See section 16 for more information

The Valspar Corporation
PO Box 1461
Minneapolis, MN 55440

Valspar Industries, Inc.
1915 Second St. W.
Cornwall, Ontario K6H 5R6

E-mail address msds@valspar.com

Emergency telephone number 1-888-345-5732

Section 2: HAZARDS IDENTIFICATION

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

HAZARD STATEMENTS

Flammable aerosol Contains gas under pressure; may explode if heated
May cause drowsiness or dizziness Causes skin irritation Suspected of causing cancer Causes damage to organs through prolonged or repeated exposure May cause an allergic skin reaction May be fatal if swallowed and enters airways Causes serious eye irritation

WHMIS Hazard Class

B5 - Flammable aerosol
A Compressed gases
D2A - Very toxic materials
D2B - Toxic materials



Signal word

DANGER

Product Code 465.0017204.076

Page 1 / 10

WPNA - CANADA WHMIS SDS

PREVENTION

Obtain special instructions before use Do not breathe dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area Wear protective gloves/protective clothing/eye protection/face protection Wash face, hands and any exposed skin thoroughly after handling Contaminated work clothing should not be allowed out of the workplace Do not handle until all safety precautions have been read and understood Do not spray on an open flame or other ignition source Do not eat, drink or smoke when using this product Pressurized container: Do not pierce or burn, even after use

RESPONSE

IF exposed or concerned: Get medical advice/attention

Eyes

If eye irritation persists: Get medical advice/attention IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Skin

If skin irritation or rash occurs: Get medical advice/attention Take off contaminated clothing and wash before reuse IF ON SKIN: Wash with plenty of soap and water

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting

STORAGE

Store locked up Store in a well-ventilated place Protect from sunlight. Store in a well-ventilated place Do not expose to temperatures exceeding 122 °F (50 °C)

DISPOSAL

Dispose of contents/containers in accordance with local regulations

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | CAS No | weight-% |
|---|------------|-----------|
| Solvent naphtha, petroleum, light aliphatic | 64742-89-8 | 25 - 50 |
| Propane | 74-98-6 | 10 - 25 |
| n-Heptane | 142-82-5 | 10 - 25 |
| Butane | 106-97-8 | 10 - 25 |
| Xylenes | 1330-20-7 | 5 - 10 |
| Methyl n-amyl ketone | 110-43-0 | 1 - 3 |
| Ethylbenzene | 100-41-4 | 1 - 3 |
| Methyl ethyl ketone | 78-93-3 | 1 - 3 |
| Stoddard solvent | 8052-41-3 | 1 - 3 |
| Titanium dioxide | 13463-67-7 | 0.3 - 1 |
| Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate | 41556-26-7 | 0.1 - 0.3 |

Section 4: FIRST AID MEASURES

First Aid Measures

General advice

IF exposed or concerned: Get medical advice/attention

Eye contact

If eye irritation persists: Get medical advice/attention IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Skin Contact

If skin irritation or rash occurs: Get medical advice/attention Take off contaminated clothing and wash before reuse IF ON SKIN: Wash with plenty of soap and water

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing

Ingestion

Product Code 465.0017204.076

Page 2 / 10

WPNA - CANADA WHMIS SDS

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

Section 5: FIRE FIGHTING MEASURES

Flammable properties Flammable liquid.

flash point -24 °F / -31 °C

Upper flammability limit: No information available

Lower flammability limit: No information available

Autoignition temperature No information available

Explosion data

Sensitivity to Mechanical Impact No information available.

Sensitivity to Static Discharge No information available.

Suitable extinguishing media

Dry chemical, CO₂, water spray or alcohol-resistant foam.

Not to be used for safety reasons: Strong water jet

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO₂).

Specific hazards arising from the chemical

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes. May cause sensitization by skin contact.

Special protective equipment for fire-fighters

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

Section 6: ACCIDENTAL RELEASE MEASURES

Personal precautions

Avoid breathing vapors or mists. Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak.

Environmental precautions

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages cannot be contained.

Methods for containment

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. Take up mechanically, placing in appropriate containers for disposal.

Section 7: HANDLING AND STORAGE

Product Code 465.0017204.076

Page 3 / 10

WPNA - CANADA WHMIS SDS

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Use only with adequate ventilation. Do not breathe dust/fume/gas/mist/vapors/spray. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

General Hygiene Considerations

When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Avoid contact with skin, eyes or clothing.

Storage Conditions

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorized personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed in a dry and well-ventilated place. Protect from sunlight. Store in a well-ventilated place.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Exposure Limits

If S* appears in the OEL table, it indicates this chemical contains a skin notation.

| Chemical Name | ACGIH TLV | Alberta | British Columbia | Ontario TWA | Quebec | OSHA PEL |
|----------------------------------|-------------------------------|--|---|---|--|--|
| Propane 74-98-6 | TWA: 1000 ppm | TWA: 1000 ppm | TWA: 1000 ppm | TWA: 1000 ppm | TWA: 1000 ppm TWA: 1800 mg/m ³ | TWA: 1000 ppm TWA: 1800 mg/m ³ |
| n-Heptane 142-82-5 | STEL: 500 ppm TWA: 400 ppm | TWA: 400 ppm TWA: 1640 mg/m ³ STEL: 500 ppm STEL: 2050 mg/m ³ | TWA: 400 ppm STEL: 500 ppm | TWA: 400 ppm STEL: 500 ppm | TWA: 400 ppm TWA: 1640 mg/m ³ STEL: 500 ppm STEL: 2050 mg/m ³ | TWA: 500 ppm TWA: 2000 mg/m ³ |
| Butane 106-97-8 | STEL: 1000 ppm | TWA: 1000 ppm | TWA: 600 ppm STEL: 750 ppm | TWA: 800 ppm | TWA: 800 ppm TWA: 1900 mg/m ³ | |
| Xylenes 1330-20-7 | STEL: 150 ppm TWA: 100 ppm | TWA: 100 ppm TWA: 434 mg/m ³ STEL: 150 ppm STEL: 651 mg/m ³ | TWA: 100 ppm STEL: 150 ppm | TWA: 100 ppm STEL: 150 ppm | TWA: 100 ppm TWA: 434 mg/m ³ STEL: 150 ppm STEL: 651 mg/m ³ | TWA: 100 ppm TWA: 435 mg/m ³ |
| Methyl n-amyl ketone 110-43-0 | TWA: 50 ppm | TWA: 50 ppm TWA: 233 mg/m ³ | TWA: 50 ppm | TWA: 25 ppm TWA: 115 mg/m ³ | TWA: 50 ppm TWA: 233 mg/m ³ | TWA: 100 ppm TWA: 465 mg/m ³ |
| Ethylbenzene 100-41-4 | TWA: 20 ppm | TWA: 100 ppm TWA: 434 mg/m ³ STEL: 125 ppm STEL: 543 mg/m ³ | TWA: 20 ppm | TWA: 20 ppm | TWA: 100 ppm TWA: 434 mg/m ³ STEL: 125 ppm STEL: 543 mg/m ³ | TWA: 100 ppm TWA: 435 mg/m ³ |
| Methyl ethyl ketone 78-93-3 | STEL: 300 ppm TWA: 200 ppm | TWA: 200 ppm TWA: 590 mg/m ³ STEL: 300 ppm STEL: 885 mg/m ³ | TWA: 50 ppm STEL: 100 ppm | TWA: 200 ppm STEL: 300 ppm | TWA: 50 ppm TWA: 150 mg/m ³ STEL: 100 ppm STEL: 300 mg/m ³ | TWA: 200 ppm TWA: 590 mg/m ³ |
| Stoddard solvent 8052-41-3 | TWA: 100 ppm | TWA: 100 ppm TWA: 572 mg/m ³ | TWA: 290 mg/m ³ STEL: 580 mg/m ³ | TWA: 525 mg/m ³ | TWA: 100 ppm TWA: 525 mg/m ³ | TWA: 500 ppm TWA: 2900 mg/m ³ |
| Titanium dioxide 13463-67-7 | TWA: 10 mg/m ³ | TWA: 10 mg/m ³ | TWA: 10 mg/m ³ TWA: 3 mg/m ³ | TWA: 10 mg/m ³ | TWA: 10 mg/m ³ | TWA: 15 mg/m ³ total dust |

Engineering Controls

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

Personal Protective Equipment

Eye/face protection

Tight sealing safety goggles.

Hand Protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

Skin and body protection

Wear anti-static clothing made of natural fiber or of high temperature resistant synthetic fiber. Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Wear suitable protective clothing.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators

Thermal Protection

No information available

Environmental exposure controls

Do not allow into any sewer, on the ground or into any body of water. Local authorities should be advised if significant spillages cannot be contained.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES**Information on basic physical and chemical properties**

| | |
|-------------------------------|----------------------------------|
| Physical state | Aerosol |
| Appearance | No information available |
| Odor | No information available |
| Color | No information available |
| Odor Threshold | No information available |
| pH value | No information available |
| Melting point/freezing point | No information available |
| Boiling point / boiling range | No information available °C / °F |
| flash point | -31 °C / -24 °F |
| evaporation rate | No information available |
| Flammability (solid, gas) | No information available |
| Flammability Limit in Air | |
| Upper flammability limit: | No information available |
| Lower flammability limit: | No information available |
| Vapor Pressure | No information available |
| vapor density | No information available |
| Density (lbs per US gallon) | 5.56 |
| specific gravity | 0.667 |
| Solubility(ies) | No information available |
| Partition coefficient | No information available |
| Autoignition temperature | No information available |
| Decomposition temperature | No information available |
| Kinematic viscosity | No information available |
| Dynamic viscosity | No information available |

Other information**Section 10: STABILITY AND REACTIVITY**

| | |
|------------------------------------|--|
| Stability | Stable under normal conditions. |
| Incompatible materials | Strong oxidizing agents. |
| Conditions to avoid | Heat, flames and sparks. |
| Hazardous Decomposition Products | Carbon monoxide. Carbon dioxide (CO2). |
| Possibility of Hazardous Reactions | None under normal processing. |
| Hazardous polymerization | None under normal processing. |

Section 11: TOXICOLOGICAL INFORMATION**Information on toxicological effects**

Product Code 465.0017204.076

Page 5 / 10

WPNA - CANADA WHMIS SDS

Information on likely routes of exposure

Eye contact

Causes serious eye irritation

Skin Contact

Causes skin irritation

May cause an allergic skin reaction

Ingestion

May be fatal if swallowed and enters airways

Inhalation

May cause drowsiness or dizziness

Numerical measures of toxicity - Component Information

| Chemical Name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|---|-----------------------|--------------------------|------------------------------------|
| Solvent naphtha, petroleum, light aliphatic | - | = 3000 mg/kg (Rabbit) | - |
| Propane | - | - | = 658 mg/L (Rat) 4 h |
| n-Heptane | - | = 3000 mg/kg (Rabbit) | = 103 g/m ³ (Rat) 4 h |
| Butane | - | - | = 658 g/m ³ (Rat) 4 h |
| Xylenes | = 3500 mg/kg (Rat) | > 4350 mg/kg (Rabbit) | = 29.08 mg/L (Rat) 4 h |
| Methyl n-amyl ketone | = 1600 mg/kg (Rat) | = 12.6 mL/kg (Rabbit) | > 2000 ppm (Rat) 4 h |
| Ethylbenzene | = 3500 mg/kg (Rat) | = 15400 mg/kg (Rabbit) | = 17.2 mg/L (Rat) 4 h |
| Methyl ethyl ketone | = 2483 mg/kg (Rat) | = 5000 mg/kg (Rabbit) | = 11700 ppm (Rat) 4 h |
| Stoddard solvent | - | - | - |
| Titanium dioxide | > 10000 mg/kg (Rat) | - | - |
| Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate | = 2615 mg/kg (Rat) | - | - |

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

Causes skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation

Skin sensitization

May cause an allergic skin reaction

Respiratory sensitization

Not applicable

Germ cell mutagenicity

Not applicable

Carcinogenicity

Suspected of causing cancer

Reproductive Toxicity

Not applicable

Specific target organ toxicity (single exposure)

May cause drowsiness or dizziness

Specific target organ toxicity (repeated exposure)

Causes damage to organs through prolonged or repeated exposure

Aspiration hazard

Not applicable

Carcinogenicity

According to IARC, Volume 93, no significant exposure to primary particles of titanium dioxide is thought to occur from use in paints since the pigment is bound to other materials. According to IARC, Volume 93, no significant exposure to primary particles of carbon black is thought to occur from use in paints since the pigment is bound to other materials.

| Chemical Name | ACGIH | IARC | NTP | OSHA |
|------------------|-------|----------|-----|------|
| Ethylbenzene | A3 | Group 2B | | X |
| Titanium dioxide | | Group 2B | | X |

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity

Product Code 465.0017204.076

Page 6 / 10

WPNA - CANADA WHMIS SDS

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Marine pollutant

This material meets the definition of a marine pollutant

Environmental precautions

Prevent product from entering drains.

| Chemical Name | Algae/aquatic plants | Fish | Crustacea |
|---|---|--|---|
| Solvent naphtha, petroleum, light aliphatic | = 4700 mg/L <i>Pseudokirchneriella subcapitata</i> 72 h EC50 | - | - |
| Propane | - | - | - |
| n-Heptane | - | = 375.0 mg/L Cichlid fish 96h LC50 | - |
| Butane | - | - | - |
| Xylenes | - | 7.711 - 9.591 mg/L <i>Lepomis macrochirus</i> 96h LC50 23.53 - 29.97 mg/L <i>Pimephales promelas</i> 96h LC50 = 780 mg/L <i>Cyprinus carpio</i> 96h LC50 > 780 mg/L <i>Cyprinus carpio</i> 96h LC50 30.26 - 40.75 mg/L <i>Poecilia reticulata</i> 96h LC50 = 19 mg/L <i>Lepomis macrochirus</i> 96h LC50 = 13.4 mg/L <i>Pimephales promelas</i> 96h LC50 2.661 - 4.093 mg/L <i>Oncorhynchus mykiss</i> 96h LC50 13.5 - 17.3 mg/L <i>Oncorhynchus mykiss</i> 96h LC50 13.1 - 16.5 mg/L <i>Lepomis macrochirus</i> 96h LC50 | = 0.6 mg/L <i>Gammarus lacustris</i> 48h LC50 = 3.82 mg/L water flea 48h EC50 |
| Methyl n-amyl ketone | - | 126 - 137 mg/L <i>Pimephales promelas</i> 96h LC50 | - |
| Ethylbenzene | 1.7 - 7.6 mg/L <i>Pseudokirchneriella subcapitata</i> 96 h EC50 > 438 mg/L <i>Pseudokirchneriella subcapitata</i> 96 h EC50 2.6 - 11.3 mg/L <i>Pseudokirchneriella subcapitata</i> 72 h EC50 = 4.6 mg/L <i>Pseudokirchneriella subcapitata</i> 72 h EC50 | 9.1 - 15.6 mg/L <i>Pimephales promelas</i> 96h LC50 = 9.6 mg/L <i>Poecilia reticulata</i> 96h LC50 = 32 mg/L <i>Lepomis macrochirus</i> 96h LC50 7.55 - 11 mg/L <i>Pimephales promelas</i> 96h LC50 = 4.2 mg/L <i>Oncorhynchus mykiss</i> 96h LC50 11.0 - 18.0 mg/L <i>Oncorhynchus mykiss</i> 96h LC50 | 1.8 - 2.4 mg/L <i>Daphnia magna</i> 48h EC50 |
| Methyl ethyl ketone | - | 3130 - 3320 mg/L <i>Pimephales promelas</i> 96h LC50 | > 520 mg/L <i>Daphnia magna</i> 48h EC50 4025 - 6440 mg/L <i>Daphnia magna</i> 48h EC50 = 5091 mg/L <i>Daphnia magna</i> 48h EC50 |
| Stoddard solvent | - | - | - |
| Titanium dioxide | - | - | - |
| Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate | - | = 0.97 mg/L <i>Lepomis macrochirus</i> 96h LC50 | - |

Persistence and degradability No information available.

Bioaccumulation No information available.

Mobility No information available.

Product Code 465.0017204.076

Page 7 / 10

WPNA - CANADA WHMIS SDS

| Chemical Name | Partition Coefficient (n-octanol/water) |
|---|---|
| Solvent naphtha, petroleum, light aliphatic | - |
| Propane | 2.3 |
| n-Heptane | 4.66 |
| Butane | 2.89 |
| Xylenes | 3.15 |
| Methyl n-amyl ketone | 1.98 |
| Ethylbenzene | 3.118 |
| Methyl ethyl ketone | 0.29 |
| Stoddard solvent | - |
| Titanium dioxide | - |
| Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate | 0.37 |

Section 13: DISPOSAL CONSIDERATIONS

Waste from residues/unused products Disposal should be in accordance with applicable regional, national and local laws and regulations

Contaminated packaging Improper disposal or reuse of this container may be dangerous and illegal.

Section 14: TRANSPORT INFORMATION

| UN/ID no | <u>TDG</u> | <u>IMDG</u> | <u>IATA</u> |
|--|--|-------------------------------|-------------------------------|
| Proper shipping name | UN1950 Aerosols, flammable | UN1950 Aerosols, flammable | UN1950 Aerosols, flammable |
| Hazard Class | 2.1 | 2.1 | 2.1 |
| Packing Group | | | |
| Environmental hazard | Yes | | |
| Marine pollutant | This material meets the definition of a marine pollutant | | |
| Marine pollutant | Solvent naphtha, petroleum, light aliphatic , n-Heptane | | |
| Special Provisions | | EmS-No F-D, S-U | |
| Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code | | No information available | |

Section 15: REGULATORY INFORMATION

International Inventories

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

All components are listed or exempt from listing

DSL - Canadian Domestic Substances List

All components are listed or exempt from listing

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

WHMIS Hazard Class

B5 - Flammable aerosol

A Compressed gases

D2A - Very toxic materials

D2B - Toxic materials



| Chemical Name | Canada - 2013 NPRI (National Pollutant Release Inventory) |
|---|---|
| Solvent naphtha, petroleum, light aliphatic | Part 5, Other Groups and Mixtures |
| Propane | Part 5, Individual Substances |
| n-Heptane | Part 4 Substance Part 5, Isomer Groups |
| Butane | Part 5, Isomer Groups Part 4 Substance |

Product Code 465.0017204.076

| | |
|----------------------|--|
| Xylenes | Part 1, Group A Substance Part 5, Isomer Groups |
| Methyl n-amyl ketone | Part 4 Substance |
| Ethylbenzene | Part 1, Group A Substance |
| Methyl ethyl ketone | Part 1, Group A Substance Part 5, Individual Substances |
| Stoddard solvent | Part 5, Other Groups and Mixtures |

GHS - Classification

| | |
|--|---------------|
| Skin corrosion/irritation | Category 2 |
| Skin sensitization | Category 1 |
| Carcinogenicity | Category 2 |
| Specific target organ toxicity (single exposure) | Category 3 |
| Specific target organ toxicity (repeated exposure) | Category 1 |
| Aspiration toxicity | Category 1 |
| Flammable aerosols | Category 2 |
| Gases under pressure | Liquefied gas |

Label elements



Signal word

DANGER

HAZARD STATEMENTS

Flammable aerosol
 Contains gas under pressure; may explode if heated
 Causes skin irritation
 May cause an allergic skin reaction
 Suspected of causing cancer
 May cause drowsiness or dizziness
 Causes damage to organs through prolonged or repeated exposure
 May be fatal if swallowed and enters airways

PREVENTION

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Wash face, hands and any exposed skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

RESPONSE

IF exposed or concerned: Get medical advice/attention.

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin

IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash before reuse. If skin irritation or rash occurs: Get medical advice/attention.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

Product Code 465.0017204.076

Page 9 / 10

WPNA - CANADA WHMIS SDS

STORAGE

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 122 °F (50 °C).

DISPOSAL

Dispose of contents/containers in accordance with local regulations.

HAZARDS NOT OTHERWISE CLASSIFIED (HNOC)

Propellant is classified as a simple asphyxiant if released in large quantities: May displace oxygen and cause rapid suffocation.

OTHER HAZARDS

Toxic to aquatic life with long lasting effects. Toxic to aquatic life.

UNKNOWN ACUTE TOXICITY 0% of the mixture consists of ingredient(s) of unknown toxicity.

Section 16: OTHER INFORMATION

HMIS

Health hazards 3*

* = Chronic Health Hazard

Flammability 4

Physical hazards 0

Personal Protection X

Supplier Address

| | | |
|--|--|--|
| Valspar Consumer Headquarters 8725 W. Higgins Rd. Suite 1000 Chicago, IL 60631 773-628-5500 | The Valspar Corporation 4999 36th St. Grand Rapids, MI 49512 800-253-3957 | Valspar Plasti-Kote 1636 Shawsone Dr. Mississauga, Ontario L4W 1N7 905-671-8333 |
|--|--|--|

Prepared By Product Stewardship

Revision date 19-Jan-2016

Revision Note No information available

Disclaimer

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

End of Safety Data Sheet