



## SAFETY DATA SHEET

Revision date 24-Aug-2015

Version 7

### Section 1: PRODUCT AND COMPANY IDENTIFICATION

**Product Name** VAL AR EN FLT BLK  
**Product Code** 044.0021826  
**UN/ID no** UN1263  
**Recommended Use** Paint, Coatings

#### Details of the supplier of the safety data sheet

*See section 16 for more information*

The Valspar Corporation  
PO Box 1461  
Minneapolis, MN 55440

Valspar Industries, Inc.  
1915 Second St. W.  
Cornwall, Ontario K6H 5R6

**E-mail address** [msds@valspar.com](mailto:msds@valspar.com)

**Emergency telephone number** 1-888-345-5732

### Section 2: HAZARDS IDENTIFICATION

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

#### HAZARD STATEMENTS

Combustible liquid.

Causes skin irritation May cause an allergic skin reaction Suspected of damaging fertility or the unborn child May cause drowsiness or dizziness May cause allergy or asthma symptoms or breathing difficulties if inhaled May be fatal if swallowed and enters airways May cause cancer Causes damage to organs through prolonged or repeated exposure

#### WHMIS Hazard Class

B3 - Combustible liquid  
D2A - Very toxic materials  
D2B - Toxic materials



Signal word

DANGER

Product Code 044.0021826

Page 1 / 10

WPNA - CANADA WHMIS SDS

## PREVENTION

Wear protective gloves/protective clothing/eye protection/face protection In case of inadequate ventilation wear respiratory protection Ground/bond container and receiving equipment Use explosion-proof electrical/ ventilating/ lighting/ equipment Do not handle until all safety precautions have been read and understood Do not breathe dust/fume/gas/mist/vapors/spray Obtain special instructions before use Wash face, hands and any exposed skin thoroughly after handling Use only non-sparking tools Contaminated work clothing should not be allowed out of the workplace Use only outdoors or in a well-ventilated area Do not eat, drink or smoke when using this product Keep container tightly closed Take precautionary measures against static discharge

## RESPONSE

IF exposed or concerned: Get medical advice/attention

### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

### Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower If skin irritation or rash occurs: Get medical advice/attention Wash contaminated clothing before reuse

### Inhalation

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician IF INHALED: Remove person to fresh air and keep comfortable for breathing

### Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting

## Fire

In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

## STORAGE

Store locked up Store in a well-ventilated place Store in a well-ventilated place. Keep cool

## DISPOSAL

Dispose of contents/containers in accordance with local regulations

## Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name                              | CAS No     | weight-%  |
|--|------------|-----------|
| Petroleum distillates, hydrotreated light  | 64742-47-8 | 25 - 50   |
| Talc                                       | 14807-96-6 | 10 - 25   |
| Limestone                                  | 1317-65-3  | 5 - 10    |
| Stoddard solvent                           | 8052-41-3  | 1 - 3     |
| Solvent naphtha, petroleum, light aromatic | 64742-95-6 | 1 - 3     |
| Benzene, 1,2,4-trimethyl-                  | 95-63-6    | 0.3 - 1   |
| Carbon black                               | 1333-86-4  | 0.3 - 1   |
| Quartz                                     | 14808-60-7 | 0.1 - 0.3 |
| Calcium 2-ethylhexanoate                   | 136-51-6   | 0.1 - 0.3 |
| 2-Butanone, oxime                          | 96-29-7    | 0.1 - 0.3 |

## Section 4: FIRST AID MEASURES

### First Aid Measures

#### General advice

IF exposed or concerned: Get medical advice/attention

#### Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

#### Skin Contact

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower If skin irritation or rash occurs: Get medical advice/attention Wash contaminated clothing before reuse

#### Inhalation

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician IF INHALED: Remove person to fresh air and keep comfortable for breathing

#### **Ingestion**

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting

#### **Most important symptoms and effects, both acute and delayed**

**Symptoms** No information available.

#### **Indication of any immediate medical attention and special treatment needed**

**Note to physicians** Treat symptomatically.

### **Section 5: FIRE FIGHTING MEASURES**

**Flammable properties** Combustible liquid.

**flash point** 100 °F / 38 °C

**Upper flammability limit:** No information available

**Lower flammability limit:** No information available

**Autoignition temperature** No information available

#### **Explosion data**

Sensitivity to Mechanical Impact No information available.  
Sensitivity to Static Discharge No information available.

#### **Suitable extinguishing media**

Dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam.

Not to be used for safety reasons: Strong water jet

**Hazardous combustion products** Carbon monoxide. Carbon dioxide (CO<sub>2</sub>).

#### **Specific hazards arising from the chemical**

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes. May cause sensitization by inhalation. May cause sensitization by skin contact. spontaneously combustible material. Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal. Keep product and empty container away from heat and sources of ignition.

#### **Special protective equipment for fire-fighters**

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

### **Section 6: ACCIDENTAL RELEASE MEASURES**

#### **Personal precautions**

Avoid breathing vapors or mists. Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Take precautionary measures against static discharges.

#### **Environmental precautions**

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages cannot be contained.

#### **Methods for containment**

Prevent further leakage or spillage if safe to do so.

### Methods for cleaning up

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. Take up mechanically, placing in appropriate containers for disposal.

## Section 7: HANDLING AND STORAGE

### General advice

Persons with a history of asthma, allergies, chronic or recurrent respiratory disease should not be exposed to any process in which this product is used. Examination of lung function should be carried out on a regular basis on persons spraying this product.

### Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Use only with adequate ventilation. Do not breathe dust/fume/gas/mist/vapors/spray. Use only in well-ventilated areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal.

### General Hygiene Considerations

When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Avoid contact with skin, eyes or clothing.

### Storage Conditions

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorized personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed in a dry and well-ventilated place. Keep tightly closed in a dry and cool place.

## Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure Guidelines

#### Exposure Limits

If S\* appears in the OEL table, it indicates this chemical contains a skin notation.

| Chemical Name  | ACGIH TLV   | Alberta                                    | British Columbia  | Ontario TWA                | Quebec                                     | OSHA PEL   |
|--|---|--|---|----------------------------|--|--|
| Petroleum distillates, hydrotreated light 64742-47-8 |   |  | TWA: 200 mg/m <sup>3</sup><br>S*  |                            |  |  |
| Talc 14807-96-6                                      | TWA: 2 mg/m <sup>3</sup><br>particulate matter containing no asbestos and <1% crystalline silica, respirable fraction | TWA: 2 mg/m <sup>3</sup>                   | TWA: 2 mg/m <sup>3</sup>  | TWA: 2 mg/m <sup>3</sup>   | TWA: 3 mg/m <sup>3</sup>                   | TWA: 20 mppcf if 1% Quartz or more, use Quartz limit                                       |
| Limestone 1317-65-3                                  |   | TWA: 10 mg/m <sup>3</sup>                  | TWA: 10 mg/m <sup>3</sup><br>TWA: 3 mg/m <sup>3</sup><br>STEL: 20 mg/m <sup>3</sup> |                            | TWA: 10 mg/m <sup>3</sup>                  | TWA: 15 mg/m <sup>3</sup><br>total dust<br>TWA: 5 mg/m <sup>3</sup><br>respirable fraction |
| Stoddard solvent 8052-41-3                           | TWA: 100 ppm  | TWA: 100 ppm<br>TWA: 572 mg/m <sup>3</sup> | TWA: 290 mg/m <sup>3</sup><br>STEL: 580 mg/m <sup>3</sup>                           | TWA: 525 mg/m <sup>3</sup> | TWA: 100 ppm<br>TWA: 525 mg/m <sup>3</sup> | TWA: 500 ppm<br>TWA: 2900 mg/m <sup>3</sup>  |
| Benzene, 1,2,4-trimethyl- 95-63-6                    | TWA: 25 ppm   | TWA: 25 ppm<br>TWA: 123 mg/m <sup>3</sup>  | TWA: 25 ppm   | TWA: 25 ppm                | TWA: 25 ppm<br>TWA: 123 mg/m <sup>3</sup>  |  |
| Carbon black 1333-86-4                               | TWA: 3 mg/m <sup>3</sup><br>inhalable fraction  | TWA: 3.5 mg/m <sup>3</sup>                 | TWA: 3 mg/m <sup>3</sup>  | TWA: 3 mg/m <sup>3</sup>   | TWA: 3.5 mg/m <sup>3</sup>                 | TWA: 3.5 mg/m <sup>3</sup>   |

|                      |   |                              |                              |                             |                            |  |
|----------------------|---|------------------------------|------------------------------|-----------------------------|----------------------------|--|
| Quartz<br>14808-60-7 | TWA: 0.025 mg/m <sup>3</sup><br>respirable fraction | TWA: 0.025 mg/m <sup>3</sup> | TWA: 0.025 mg/m <sup>3</sup> | TWA: 0.10 mg/m <sup>3</sup> | TWA: 0.1 mg/m <sup>3</sup> | TWA:<br>(30)/(%SiO <sub>2</sub> + 2)<br>mg/m <sup>3</sup> TWA total<br>dust<br>TWA:<br>(250)/(%SiO <sub>2</sub> + 2)<br>mppcf TWA<br>respirable fraction<br>TWA:<br>(10)/(%SiO <sub>2</sub> + 2)<br>mg/m <sup>3</sup> TWA<br>respirable fraction |
|----------------------|---|------------------------------|------------------------------|-----------------------------|----------------------------|--|

### Engineering Controls

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

### Personal Protective Equipment

#### Eye/face protection

Tight sealing safety goggles.

#### Hand Protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

#### Skin and body protection

Wear anti-static clothing made of natural fiber or of high temperature resistant synthetic fiber. Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Wear suitable protective clothing.

#### Respiratory protection

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators

#### Thermal Protection

No information available

### Environmental exposure controls

Do not allow into any sewer, on the ground or into any body of water. Local authorities should be advised if significant spillages cannot be contained.

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

|                               |                                  |
|-------------------------------|----------------------------------|
| Physical state                | liquid                           |
| Appearance                    | No information available         |
| Odor                          | Solvent                          |
| Color                         | black                            |
| Odor Threshold                | No information available         |
| pH value                      | No information available         |
| Melting point/freezing point  | No information available         |
| Boiling point / boiling range | No information available °C / °F |
| flash point                   | 38 °C / 100 °F                   |
| evaporation rate              | No information available         |
| Flammability (solid, gas)     | No information available         |
| Flammability Limit in Air     |                                  |
| Upper flammability limit:     | No information available         |
| Lower flammability limit:     | No information available         |
| Vapor Pressure                | No information available         |
| vapor density                 | No information available         |
| Density (lbs per US gallon)   | 9.93                             |
| specific gravity              | 1.19                             |
| Solubility(ies)               | No information available         |
| Partition coefficient         | No information available         |

Product Code 044.0021826

Page 5 / 10

WPNA - CANADA WHMIS SDS

|                                  |                          |
|----------------------------------|--------------------------|
| <b>Autoignition temperature</b>  | No information available |
| <b>Decomposition temperature</b> | No information available |
| <b>Kinematic viscosity</b>       | No information available |
| <b>Dynamic viscosity</b>         | No information available |

**Other information**

## Section 10: STABILITY AND REACTIVITY

|   |   |
|---|---|
| <b>Stability</b>                          | Stable under normal conditions.                     |
| <b>Incompatible materials</b>             | Strong oxidizing agents. Acids. Alkali.             |
| <b>Conditions to avoid</b>                | Heat, flames and sparks.                            |
| <b>Hazardous Decomposition Products</b>   | Carbon monoxide. Carbon dioxide (CO <sub>2</sub> ). |
| <b>Possibility of Hazardous Reactions</b> | None under normal processing.                       |
| <b>Hazardous polymerization</b>           | None under normal processing.                       |

## Section 11: TOXICOLOGICAL INFORMATION

**Information on toxicological effects**

**Information on likely routes of exposure**

**Eye contact**

Not applicable

**Skin Contact**

Causes skin irritation

May cause an allergic skin reaction

**Ingestion**

May be fatal if swallowed and enters airways

**Inhalation**

May cause drowsiness or dizziness

**Numerical measures of toxicity - Component Information**

| Chemical Name                              | Oral LD50            | Dermal LD50             | Inhalation LC50                   |
|--|----------------------|-------------------------|-----------------------------------|
| Petroleum distillates, hydrotreated light  | > 5000 mg/kg ( Rat ) | > 2000 mg/kg ( Rabbit ) | > 5.2 mg/L ( Rat ) 4 h            |
| Talc                                       | -                    | -                       | -                                 |
| Limestone                                  | -                    | -                       | -                                 |
| Stoddard solvent                           | -                    | -                       | -                                 |
| Solvent naphtha, petroleum, light aromatic | -                    | > 2000 mg/kg ( Rabbit ) | = 3400 ppm ( Rat ) 4 h            |
| Benzene, 1,2,4-trimethyl-                  | = 3280 mg/kg ( Rat ) | > 3160 mg/kg ( Rabbit ) | = 18 g/m <sup>3</sup> ( Rat ) 4 h |
| Carbon black                               | -                    | -                       | -                                 |
| Quartz                                     | = 500 mg/kg ( Rat )  | -                       | -                                 |
| Calcium 2-ethylhexanoate                   | -                    | -                       | -                                 |
| 2-Butanone, oxime                          | = 930 mg/kg ( Rat )  | = 0.2 mg/kg ( Rabbit )  | = 20 mg/L ( Rat ) 4 h             |

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

|  |   |
|--|---|
| <b>Skin corrosion/irritation</b>         | Causes skin irritation  |
| <b>Serious eye damage/eye irritation</b> | Not applicable  |
| <b>Skin sensitization</b>                | May cause an allergic skin reaction                                       |
| <b>Respiratory sensitization</b>         | May cause allergy or asthma symptoms or breathing difficulties if inhaled |
| <b>Germ cell mutagenicity</b>            | Not applicable  |
| <b>Carcinogenicity</b>                   | May cause cancer  |
| <b>Reproductive Toxicity</b>             | Suspected of damaging fertility or the unborn child                       |

**Product Code 044.0021826**

Page 6 / 10

WPNA - CANADA WHMIS SDS

**Specific target organ toxicity (single exposure)** May cause drowsiness or dizziness

**Specific target organ toxicity (repeated exposure)** Causes damage to organs through prolonged or repeated exposure

**Aspiration hazard** Not applicable

#### **Carcinogenicity**

According to IARC, Volume 93, no significant exposure to primary particles of carbon black is thought to occur from use in paints since the pigment is bound to other materials.

| Chemical Name | ACGIH | IARC     | NTP   | OSHA |
|---------------|-------|----------|-------|------|
| Carbon black  | A3    | Group 2B |       | X    |
| Quartz        | A2    | Group 1  | Known | X    |

#### **ACGIH (American Conference of Governmental Industrial Hygienists)**

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

#### **IARC (International Agency for Research on Cancer)**

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

#### **NTP (National Toxicology Program)**

Known - Known Carcinogen

#### **OSHA (Occupational Safety and Health Administration of the US Department of Labor)**

X - Present

## **Section 12: ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Marine pollutant This material meets the definition of a marine pollutant

Environmental precautions Prevent product from entering drains.

| Chemical Name                              | Algae/aquatic plants                        | Fish   | Crustacea                          |
|--|---|--|------------------------------------|
| Petroleum distillates, hydrotreated light  | -   | = 2.4 mg/L Oncorhynchus mykiss 96h LC50<br>= 2.2 mg/L Lepomis macrochirus 96h LC50<br>= 45 mg/L Pimephales promelas 96h LC50 | -                                  |
| Talc                                       | -   | > 100 g/L Brachydanio rerio 96h LC50   | -                                  |
| Limestone                                  | -   | -  | -                                  |
| Stoddard solvent                           | -   | -  | -                                  |
| Solvent naphtha, petroleum, light aromatic | -   | = 9.22 mg/L Oncorhynchus mykiss 96h LC50   | = 6.14 mg/L Daphnia magna 48h EC50 |
| Benzene, 1,2,4-trimethyl-                  | -   | 7.19 - 8.28 mg/L Pimephales promelas 96h LC50<br>= 7.72 mg/L Pimephales promelas 96h LC50                                    | = 6.14 mg/L Daphnia magna 48h EC50 |
| Carbon black                               | -   | -  | -                                  |
| Quartz                                     | -   | -  | -                                  |
| Calcium 2-ethylhexanoate                   | -   | -  | -                                  |
| 2-Butanone, oxime                          | = 83 mg/L Desmodesmus subspicatus 72 h EC50 | 777 - 914 mg/L Pimephales promelas 96h LC50<br>= 760 mg/L Poecilia reticulata 96h LC50                                       | = 750 mg/L Daphnia magna 48h EC50  |

**Persistence and degradability** No information available.

**Bioaccumulation** No information available.

**Product Code 044.0021826**

**Page 7 / 10**

**WPNA - CANADA WHMIS SDS**

**Mobility** No information available.

| Chemical Name                              | Partition Coefficient (n-octanol/water) |
|--|---|
| Petroleum distillates, hydrotreated light  | -                                       |
| Talc                                       | -                                       |
| Limestone                                  | -                                       |
| Stoddard solvent                           | -                                       |
| Solvent naphtha, petroleum, light aromatic | -                                       |
| Benzene, 1,2,4-trimethyl-                  | 3.63                                    |
| Carbon black                               | -                                       |
| Quartz                                     | -                                       |
| Calcium 2-ethylhexanoate                   | -                                       |
| 2-Butanone, oxime                          | 0.65                                    |

### Section 13: DISPOSAL CONSIDERATIONS

**Waste from residues/unused products** Disposal should be in accordance with applicable regional, national and local laws and regulations

**Contaminated packaging** Improper disposal or reuse of this container may be dangerous and illegal.

### Section 14: TRANSPORT INFORMATION

|  | <u><b>TDG</b></u> | <u><b>IMDG</b></u>        | <u><b>IATA</b></u>       |
|--|-------------------|---------------------------|--------------------------|
| UN/ID no   | UN1263            | UN1263                    | UN1263                   |
| Proper shipping name   | Paint             | Paint                     | Paint                    |
| <b>Hazard Class</b>  | 3                 | 3                         | 3                        |
| <b>Packing Group</b>   | III               | III                       | III                      |
| <b>Environmental hazard</b> Yes  |                   |                           |                          |
| <b>Marine pollutant</b> This material meets the definition of a marine pollutant     |                   |                           |                          |
| <b>Marine pollutant</b> Petroleum distillates, hydrotreated light , Stoddard solvent |                   |                           |                          |
| <b>Special Provisions</b>  |                   | 163, 223, 955             | A3, A72                  |
|  |                   | <b>EmS-No</b><br>F-E, S-E |                          |
| <b>Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</b>      |                   |                           | No information available |

### Section 15: REGULATORY INFORMATION

#### International Inventories

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory All components are listed or exempt from listing

**DSL** - Canadian Domestic Substances List Not all components are listed or exempt from listing

**This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR**

#### **WHMIS Hazard Class**

B3 - Combustible liquid

D2A - Very toxic materials

D2B - Toxic materials



| Chemical Name                              | Canada - 2013 NPRI (National Pollutant Release Inventory) |
|--|---|
| Petroleum distillates, hydrotreated light  | Part 5, Other Groups and Mixtures                         |
| Stoddard solvent                           | Part 5, Other Groups and Mixtures                         |
| Solvent naphtha, petroleum, light aromatic | Part 5, Other Groups and Mixtures                         |

**Product Code 044.0021826**

Page 8 / 10

WPNA - CANADA WHMIS SDS



|                           |  |
|---------------------------|--|
| Benzene, 1,2,4-trimethyl- | Part 1, Group A Substance<br>Part 5, Individual Substances |
|---------------------------|--|

### **GHS - Classification**

|  |             |
|--|-------------|
| Skin corrosion/irritation                          | Category 2  |
| Respiratory sensitization                          | Category 1  |
| Skin sensitization                                 | Category 1  |
| Carcinogenicity                                    | Category 1A |
| Reproductive toxicity                              | Category 2  |
| Specific target organ toxicity (single exposure)   | Category 3  |
| Specific target organ toxicity (repeated exposure) | Category 1  |
| Aspiration toxicity                                | Category 1  |
| Flammable liquids                                  | Category 3  |

### **Label elements**



**Signal word**

**DANGER**

### **HAZARD STATEMENTS**

Flammable liquid and vapor  
 Causes skin irritation  
 May cause allergy or asthma symptoms or breathing difficulties if inhaled  
 May cause an allergic skin reaction  
 May cause cancer  
 Suspected of damaging fertility or the unborn child  
 May cause drowsiness or dizziness  
 Causes damage to organs through prolonged or repeated exposure  
 May be fatal if swallowed and enters airways

### **PREVENTION**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Wash face, hands and any exposed skin thoroughly after handling. In case of inadequate ventilation wear respiratory protection. Contaminated work clothing should not be allowed out of the workplace. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

### **RESPONSE**

IF exposed or concerned: Get medical advice/attention.

#### **Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

#### **Skin**

If skin irritation or rash occurs: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse.

#### **Inhalation**

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician. IF INHALED: Remove person to fresh air and keep comfortable for breathing.

#### **Ingestion**

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

**Fire**

In case of fire: Use CO2, dry chemical, or foam for extinction.

**STORAGE**

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool.

**DISPOSAL**

Dispose of contents/containers in accordance with local regulations.

**HAZARDS NOT OTHERWISE CLASSIFIED (HNOC)**

Not applicable.

**OTHER HAZARDS**

Toxic to aquatic life with long lasting effects. spontaneously combustible material. Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal.

**UNKNOWN ACUTE TOXICITY** 0% of the mixture consists of ingredient(s) of unknown toxicity.

**Section 16: OTHER INFORMATION****HMIS**

**Health hazards** 3\*

\* = Chronic Health Hazard

**Flammability** 2

**Physical hazards** 0

**Personal Protection** X

**Supplier Address**

|   |  |  |
|---|--|--|
| Valspar Consumer Headquarters                                       | The Valspar Corporation<br>4999 36th St.<br>Grand Rapids, MI 49512<br>800-253-3957 | Valspar Plasti-Kote<br>1636 Shawsone Dr.<br>Mississauga, Ontario L4W 1N7<br>905-671-8333 |
| 8725 W. Higgins Rd. Suite 1000<br>Chicago, IL 60631<br>773-628-5500 |  |  |

**Prepared By** Product Stewardship

**Revision date** 24-Aug-2015

**Revision Note** No information available

**Disclaimer**

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

**End of Safety Data Sheet**