



SAFETY DATA SHEET

Revision date 24-Aug-2015

Version 7

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name VAL HD ALUMINUM
Product Code 044.0021840
UN/ID no UN1263
Recommended Use Paint, Coatings

Details of the supplier of the safety data sheet

See section 16 for more information

The Valspar Corporation
PO Box 1461
Minneapolis, MN 55440

Valspar Industries, Inc.
1915 Second St. W.
Cornwall, Ontario K6H 5R6

E-mail address msds@valspar.com

Emergency telephone number 1-888-345-5732

Section 2: HAZARDS IDENTIFICATION

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

HAZARD STATEMENTS

Combustible liquid.

Causes skin irritation Suspected of causing cancer Causes damage to organs through prolonged or repeated exposure May be fatal if swallowed and enters airways May cause drowsiness or dizziness May cause an allergic skin reaction

WHMIS Hazard Class

B3 - Combustible liquid
D2A - Very toxic materials
D2B - Toxic materials



Signal word

DANGER

Product Code 044.0021840

Page 1 / 10

WPNA - CANADA WHMIS SDS

PREVENTION

Contaminated work clothing should not be allowed out of the workplace Use only non-sparking tools Do not handle until all safety precautions have been read and understood Wear protective gloves/protective clothing/eye protection/face protection Ground/bond container and receiving equipment Obtain special instructions before use Do not breathe dust/fume/gas/mist/vapors/spray Do not eat, drink or smoke when using this product Use only outdoors or in a well-ventilated area Keep container tightly closed Wash face, hands and any exposed skin thoroughly after handling Use explosion-proof electrical/ ventilating/ lighting/ equipment Take precautionary measures against static discharge

RESPONSE

IF exposed or concerned: Get medical advice/attention

Eyes

If eye irritation persists: Get medical advice/attention IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Skin

If skin irritation or rash occurs: Get medical advice/attention Wash contaminated clothing before reuse IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing

Ingestion

Do NOT induce vomiting IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Fire

In case of fire: Use CO₂, dry chemical, or foam for extinction

STORAGE

Store locked up Store in a well-ventilated place. Keep cool Store in a well-ventilated place

DISPOSAL

Dispose of contents/containers in accordance with local regulations

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	weight-%
Solvent naphtha, petroleum, medium aliphatic	64742-88-7	10 - 25
Stoddard solvent	8052-41-3	10 - 25
Aluminum	7429-90-5	5 - 10
Petroleum distillates, hydrotreated light	64742-47-8	5 - 10
Solvent naphtha, petroleum, light aromatic	64742-95-6	1 - 3
Benzene, 1,2,4-trimethyl-	95-63-6	0.3 - 1
2-Butanone, oxime	96-29-7	0.1 - 0.3
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	0.1 - 0.3

Section 4: FIRST AID MEASURES

First Aid Measures

General advice

IF exposed or concerned: Get medical advice/attention

Eye contact

If eye irritation persists: Get medical advice/attention IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Skin Contact

If skin irritation or rash occurs: Get medical advice/attention Wash contaminated clothing before reuse IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing

Ingestion

Do NOT induce vomiting IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Product Code 044.0021840

Page 2 / 10

WPNA - CANADA WHMIS SDS

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

Section 5: FIRE FIGHTING MEASURES

Flammable properties Combustible liquid.

flash point 102 °F / 39 °C

Upper flammability limit: No information available

Lower flammability limit: No information available

Autoignition temperature No information available

Explosion data

Sensitivity to Mechanical Impact	No information available.
Sensitivity to Static Discharge	No information available.

Suitable extinguishing media

Dry chemical, CO₂, water spray or alcohol-resistant foam.

Not to be used for safety reasons: Strong water jet

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO₂).

Specific hazards arising from the chemical

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes. May cause sensitization by skin contact. spontaneously combustible material. Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal. Keep product and empty container away from heat and sources of ignition.

Special protective equipment for fire-fighters

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

Section 6: ACCIDENTAL RELEASE MEASURES**Personal precautions**

Avoid breathing vapors or mists. Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Take precautionary measures against static discharges.

Environmental precautions

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages cannot be contained.

Methods for containment

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. Take up mechanically, placing in appropriate containers for disposal.

Section 7: HANDLING AND STORAGE

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Use only with adequate ventilation. Do not breathe dust/fume/gas/mist/vapors/spray. Use only in well-ventilated areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal.

General Hygiene Considerations

When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Avoid contact with skin, eyes or clothing.

Storage Conditions

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorized personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed in a dry and well-ventilated place. Keep tightly closed in a dry and cool place.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Exposure Limits

If S* appears in the OEL table, it indicates this chemical contains a skin notation.

Chemical Name	ACGIH TLV	Alberta	British Columbia	Ontario TWA	Quebec	OSHA PEL
Stoddard solvent 8052-41-3	TWA: 100 ppm	TWA: 100 ppm TWA: 572 mg/m ³	TWA: 290 mg/m ³ STEL: 580 mg/m ³	TWA: 525 mg/m ³	TWA: 100 ppm TWA: 525 mg/m ³	TWA: 500 ppm TWA: 2900 mg/m ³
Aluminum 7429-90-5	TWA: 1 mg/m ³ respirable fraction	TWA: 10 mg/m ³	TWA: 1.0 mg/m ³	TWA: 1 mg/m ³	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction
Petroleum distillates, hydrotreated light 64742-47-8			TWA: 200 mg/m ³ S*			
Benzene, 1,2,4-trimethyl- 95-63-6	TWA: 25 ppm	TWA: 25 ppm TWA: 123 mg/m ³	TWA: 25 ppm	TWA: 25 ppm	TWA: 25 ppm TWA: 123 mg/m ³	

Engineering Controls

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

Personal Protective Equipment

Eye/face protection

Tight sealing safety goggles.

Hand Protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

Skin and body protection

Wear anti-static clothing made of natural fiber or of high temperature resistant synthetic fiber. Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Wear suitable protective clothing.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators

Thermal Protection

No information available

Environmental exposure controls

Do not allow into any sewer, on the ground or into any body of water. Local authorities should be advised if significant spillages cannot be contained.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES**Information on basic physical and chemical properties**

Physical state	liquid
Appearance	No information available
Odor	Solvent
Color	metallic
Odor Threshold	No information available
pH value	No information available
Melting point/freezing point	No information available
Boiling point / boiling range	No information available °C / °F
flash point	39 °C / 102 °F
evaporation rate	No information available
Flammability (solid, gas)	No information available
Flammability Limit in Air	
Upper flammability limit:	No information available
Lower flammability limit:	No information available
Vapor Pressure	No information available
vapor density	No information available
Density (lbs per US gallon)	8.19
specific gravity	.98
Solubility(ies)	No information available
Partition coefficient	No information available
Autoignition temperature	No information available
Decomposition temperature	No information available
Kinematic viscosity	No information available
Dynamic viscosity	No information available

Other information**Section 10: STABILITY AND REACTIVITY**

Stability	Stable under normal conditions.
Incompatible materials	Bases. Strong oxidizing agents. Acids.
Conditions to avoid	Heat, flames and sparks.
Hazardous Decomposition Products	Carbon monoxide. Carbon dioxide (CO2).
Possibility of Hazardous Reactions	None under normal processing.
Hazardous polymerization	None under normal processing.

Section 11: TOXICOLOGICAL INFORMATION**Information on toxicological effects****Information on likely routes of exposure****Eye contact**

Not applicable

Skin Contact

Causes skin irritation

May cause an allergic skin reaction

Ingestion

May be fatal if swallowed and enters airways

Inhalation

May cause drowsiness or dizziness

Numerical measures of toxicity - Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Solvent naphtha, petroleum, medium aliphatic	> 5000 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	> 5.28 mg/L (Rat) 4 h
Stoddard solvent	-	-	-
Aluminum	-	-	-
Petroleum distillates, hydrotreated light	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
Solvent naphtha, petroleum, light aromatic	-	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat) 4 h
Benzene, 1,2,4-trimethyl-	= 3280 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m ³ (Rat) 4 h
2-Butanone, oxime	= 930 mg/kg (Rat)	= 0.2 mg/kg (Rabbit)	= 20 mg/L (Rat) 4 h
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	-	-	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Causes skin irritation
Serious eye damage/eye irritation	Not applicable
Skin sensitization	May cause an allergic skin reaction
Respiratory sensitization	Not applicable
Germ cell mutagenicity	Not applicable
Carcinogenicity	Suspected of causing cancer
Reproductive Toxicity	Not applicable
Specific target organ toxicity (single exposure)	May cause drowsiness or dizziness
Specific target organ toxicity (repeated exposure)	Causes damage to organs through prolonged or repeated exposure
Aspiration hazard	Not applicable

Chemical Name	ACGIH	IARC	NTP	OSHA
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)		Group 2B		X

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Section 12: ECOLOGICAL INFORMATION**Ecotoxicity**

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

This product contains a chemical which is listed as a marine pollutant according to DOT.

Marine pollutant This material meets the definition of a marine pollutant

Environmental precautions Prevent product from entering drains.

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Solvent naphtha, petroleum, medium aliphatic	= 450 mg/L Pseudokirchneriella subcapitata 96 h EC50	= 800 mg/L Pimephales promelas 96h LC50	> 100 mg/L Daphnia magna 48h EC50
Stoddard solvent	-	-	-
Aluminum	-	-	-

Petroleum distillates, hydrotreated light	-	= 2.4 mg/L Oncorhynchus mykiss 96h LC50 = 2.2 mg/L Lepomis macrochirus 96h LC50 = 45 mg/L Pimephales promelas 96h LC50	-
Solvent naphtha, petroleum, light aromatic	-	= 9.22 mg/L Oncorhynchus mykiss 96h LC50	= 6.14 mg/L Daphnia magna 48h EC50
Benzene, 1,2,4-trimethyl-	-	7.19 - 8.28 mg/L Pimephales promelas 96h LC50 = 7.72 mg/L Pimephales promelas 96h LC50	= 6.14 mg/L Daphnia magna 48h EC50
2-Butanone, oxime	= 83 mg/L Desmodemus subspicatus 72 h EC50	777 - 914 mg/L Pimephales promelas 96h LC50 = 760 mg/L Poecilia reticulata 96h LC50	= 750 mg/L Daphnia magna 48h EC50
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	-	-	-

Persistence and degradability No information available.

Bioaccumulation No information available.

Mobility No information available.

Chemical Name	Partition Coefficient (n-octanol/water)
Solvent naphtha, petroleum, medium aliphatic	-
Stoddard solvent	-
Aluminum	-
Petroleum distillates, hydrotreated light	-
Solvent naphtha, petroleum, light aromatic	-
Benzene, 1,2,4-trimethyl-	3.63
2-Butanone, oxime	0.65
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	-

Section 13: DISPOSAL CONSIDERATIONS

Waste from residues/unused products Disposal should be in accordance with applicable regional, national and local laws and regulations

Contaminated packaging Improper disposal or reuse of this container may be dangerous and illegal.

Section 14: TRANSPORT INFORMATION

UN/ID no	TDG UN1263	IMDG UN1263	IATA UN1263
Proper shipping name	Paint	Paint	Paint
Hazard Class	3	3	3
Packing Group	III	III	III
Environmental hazard Yes			
Marine pollutant This material meets the definition of a marine pollutant			
Marine pollutant Solvent naphtha, petroleum, medium aliphatic , Stoddard solvent			
Special Provisions		163, 223, 955 EmS-No F-E, S-E	A3, A72
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code			No information available

Section 15: REGULATORY INFORMATION

International Inventories

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

All components are listed or exempt from listing

Product Code 044.0021840

Page 7 / 10

WPNA - CANADA WHMIS SDS

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

WHMIS Hazard Class

B3 - Combustible liquid

D2A - Very toxic materials

D2B - Toxic materials



Chemical Name	Canada - 2013 NPRI (National Pollutant Release Inventory)
Solvent naphtha, petroleum, medium aliphatic	Part 5, Other Groups and Mixtures
Stoddard solvent	Part 5, Other Groups and Mixtures
Aluminum	Part 1, Group A Substance
Petroleum distillates, hydrotreated light	Part 5, Other Groups and Mixtures
Solvent naphtha, petroleum, light aromatic	Part 5, Other Groups and Mixtures
Benzene, 1,2,4-trimethyl-	Part 1, Group A Substance Part 5, Individual Substances
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	Part 1, Group A Substance

GHS - Classification

Skin corrosion/irritation	Category 2
Skin sensitization	Category 1
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1
Flammable liquids	Category 3

Label elements



Signal word

DANGER

HAZARD STATEMENTS

Flammable liquid and vapor

Causes skin irritation

May cause an allergic skin reaction

Suspected of causing cancer

May cause drowsiness or dizziness

Causes damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways

PREVENTION

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Wash face, hands and any exposed skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

RESPONSE

IF exposed or concerned: Get medical advice/attention.

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin

If skin irritation or rash occurs: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction.

STORAGE

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool.

DISPOSAL

Dispose of contents/containers in accordance with local regulations.

HAZARDS NOT OTHERWISE CLASSIFIED (HNOC)

Not applicable.

OTHER HAZARDS

Toxic to aquatic life with long lasting effects. spontaneously combustible material. Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal. Not applicable.

UNKNOWN ACUTE TOXICITY 0% of the mixture consists of ingredient(s) of unknown toxicity.

Section 16: OTHER INFORMATION

HMIS

Health hazards 3*

* = Chronic Health Hazard

Flammability 2

Physical hazards 1

Personal Protection X

Supplier Address

Valspar Consumer Headquarters	The Valspar Corporation 4999 36th St. Grand Rapids, MI 49512 800-253-3957	Valspar Plasti-Kote 1636 Shawsone Dr. Mississauga, Ontario L4W 1N7 905-671-8333
8725 W. Higgins Rd. Suite 1000 Chicago, IL 60631 773-628-5500		

Prepared By Product Stewardship

Revision date 24-Aug-2015

Revision Note No information available

Disclaimer

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

End of Safety Data Sheet