



## SAFETY DATA SHEET

Revision date 02-Nov-2015

Version 1

### Section 1: PRODUCT AND COMPANY IDENTIFICATION

|                 |                 |    |
|-----------------|-----------------|----|
| Product Name    | 500 GRAY/WHITE  | 6U |
| Product Code    | 400.0000500.076 |    |
| UN/ID no        | UN1950          |    |
| Recommended Use | Aerosol, Paint  |    |

#### Details of the supplier of the safety data sheet

See section 16 for more information

The Valspar Corporation  
PO Box 1461  
Minneapolis, MN 55440

Valspar Industries, Inc.  
1915 Second St. W.  
Cornwall, Ontario K6H 5R6

E-mail address [msds@valspar.com](mailto:msds@valspar.com)

Emergency telephone number 1-888-345-5732

### Section 2: HAZARDS IDENTIFICATION

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

#### HAZARD STATEMENTS

Flammable aerosol Contains gas under pressure; may explode if heated

May be fatal if swallowed and enters airways May cause drowsiness or dizziness May cause cancer May cause damage to organs through prolonged or repeated exposure Causes skin irritation

#### WHMIS Hazard Class

B5 - Flammable aerosol

A Compressed gases

D2A - Very toxic materials

D2B - Toxic materials



Signal word

DANGER

Product Code 400.0000500.076

Page 1 / 9

WPNA - CANADA WHMIS SDS

## PREVENTION

Obtain special instructions before use Pressurized container: Do not pierce or burn, even after use Do not handle until all safety precautions have been read and understood Wear protective gloves/protective clothing/eye protection/face protection Do not spray on an open flame or other ignition source Wash face, hands and any exposed skin thoroughly after handling Do not breathe dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area

## RESPONSE

IF exposed or concerned: Get medical advice/attention

### Eyes

If eye irritation persists: Get medical advice/attention IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

### Skin

If skin irritation occurs: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water Take off contaminated clothing and wash before reuse

### Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing

### Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting

## STORAGE

Store locked up Store in a well-ventilated place Protect from sunlight. Store in a well-ventilated place Do not expose to temperatures exceeding 122 °F (50 °C)

## DISPOSAL

Dispose of contents/containers in accordance with local regulations

## Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name                          | CAS No     | weight-% |
|----------------------------------------|------------|----------|
| Quartz                                 | 14808-60-7 | 10 - 25  |
| Naphtha, petroleum, hydrotreated heavy | 64742-48-9 | 10 - 25  |
| Propane                                | 74-98-6    | 10 - 25  |
| Naphtha, petroleum, hydrotreated heavy | 64742-48-9 | 10 - 25  |
| Naphtha, petroleum, light alkylate     | 64741-66-8 | 5 - 10   |
| Butane                                 | 106-97-8   | 5 - 10   |
| Titanium dioxide                       | 13463-67-7 | 1 - 3    |

## Section 4: FIRST AID MEASURES

### First Aid Measures

#### General advice

IF exposed or concerned: Get medical advice/attention

#### Eye contact

If eye irritation persists: Get medical advice/attention IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

#### Skin Contact

If skin irritation occurs: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water Take off contaminated clothing and wash before reuse

#### Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing

#### Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting

### Most important symptoms and effects, both acute and delayed

#### Symptoms

No information available.

**Product Code 400.0000500.076**

Page 2 / 9

WPNA - CANADA WHMIS SDS

## Indication of any immediate medical attention and special treatment needed

**Note to physicians** Treat symptomatically.

### Section 5: FIRE FIGHTING MEASURES

**Flammable properties** Flammable liquid.

**flash point** -31 °F / -35 °C

**Upper flammability limit:** No information available

**Lower flammability limit:** No information available

**Autoignition temperature** No information available

**Explosion data**

|                                  |                           |
|----------------------------------|---------------------------|
| Sensitivity to Mechanical Impact | No information available. |
| Sensitivity to Static Discharge  | No information available. |

#### Suitable extinguishing media

Dry chemical, CO2, water spray or alcohol-resistant foam.

Not to be used for safety reasons: Strong water jet

**Hazardous combustion products** Carbon monoxide. Carbon dioxide (CO2).

#### Specific hazards arising from the chemical

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes.

#### Special protective equipment for fire-fighters

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

### Section 6: ACCIDENTAL RELEASE MEASURES

#### Personal precautions

Avoid breathing vapors or mists. Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak.

#### Environmental precautions

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages cannot be contained.

#### Methods for containment

Prevent further leakage or spillage if safe to do so.

#### Methods for cleaning up

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

### Section 7: HANDLING AND STORAGE

### Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Use only with adequate ventilation. Do not breathe dust/fume/gas/mist/vapors/spray. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

### General Hygiene Considerations

When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Avoid contact with skin, eyes or clothing.

### Storage Conditions

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorized personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed in a dry and well-ventilated place. Protect from sunlight. Store in a well-ventilated place.

## Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure Guidelines

#### Exposure Limits

If S\* appears in the OEL table, it indicates this chemical contains a skin notation.

| Chemical Name                  | ACGIH TLV                                           | Alberta                      | British Columbia                                      | Ontario TWA                 | Quebec                                       | OSHA PEL                                                                                                                                                                                                                                         |
|--------------------------------|-----------------------------------------------------|------------------------------|-------------------------------------------------------|-----------------------------|----------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Quartz<br>14808-60-7           | TWA: 0.025 mg/m <sup>3</sup><br>respirable fraction | TWA: 0.025 mg/m <sup>3</sup> | TWA: 0.025 mg/m <sup>3</sup>                          | TWA: 0.10 mg/m <sup>3</sup> | TWA: 0.1 mg/m <sup>3</sup>                   | TWA:<br>(30)/(%SiO <sub>2</sub> + 2)<br>mg/m <sup>3</sup> TWA total<br>dust<br>TWA:<br>(250)/(%SiO <sub>2</sub> + 5)<br>mppcf TWA<br>respirable fraction<br>TWA:<br>(10)/(%SiO <sub>2</sub> + 2)<br>mg/m <sup>3</sup> TWA<br>respirable fraction |
| Propane<br>74-98-6             | TWA: 1000 ppm                                       | TWA: 1000 ppm                | TWA: 1000 ppm                                         | TWA: 1000 ppm               | TWA: 1000 ppm<br>TWA: 1800 mg/m <sup>3</sup> | TWA: 1000 ppm<br>TWA: 1800 mg/m <sup>3</sup>                                                                                                                                                                                                     |
| Butane<br>106-97-8             | STEL: 1000 ppm                                      | TWA: 1000 ppm                | TWA: 600 ppm<br>STEL: 750 ppm                         | TWA: 800 ppm                | TWA: 800 ppm<br>TWA: 1900 mg/m <sup>3</sup>  |                                                                                                                                                                                                                                                  |
| Titanium dioxide<br>13463-67-7 | TWA: 10 mg/m <sup>3</sup>                           | TWA: 10 mg/m <sup>3</sup>    | TWA: 10 mg/m <sup>3</sup><br>TWA: 3 mg/m <sup>3</sup> | TWA: 10 mg/m <sup>3</sup>   | TWA: 10 mg/m <sup>3</sup>                    | TWA: 15 mg/m <sup>3</sup><br>total dust                                                                                                                                                                                                          |

### Engineering Controls

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

### Personal Protective Equipment

#### Eye/face protection

Wear safety glasses with side shields (or goggles).

#### Hand Protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

#### Skin and body protection

Wear anti-static clothing made of natural fiber or of high temperature resistant synthetic fiber. Wear suitable protective clothing.

#### Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators

#### Thermal Protection

No information available

**Environmental exposure controls**

Do not allow into any sewer, on the ground or into any body of water. Local authorities should be advised if significant spillages cannot be contained.

**Section 9: PHYSICAL AND CHEMICAL PROPERTIES****Information on basic physical and chemical properties**

|                                      |                                  |
|--------------------------------------|----------------------------------|
| <b>Physical state</b>                | Aerosol                          |
| <b>Appearance</b>                    | No information available         |
| <b>Odor</b>                          | Solvent                          |
| <b>Color</b>                         | Silver                           |
| <b>Odor Threshold</b>                | No information available         |
| <b>pH value</b>                      | No information available         |
| <b>Melting point/freezing point</b>  | No information available         |
| <b>Boiling point / boiling range</b> | No information available °C / °F |
| <b>flash point</b>                   | -35 °C / -31 °F                  |
| <b>evaporation rate</b>              | No information available         |
| <b>Flammability (solid, gas)</b>     | No information available         |
| <b>Flammability Limit in Air</b>     |                                  |
| <b>Upper flammability limit:</b>     | No information available         |
| <b>Lower flammability limit:</b>     | No information available         |
| <b>Vapor Pressure</b>                | No information available         |
| <b>vapor density</b>                 | No information available         |
| <b>Density (lbs per US gallon)</b>   | 7.16                             |
| <b>specific gravity</b>              | .86                              |
| <b>Solubility(ies)</b>               | Not Determined                   |
| <b>Partition coefficient</b>         | No information available         |
| <b>Autoignition temperature</b>      | No information available         |
| <b>Decomposition temperature</b>     | No information available         |
| <b>Kinematic viscosity</b>           | No information available         |
| <b>Dynamic viscosity</b>             | No information available         |

**Other information****Section 10: STABILITY AND REACTIVITY**

|                                           |                                        |
|-------------------------------------------|----------------------------------------|
| <b>Stability</b>                          | Stable under normal conditions.        |
| <b>Incompatible materials</b>             | Strong oxidizing agents.               |
| <b>Conditions to avoid</b>                | Heat, flames and sparks.               |
| <b>Hazardous Decomposition Products</b>   | Carbon monoxide. Carbon dioxide (CO2). |
| <b>Possibility of Hazardous Reactions</b> | None under normal processing.          |
| <b>Hazardous polymerization</b>           | None under normal processing.          |

**Section 11: TOXICOLOGICAL INFORMATION****Information on toxicological effects****Information on likely routes of exposure****Eye contact**

Not applicable

**Skin Contact**

Causes skin irritation

**Ingestion**

May be fatal if swallowed and enters airways

**Inhalation**

May cause drowsiness or dizziness

**Product Code 400.0000500.076**

Page 5 / 9

WPNA - CANADA WHMIS SDS

**Numerical measures of toxicity - Component Information**

| Chemical Name                          | Oral LD50             | Dermal LD50             | Inhalation LC50                    |
|----------------------------------------|-----------------------|-------------------------|------------------------------------|
| Quartz                                 | = 500 mg/kg ( Rat )   | -                       | -                                  |
| Naphtha, petroleum, hydrotreated heavy | > 5000 mg/kg ( Rat )  | > 3160 mg/kg ( Rabbit ) | -                                  |
| Propane                                | -                     | -                       | = 658 mg/L ( Rat ) 4 h             |
| Naphtha, petroleum, hydrotreated heavy | > 5000 mg/kg ( Rat )  | > 3160 mg/kg ( Rabbit ) | -                                  |
| Naphtha, petroleum, light alkylate     | > 7000 mg/kg ( Rat )  | > 2000 mg/kg ( Rabbit ) | > 5.04 mg/L ( Rat ) 4 h            |
| Butane                                 | -                     | -                       | = 658 g/m <sup>3</sup> ( Rat ) 4 h |
| Titanium dioxide                       | > 10000 mg/kg ( Rat ) | -                       | -                                  |

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

|                                                           |                                                                   |
|-----------------------------------------------------------|-------------------------------------------------------------------|
| <b>Skin corrosion/irritation</b>                          | Causes skin irritation                                            |
| <b>Serious eye damage/eye irritation</b>                  | Not applicable                                                    |
| <b>Skin sensitization</b>                                 | Not applicable                                                    |
| <b>Respiratory sensitization</b>                          | Not applicable                                                    |
| <b>Germ cell mutagenicity</b>                             | Not applicable                                                    |
| <b>Carcinogenicity</b>                                    | May cause cancer                                                  |
| <b>Reproductive Toxicity</b>                              | Not applicable                                                    |
| <b>Specific target organ toxicity (single exposure)</b>   | May cause drowsiness or dizziness                                 |
| <b>Specific target organ toxicity (repeated exposure)</b> | May cause damage to organs through prolonged or repeated exposure |
| <b>Aspiration hazard</b>                                  | Not applicable                                                    |

**Carcinogenicity**

According to IARC, Volume 93, no significant exposure to primary particles of titanium dioxide is thought to occur from use in paints since the pigment is bound to other materials.

| Chemical Name    | ACGIH | IARC     | NTP   | OSHA |
|------------------|-------|----------|-------|------|
| Quartz           | A2    | Group 1  | Known | X    |
| Titanium dioxide |       | Group 2B |       | X    |

**ACGIH (American Conference of Governmental Industrial Hygienists)**

A2 - Suspected Human Carcinogen

**IARC (International Agency for Research on Cancer)**

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

**NTP (National Toxicology Program)**

Known - Known Carcinogen

**OSHA (Occupational Safety and Health Administration of the US Department of Labor)**

X - Present

**Section 12: ECOLOGICAL INFORMATION****Ecotoxicity**

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

This product contains a chemical which is listed as a marine pollutant according to DOT.

Marine pollutant                      This material meets the definition of a marine pollutant

Environmental precautions                      Prevent product from entering drains.

| Chemical Name                          | Algae/aquatic plants | Fish                                     | Crustacea |
|----------------------------------------|----------------------|------------------------------------------|-----------|
| Quartz                                 | -                    | -                                        | -         |
| Naphtha, petroleum, hydrotreated heavy | -                    | = 2200 mg/L Pimephales promelas 96h LC50 | -         |

**Product Code 400.0000500.076**

Page 6 / 9

WPNA - CANADA WHMIS SDS

|                                        |                                                        |                                          |                                    |
|----------------------------------------|--------------------------------------------------------|------------------------------------------|------------------------------------|
| Propane                                | -                                                      | -                                        | -                                  |
| Naphtha, petroleum, hydrotreated heavy | -                                                      | = 2200 mg/L Pimephales promelas 96h LC50 | -                                  |
| Naphtha, petroleum, light alkylate     | = 30000 mg/L Pseudokirchneriella subcapitata 72 h EC50 | -                                        | = 2 mg/L Mysidopsis bahia 48h LC50 |
| Butane                                 | -                                                      | -                                        | -                                  |
| Titanium dioxide                       | -                                                      | -                                        | -                                  |

**Persistence and degradability** No information available.

**Bioaccumulation** No information available.

**Mobility** No information available.

| Chemical Name                          | Partition Coefficient (n-octanol/water) |
|----------------------------------------|-----------------------------------------|
| Quartz                                 | -                                       |
| Naphtha, petroleum, hydrotreated heavy | -                                       |
| Propane                                | 2.3                                     |
| Naphtha, petroleum, hydrotreated heavy | -                                       |
| Naphtha, petroleum, light alkylate     | -                                       |
| Butane                                 | 2.89                                    |
| Titanium dioxide                       | -                                       |

### Section 13: DISPOSAL CONSIDERATIONS

**Waste from residues/unused products** Disposal should be in accordance with applicable regional, national and local laws and regulations

**Contaminated packaging** Improper disposal or reuse of this container may be dangerous and illegal.

### Section 14: TRANSPORT INFORMATION

|                             | <u><b>TDG</b></u> | <u><b>IMDG</b></u> | <u><b>IATA</b></u> |
|-----------------------------|-------------------|--------------------|--------------------|
| <b>UN/ID no</b>             | UN1950            | UN1950             | UN1950             |
| <b>Proper shipping name</b> | Aerosols          | Aerosols           | Aerosols           |

**Hazard Class** 2.1 2.1 2.1

**Packing Group**

**Environmental hazard** Yes

**Marine pollutant** This material meets the definition of a marine pollutant

**Marine pollutant** Naphtha, petroleum, hydrotreated heavy

**Special Provisions**

**EmS-No**  
F-D, S-U

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

No information available

### Section 15: REGULATORY INFORMATION

#### International Inventories

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

All components are listed or exempt from listing

**DSL** - Canadian Domestic Substances List

All components are listed or exempt from listing

**This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR**

#### **WHMIS Hazard Class**

B5 - Flammable aerosol

A Compressed gases

D2A - Very toxic materials

D2B - Toxic materials

**Product Code 400.0000500.076**

Page 7 / 9

WPNA - CANADA WHMIS SDS



| Chemical Name                          | Canada - 2013 NPRI (National Pollutant Release Inventory) |
|----------------------------------------|-----------------------------------------------------------|
| Naphtha, petroleum, hydrotreated heavy | Part 5, Other Groups and Mixtures                         |
| Propane                                | Part 5, Individual Substances                             |
| Naphtha, petroleum, hydrotreated heavy | Part 5, Other Groups and Mixtures                         |
| Butane                                 | Part 5, Isomer Groups Part 4 Substance                    |

### GHS - Classification

|                                                    |               |
|----------------------------------------------------|---------------|
| Skin corrosion/irritation                          | Category 2    |
| Carcinogenicity                                    | Category 1A   |
| Specific target organ toxicity (single exposure)   | Category 3    |
| Specific target organ toxicity (repeated exposure) | Category 2    |
| Aspiration toxicity                                | Category 1    |
| Flammable aerosols                                 | Category 2    |
| Gases under pressure                               | Liquefied gas |

### Label elements



Signal word

**DANGER**

### **HAZARD STATEMENTS**

Flammable aerosol  
 Contains gas under pressure; may explode if heated  
 Causes skin irritation  
 May cause cancer  
 May cause drowsiness or dizziness  
 May cause damage to organs through prolonged or repeated exposure  
 May be fatal if swallowed and enters airways

### **PREVENTION**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Wash face, hands and any exposed skin thoroughly after handling. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

### **RESPONSE**

IF exposed or concerned: Get medical advice/attention.

#### **Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

#### **Skin**

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

#### **Inhalation**

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

**Product Code 400.0000500.076**

Page 8 / 9

WPNA - CANADA WHMIS SDS



### Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

### STORAGE

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 122 °F (50 °C).

### DISPOSAL

Dispose of contents/containers in accordance with local regulations.

### HAZARDS NOT OTHERWISE CLASSIFIED (HNOC)

Propellant is classified as a simple asphyxiant if released in large quantities: May displace oxygen and cause rapid suffocation.

### OTHER HAZARDS

Toxic to aquatic life with long lasting effects.

**UNKNOWN ACUTE TOXICITY** 0% of the mixture consists of ingredient(s) of unknown toxicity.

## Section 16: OTHER INFORMATION

### HMIS

**Health hazards** 3\*

\* = Chronic Health Hazard

**Flammability** 4

**Physical hazards** 0

**Personal Protection** X

### Supplier Address

|                                                                     |                                                                                    |                                                                                          |
|---------------------------------------------------------------------|------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|
| Valspar Consumer Headquarters                                       | The Valspar Corporation<br>4999 36th St.<br>Grand Rapids, MI 49512<br>800-253-3957 | Valspar Plasti-Kote<br>1636 Shawsone Dr.<br>Mississauga, Ontario L4W 1N7<br>905-671-8333 |
| 8725 W. Higgins Rd. Suite 1000<br>Chicago, IL 60631<br>773-628-5500 |                                                                                    |                                                                                          |

**Prepared By** Product Stewardship

**Revision date** 02-Nov-2015

**Revision Note** No information available

### Disclaimer

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

**End of Safety Data Sheet**