Valvoline	Page: 1
SAFETY DATA SHEET	Revision Date: 10/14/2016
	Print Date: 2/21/2017
	SDS Number: R0200299
Durablend™ Dexron III/Mercon	Version: 1.17
381316	

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Valvoline Canada CorpRegulatory Information Number1-800-TEAMVAL905 Winston Churchill BlvdTelephone1-800-TEAMVALMississauga ON L5J 4P2Emergency telephone number1-800-VALVOLINE

Product name Durablend™ Dexron III/Mercon

Product code 381316

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid, red

MAY CAUSE EYE IRRITATION.

Potential Health Effects

Exposure routes

Inhalation, Skin contact, Eye Contact, Ingestion

Eve contact

Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes.

Skin contact

Unlikely to cause skin irritation or injury.

Ingestion

Swallowing this material is not likely to be harmful.

Inhalation

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material:, Skin, lung (for example, asthma-like conditions)

Symptoms

Valvoline	Page: 2
SAFETY DATA SHEET	Revision Date: 10/14/2016
	Print Date: 2/21/2017
	SDS Number: R0200299
Durablend™ Dexron III/Mercon	Version: 1.17
381316	

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:, stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways)

Target Organs

No data.

Carcinogenicity

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA). Used motor oil has been shown to cause skin cancer in laboratory animals continually exposed by repeated applications. Avoid prolonged or repeated skin contact.

Reproductive hazard

There are no data available for assessing risk to the fetus from maternal exposure to this material. There are no data available for assessing risk to the fetus from maternal exposure to this material., Based on the available information, risk to the fetus from maternal exposure to this material cannot be assessed.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components	CAS-No. / Trade Secret No.	Concentration
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	>=10-<15%
METHACRYLATE COPOLYMER		>=1.5-<5%

Hazardous Components	CAS-No. / Trade Secret No.	Concentration
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	>=10-<15%
METHACRYLATE COPOLYMER		>=1.5-<5%

4. FIRST AID MEASURES

General Information

No hazards which require special first aid measures.

Eyes

Remove contact lenses. Protect unharmed eye.

Skin

Valvoline	Page: 3
SAFETY DATA SHEET	Revision Date: 10/14/2016
	Print Date: 2/21/2017
	SDS Number: R0200299
Durablend™ Dexron III/Mercon	Version: 1.17
381316	

First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.

Ingestion

Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.

Inhalation

If breathed in, move person into fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.

Notes to physician

Hazards: Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

Treatment: No hazards which require special first aid measures.

5. FIREFIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment., Water spray, Foam, Carbon dioxide (CO2), Dry chemical

Hazardous combustion products

carbon dioxide and carbon monoxide, Hydrocarbons

Precautions for fire-fighting

Do not allow run-off from fire fighting to enter drains or water courses. In the event of fire, wear self-contained breathing apparatus. Standard procedure for chemical fires.

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions

Prevent further leakage or spillage if safe to do so.

Valvoline	Page: 4
SAFETY DATA SHEET	Revision Date: 10/14/2016
	Print Date: 2/21/2017
	SDS Number: R0200299
Durablend™ Dexron III/Mercon	Version: 1.17
381316	

Methods for cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

Other information

Comply with all applicable federal, state, and local regulations.

7. HANDLING AND STORAGE

Handling

Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8. Normal measures for preventive fire protection.

Storage

No decomposition if stored and applied as directed.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

HYDROTREATED LIGHT	PARAFFINIC DISTILLATE	64742-55-8		
ZCAAB_OEL	8-hour Occupational exposure limit	5 mg/m3	Mist	
ZCAAB_OEL	15-minute occupational exposure limit	10 mg/m3	Mist	
ZCAQC_OEL	Time-weighted average exposure value	5 mg/m3	Mist	
ZCAQC_OEL	Short-term exposure value	10 mg/m3	Mist	
ZCABC_OEL	8-hour time weighted average	1 mg/m3	Mist	
HEAVY PARAFFINIC DIS	TILLATE	64742-54-7		

HYDROTREATED LIGHT	PARAFFINIC DISTILLATE	64742-55-8		
ZCAAB_OEL	8-hour Occupational exposure limit	5 mg/m3	Mist	_
ZCAAB_OEL	15-minute occupational exposure limit	10 mg/m3	Mist	
ZCAQC_OEL	Time-weighted average exposure value	5 mg/m3	Mist	
ZCAQC_OEL	Short-term exposure value	10 mg/m3	Mist	
ZCABC_OEL	8-hour time weighted	1 mg/m3	Mist	

Valvoline	Page: 5
SAFETY DATA SHEET	Revision Date: 10/14/2016
	Print Date: 2/21/2017
	SDS Number: R0200299
Durablend™ Dexron III/Mercon	Version: 1.17
381316	

a١	ra	α	2

HEAVY PARAFFINIC DISTILLATE	64742-54-7

General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

General industrial hygiene practice.

Exposure controls

General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Eye protection

Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection

Wear as appropriate:

Safety shoes

Wear resistant gloves (consult your safety equipment supplier).

Respiratory protection

No personal respiratory protective equipment normally required.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Colour	red
Odour	hydrocarbon-like
Boiling point/boiling range	/ No data available
pH	No data available
Flash point	> 390 °F / > 199 °C Cleveland open cup
Evaporation rate	(>)1 Ethyl Ether
Lower explosion limit/Upper explosion limit	1 %(V) / 6 %(V) Calculated Explosive Limit
Vapour pressure	0.013 hPa @ 70.00 °F / 21.11 °C Calculated Vapor
	Pressure
Density	0.862 g/cm3 @ 60.01 °F / 15.56 °C
	7.29 lb/gal @ 60.00 °F / 15.56 °C
Water solubility	No data available
•	

Valvoline	Page: 6
SAFETY DATA SHEET	Revision Date: 10/14/2016
	Print Date: 2/21/2017
	SDS Number: R0200299
Durablend™ Dexron III/Mercon	Version: 1.17
381316	

Solubility(ies)	No data available
Auto-ignition temperature	No data available
Viscosity, dynamic	No data available
Viscosity, kinematic	(ca.)43 mm2/s @ 40 °C
Decomposition temperature	
·	No data available

10. STABILITY AND REACTIVITY

Stability

Stable under recommended storage conditions.

Conditions to avoid

excessive heat

Incompatible products

Strong oxidizing agents

Hazardous decomposition products

carbon dioxide and carbon monoxide, Hydrocarbons

Hazardous reactions

Product will not undergo hazardous polymerization.

Thermal decomposition

No data available

11. TOXICOLOGICAL INFORMATION

Information on likely routes of

exposure

: Inhalation

Skin contact Eye Contact Ingestion

Product

Acute oral toxicity : No data available

Acute inhalation toxicity : No data available

Acute dermal toxicity : No data available

Valvoline	Page: 7
SAFETY DATA SHEET	Revision Date: 10/14/2016
	Print Date: 2/21/2017
	SDS Number: R0200299
Durablend™ Dexron III/Mercon	Version: 1.17
381316	

Skin corrosion/irritation : No data available

Serious eye damage/eye

irritation

Unlikely to cause eye irritation or injury.

Respiratory or skin sensitisation : Classification: Does not cause skin sensitisation.

Expected based on components.

Aspiration toxicity : No aspiration toxicity classification

Further information : No data available

Components:

No data available

12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

No data available

Components:

No data available

Persistence and degradability

Product:

No data available

Components:

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-

: No data available

octanol/water Components:

No data available

Valvoline	Page: 8
SAFETY DATA SHEET	Revision Date: 10/14/2016
	Print Date: 2/21/2017
	SDS Number: R0200299
Durablend™ Dexron III/Mercon	Version: 1.17
381316	

Mobility in soil

Product:

No data available

Components:

No data available

Other adverse effects

Product:

Additional ecological information : No data available

13. DISPOSAL CONSIDERATIONS

Waste disposal methods

Dispose of in accordance with all applicable local, state and federal regulations. Empty remaining contents.

14. TRANSPORT INFORMATION

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT /
					LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

Valvoline	Page: 9
SAFETY DATA SHEET	Revision Date: 10/14/2016
	Print Date: 2/21/2017
	SDS Number: R0200299
Durablend™ Dexron III/Mercon	Version: 1.17
381316	

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

15. REGULATORY INFORMATION

WHMIS Classification

D2B Toxic Material Causing Other Toxic Effects



This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

Valvoline	Page: 10
SAFETY DATA SHEET	Revision Date: 10/14/2016
	Print Date: 2/21/2017
	SDS Number: R0200299
Durablend™ Dexron III/Mercon	Version: 1.17
381316	

Canadian National Pollutant Release Inventory (NPRI)Canadian National Pollutant Release Inventory (NPRI): No component is listed on NPRI.Canadian National Pollutant Release Inventory (NPRI): No component is listed on NPRI.

Notification status

United States TSCA Inventory	y (positive listing)
Canadian Domestic Substances List (DSL)	y (positive listing)
Australia Inventory of Chemical Substances (AICS)	y (positive listing)
Japan. ENCS - Existing and New Chemical Substances Inventory	y (positive listing)
Korea. Korean Existing Chemicals Inventory (KECI)	y (positive listing)
Philippines Inventory of Chemicals and Chemical Substances (PICCS)	y (positive listing)
China. Inventory of Existing Chemical Substances in China (IECSC)	y (positive listing)

	HMIS	NFPA
Health	1	1
Flammability	1	1
Physical hazards	0	
Instability		0
Specific Hazard	-	

16. OTHER INFORMATION

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet:

ACGIH: American Conference of Industrial Hygienists

BEI: Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Valvoline.	Page: 11
SAFETY DATA SHEET	Revision Date: 10/14/2016
	Print Date: 2/21/2017
	SDS Number: R0200299
Durablend™ Dexron III/Mercon	Version: 1.17
381316	

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV : Threshold Limit Value TWA : Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

DOT: Department of Transportation

FIFRA: Federal Insecticide, Fungicide, and Rodenticide Act HMIRC: Hazardous Materials Information Review Commission

HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety and Health Administration

PMRA: Health Canada Pest Management Regulatory Agency

RTK: Right to Know

WHMIS: Workplace Hazardous Materials Information System