



Safety Data Sheet

Copyright, 2014 Meguiar's, Inc.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Meguiar's, Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's, Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	27-6203-7	Version Number:	4.00
Issue Date:	05/19/14	Supersedes Date:	05/22/13

SECTION 1: Identification

1.1. Product identifier

G12711, NXT Paste Wax 2.0 (21-135A): G12711

Product Identification Numbers

14-1000-0519-9, 14-1000-0521-5, 14-1000-0522-3, 14-1000-0525-6

1.2. Recommended use and restrictions on use

Recommended use

Automotive, Paste wax

1.3. Supplier's details

MANUFACTURER:	Meguiar's, Inc.
DIVISION:	Meguiar's
ADDRESS:	17991 Mitchell South, Irvine, CA 92614, USA
Telephone:	949-752-8000 (Fax: 949-752-5784)

1.4. Emergency telephone number

CHEMTREC 1-800-424-9300 (24 hours)

SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

2.1. Hazard classification

Flammable Solid: Category 1.

Skin Corrosion/Irritation: Category 2.

Specific Target Organ Toxicity (central nervous system): Category 3.

2.2. Label elements

Signal word

Danger

Symbols

Flame | Exclamation mark |

Pictograms



Hazard Statements

Flammable solid.

Causes skin irritation.

May cause drowsiness or dizziness.

Precautionary Statements

General:

Keep out of reach of children.

Prevention:

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves and eye/face protection.

Wash thoroughly after handling.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Call a POISON CENTER or doctor/physician if you feel unwell.

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

Storage:

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified

None.

15% of the mixture consists of ingredients of unknown acute oral toxicity.

24% of the mixture consists of ingredients of unknown acute dermal toxicity.

56% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Petroleum Distillate	64742-48-9	30 - 50 Trade Secret *
Poly(Dimethylsiloxane)	63148-62-9	10 - 30 Trade Secret *
Organic Salt (NJTSRN 04499600-6842)	Trade Secret*	10 - 30 Trade Secret *
Calcined Clay	66402-68-4	7 - 13 Trade Secret *
Fatty acids, montan-wax, ethylene esters	73138-45-1	5 - 10 Trade Secret *
Trimethylated Silica	68988-56-7	1 - 5 Trade Secret *
Petroleum Distillate	64742-47-8	1 - 5 Trade Secret *
Conditioners	Trade Secret*	< 5 Trade Secret *
Silicone Alkylmethyl Glycol	212335-52-9	0.5 - 1.5 Trade Secret *
1-Propoxy-2-Propanol	1569-01-3	0.1 - 1.0 Trade Secret *

NJTS or NJTSRN: New Jersey Trade Secret Registry Number.

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Formaldehyde	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Irritant Vapors or Gases	During Combustion

5.3. Special protective actions for fire-fighters

No unusual fire or explosion hazards are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Petroleum Distillate	64742-47-8	Chemical Manufacturer Rec Guid	TWA:165 ppm	
Petroleum Distillate	64742-48-9	Manufacturer determined	TWA:100 ppm	

Amer Conf of Gov. Indust. Hyg. : American Conference of Governmental Industrial Hygienists

American Indust. Hygiene Assoc : American Industrial Hygiene Association
 Chemical Manufacturer Rec Guid : Chemical Manufacturer's Recommended Guidelines
 US Dept of Labor - OSHA : United States Department of Labor - Occupational Safety and Health Administration
 TWA: Time-Weighted-Average
 STEL: Short Term Exposure Limit
 CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Wear eye/face protection. Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
 Safety Glasses with side shields

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Wear protective gloves.

Gloves made from the following material(s) are recommended: Neoprene
 Nitrile Rubber

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form:	Solid
Specific Physical Form:	Paste
Odor, Color, Grade:	Pleasant odor; Soft, waxy, cream-colored paste
Odor threshold	<i>No Data Available</i>
pH	<i>Not Applicable</i>
Melting point	<i>Not Applicable</i>
Boiling Point	365 °F
Flash Point	150 °F [<i>Test Method: Pensky-Martens Closed Cup</i>]
Evaporation rate	<i>No Data Available</i>
Flammability (solid, gas)	Flammable Solid: Category 1.
Flammable Limits(LEL)	<i>No Data Available</i>
Flammable Limits(UEL)	<i>No Data Available</i>

Vapor Pressure	No Data Available
Vapor Density	No Data Available
Density	0.86 g/cm ³
Specific Gravity	0.86 [Ref Std: WATER=1]
Solubility in Water	Nil
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Viscosity	>=100 centipoise
Volatile Organic Compounds	44.6 % weight

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

Sparks and/or flames

10.5. Incompatible materials

Strong acids

Strong oxidizing agents

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

May be harmful if inhaled.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause target organ effects after inhalation.

Skin Contact:

May be harmful in contact with skin.

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause target organ effects after ingestion.

Target Organ Effects:

Single exposure may cause:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE 2,000 - 5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE 20 - 50 mg/l
Overall product	Ingestion		No data available; calculated ATE > 5,000 mg/kg
Petroleum Distillate	Inhalation-Vapor		LC50 estimated to be 20 - 50 mg/l
Petroleum Distillate	Dermal	Rabbit	LD50 > 3,000 mg/kg
Petroleum Distillate	Ingestion	Rat	LD50 > 5,000 mg/kg
Poly(Dimethylsiloxane)	Dermal	Rabbit	LD50 > 19,400 mg/kg
Poly(Dimethylsiloxane)	Ingestion	Rat	LD50 > 17,000 mg/kg
Calcined Clay	Dermal		LD50 estimated to be > 5,000 mg/kg
Calcined Clay	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Fatty acids, montan-wax, ethylene esters	Ingestion	Rat	LD50 > 2,000 mg/kg
Petroleum Distillate	Dermal	Rabbit	LD50 > 3,160 mg/kg
Petroleum Distillate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 3.0 mg/l
Petroleum Distillate	Ingestion	Rat	LD50 > 5,000 mg/kg
Conditioners	Ingestion	Rat	LD50 > 15,000 mg/kg
1-Propoxy-2-Propanol	Dermal	Rabbit	LD50 2,805 mg/kg
1-Propoxy-2-Propanol	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 11.8 mg/l
1-Propoxy-2-Propanol	Ingestion	Rat	LD50 2,500 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Petroleum Distillate	Rabbit	Irritant
Poly(Dimethylsiloxane)	Rabbit	No significant irritation
Calcined Clay	Rabbit	No significant irritation
Petroleum Distillate	Rabbit	Mild irritant
1-Propoxy-2-Propanol	Rabbit	Minimal irritation

Serious Eye Damage/Irritation

Name	Species	Value
Petroleum Distillate	Rabbit	No significant irritation
Poly(Dimethylsiloxane)	Rabbit	No significant irritation
Calcined Clay	Rabbit	Mild irritant
Petroleum Distillate	Rabbit	Mild irritant
1-Propoxy-2-Propanol	Rabbit	Severe irritant

Skin Sensitization

Name	Species	Value
Petroleum Distillate	Guinea pig	Not sensitizing
Petroleum Distillate	Guinea pig	Not sensitizing

Respiratory Sensitization

Name	Species	Value

Germ Cell Mutagenicity

Name	Route	Value
Petroleum Distillate	In vivo	Not mutagenic
Petroleum Distillate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Calcined Clay	In Vitro	Some positive data exist, but the data are not sufficient for classification
Petroleum Distillate	In Vitro	Not mutagenic
1-Propoxy-2-Propanol	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Petroleum Distillate	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Petroleum Distillate	Inhalation	Human and animal	Some positive data exist, but the data are not sufficient for classification
Calcined Clay	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Petroleum Distillate	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Petroleum Distillate	Inhalation	Not toxic to development	Rat	NOAEL 2.4 mg/l	during organogenesis
1-Propoxy-2-Propanol	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 3.6 mg/l	during organogenesis

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Petroleum Distillate	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Petroleum Distillate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Petroleum Distillate	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 6.5 mg/l	4 hours
Petroleum Distillate	Inhalation	central nervous system depression	May cause drowsiness or dizziness		NOAEL Not available	
Petroleum Distillate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
1-Propoxy-2-Propanol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	LOAEL 10.8 mg/l	6 hours
1-Propoxy-2-Propanol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
1-Propoxy-2-Propanol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	LOAEL 1,770 mg/kg	not applicable

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Petroleum Distillate	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 4.6 mg/l	6 months
Petroleum Distillate	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 1.9 mg/l	13 weeks
Petroleum Distillate	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL 0.6 mg/l	90 days
Petroleum Distillate	Inhalation	bone, teeth, nails, and/or hair blood liver muscles	All data are negative	Rat	NOAEL 5.6 mg/l	12 weeks
Petroleum Distillate	Inhalation	heart	All data are negative	Multiple animal species	NOAEL 1.3 mg/l	90 days
Calcined Clay	Inhalation	pulmonary fibrosis	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL not available	
Calcined Clay	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL not available	occupational exposure
1-Propoxy-2-Propanol	Inhalation	liver kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 9.5 mg/l	11 days

Aspiration Hazard

Name	Value
Petroleum Distillate	Aspiration hazard
Petroleum Distillate	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information**DOTG:**

LIMITED QUANTITY

DOTW:

UN1325, FLAMMABLE SOLID, ORGANIC, N.O.S., (HYDROTREATED HEAVY NAPHTHA (PETROLEUM) AND HYDROTREATED LIGHT PETROLEUM DISTILLATES), 4.1, II, LIMITED QUANTITY

IATA:

UN1325, FLAMMABLE SOLID, ORGANIC, N.O.S., (HYDROTREATED HEAVY NAPHTHA (PETROLEUM) AND HYDROTREATED LIGHT PETROLEUM DISTILLATES), 4.1, II

IMO:

UN1325, FLAMMABLE SOLID, ORGANIC, N.O.S., (HYDROTREATED HEAVY NAPHTHA (PETROLEUM) AND HYDROTREATED LIGHT PETROLEUM DISTILLATES), 4.1, II, LIMITED QUANTITY

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

SECTION 15: Regulatory information**15.1. US Federal Regulations**

Contact manufacturer for more information

311/312 Hazard Categories:

Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

15.2. State Regulations

Contact manufacturer for more information

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact manufacturer for more information

15.4. International Regulations

Contact manufacturer for more information

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 Flammability: 2 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	27-6203-7	Version Number:	4.00
Issue Date:	05/19/14	Supersedes Date:	05/22/13

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. Meguiar's, Inc. MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Meguiar's, Inc. product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a Meguiar's, Inc. product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Meguiar's, Inc. product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

Meguiar's, Inc. provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, Meguiar's, Inc. makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from Meguiar's, Inc.

Meguiar's, Inc. USA SDSs are available at www.Meguiars.com