



Safety Data Sheet

Copyright, 2014 Meguiar's, Inc.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Meguiar's, Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's, Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|------------------------|-----------|-------------------------|----------|
| Document Group: | 28-4877-8 | Version Number: | 8.00 |
| Issue Date: | 04/01/14 | Supersedes Date: | 05/22/13 |

SECTION 1: Identification

1.1. Product identifier

M08, Mirror Glaze Maximum Mold Release Wax (23-135A): M0811

Product Identification Numbers

14-1000-1167-6

1.2. Recommended use and restrictions on use

Recommended use

Release agent

1.3. Supplier's details

| | |
|----------------------|---|
| MANUFACTURER: | Meguiar's, Inc. |
| DIVISION: | Meguiar's |
| ADDRESS: | 17991 Mitchell South, Irvine, CA 92614, USA |
| Telephone: | 949-752-8000 (Fax: 949-752-5784) |

1.4. Emergency telephone number

CHEMTREC 1-800-424-9300 (24 hours)

SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

2.1. Hazard classification

Flammable Solid: Category 1.

Skin Corrosion/Irritation: Category 2.

Skin Sensitizer: Category 1.

Specific Target Organ Toxicity (central nervous system): Category 3.

2.2. Label elements

Signal word

Danger

Symbols

Flame | Exclamation mark |

Pictograms



Hazard Statements

Flammable solid.

Causes skin irritation.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

Precautionary Statements

General:

Keep out of reach of children.

Prevention:

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves and eye/face protection.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Call a POISON CENTER or doctor/physician if you feel unwell.

In case of fire: Use a fire fighting agent suitable for flammable liquids and solids such as dry chemical or carbon dioxide to extinguish.

Storage:

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified

None.

28% of the mixture consists of ingredients of unknown acute oral toxicity.

48% of the mixture consists of ingredients of unknown acute dermal toxicity.

76% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|---|---------------|------------------------|
| PETROLEUM DISTILLATES | 64742-47-8 | 10 - 30 Trade Secret * |
| PETROLEUM DISTILLATES | 64742-48-9 | 10 - 30 Trade Secret * |
| CONDITIONERS | Trade Secret* | < 20 Trade Secret * |
| POLY(METHYLENE), OXIDIZED, LITHIUM SALT | 68649-48-9 | 7 - 13 Trade Secret * |
| POLY(DIMETHYLSILOXANE) | 63148-62-9 | 5 - 10 Trade Secret * |
| PARAFFIN WAX | 8002-74-2 | 5 - 10 Trade Secret * |
| BETA-PINENE | 127-91-3 | 5 - 10 Trade Secret * |
| ALPHA-PINENE | 80-56-8 | 5 - 10 Trade Secret * |
| OTHER TERPENES | Mixture | 1 - 5 Trade Secret * |

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for flammable liquids and solids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-ProductsSubstance

Carbon monoxide
Carbon dioxide
Irritant Vapors or Gases

Condition

During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

No unusual fire or explosion hazards are anticipated.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Decontaminate work surfaces frequently to avoid exposure by contact. Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

Occupational exposure limits

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|-----------------------|-------------------|--------------------------------|--|----------------------------|
| BETA-PINENE | 127-91-3 | Amer Conf of Gov. Indust. Hyg. | TWA:20 ppm | Sensitizer |
| Kerosine (petroleum) | 64742-47-8 | Amer Conf of Gov. Indust. Hyg. | TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m3 | Skin Notation |
| PETROLEUM DISTILLATES | 64742-47-8 | Chemical Manufacturer Rec Guid | TWA:165 ppm | |
| PETROLEUM DISTILLATES | 64742-48-9 | Manufacturer determined | TWA:100 ppm | |
| ALPHA-PINENE | 80-56-8 | Amer Conf of Gov. Indust. Hyg. | TWA:20 ppm | Sensitizer |
| PARAFFIN WAX | 8002-74-2 | Amer Conf of Gov. Indust. Hyg. | TWA(as fume):2 mg/m3 | |

Amer Conf of Gov. Indust. Hyg. : American Conference of Governmental Industrial Hygienists

American Indust. Hygiene Assoc : American Industrial Hygiene Association

Chemical Manufacturer Rec Guid : Chemical Manufacturer's Recommended Guidelines

US Dept of Labor - OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls**8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)**Eye/face protection**

Wear eye/face protection. Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety Glasses with side shields

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Nitrile Rubber

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Nitrile

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--|---|
| General Physical Form: | Solid |
| Specific Physical Form: | Paste |
| Odor, Color, Grade: | Pleasant odor; Gold paste |
| Odor threshold | <i>No Data Available</i> |
| pH | <i>Not Applicable</i> |
| Melting point | <i>Not Applicable</i> |
| Boiling Point | <i>Not Applicable</i> |
| Flash Point | 150 °F [<i>Test Method: Pensky-Martens Closed Cup</i>] [<i>Details: D93-90</i>] |
| Evaporation rate | <i>No Data Available</i> |
| Flammability (solid, gas) | Flammable Solid: Category 1. Flammable Solid: Category 1. |
| Flammable Limits(LEL) | <i>No Data Available</i> |
| Flammable Limits(UEL) | <i>No Data Available</i> |
| Vapor Pressure | <i>No Data Available</i> |
| Vapor Density | <i>No Data Available</i> |
| Density | 0.86 g/cm ³ |
| Specific Gravity | 0.86 [<i>Ref Std: WATER=1</i>] |
| Solubility in Water | Nil |
| Solubility- non-water | <i>No Data Available</i> |
| Partition coefficient: n-octanol/ water | <i>No Data Available</i> |
| Autoignition temperature | <i>No Data Available</i> |
| Decomposition temperature | <i>No Data Available</i> |
| Viscosity | >=100 centipoise |
| Volatile Organic Compounds | 65.34 % weight |
| VOC Less H₂O & Exempt Solvents | 561.89 g/l |

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat
Sparks and/or flames

10.5. Incompatible materials

Strong acids
Strong bases
Strong oxidizing agents

10.6. Hazardous decomposition products

| <u>Substance</u> | <u>Condition</u> |
|------------------|------------------|
| None known. | |

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

May be harmful if inhaled.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause target organ effects after inhalation.

Skin Contact:

May be harmful in contact with skin.

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.
Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause target organ effects after ingestion.

Target Organ Effects:**Single exposure may cause:**

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|------------------------|--------------------------------|---------|---|
| Overall product | Dermal | | No data available; calculated ATE 2,000 - 5,000 mg/kg |
| Overall product | Inhalation-Vapor(4 hr) | | No data available; calculated ATE 20 - 50 mg/l |
| Overall product | Ingestion | | No data available; calculated ATE > 5,000 mg/kg |
| PETROLEUM DISTILLATES | Inhalation-Vapor | | LC50 estimated to be 20 - 50 mg/l |
| PETROLEUM DISTILLATES | Dermal | Rabbit | LD50 > 3,000 mg/kg |
| PETROLEUM DISTILLATES | Ingestion | Rat | LD50 > 5,000 mg/kg |
| PETROLEUM DISTILLATES | Dermal | Rabbit | LD50 > 3,160 mg/kg |
| PETROLEUM DISTILLATES | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 3.0 mg/l |
| PETROLEUM DISTILLATES | Ingestion | Rat | LD50 > 5,000 mg/kg |
| CONDITIONERS | Ingestion | | LD50 estimated to be > 5,000 mg/kg |
| PARAFFIN WAX | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| PARAFFIN WAX | Ingestion | Rat | LD50 > 5,000 mg/kg |
| POLY(DIMETHYLSILOXANE) | Dermal | Rabbit | LD50 > 19,400 mg/kg |
| POLY(DIMETHYLSILOXANE) | Ingestion | Rat | LD50 > 17,000 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|------------------------|---------------|---------------------------|
| PETROLEUM DISTILLATES | Rabbit | Irritant |
| PETROLEUM DISTILLATES | Rabbit | Mild irritant |
| ALPHA-PINENE | In vitro data | Irritant |
| BETA-PINENE | In vitro data | Irritant |
| POLY(DIMETHYLSILOXANE) | Rabbit | No significant irritation |

Serious Eye Damage/Irritation

| Name | Species | Value |
|------------------------|---------|---------------------------|
| PETROLEUM DISTILLATES | Rabbit | No significant irritation |
| PETROLEUM DISTILLATES | Rabbit | Mild irritant |
| POLY(DIMETHYLSILOXANE) | Rabbit | No significant irritation |

Skin Sensitization

| Name | Species | Value |
|-----------------------|-------------------|-----------------|
| PETROLEUM DISTILLATES | Guinea pig | Not sensitizing |
| PETROLEUM DISTILLATES | Guinea pig | Not sensitizing |
| ALPHA-PINENE | similar compounds | Sensitizing |
| BETA-PINENE | Mouse | Sensitizing |

Respiratory Sensitization

| Name | Species | Value |
|------|---------|-------|
| | | |

Germ Cell Mutagenicity

| Name | Route | Value |
|-----------------------|----------|--|
| PETROLEUM DISTILLATES | In vivo | Not mutagenic |
| PETROLEUM DISTILLATES | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| PETROLEUM DISTILLATES | In Vitro | Not mutagenic |

Carcinogenicity

| Name | Route | Species | Value |
|-----------------------|------------|------------------|--|
| PETROLEUM DISTILLATES | Dermal | Mouse | Some positive data exist, but the data are not sufficient for classification |
| PETROLEUM DISTILLATES | Inhalation | Human and animal | Some positive data exist, but the data are not sufficient for classification |
| PETROLEUM DISTILLATES | Dermal | Mouse | Some positive data exist, but the data are not sufficient for classification |

Reproductive Toxicity**Reproductive and/or Developmental Effects**

| Name | Route | Value | Species | Test Result | Exposure Duration |
|-----------------------|------------|--------------------------|---------|----------------|----------------------|
| PETROLEUM DISTILLATES | Inhalation | Not toxic to development | Rat | NOAEL 2.4 mg/l | during organogenesis |

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|-----------------------|------------|-----------------------------------|--|------------------|---------------------|-------------------|
| PETROLEUM DISTILLATES | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human and animal | NOAEL Not available | |
| PETROLEUM DISTILLATES | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | | NOAEL Not available | |
| PETROLEUM DISTILLATES | Inhalation | nervous system | Some positive data exist, but the data are not sufficient for classification | Dog | NOAEL 6.5 mg/l | 4 hours |
| PETROLEUM DISTILLATES | Inhalation | central nervous system depression | May cause drowsiness or dizziness | | NOAEL Not available | |
| PETROLEUM DISTILLATES | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | | NOAEL Not available | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|-----------------------|------------|-----------------------|--|-------------------------|----------------|-------------------|
| PETROLEUM DISTILLATES | Inhalation | nervous system | Some positive data exist, but the data are not sufficient for classification | Rat | LOAEL 4.6 mg/l | 6 months |
| PETROLEUM DISTILLATES | Inhalation | kidney and/or bladder | Some positive data exist, but the data are not sufficient for classification | Rat | LOAEL 1.9 mg/l | 13 weeks |
| PETROLEUM DISTILLATES | Inhalation | respiratory system | Some positive data exist, but the data are not sufficient for classification | Multiple animal species | NOAEL 0.6 mg/l | 90 days |

| | | | | | | |
|-----------------------|------------|---|-----------------------|-------------------------|----------------|----------|
| PETROLEUM DISTILLATES | Inhalation | bone, teeth, nails, and/or hair blood liver muscles | All data are negative | Rat | NOAEL 5.6 mg/l | 12 weeks |
| PETROLEUM DISTILLATES | Inhalation | heart | All data are negative | Multiple animal species | NOAEL 1.3 mg/l | 90 days |

Aspiration Hazard

| Name | Value |
|-----------------------|-------------------|
| PETROLEUM DISTILLATES | Aspiration hazard |
| PETROLEUM DISTILLATES | Aspiration hazard |
| ALPHA-PINENE | Aspiration hazard |
| BETA-PINENE | Aspiration hazard |

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

DOTG:

LIMITED QUANTITY

DOTW:

UN1325, FLAMMABLE SOLID, ORGANIC, N.O.S., (HYDROTREATED HEAVY NAPHTHA (PETROLEUM) AND HYDROTREATED LIGHT PETROLEUM DISTILLATES), 4.1, II, LIMITED QUANTITY, MARINE POLLUTANT, (ALPHA-PINENE)

IATA:

UN1325, FLAMMABLE SOLID, ORGANIC, N.O.S., (HYDROTREATED HEAVY NAPHTHA (PETROLEUM) AND HYDROTREATED LIGHT PETROLEUM DISTILLATES), 4.1, II

IMO:

UN1325, FLAMMABLE SOLID, ORGANIC, N.O.S., (HYDROTREATED HEAVY NAPHTHA (PETROLEUM) AND HYDROTREATED LIGHT PETROLEUM DISTILLATES), 4.1, II, LIMITED QUANTITY, LIMITED QUANTITY, MARINE POLLUTANT, (ALPHA-PINENE)

ID Number(s):

14-1000-1167-6

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact manufacturer for more information

311/312 Hazard Categories:

Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

15.2. State Regulations

Contact manufacturer for more information

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact manufacturer for more information

15.4. International Regulations

Contact manufacturer for more information

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 **Flammability:** 2 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

| | | | |
|------------------------|-----------|-------------------------|----------|
| Document Group: | 28-4877-8 | Version Number: | 8.00 |
| Issue Date: | 04/01/14 | Supersedes Date: | 05/22/13 |

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. Meguiar's, Inc. MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Meguiar's, Inc. product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a Meguiar's, Inc. product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Meguiar's, Inc. product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

Meguiar's, Inc. provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, Meguiar's, Inc. makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from Meguiar's, Inc.

Meguiar's, Inc. USA SDSs are available at www.Meguiars.com