

1. Identification

Product identifier: ECOTEC

Product code: Amber: 1155, 1156, 1159 Black: 1175, 1176, 1179

Supplier Name: Otoprotec Inc.
3055 Boul. Saint-Martin Ouest, Suite T500
Laval, Qc H7T 0J3

Telephone: 450-663-0505

Emergency telephone number: 450-663-0505

Available hours: 8h-17h

Recommended use: Permanent rustproofing treatment

Restrictions on use: None

2. Hazard identification

Hazard classification: **WARNING**

Product classification:



Skin sensitizer - Category 1B

Hazard statement(s): May cause an allergic skin reaction.

Precautionary statement(s)

Prevention: Avoid breathing mist, vapours, and spray. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, protective clothing, eye and face protection.

Response: IF ON SKIN: Wash with plenty of water and soap. If skin irritation or a rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.



Safety Data Sheet

ECOTEC

Disposal: Keep container tightly closed.

Storage: Dispose of contents/container in accordance with local, regional, national and/or international regulations in force.

Other hazards: No other effects shown.

See toxicological information, section 11

3. Composition/Information on ingredients

No	CAS no	Common name and synonyms	Concentration (W/W)
1	70024-69-0	Alkyd (C16-C24) benzene sulfonate calcium salt	7.50%
2	14808-60-7	Silica, crystalline (Quartz) (C.I. pigment white 27)	0.12%

4. First-aid measures

If swallowed, irritation, any type of overexposure or symptoms of overexposure occur during use of the product or persists after use, immediately contact a POISON CENTER, an EMERGENCY ROOM or a PHYSICIAN; ensure that the product safety data sheet is available.

Eye contact: Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.

Skin contact: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.

Inhalation: Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.

Ingestion: Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.



Safety Data Sheet

ECOTEC

Symptoms: Cough, breathing pain, eye redness and skin edema.

Effects (acute or delayed): May cause irritation of eyes, skin and respiratory tract.

Immediate medical attention and special treatment: No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5. Fire-fighting measures

Suitable extinguishing media: Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media: Jets of water can facilitate the spread of fire.

Specific hazards arising from the hazardous product: No specific hazard.

Hazardous combustion products: Carbon monoxide and dioxide. Sulfur oxides.

Special protective equipment and precautions for fire-fighters: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Protective equipment and emergency procedures: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosionproof equipment. Dispose of via a licensed waste disposal contractor.

7. Handling and storage

Precautions for safe handling: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Avoid exposure - obtain special instructions before use. Avoid contact with eyes, skin and clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Conditions for safe storage: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Incompatibility: Oxidizing agents.

8. Exposure controls/Personal protection

No	CAS no	CAS name	IDHL mg/m3	TWA mg/m3	STEL mg/m3	CEIL mg/m3
1	70024-69-0	Alkyd (C16-C24) benzene sulfonate calcium salt	Not available	Not available	Not available	Not available
2	14808-60-7	Silica, crystalline (Quartz) (C.I. pigment white 27)	50	0.1	Not available	Not available

IDHL: Immediately Dangerous to Life or Health Concentrations

TWA : Time Weighted Average

STEL: Short -Term Exposure Limit

CEIL: Ceiling Limit

IPVS = Inmediatamente peligroso para la vida o la salud

VEPP = Valor de exposición promedio ponderado

VECD = valor de exposición de corta duración

VL = valor límite

Appropriate engineering controls: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eyes: DO NOT WEAR CONTACT LENSES Wear anti-splash safety goggles.

Hands: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties.

Respiratory: If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Others: Wear protective clothing with long sleeves and appropriate safety shoes at all times.

9. Physical and chemical properties

Physical state: Liquid

Colour: Amber or black

Odour: Vegetable oil

Odour threshold: Not available

pH: Not applicable

Melting/Freezing point: Not available

Initial boiling point/boiling range: >200°C (392°F)

Flash point: 315°C (599°F) Close cup

Lower flammable/explosive limit: 0,9% at 25 °C

Upper flammable/explosive limit: 7% at 25 °C

Auto-ignition temperature: 320°C (608°F)

Evaporation rate: Not available

Vapour pressure: Not available

Vapour density: > 1 (air=1)

Relative density: 0,960 kg/L à 20 °C (water = 1)

Solubility in water: Insoluble

Partition coefficient - n-octanol/water: Not available

Decomposition temperature: Not available

Kinematic viscosity: >20,5 mm²/s (à 40 °C)

10. Stability and reactivity

Reactivity: Stable under recommended conditions of storage and handling.

Chemical stability: The product is chemically stable under normal conditions of use.

Possibility of hazardous reactions: No dangerous or polymerization reactions will not occur under normal conditions of use.

Conditions to avoid: Do not pierce or burn, even after use.

Incompatible materials: None known.

Hazardous decomposition products: Carbon monoxide and dioxide. Sulfur oxides.

11. Toxicological information

No	CAS no	CAS name	(1) LD oral	(2) LD skin	(3) LD skin	(4) LC gases	(5) LC vapours	(6) LC dusts-mist
1	70024-69-0	Alkyd (C16-C24) benzene sulfonate calcium salt	Not available	Not available	Not available	Not applicable	Not applicable	>5,00
2	14808-60-7	Silica, crystalline (Quartz) (C.I. pigment white 27)	>2000	Not available	>5000	Not applicable	Not applicable	>5,00

(1) LD₅₀ oral mg/kg

(2) LD₅₀ skin mg/kg

(3) LD₅₀ skin mg/kg

(4) LC₅₀ inhalation ppmV 4h gases

(5) LC₅₀ inhalation mg/l 4h vapours

(6) LC₅₀ inhalation mg/l 4h dusts-mist

Routes of exposure: This product is absorbed through the skin and by the digestive tract.

Symptoms: Cough, breathing pain, eye redness and skin edema.

Delayed and immediate effects: May cause irritation of eyes, skin and respiratory tract.

No	CAS no	CAS name	IARC	ACGIH	Mutagenicity	Effect on reproduction
1	70024-69-0	Alkyd (C16-C24) benzene sulfonate calcium salt	Not available	Not available	Not available.	Not available.
2	14808-60-7	Silica, crystalline (Quartz) (C.I. pigment white 27)	1	A2	No effects shown.	No effects shown.

Cancer classification under IARC (International Agency for Research on Cancer)

Group 1: carcinogenic to humans.

Group 2A: probably carcinogenic to humans.

Group 2B: possibly carcinogenic to humans.

Group 3: not classifiable as to its carcinogenicity to humans.

Group 4: probably not carcinogenic to humans.

Cancer classification under ACGIH (American Conference of Governmental Industrial Hygienists)

Group A1: confirmed human carcinogen.

Group A2: suspected human carcinogen.

Group A3: confirmed animal carcinogen with unknown relevance to humans.

Group A4: not classifiable as a human carcinogen.

Group A5: not suspected as a human carcinogen.

12. Ecological information

No	CAS no	CAS name	%	Persistent	Bio-accumulation	Aquatic ecotoxicity
1	70024-69-0	Alkyd (C16-C24) benzene sulfonate calcium salt	7.50	Yes	No	Uncertain
2	14808-60-7	Silica, crystalline (Quartz) (C.I. pigment white 27)	0.12	Yes	No	No

No	CAS no	CAS name	%	Ecotoxicity for aquatic organisms-Short term	Ecotoxicity for aquatic organisms-Long term	Environmental effects
1	70024-69-0	Alkyd (C16-C24) benzene sulfonate calcium salt	7.50	Not available.	Harmful to aquatic life with long lasting effects.	No known adverse effect to the environment.
2	14808-60-7	Silica, crystalline (Quartz) (C.I. pigment white 27)	0.12	No known adverse effect to aquatic life.	No known adverse effect to aquatic life.	No known adverse effect to the environment.

13. Disposal considerations

Methods of disposal: The generation of waste should be avoided or minimized wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

14. Transport information

	TDG	DOT	IMDG	IATA
UN number				
Proper shipping name	Not regulated	Not regulated	Not regulated	Not regulated
Transport hazard class(es)				
Packing group				

Other information

Marine pollutant: No

IMDG: Not applicable

Exemption for limited quantity: Not applicable

Special precautions: Not applicable

Others exemptions: Not applicable

15. Regulatory information

Canada

No	CAS	CAS name	%	DSL	NDSL	NPRI
1	14808-60-7	Silica, crystalline (Quartz) (C.I. pigment white 27)	0.12	X		
2	70024-69-0	Alkyd (C16-C24) benzene sulfonate calcium salt	7.50	X		

United-States

No	No CAS	Nom CAS	%	TSCA	PROP-65	Right to Know
1	14808-60-7	Silica, crystalline (Quartz) (C.I. pigment white 27)	0.12	X		X
2	70024-69-0	Alkyd (C16-C24) benzene sulfonate calcium salt	7.50	X		

All ingredients are listed on the EINECS or in compliance with the inventory.

The customer is responsible for determining the PPE (personal protection equipment) code for this material.

The classification of the product and the SDS were developed in accordance with HPR.

16. Other information

Date: 2019-08-07

Version: 1

Notice to the reader: The manufacturer hereby declares that the information disclosed herein have been based on governmental sites and/or raw material suppliers'. The manufacturer has no control over the nature and content of such information. The manufacturer fully reproduces all the information it holds on the constituent of the product, at the time it is manufactured. The manufacturer does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. By this data sheet, the manufacturer hereby discloses all the potential dangers it has knowledge of and which might be related to the using or manipulation of the product in order to allow the proper care to be brought and use with regard to the product. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist and notification is hereby given to the user. Notice is hereby given that injury can derive therefrom if the foregoing is not respected. The manufacturer assumes no responsibility for personal and/or material damage, lost or injury of whichever nature caused or which may occur following the wrongful, inappropriate, negligent or abusive use or handling of the product or from not having read the herein contained information.