

SAFETY DATA SHEET

Gear Shield Extra Heavy - Aerosol (for Canada)

According to WHMIS 2015, in compliance with the Hazardous Product Act (HPA, as amended) and the requirements of the Hazardous Product Regulations (HPR)

1. Identification

Product identifier

Product name Gear Shield Extra Heavy - Aerosol (for Canada)

Product number L0152-063C

Recommended use of the chemical and restrictions on use

Restriction on use Petroleum lubricating grease

Uses advised against No specific uses advised against are identified.

Details of the supplier of the safety data sheet

Manufacturer Lubriplate Lubricants Co.

Corporate Headquarters 129 Lockwood Street Newark, NJ 07105

Midwest Office & Plant 1500 Oakdale Ave. Toledo, OH 43605 419-691-2491 419-693-3806

Emergency telephone number

Emergency telephone Chem-Tel: 1-800-255-3924 (US & Canada only)

01-813-248-0585 (Outside US & Canada)

2. Hazard identification

Classification of the substance or mixture

Physical hazards Flam. Aerosol 1 - H222 Press. Gas, Compressed - H280

Health hazards Not Classified

Environmental hazards Aquatic Acute 3 - H402 Aquatic Chronic 3 - H412

Label elements

Pictogram





Signal word Danger

Hazard statements H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated. H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use. P273 Avoid release to the environment.

P410+P403 Protect from sunlight. Store in a well-ventilated place. P412 Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/ container in accordance with national regulations.

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

Mixtures

Distillates (petroleum), hydrotreated light

30-60%

CAS number: 64742-47-8

Classification

Asp. Tox. 1 - H304

Distillates (petroleum), hydrotreated heavy naphthenic

5-10%

CAS number: 64742-52-5

Classification

Not Classified

Residual oils (petroleum,) solvent-refined

1-5%

CAS number: 64742-01-4

Classification

Skin Irrit. 2 - H315

zinc oxide 1-5%

CAS number: 1314-13-2

M factor (acute) = 1 M factor (chronic) = 1

Classification

Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

Carbon black 1-5%

CAS number: 1333-86-4

Classification

Not Classified

The full text for all hazard statements is displayed in Section 16.

4. First-aid measures

Description of first aid measures

Gear Shield Extra Heavy - Aerosol (for Canada)

General information If in doubt, get medical attention promptly. Show this Safety Data Sheet to the medical

personnel.

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. Loosen tight clothing such as collar, tie or belt. Get medical attention if symptoms

are severe or persist.

Ingestion Rinse mouth thoroughly with water. Get medical advice/attention if you feel unwell. Do not

induce vomiting unless under the direction of medical personnel.

Skin contact Rinse with water.

Eye contact Remove any contact lenses and open eyelids wide apart. Rinse with water. Get medical

attention if any discomfort continues.

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue.

Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation Spray/mists may cause respiratory tract irritation.

Ingestion Due to the physical nature of this product, it is unlikely that ingestion will occur.

Skin contact Repeated exposure may cause skin dryness or cracking.

Eye contact May be slightly irritating to eyes. May cause discomfort.

Indication of any immediate medical attention and special treatment needed

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder

or water fog. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the hazardous product

Specific hazardsContainers can burst violently or explode when heated, due to excessive pressure build-up.

Bursting aerosol containers may be propelled from a fire at high speed. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurized contents and

propellant. Vapours may form explosive mixtures with air.

Hazardous combustion

products

Thermal decomposition or combustion products may include the following substances:

Harmful gases or vapours.

Advice for firefighters

Protective actions during

firefighting

Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing that provides a basic level of protection during chemical incidents is defined by the Canada Occupational Health and Safety Regulations, by provincial guidelines on occupational health and safety or by NFPA standards if applicable.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions

Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be taken without appropriate training or involving any personal risk. Do not touch or walk into spilled material. Evacuate area. Risk of explosion. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Promptly remove any clothing that becomes contaminated.

Environmental precautions

Environmental precautions

Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment.

Methods and material for containment and cleaning up

Methods for cleaning up

Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Under normal conditions of handling and storage, spillages from aerosol containers are unlikely. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. Small Spillages: Wipe up with an absorbent cloth and dispose of waste safely. Large Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dangerous for the environment. Do not empty into drains. For waste disposal, see Section 13.

Reference to other sections

Reference to other sections

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

7. Handling and storage

Precautions for safe handling

Usage precautions

Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Avoid exposing aerosol containers to high temperatures or direct sunlight. The product is flammable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid discharge to the aquatic environment. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin. Avoid contact with eyes. Avoid inhalation of vapours and spray/mists.

Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse.

Conditions for safe storage, including any incompatibilities

Gear Shield Extra Heavy - Aerosol (for Canada)

Storage precautions Store away from incompatible materials (see Section 10). Keep away from oxidizing materials,

> heat and flames. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Protect from sunlight. Do not store near heat sources or expose to high temperatures. Do not expose to

temperatures exceeding 50°C/122°F.

Storage class Miscellaneous hazardous material storage.

Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

8. Exposure controls/Personal protection

Control parameters

Occupational exposure limits

Distillates (petroleum), hydrotreated heavy naphthenic

Mineral oil, excluding metal working fluids (pure, highly and severely refined) **ACGIH**

zinc oxide

Long-term exposure limit (8-hour TWA): ACGIH 2 mg/m³ respirable fraction Short-term exposure limit (15-minute): ACGIH 10 mg/m³ respirable fraction

Long-term exposure limit (8-hour TWA): ACGIH 3 mg/m³ inhalable fraction

ACGIH = American Conference of Governmental Industrial Hygienists. A3 = Confirmed Animal Carcinogen with Unknown Relevance to Humans.

Exposure controls

Protective equipment





Appropriate engineering

controls

Provide adequate ventilation. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Unless the assessment indicates a higher degree of protection is required, the following

protection should be worn: Tight-fitting safety glasses.

Hand protection

No specific hand protection recommended. Avoid contact with skin.

Other skin and body

protection

Wear appropriate clothing to prevent repeated or prolonged skin contact.

Hygiene measures Wash after use and before eating, smoking and using the toilet. Do not eat, drink or smoke

when using this product.

Gear Shield Extra Heavy - Aerosol (for Canada)

Respiratory protection

Ensure all respiratory protective equipment is suitable for its intended use and is NIOSH approved. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work. Full face mask respirators with replaceable filter cartridges should comply with the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work. Half mask and quarter mask respirators with replaceable filter cartridges should comply with the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work.

Environmental exposure controls

Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance Aerosol.

Colour Black. Gray.

Odour Solvent.

Odour threshold Not available.

pH Not available.Melting point Not available.

Initial boiling point and range Not available.

Flash point -18°C/-0.4°F Cleveland open cup.

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or

explosive limits

Lower flammable/explosive limit: 0.9 % Upper flammable/explosive limit: 7 %

Vapour pressure 115 psig @ 54°C

Vapour density > 1

Relative density 0.98

Solubility(ies) Insoluble in water.

Partition coefficient Not available.

Auto-ignition temperature Not available.

Viscosity 31 cSt @ 100°C/212°F

Explosive properties Not considered to be explosive.

Oxidising properties Does not meet the criteria for classification as oxidizing.

Not available.

10. Stability and reactivity

Decomposition Temperature

Reactivity See the other subsections of this section for further details.

Gear Shield Extra Heavy - Aerosol (for Canada)

Stability Stable at normal ambient temperatures and when used as recommended. Stable under the

prescribed storage conditions.

Possibility of hazardous

reactions

No potentially hazardous reactions known.

Conditions to avoid Avoid heat, flames and other sources of ignition.

Materials to avoid Oxidizing materials. Chlorine.

Hazardous decomposition

products

Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀)

Based on available data the classification criteria are not met.

Skin corrosion/irritation

Animal data Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitization

Respiratory sensitization Based on available data the classification criteria are not met.

Skin sensitization

Skin sensitization Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitroBased on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicity Contains a substance which has been shown to cause cancer in laboratory animals. IARC

Group 2A Probably carcinogenic to humans.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity -

Based on available data the classification criteria are not met.

development

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Gear Shield Extra Heavy - Aerosol (for Canada)

Aspiration hazard

Aspiration hazard May be fatal if swallowed and enters airways.

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation Spray/mists may cause respiratory tract irritation.

Ingestion Due to the physical nature of this product, it is unlikely that ingestion will occur.

Skin contact Repeated exposure may cause skin dryness or cracking.

Eye contact May be slightly irritating to eyes. May cause discomfort.

Route of exposure Ingestion Inhalation Skin and/or eye contact

Target organs No specific target organs known.

12. Ecological information

Toxicity Aquatic Acute 3 - H402 Aquatic Chronic 3 - H412 Harmful to aquatic life with long lasting

effects.

Persistence and degradability

Persistence and degradability The degradability of the product is not known.

Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not available.

Mobility in soil

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all

surfaces.

Other adverse effects

Other adverse effects None known.

13. Disposal considerations

Waste treatment methods

General information The generation of waste should be minimized or avoided wherever possible. Reuse or recycle

products wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product

residues and hence be potentially hazardous.

Disposal methodsDo not empty into drains. Empty containers must not be punctured or incinerated because of

the risk of an explosion. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers,

labeled with their contents.

14. Transport information

UN number

UN No. (TDG) 1950

UN No. (IMDG) 1950 UN No. (ICAO) 1950 UN No. (DOT) UN1950

UN proper shipping name

Proper shipping name (TDG) AEROSOLS
Proper shipping name (IMDG) AEROSOLS
Proper shipping name (ICAO) AEROSOLS
Proper shipping name (DOT) AEROSOLS

Transport hazard class(es)

DOT class 2.1

DOT hazard label 2.1

TDG class 2.1

TDG label(s) 2.1

IMDG class 2.1

ICAO class/division 2.1

Transport labels



DOT transport label



Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

Special precautions for user

EmS F-D, S-U

15. Regulatory information

Inventories

Canada - DSL/NDSL

All the ingredients are listed or exempt.

Distillates (petroleum), hydrotreated light

Petroleum gases, liquefied, sweetened

Asphalt, oxidized

Residual oils (petroleum,) solvent-refined

Petroleum Resins

Residues (petroleum), atm. tower

Distillates (petroleum), hydrotreated heavy naphthenic

zinc oxide

12-hydroxystearic acid

Carbon black

Tallow

Petroleum oil

Polyisobutylene

16. Other information

Classification abbreviations

Aerosol = Aerosol

and acronyms

Press. Gas (Comp.) = Gas under pressure: Compressed gas

Aquatic Chronic = Hazardous to the aquatic environment (chronic)

Training advice Only trained personnel should use this material.

Revision date 2018-08-20

SDS number 5212

Hazard statements in full H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation. H400 Very toxic to aquatic life. H402 Harmful to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

End of SDS

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.