Product Name: ACDELCO DEXOS1 6W-20

Revision Date: 01 Oct 2012

Page 1 of 9

CN38042

MATERIAL SAFETY DATA SHEET

SECTION 1

PRODUCT AND COMPANY IDENTIFICATION

PRODUCT

Product Name: AODEL-GO DEXOS1 6W-20 Product Description: Base Oil and Additives

Product Code: 485771-01 Intended Use: Engine oil

COMPANY IDENTIFICATION

Supplier: EXXON MOBIL CORPORATION

3226 GALLOWS ROAD

FAIRFAX, VA. 22037 USA

24 Hour Health Emergency
Transportation Umergency Phone

ExxonMobil Transportation No.
Product Toolmical Information

MSDS internet Address

609-737-4411

800-424-9300 281-834-3296

800-662-4626 / 800-947-9147

http://www.exxon.com, http://www.mobil.com

SECTION 2

COMPOSITION / INFORMATION ON INGREDIENTS

Reportable Hazardous Substance(s) or Complex Substance(s)

The state of the s		
Namo	CAS#	Concentration ⁴
PHOSPHORODITHOIO ACID, O,O-DI C1-14-ALKYL ESYERS, ZINC SALTS (2:1) (ZDDP)	08649-42-3	1 - 2.6%

* All concentrations are percent by weight unless material is a gas. Gas concentrations are in percent by volume.

SECTION 3

HAZARDS IDENTIFICATION

This material is not considered to be hazardous according to regulatory guidelines (see (M)SDS Section 15).

POTENTIAL HEALTH EFFECTS

Excessive exposure may result in eye, skin, or respiratory irritation. High-pressure injection under skin may cause serious damage.

NFPA Hazard ID:

Health:

Flantmability:

Readivity: (

HMIS Hazard ID:

Health:

0

Flammabliliy:

Reactivity:

NOTE: This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.



Product Name: AODELOO DEXOS1 6W-20

Revision Date: 01 Oct 2012

Page 2 of 9

SECTION 4

FIRST AID MEASURES

INHALATION

Remove from further exposure. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory proteotion. If respiratory inflation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If broathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation.

SKIN CONTACT

Wash contact areas with scap and water. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

EYE CONTACT

Flush thoroughly with water. If irritation occurs, get medical assistance,

INGESTION

First aid is normally not required. Seek medical attention if discomfort occurs.

SECTION 6

FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

Appropriate Extinguishing Media: Use water log, foam, dry chemical or carbon dioxide (CO2) to extinguish flames.

Inappropriate Extinguishing Media: Straight Streams of Water

FIRE FIGHTING

Fire Fighting Instructions: Evacuate area. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. Firefighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.

Hazardous Combustion Products: Smoke, Fume, Aldehydes, Sulfur oxides, Incomplete combustion products, Oxides of carbon

FLAMMABILITY PROPERTIES

Flash Point [Mothod]: 234°C (463°F) [ASTM D-92]

Flammable Limits (Approximate volume % in air); LEL: 0.9 UEL: 7.0

Autolgnillon Temperature: N/D

SECTION 6

ACCIDENTAL RELEASE MEASURES

NOTIFICATION PROCEDURES

in the event of a spill or accidental release, notify relevant authorities in accordance with all applicable



Product Name: ACDELCO DEXOS1 6W-20

Revision Date: 01 Oct 2012

Page 3 of 9

regulations. US regulations—require reporting releases of this material to the environment which exceed the applicable reportable quantity or oil spills which could reach any waterway including intermittent dry creeks. The National Response Center can be reached at (800)424-8802.

PROTECTIVE MEASURES

Avoid contact with spilled material. See Section 6 for fire lighting information. See the Hezard Identification Section for Significant Hazards. See Section 4 for First Ald Advice. See Section 8 for advice on the minimum requirements for personal protective equipment. Additional protective measures may be necessary, depending on the specific circumstances and/or the expert judgment of the emergency responders. For emergency responders. For emergency responders: Respiratory protection: respiratory protection will be necessary only in special cases, e.g., formation of mists. Half-face or full-face respirator with filter(e) for dust/organic vapor or Self Contained Breathing Apparatus (SCBA) can be used depending on the size of spill and potential level of exposure. If the exposure cannot be completely characterized or an oxygen deficient atmosphere is possible or sufficipated, SCBA is recommended. Work gloves that are resistant to hydrocarbons are recommended. Gloves made of polyvinyl acetate (PVA) are not water-resistant and are not suitable for emergency use. Chemical goggles are recommended if spiashes or contact with eyes is possible. Small spills: normal antistatic work clothes are usually adequate. Large spills: full body suit of chemical resistant, antistatic material is recommended.

SPILL MANAGEMENT

Land Splii: Stop leak if you can do it without risk. Recover by pumping or with sultable absorbent.

Water Spill: Stop leak if you can do it without risk. Confine the spill immediately with booms. Warn other shipping. Remove from the surface by skimming or with sullable absorbents. Seek the advice of a specialist before using dispersants.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

ENVIRONMENTAL PRECAUTIONS

Large Spills: Dike far shead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas.

SECTION 7

HANDLING AND STORAGE

HANDLING

Avoid contact with used product. Prevent small spills and leakage to avoid slip hazard. Material can accumulate static charges which may cause an electrical spark (ignition source). When the material is handled in bulk, an electrical spark could ignite any flammable vapors from liquids or residues that may be present (e.g., during switch-leading operations). Use proper bonding and/or ground procedures. However, bonding and grounds may not eliminate the hazard from static accumulation. Consult local applicable standards for guidence. Additional references include American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practice on Static Electricity) or CENELEC CLOTR 60404 (Electrostatics - Code of practice for the avoidance of hazards due to static electricity).

Static Accumulator: This material is a static accumulator.

STORAGE

The container choice, for example storage vessel, may effect static accumulation and dissipation. Do not store



Produol Name: ACDELCO DEXOS1 5W-20

Revision Dale: 01 Oct 2012

Page 4 of 9

	The state of the s
In open or unlabelled containers.	
III OBGII OL KIRKBÖNDA AANKINAA	

SECTION 8

EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits/standards for materials that can be formed when handling this product: When mists/aerosols can occur the following are recommended: 5 mg/m3 - ACGIH TLV (inhalable fraction), 5 mg/m3 - OSHA PEL.

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

ENGINEERING CONTROLS

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Control measures to consider:

No special requirements under ordinary conditions of use and with adequate ventilation.

PERSONAL PROTECTION

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

Respiratory Protection: If engineering controls do not maintain alriborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include:

No special requirements under ordinary conditions of use and with adequate ventilation.

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode, Supplied air respirators with an escape boille may be appropriate when oxygen levels are inadequate, gas/vapor warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions, inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include:

No protection is ordinarily required under normal conditions of use.

Eye Protection: If contact is likely, safety glasses with side shields are recommended.

Any specific clothing information provided is based on published literature or Skin and Body Protection: manufacturer data. The types of clothing to be considered for this material include:

No skin protection is ordinarily required under normal conditions of use. In accordance with good Industrial hygiene practices, precautions should be taken to avoid skin contact.

Specific Hygiene Measures: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective



Produol Name: ACDELCO DEXOS1 6W-20

Revision Date: 01 Oct 2012

Page 6 of 9

equipment to remove contaminants. Discard contaminated clothing and foolwear that cannot be cleaned. Practice good housekeeping.

ENVIRONMENTAL CONTROLS

Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions.

SECTION 9

PHYSICAL AND CHEMICAL PROPERTIES

Note: Physical and chemical proporties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

GENERAL INFORMATION

Physical State: Liquid

Form: Clear
Golor: Amber
Odor: Characteristic
Odor Threshold: N/D

IMPORTANT HEALTH, SAFETY, AND ENVIRONMENTAL INFORMATION

Rolative Density (at 15 °C): 0.861

Plash Point [Method]: 234°C (463°F) [ASTM D-92]

Flammable Limits (Approximate volume % in air): LEL: 0.9 UEL: 7.0

Autolgnition Temperature: N/D Bolling Point / Range: N/D

Vapor Density (Air = 1): > 2 at 101 kPa [Estimated]

Vapor Pressure: < 0.013 kPa (0.1 mm Hg) at 20 °C [Estimated]

Evaporation Rate (n-butyl acotate = 1): N/D

AW Hg

Log Pow (n-Octanol/Water Partition Coefficient): > 3.5 [Estimated]

Solubility in Water: Negligible

Viscosity: 47.7 cSt (47.7 mm2/sec) at 40 °C

Oxidizing Proportios: See Hazards Identification Section.

OTHER INFORMATION

Freezing Point: N/D Melting Point: N/A

Pour Point: -42°C (-44°F)

DM80 Extract (mineral oil only), iP-346: < 3 %wt

SECTION 10

STABILITY AND REACTIVITY

STABILITY: Material is stable under normal conditions.

CONDITIONS TO AVOID: Excessive heat. High energy sources of Ignillon.

MATERIALS TO AVOID: Strong oxidizers

HAZARDOUS DECOMPOSITION PRODUCTS: Malerial does not decompose at ambient temperatures.



Product Name: ACDELCO DEXOS1 5W-20

Revision Date: 01 Oct 2012

Page 6 of 9

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION 11

TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

MOOTE TONION I	
Route of Exposure	Conclusion / Romarks
inhalation	
Toxicily: No end point data for material.	Minimally Toxlo, Based on assessment of the components.
Initation: No end point data for material.	Negligible hazard at ambient/normal handling temperatures. Based on assessment of the components.
Ingostion	
Toxicity: No end point data for material.	Minimally Toxic. Based on assessment of the components.
Skin	
Toxicity: No end point data for material.	Minimally Toxic, Based on assessment of the components.
Irritation: No and point data for material.	Negligible initiation to skin at ambient temperatures. Based on assessment of the components.
Нуе	
initation: No end point data for material.	May cause mild, short-lasting discomfort to eyes. Based on assessment of the components.

CHRONIC/OTHER EFFECTS

For the product itself:

Diesel engine oils: Not carcinogenic in animals tests. Used and unused diesel engine oils did not produce any carcinogenic effects in chronic mouse skin painting studies.

Oils that are used in gasoline engines may become hazardous and display the following properties; Carcinogenic in animal tests. Caused mutations in vitro. Possible allergen and photoaliergen. Contains polycyclic aromatic compounds (PAC) from combustion products of gasoline and/or thermal degradation products.

Contains:

Base oil severely refined: Not carolnogenio in animal studies. Representative material passes IP-346, Modified Ames test, and/or other screening tests. Dermal and inhalation studies showed minimal effects; lung non-specific inititration of immune cells, oil deposition and minimal granuloma formation. Not sensitizing in test animals.

Additional information is available by request.

The following ingredients are olted on the lists below: None.

-- REGULATORY LISTS SEARCHED --

1 = NTP CARC

3 = IARC 1

5 ± IARC 28

2 # NTP SUS

4 = IARC 2A

6 = OSHA CARC

SECTION 12

ECOLOGICAL INFORMATION

The information given is based on data available for the material, the components of the material, and similar



Product Name: ACDELCO DEXOS1 6W-20

Revision Date: 01 Oct 2012

Page 7 of 9

malerials.

ECOTOXICITY

Material -- Not expected to be harmful to aquatic organisms.

MOBILITY

Base oil component -- Low solubility and floats and is expected to migrate from water to the land. Expected to partition to sediment and wastewater solids.

PERSISTENCE AND DEGRADABILITY

Blodogradation:

Base oil component -- Expected to be inherently blodegradable

BIOACCUMULATION POTENTIAL

Base oil component -- Has the potential to bloaccumulate, however metabolism or physical properties may reduce the bloconcentration or limit bloavallability.

SECTION 13

DISPOSAL CONSIDERATIONS

Disposal recommendations based on material as supplied. Disposal must be in accordance with ourrent applicable laws and regulations, and material characteristics at time of disposal.

DISPOSAL RECOMMENDATIONS

Product is sultable for burning in an enclosed controlled burner for fuel value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products. Protect the environment, Dispose of used oil at designated sites. Minimize skin contact. Do not mix used oils with solvents, brake fluids or coolants.

REGULATORY DISPOSAL INFORMATION

RORA Information: The unused product, in our opinion, is not specifically listed by the EPA as a hazardous waste (40 CFR, Part 261D), nor is it formulated to contain materials which are listed as hazardous wastes. It does not exhibit the hazardous characteristics of ignitability, correstivity or reactivity and is not formulated with contaminants as determined by the Toxicity Characteristic Leaching Procedure (TCLP). However, used product may be regulated.

Empty Container Warning Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not alternot to refill or clean containers without proper instructions. Empty drums should be completely drained and safety stored until appropriately reconditioned or disposed. Empty containers should be taken for recovery, or disposal through sultably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION, THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

SECTION 14

TRANSPORT INFORMATION



Product Name: ACDELCO DEXOS1 5W-20

Revision Date: 01 Oct 2012

Page 8 of 9

LAND (DOT): Not Regulated for Land Transport

LAND (TDG): Not Regulated for Land Transport

SEA (IMDG): Not Regulated for Sea Transport according to IMDG-Code

AIR (IATA): Not Regulated for Air Transport

SECTION 15

REQULATORY INFORMATION

OSHA HAZARD COMMUNICATION STANDARD: When used for its intended purposes, this material is not classified as hexardous in accordance with OSHA 29 CFR 1910.1200.

Compiles with the following national/regional chemical inventory requirements: AICS, DSL, ENGS, IECSC, KECI, PICCS, TSCA

EPCRA SECTION 302: This material contains no extremely hazardous substances.

SARA (311/312) REPORTABLE HAZARD CATEGORIES: None.

SARA (313) TOXIC RELEASE INVENTORY:

	the company of the last construction of the la		
Chemical Name	CA6 Number	Typical Value	
PHOSPHORODITHOIC ACID,	08649-42-3	1 - 2.5%	•
O,O.DI C1-14-ALKYL ESTERS,		1	
ZING SALTS (2:1) (ZDDP)			

The following ingredients are cited on the lists below:

	The state of the s	
Chemical Name	GAS Numbor	List Citations
PHOSPHORODITHOIC ACID,	68649-42-3	13, 15, 17
O,O-DI C1-14-ALKYL ESTERS,	•	
ZING SALTS (2:1) (ZDDP)		

-- REGULATORY LISTS SEARCHED --

1 = ACGIH ALL	6 = TSCA 6a2	11 # CA P68 REPRO	16 ¤ MN RTK
2 = ACOIH A1	7 11 TSCA 50	12 = CA RTK	17 = NJ RTK
3 a ACGIH A2	8 ⊭ TSCA 6	13 # IL RTK	18 ¤ PA RTK
4 = OSHA Z	9 = TSCA 12b	14 × LA RTK	19 = RI RTK
S = TSCA 4	10 # CA P65 CARC	16 = MI 293	

Code key: CARC=Carcinogen; REPRO=Reproductive



Product Name: ACDELCO DEXOS1 5W-20 Revision Date: 01 Oct 2012 Page 9 of 9

SECTION 18	OTHER INFORMATION
N/D = Not determined, N/A = Not applicat	le .
THIS SAFETY DATA SHEET CONTAINS No revision information is available.	THE FOLLOWING REVISIONS:
and reliable as of the date issued. You c available from ExxonMobil. The informat examination. It is the user's responsibility repackages this product, it is the user's reincluded with and/or on the container. Aphandlers and users. Alteration of this docre-publication or retransmission of this docre-publication or retransmission of this docre-publication.	Intellined herein are, to the best of ExxonMobil's knowledge and belief, accurate an contact ExxonMobil to insure that this document is the most ourrent on and recommendations are offered for the user's consideration and to eatisfy itself that the product is suitable for the intended use. If buyer sponsibility to insure proper health, safety and other necessary information is propriate warnings and safe-handling procedures should be provided to ument is strictly prohibited. Except to the extent required by law, ument, in whole or in part, is not permitted. The term, "ExxonMobil" is used or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any hold any interest.
Internal Use Only MHC: 08, 08, 0, 0, 0, 0	PPEC: A
DGN: 7122802 (1020648) (NA Core)	
Convelobl 2002 Exxon Mobil Corneration	Il rights reserved