Safety Data Sheet

Engine Shampoo

SECTION 1. IDENTIFICATION

Product IdentifierEngine ShampooPart number992724, 992725

Product Family Blend of petroleum based solvents and detergents

Recommended Use Degreaser. **Restrictions on Use** None known.

Supplier Identifier General Motors of Canada Company/Compagnie General Motors du Canada

1908 Colonel Sam Drive Oshawa, ON L1H 8P7 1.800.223.3526

Emergency Phone No. Immediately contact your local poison control centre.

CANUTEC, +1.613.996.6666, for transportation emergencies.

SECTION 2. HAZARD IDENTIFICATION

Classification

Flammable liquid - Category 3; Skin irritation - Category 2; Serious eye damage - Category 1; Aspiration hazard - Category 1

Label Elements







Danger

Flammable liquid and vapour.

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye damage.

Keep away from heat, sparks, open flames, and hot surfaces. – No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical, ventilating, lighting, and other equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash hands and skin thoroughly after handling.

Wear protective gloves/eye protection/face protection.

Product Identifier: Engine Shampoo - Ver. 2

 SDS No.:
 992724, 992725

 Date of Preparation:
 December 22, 2016

Date of Last Revision: April 22, 2019 Page 01 of 09

IF SWALLOWED: Immediately call a POISON CENTRE or doctor.

Do NOT induce vomiting.

Immediately call a POISON CENTRE or doctor.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

In case of fire: Use carbon dioxide, dry chemical powder to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents and container in accordance with local, regional, national and international regulations.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture:

Chemical Name	CAS No.	%	Other Identifiers	Other Names
Solvent naphtha (petroleum), light aromatic	64742-94-5	10-30		
Stoddard solvent	8052-41-3	10-30		
1,2,4-Trimethylbenzene	95-63-6	7-13		
Ethylene glycol	107-21-1	1-5		
1,3,5-Trimethylbenzene	108-67-8	1-5		
Alcohols, C9-11, ethoxylated, liquids	68439-46-3	1-5		
Ethylbenzene	100-41-4	0.1-1.0		
n-Nonane	111-84-2	0.5-1.5		
Potassium hydroxide	1310-58-3	0.1-1.0		
Xylene (mixed isomers)	1330-20-7	0.5-1.5		
2-aminoethanol	141-43-5	0.1-1.0		
Diethylbenzene	25340-17-4	0.1-1.0		
Naphthalene	91-20-3	0.1-1.0		
Cumene	98-82-8	0.1-1.0		

Notes

Any concentration shown as a range is due to batch processing.

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Remove source of exposure or move to fresh air. If breathing is difficult, trained personnel should administer emergency oxygen if advised to do so by Poison Centre or doctor. If breathing has stopped, trained personnel should begin rescue breathing. Get medical attention immediately.

Skin Contact

Take off immediately contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 5 minutes. If skin irritation occurs, get medical

Product Identifier: Engine Shampoo - Ver. 2

SDS No.: 992724, 992725

Date of Preparation: December 22, 2016

Date of Last Revision: April 22, 2019 Page 02 of 09

advice or attention.

Eye Contact

Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical attention.

Ingestion

Never give anything by mouth if person is rapidly losing consciousness, or is unconscious or convulsing. Do not induce vomiting. Drink two glasses of water. If vomiting occurs naturally, lie on your side in the recovery position. Rinse mouth with water again. Seek medical attention.

First-aid Comments

Get medical advice or attention if you feel unwell or are concerned.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Carbon dioxide or dry chemical.

Unsuitable Extinguishing Media

Do not use a direct stream of water.

Specific Hazards Arising from the Product

Vapours are heavier than air. May travel a considerable distance to a source of ignition and flash back to a leak or open container.

Carbon oxides, and other unidentified organic compounds.

Special Protective Equipment and Precautions for Fire-fighters

Fire-fighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA).

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Evacuate the area immediately. Isolate the hazard area. Keep out unnecessary and unprotected personnel. Distant ignition and flashback are possible.

Environmental Precautions

If the spill is inside a building, prevent product from entering drains, ventilation systems and confined areas. Do not allow into any sewer, on the ground or into any waterway.

Methods and Materials for Containment and Cleaning Up

Stop or reduce leak if safe to do so. Contain and soak up spill with absorbent that does not react with spilled product. Contaminated absorbent poses the same hazard as the spilled product. Place used absorbent into suitable, covered, labelled containers for disposal.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

It is good practice to: avoid breathing product; avoid skin and eye contact and wash hands after handling. Eliminate heat and ignition sources such as sparks, open flames, hot surfaces and static discharge. Post "No Smoking" signs. Only use where there is adequate ventilation. Containers of this material may contain hazardous residues when "emptied". Do not weld, cut or perform hot work on empty container until all traces of product have been removed.

Conditions for Safe Storage

Store at temperatures not exceeding: 40°C.

Store in an area that is: cool, dry, well-ventilated.

Keep from freezing.

Product Identifier: Engine Shampoo - Ver. 2

SDS No.: 992724, 992725

Date of Preparation: December 22, 2016

Date of Last Revision: April 22, 2019 Page 03 of 09

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

	ACGIH® TLV®		OSHA PEL	
Chemical Name	TWA	STEL [C]	TWA	Ceiling
Ethylbenzene	20 ppm A3	Not established	100 ppm	Not established
Ethylene glycol	Not established	100 mg/m3 A4	Not established	50 ppm
1,3,5-Trimethylbenzene	25 ppm	Not established	Not established	Not established
n-Nonane	200 ppm	Not established	Not established	Not established
Xylene (mixed isomers)	100 ppm A4	150 ppm A4	435 mg/m3	Not established
2-aminoethanol	3 ppm	6 ppm		
Alcohols, C9-11, ethoxylated, liquids	Not established			
Stoddard solvent	100 ppm	Not established	Not established	Not established
Naphthalene	10 ppm	15 ppm	10 ppm	Not established
1,2,4-Trimethylbenzene	25 ppm	Not established	Not established	Not established
Cumene	50 ppm	Not established	50 ppm	Not established

Appropriate Engineering Controls

Sufficient mechanical ventilation to maintain exposures below the TLV. Under normal conditions of use, general ventilation should be satisfactory. Local ventilation is recommended if the product is misted or used in a confined space or if the TLV is exceeded. Make up air should always be supplied to balance air exhausted. Provide safety shower in work area, if contact or splash hazard exists.

Individual Protection Measures

Eye/Face Protection

Safety glasses with side shields. Contact lenses should not be worn, they may contribute to the severity of the injury.

Skin Protection

Wear chemical protective clothing e.g. gloves, aprons, boots.

Suitable materials are: neoprene rubber, nitrile rubber.

Respiratory Protection

Not normally required if product is used as directed.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties

Appearance Clear yellow liquid.
Odour Not available
Odour Threshold Not available
pH 9.9 (10% solution)

Melting Point/Freezing Point Not available (melting); Not available (freezing)

Initial Boiling Point/RangeNot availableFlash Point49 °C (closed cup)Evaporation RateNot available

Flammability (solid, gas) Not applicable (liquid).

Upper/Lower Flammability or

Explosive Limit

Not available (upper); Not available (lower)

Vapour Pressure Not available

Vapour Density (air = 1) > 1

Product Identifier: Engine Shampoo - Ver. 2

 SDS No.:
 992724, 992725

 Date of Preparation:
 December 22, 2016

Date of Last Revision: April 22, 2019 Page 04 of 09

Relative Density (water = 1) 0.88 at 15 °C
Solubility Partial in water
Partition Coefficient, Not available

n-Octanol/Water (Log Kow)

Auto-ignition TemperatureNot availableDecomposition TemperatureNot available

Viscosity < 14 centistokes at 40°C (kinematic)

Other Information

VOC % 66.2

Flame projection Not applicable

NFPA Classification Combustible liquid, Class II

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions of use.

Chemical Stability

Stable at ambient temperatures and pressures.

Possibility of Hazardous Reactions

None expected under normal conditions of storage and use.

Conditions to Avoid

Open flames, sparks, static discharge, heat and other ignition sources.

Incompatible Materials

Increased risk of fire and explosion on contact with: strong oxidizing agents (e.g. perchloric acid).

Hazardous Decomposition Products

Carbon oxides. And other unidentified organic compounds.

SECTION 11. TOXICOLOGICAL INFORMATION

Information presented below is for the entire product, unless otherwise specified.

Likely Routes of Exposure

Inhalation;

Skin contact;

Eye contact;

Ingestion.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Ethylbenzene	~ 4000 ppm (rat) (4-hour exposure)	3500 mg/kg (rat)	15380 mg/kg (rabbit)
Ethylene glycol	2725 mg/m3 (rat) (4-hour exposure)	4700 mg/kg (rat)	10600 mg/kg (rabbit)
1,3,5-Trimethylbenzene	24000 mg/m3 (rat) (4-hour exposure)	Not available	Not available
n-Nonane	3200 ppm (rat) (4-hour exposure)	> 15000 mg/kg (rat)	Not available
Potassium hydroxide	Not available	250 mg/kg (rat)	> 1260 mg/kg (rabbit)
Xylene (mixed isomers)	6350 ppm (male rat)	3523 mg/kg (rat)	> 1700 mg/kg (rabbit)

Product Identifier: Engine Shampoo - Ver. 2

SDS No.: 992724, 992725

Date of Preparation: December 22, 2016

Date of Last Revision: April 22, 2019 Page 05 of 09

	(4-hour exposure)		
2-aminoethanol	> 1210 mg/m3 (mouse) (4-hour exposure)	1720 mg/kg (female rat)	1000 mg/kg (rabbit)
Diethylbenzene	> 30000 mg/m3 (mouse)	1200 mg/kg (rat)	> 5000 mg/kg (rabbit)
Solvent naphtha (petroleum), light aromatic	> 14.4 mg/L (rat) (6-hour)	8400 mg/kg (rat)	> 3160 mg/kg (rabbit)
Stoddard solvent	> 5500 mg/m3 (rat) (4-hour exposure)	> 5000 mg/kg (rat)	> 3000 mg/kg (rabbit)
Naphthalene	141 ppm (rat) (4-hour exposure)	490 mg/kg (rat)	> 20000 mg/kg (rabbit)
1,2,4-Trimethylbenzene	18000 mg/m3 (rat) (4-hour exposure)	5000 mg/kg (rat)	Not available
Cumene	39 mg/L (rat) (4-hour exposure)	1400 mg/kg (rat)	10627 mg/kg (rabbit)

19% of the mixture consists of an ingredient or ingredients of unknown acute toxicity (inhalation)

20% of the mixture consists of an ingredient or ingredients of unknown acute toxicity (oral)

34% of the mixture consists of an ingredient or ingredients of unknown acute toxicity (dermal)

Skin Corrosion/Irritation

Moderate skin irritant.

Serious Eye Damage/Irritation

Moderate irritant.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

No hazard under normal conditions of use.

At high concentrations depression of the central nervous system, nose and throat irritation. Symptoms may include headache, nausea, dizziness, drowsiness and confusion.

Skin Absorption

No information was located.

Ingestion

Harmful based on information for closely related materials. Can cause effects as described for inhalation.

Aspiration Hazard

Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

No information was located.

Respiratory and/or Skin Sensitization

Not known to be a respiratory sensitizer.

Not known to be a skin sensitizer.

Carcinogenicity

Chemical Name	ACGIH®	IARC	NTP	OSHA
Ethylbenzene	A3	Group 2B	Not Listed	Not Listed
Ethylene glycol	Not designated	Not evaluated	Not Listed	Not Listed
Potassium hydroxide	Not designated	Not evaluated	Not Listed	
Xylene (mixed isomers)	A4	Group 3	Not Listed	Not Listed
Solvent naphtha (petroleum), light aromatic	Not Listed	Not evaluated	Not Listed	Not Listed

Product Identifier: Engine Shampoo - Ver. 2

SDS No.: 992724, 992725

Date of Preparation: December 22, 2016

Date of Last Revision: April 22, 2019 Page 06 of 09

Naphthalene	A4		Reasonably anticipated	Not Listed
Cumene	Not designated	Group 2B	Not Listed	Not Listed

Contains. (Ethylbenzene) which has been classified as a Group 2B carcinogen (possibly carcinogenic to humans) contains. (2,2-iminodiethanol) which has been classified as a Group 2B carcinogen (possibly carcinogenic to humans) contains. (Naphthalene) which has been classified as a Group 2B carcinogen (possibly carcinogenic to humans) contains. (Cumene) which has been classified as a Group 2B carcinogen (possibly carcinogenic to humans). Key to Abbreviations

ACGIH® = American Conference of Governmental Industrial Hygienists. A3 = Animal carcinogen. A4 = Not classifiable as a human carcinogen.

IARC = International Agency for Research on Cancer. Group 2B = Possibly carcinogenic to humans. Group 3 = Not classifiable as to its carcinogenicity to humans.

NTP = National Toxicology Program. Reasonably anticipated = Reasonably anticipated human carcinogen.

No information was located for: Development of Offspring, Sexual Function and Fertility, Effects on or via Lactation, Germ Cell Mutagenicity, Interactive Effects

SECTION 12. ECOLOGICAL INFORMATION

This section is not required by WHMIS.

This section is not required by OSHA HCS 2012.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Empty containers retain product residue. Follow label warnings even if container appears to be empty. The container for this product can present explosion or fire hazards, even when emptied. Do not cut, puncture, or weld on or near this container. Dispose of in accordance with municipal, provincial/state or federal regulations.

SECTION 14. TRANSPORT INFORMATION

Regulation	UN No.	Proper Shipping Name	Transport Hazard Class(es)	Packing Group
Canadian TDG	UN1268	Petroleum products, n.o.s.	3	Ш
IMDG (Marine)	UN1268	Petroleum products, n.o.s.	3	III
IATA (Air)	UN1268	Petroleum products, n.o.s.	3	Ш

Special Precautions Not applicable

Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

Emergency Response 128 EmS F-E, S-E

Guide No.

Other Information ICAO/IATA PI Y344/355/366

Product may ship as LTD QTY if TDG, ICAO/IATA or IMDG Limited Quantity provisions are

met.

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

Canada

Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)

All ingredients are listed on the DSL/NDSL.

CEPA - National Pollutant Release Inventory (NPRI)

Product Identifier: Engine Shampoo - Ver. 2

SDS No.: 992724, 992725

Date of Preparation: December 22, 2016

Date of Last Revision: April 22, 2019 Page 07 of 09

(Ethylbenzene) Part 1A. (Ethylene glycol) Part 1A. (2,2-iminodiethanol) Part 1A. (Xylene (mixed isomers)) Part 1A.

(Solvent naphtha (petroleum), light aromatic) Part 5.

(Stoddard solvent) Part 5. (Naphthalene) Part 1A.

(1,2,4-Trimethylbenzene) Part 1A.

(Cumene) Part 1A.

USA

Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are listed on the TSCA Inventory.

Additional USA Regulatory Lists

CERCLA. (Ethylbenzene). (Ethylene glycol). (2,2-iminodiethanol). (Potassium hydroxide). (Xylene (mixed isomers)). (Naphthalene). (Cumene)

SARA Title III - Section 302:

SARA Title III - Section 313. (Ethylbenzene). (Ethylene glycol). (2,2-iminodiethanol). (Xylene (mixed isomers)).

(Naphthalene). (1,2,4-Trimethylbenzene). (Cumene)

California Proposition 65. (Ethylbenzene). (Naphthalene)

Massachusetts Right To Know: Not applicable.

New Jersey Right To Know. (Ethylbenzene). (Ethylene glycol). (2,2-iminodiethanol). (n-Nonane). (Potassium hydroxide). (Xylene (mixed isomers)). (2-aminoethanol). (Diethylbenzene). (Glycerine). (Stoddard solvent). (Naphthalene). (1,2,4-Trimethylbenzene). (Cumene)

Pennsylvania Right To Know. (Ethylbenzene). (Ethylene glycol). (2,2-iminodiethanol). (n-Nonane). (Potassium hydroxide). (Xylene (mixed isomers)). (2-aminoethanol). (Glycerine). (Stoddard solvent). (Naphthalene). (1,2,

4-Trimethylbenzene). (Cumene)

SECTION 16. OTHER INFORMATION

NFPA Rating Health - 2 Flammability - 2 Instability - 0

SDS Prepared By Regulatory Compliance

Phone No. 800.201.9486

Date of Preparation December 22, 2016 **Date of Last Revision** April 22, 2019

Revision Indicators The following SDS content was changed on April 22, 2019:

SECTION 1. IDENTIFICATION; Emergency Phone No.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS: Ingredient Information:

Notes.

Key to Abbreviations ACGIH® = American Conference of Governmental Hygienists

CANUTEC = Canadian Transport Emergency Centre

CAS = Chemical Abstract Service

CCOHS = Canadian Centre for Occupational Health & Safety

CNS = Central nervous system

GESTIS = GESTIS Substance Database HSDB® = Hazardous Substances Data Bank

IARC = International Agency for Research on Cancer ICAO = International Civil Aviation Organization IMDG = International Maritime Dangerous Goods Code

LC = Lethal concentration

LC = Lethal dose

NFPA = National Fire Protection Association

NTP = National Toxicology Program

OSHA = US Occupational Safety and Health Administration

Product Identifier: Engine Shampoo - Ver. 2

SDS No.: 992724, 992725

Date of Preparation: December 22, 2016

Date of Last Revision: April 22, 2019 Page 08 of 09

PPM = Parts per million

RTECS® = Registry of Toxic Effects of Chemical Substances

STEL = Short term exposure limit

TDG = Transportation of Dangerous Goods Regulations (Canada)

TWA = Time weighted average

References Material Safety Data Sheet from manufacturer.

CHEMINFO database. Canadian Centre for Occupational Health and Safety (CCOHS). HSDB® database. US National Library of Medicine. Available from Canadian Centre for

Occupational Health and Safety (CCOHS).

Registry of Toxic Effects of Chemical Substances (RTECS®) database. Dassault

Systèmes/BIOVIA ("BIOVIA"). Available from Canadian Centre for Occupational Health and

Safety (CCOHS).

Disclaimer

ECHA - European Chemical Agency, Classification and Labelling Inventory

GESTIS Substance Database

OECD - The Global Portal to Information on Chemical Substances - eChemPortal, 2015.

The information contained herein is offered only as a guide to the use and handling of this specific material and has been prepared in good faith. It is not intended to be all-inclusive, and

the manner and conditions of use and handling may involve other and additional

considerations. No warranty of any kind is given or implied. Shrader Canada Limited will not be liable for any damages, losses, injuries or consequential damages which may result from the

use of or reliance on any information contained herein.

Product Identifier: Engine Shampoo - Ver. 2

 SDS No.:
 992724, 992725

 Date of Preparation:
 December 22, 2016

Date of Last Revision: April 22, 2019 Page 09 of 09

