

# SAFETY DATA SHEET

Prepared according to USA OSHA Hazcom 2012 / Canada WHMIS 2015



Date Prepared : 12/21/2015

MSDS No : XE89\_PART A\_EPOXO 89 Plastic Surgery\_ENG

## XE89 Part A SURE SEAL Plastic Surgery - EPOXO 89

### 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Name** : XE89 Part A SURE SEAL Plastic Surgery - EPOXO 89  
**Product Description**: Part A EPOXO 89 SURE SEAL Plastic Surgery, 220 g / 7.75 oz  
**General Use** : Epoxy adhesive / sealant  
**Product Stock/Code** : XE89 / 4019 (Kit: 440 g / 15.5 oz)  
**Chemical Family** : Epoxy / époxy  
**Molecular Formula** : Mixture / Mélange

#### Manufacturer / Supplier

Dominion Sure Seal Ltd.  
6175 Danville Road, Mississauga  
Ontario, Canada L5T 2H7  
Fax: 905-670-5174  
www.dominionsureseal.com

**Customer Service**: 905-670-5411

#### Emergency Telephone Numbers (24 hour)

CANUTEC : (613) 996-6666  
CHEMTREC : (800) 424-9300

### 2. HAZARDS IDENTIFICATION

#### GHS CLASSIFICATIONS

##### Health:

Eye Irritation, Category 2A  
Skin Irritation, Category 2  
Skin Sensitization, Category 1  
Carcinogenicity, Category 2

#### GHS LABEL

Hazardous components for labelling:

**Epoxy resin, Alkyl (C12-14) glycidyl ether and Titanium dioxide**



Exclamation  
mark



Health  
hazard

**SIGNAL WORD:** WARNING

#### HAZARD STATEMENTS

H319: Causes serious eye irritation.  
H315: Causes skin irritation.  
H317: May cause an allergic skin reaction.  
H351: Suspected of causing cancer by dust inhalation.

**PRECAUTIONARY STATEMENT(S)**

**Prevention:**

- P201: Obtain special instructions before use.
- P202: Do not handle until all safety precautions have been read and understood.
- P261: Avoid breathing dust or vapours.
- P264: Wash hands thoroughly after handling.
- P280: Wear protective gloves and eye protection.
- P272: Contaminated work clothing should not be allowed out of the workplace.

**Response:**

- P308+P313: IF exposed or concerned: Get medical advice/ attention.
- P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337+P313: If eye irritation persists: Get medical advice/attention.
- P302+P350: IF ON SKIN: Gently wash with plenty of soap and water.
- P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
- P362+P364: Take off contaminated clothing and wash it before reuse.

**Storage:**

- P405: Store locked up.

**Disposal:**

- P501: Dispose of contents/container in accordance with applicable local, regional and/or national regulations.

**Emergency Overview**

**Immediate Concerns:**

Causes serious eye irritation. Causes skin irritation. May cause sensitization by skin contact. Persons previously sensitized can experience allergic skin reaction with symptoms of reddening, itching, swelling, and rash. Suspected of causing cancer by dust inhalation.

**Hazards Not Otherwise Classified:**

No data available.

**Comments:**

<5 % of the mixture consists of an ingredient or ingredients of unknown acute toxicity.  
See sections 9 and 10 for more detailed information on physicochemical effects.  
See section 11 for more detailed information on health effects.  
See sections 12 for more detailed information on environmental effects.

This product is a consumer product and is labeled in accordance with the Canadian Consumer Chemicals and Containers Regulations and US Consumer Product Safety Commission regulations which take precedence over Canadian WHMIS 2015 and OSHA Hazcom 2012 Hazard Communication labeling. The actual container label will not include the above label elements. The labeling above applies to products used solely for industrial / professional use.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

| <b>Chemical Name</b>          | <b>Wt.%</b> | <b>CAS No.</b> |
|-------------------------------|-------------|----------------|
| Talc                          | 39 - 42     | 14807-96-6     |
| Epoxy resin                   | 36 - 38     | 25068-38-6     |
| Barium sulfate                | 15 - 16     | 7727-43-7      |
| Alkyl (C12-14) glycidyl ether | 1.5 - 2.5   | 68609-97-2     |
| Iron oxide                    | 1.5 - 2     | 1317-61-9      |
| Titanium dioxide              | 1 - 1.5     | 13463-67-7     |

**Comments:** There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the product and hence require reporting in this section.

#### **4. FIRST AID MEASURES**

**Eye Contact:**

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention, if irritation persists.

**Skin Contact:**

Wash with soap and water. Get medical attention if irritation develops or persists. Remove contaminated clothing and wash before reuse.

**Ingestion:**

Do not induce vomiting. Rinse mouth with water. Give 1 to 2 glasses of water to drink. Never give anything by mouth to an unconscious person. Get medical attention.

**Inhalation:**

Not expected to present a significant inhalation hazard under anticipated conditions of normal use. If you experience eye watering, headaches or dizziness, increase fresh air or leave the area.

#### **Signs and Symptoms of Overexposure**

**Eye Contact:**

Contact causes serious eye irritation. Symptoms may include pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

**Skin Contact:**

Causes skin irritation. Prolonged contact with this product can cause reddening, swelling, rash scaling or blistering. In those who have developed skin sensitization, these symptoms can develop as a result of contact with very small amount of the liquid material.

**Ingestion:**

Substance may be harmful if swallowed. May cause irritation. Symptoms of ingestion may include abdominal pain, nausea, vomiting and diarrhea.

**Inhalation:**

At room temperature, exposure to vapor is minimal due to low volatility.

**Additional Information:**

No data available.

#### **5. FIRE FIGHTING MEASURES**

**Flammable Properties:**

Will burn if involved in a fire.

**Extinguishing Media:**

Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material. Use an extinguishing agent suitable for the surrounding fire.

**Hazardous Combustion Products:**

During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.

**Fire Fighting Procedures:**

Containers can build up pressure if exposed to heat (fire).

**Fire Fighting Equipment:**

As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.

**Sensitivity to Static Discharge:**

Product is not sensitive to static discharge.

**Sensitivity to Mechanical Impact:**

Product is not sensitive to mechanical impact.

## **6. ACCIDENTAL RELEASE MEASURES**

**Small Spill:**

Ensure adequate ventilation. Cover spill area with suitable absorbent material (e.g., sand, earth, sawdust, vermiculite, Oil-Dri, Kitty Litter, etc.). Sweep up material being careful not to raise dust. Place in an appropriate disposal container and seal tightly. Avoid contact with eyes, skin, and clothing.

**Environmental Precautions**

**Water Spill:**

Do not flush to sewer.

**Land Spill:**

Avoid runoff into storm sewers and ditches which lead to waterways.

**Special Protective Equipment:**

Clean up spills immediately, observing precautions in Protective Equipment section 8.

## **7. HANDLING AND STORAGE**

**General Procedures:**

Ensure thorough ventilation of stores and work areas.

**Handling:**

Do not use in the presence of open flame or spark. Wear recommended personal protective equipment. Avoid contact with eyes, skin, and clothing. After handling, always wash hands thoroughly with soap and water.

**Storage:**

Store away from heat, sparks, open flames, strong oxidizing agents and direct sunlight. Protect from physical damage. Keep containers tightly closed, when not in use. Store in a cool place.

## **8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Exposure Guidelines**

| OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)   |            |                              |                   |           |                   |           |                   |
|---|------------|------------------------------|-------------------|-----------|-------------------|-----------|-------------------|
|   |            | Occupational Exposure Limits |                   |           |                   |           |                   |
|   |            | OSHA PEL                     |                   | ACGIH TLV |                   | NIOSH REL |                   |
| Chemical Name   |            | ppm                          | mg/m <sup>3</sup> | ppm       | mg/m <sup>3</sup> | ppm       | mg/m <sup>3</sup> |
| Talc  | <b>TWA</b> | -- [1]                       | 2 [1]             | -- [1]    | 2 [1]             | -- [1]    | 2 [1]             |
| Epoxy resin   | <b>TWA</b> | [2]                          | [2]               | [2]       | [2]               | [2]       | [2]               |
| Barium sulfate  | <b>TWA</b> | -- [3]                       | 5 [3]             | -- [1]    | 5 [1]             | -- [4]    | 5 [4]             |
| Alkyl (C12-14) glycidyl ether   | <b>TWA</b> | [2]                          | [2]               | [2]       | [2]               | [2]       | [2]               |
| Iron oxide  | <b>TWA</b> | [2]                          | [2]               | [2]       | [2]               | [2]       | [2]               |
| Titanium dioxide  | <b>TWA</b> | -- [5]                       | 15 [5]            | -- [5]    | 10 [5]            | [2]       | [2]               |
| <b>Footnotes:</b><br>1. Dust - respirable fraction.<br>2. NL: This material does not have established exposure limits.<br>3. Dust - respirable fraction (15 mg/m <sup>3</sup> total inhalable).<br>4. Dust - respirable fraction (10 mg/m <sup>3</sup> total inhalable).<br>5. Dust - total fraction. |            |                              |                   |           |                   |           |                   |

**Engineering Controls:**

If user operations generate dust during sanding of this product, use ventilation to keep exposure to airborne dust below the above exposure limits. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

**Personal Protective Equipment**

**Eyes and Face:**

Wear safety glasses with side shields (or goggles). Contact lenses should not be worn when working with this product. Eye wash fountains should be readily available to areas of use and handling.

**Skin Contact:**

Wear chemical resistant gloves.

**Respiratory:**

Generally not required. Wear respiratory protection if ventilation is inadequate.

**Protective Clothing:**

Wear protective clothing as necessary to prevent contact.

**Work Hygienic Practices:**

Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Promptly remove soiled clothing/wash thoroughly before reuse.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

|                       |                             |
|-----------------------|-----------------------------|
| <b>Physical State</b> | : Liquid                    |
| <b>Odor</b>           | : Mild                      |
| <b>Odor Threshold</b> | : No data available.        |
| <b>Appearance</b>     | : Viscous thixotropic paste |
| <b>Color</b>          | : Dark gray                 |
| <b>pH</b>             | : No data available.        |
| <b>% Volatiles</b>    | : < 0.4% w/w                |

**Flash Point and Method** : > 100°C (212°F) Closed Cup  
**Flammable Limits** : No data available.  
**Autoignition Temperature** : No data available.  
**Vapor Pressure** : No data available.  
**Vapor Density** : No data available.  
**Boiling Point** : No data available.  
**Freezing Point** : No data available.  
**Melting Point** : Not Applicable  
**Solubility in Water** : Practically insoluble  
**Evaporation Rate**  
**(n-butyl acetate = 1)** : < 1  
**Density** : 1.55±0.03g/ml at 20°C  
**Viscosity** : > 200000 cps at 20°C  
**VOC Content** : < 7 g/l (<0.058 lb/gal); < 0.4% w/w  
**Oxidizing Properties** : None

**Comments:****VOC Compliance Statement**

**Part A VOC Content:** Less Exempts: < 7 g/l (< 0.058 lb/gal)  
Total Material: < 7 g/l (< 0.058 lb/gal)  
**Part A Density:** 1.55 ± 0.03 g/ml  
**Part A Total Volatiles:** < 0.4 % w/w  
**Part A Exempt Content:** 0 % w/w; 0% v/v

**VOC Regulation:** CARB-California, OTC state, Canada proposed Consumer Product Regulations  
**Coating Category:** Sealant or Caulking Compound, Chemically Curing, non-aerosol  
**Mixed Kit VOC Content:** < 0.4 % w/w  
Less Exempts: < 5.0 g/l (< 0.04 lb/gal)  
Total Material: < 5.0 g/l (< 0.04 lb/gal)

**The product VOC content meets the current 3% w/w limit under the CARB Consumer Product Regulations for Sealant or Caulking Compound, Chemically Curing, non-aerosol. 50 State compliant.**

**Note: In California this product is exempt under Adhesives and Sealants district rules (meets small container exemption - packaged in ≤475 ml (16 fl oz) cartridges) but is covered by the CARB Consumer Product Regulation.**

**10. STABILITY AND REACTIVITY**

**Reactive Hazard** : No

**Hazardous Polymerization:**

Not expected to occur.

**Stability:**

Stable.

**Conditions to Avoid:**

Keep away from flames and any object that sparks.

**Possibility of Hazardous Reactions:**

No data available.

**Hazardous Decomposition Products:**

Carbon Monoxide and other toxic vapors.

**Incompatible Materials:**

Oxidizing materials.

**11. TOXICOLOGICAL INFORMATION****Product Acute Toxicity**

| Chemical Name                 | ORAL LD <sub>50</sub><br>mg/kg (rat) | DERMAL LD <sub>50</sub><br>mg/kg (rabbit) | INHALATION<br>LC <sub>50</sub> mg/l |
|-------------------------------|--------------------------------------|---|-------------------------------------|
| Talc                          | Not classified.                      | Not classified.                           | Not classified.                     |
| Epoxy resin                   | 11,400<br>> 15,000                   | > 22,800                                  | No data<br>available.               |
| Barium sulfate                | Not classified.                      | Not classified.                           | Not classified.                     |
| Alkyl (C12-14) glycidyl ether | 17,100,<br>19,200                    | > 4500                                    | Not Applicable                      |
| Iron oxide                    | No data<br>available.                | No data<br>available.                     | No data<br>available.               |
| Titanium dioxide              | > 10,000                             | No data<br>available.                     | No data<br>available.               |

**Acute Toxicity - Dermal LD<sub>50</sub>:** The calculated ATE is >2000 mg/kg.

**Notes:** Based on available ingredient data, the classification criteria for Acute Dermal Toxicity are not met for this mixture.

**Acute Toxicity - Oral LD<sub>50</sub>:** The calculated ATE is >2000 mg/kg.

**Notes:** Based on available data, the classification criteria for Acute Oral Toxicity are not met for this mixture.

**Acute Toxicity - Inhalation LC<sub>50</sub>:** Not Applicable

**Notes:** The mixture is not classified due to lack of data. At room temperature, exposure to vapor is minimal due to low volatility. An estimate based on component information. Not classified.

**Toxicological Data:**

< 5% of the mixture consists of an ingredient or ingredients of unknown acute toxicity.

No additional toxicology information is available for this product itself. (See Component Toxicity Information).

**Eye Irritation / Serious Eye Damage:**

Contains: Epoxy resin. Contact causes serious eye irritation. The mixture is classified as: Eye Irritant, category 2, based on summation of ingredient data (>10% ingredients classified as eye irritant, category 2). Symptoms may include pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

**Skin Irritation / Corrosion:**

Contains: Epoxy resin. Causes skin irritation. The mixture is classified as: Skin Irritant, category 2, based on summation of ingredient data (>10% ingredients classified as skin irritant, category 2). Persons previously sensitized can experience allergic skin reaction with symptoms of reddening, itching, swelling, and rash.

**Specific Target Organ Toxicity - Single Exposure:**

Based on available data, the classification criteria for Specific Target Organ Toxicity - Single Exposure are not met for this mixture (< 1.0% ingredients classified as Specific Target Organ Toxicity - Single Exposure, category 1 or 2 and < 20% summation of all ingredients classified as Specific Target Organ Toxicity - Single Exposure, category 3).

**Carcinogenicity**

| Chemical Name                 | NTP Status | IARC Status | OSHA Status | Other      |
|-------------------------------|------------|-------------|-------------|------------|
| Talc                          | --         | 3           | --          | A4 (ACGIH) |
| Epoxy resin                   | --         | --          | --          | --         |
| Barium sulfate                | --         | --          | --          | --         |
| Alkyl (C12-14) glycidyl ether | --         | --          | --          | --         |
| Iron oxide                    | --         | --          | --          | --         |
| Titanium dioxide              | --         | 2B          | --          | --         |

**Notes:**

The mixture is classified as: Carcinogenicity, category 2 based on ingredient data using the applicable cut-off/concentration limits ( $\geq 0.1\%$  ingredients classified as a Carcinogen, category 2). Titanium dioxide is listed as Group 2B (possibly carcinogenic to humans) Titanium dioxide: applies only to respirable dust. This product may be sanded during normal conditions of use and there may be potential exposure to respirable dust during such sanding operations.

**Specific Target Organ Toxicity - Repeated Exposure:**

Based on available data, the classification criteria for Specific Target Organ Toxicity - Repeated Exposure are not met for this mixture (< 1.0% ingredients classified as Specific Target Organ Toxicity - Repeated Exposure, category 1 or 2). Prolonged skin contact may cause reddening, swelling, rash, scaling, blistering, and in some cases, skin sensitization.

**Respiratory / Skin Sensitizer.:**

Contains: Epoxy resin. May cause sensitization by skin contact. The mixture is classified as: Skin Sensitizer, category 1 based on ingredient data ( $\geq 0.1\%$  ingredients classified as a skin sensitizer, category 1 or sub-category 1A or  $\geq 1.0\%$  ingredients classified as a skin sensitizer, sub-category 1B). Prolonged contact with this product can cause reddening, swelling, rash scaling or blistering. In those who have developed skin sensitization, these symptoms can develop as a result of contact with very small amount of the liquid material.

Based on available data, the classification criteria for respiratory sensitization are not met for this mixture (< 0.1% ingredients classified as a respiratory sensitizer, category 1 or sub-category 1A and < 1.0% ingredients classified as a respiratory sensitizer, sub-category 1B).

**Reproductive Toxicity:**

Based on available data, the classification criteria for Reproductive Toxicity are not met for this mixture (< 0.1% ingredients classified as Reproductive Toxicity, category 1 or 2).

**Specific Target Organ Toxicity - Single Exposure:**

Based on available data, the classification criteria for Specific Target Organ Toxicity - Single Exposure are not met for this mixture (< 1.0% ingredients classified as Specific Target Organ Toxicity - Single Exposure, category 1 or 2 and < 20% summation of all ingredients classified as Specific Target Organ Toxicity - Single Exposure, category 3).



**Germ Cell Mutagenicity:**

Based on available data, the classification criteria for Germ Cell Mutagenicity are not met for this mixture (< 0.1% ingredients classified as Germ Cell Mutagen, category 1A or 1B and < 1.0% ingredients classified as Germ Cell Mutagen, category 2).

**Aspiration Hazard:**

Based on available data, the classification criteria for Aspiration Hazard are not met for this mixture (< 10% ingredients classified as an Aspiration Hazard, category 1 and/or mixture viscosity > 20.5 mm<sup>2</sup>/s at 40 °C).

**12. ECOLOGICAL INFORMATION****Environmental Data:**

No data available.

**Ecotoxicological Information:**

No data available.

**Bioaccumulation/Accumulation:**

No data available.

**Distribution:**

No data available.

**Aquatic Toxicity (Acute):**

No data available.

**Chemical Fate Information:**

No data available.

**13. DISPOSAL CONSIDERATIONS****Disposal Method:**

Comply with applicable local, state or international regulations concerning solid or hazardous waste disposal and/or container disposal. Do not discharge substance/product into sewer system.

**Product Disposal:**

Empty containers retain product residue; observe all precautions for product. Decontaminate containers prior to disposal.

**14. TRANSPORT INFORMATION****DOT (Department of Transportation)**

**Proper Shipping Name** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

**Technical Name** : Epoxy Resin

**Primary Hazard Class/Division:** 9

**UN/NA Number** : 3082

**Packing Group** : III

**Marine Pollutant** : Yes

**Other Shipping Information:**

These Regulations do not apply to the handling, offering for transport or transporting of less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., on a road vehicle or a railway vehicle.

**Air (ICAO/IATA)**

**Shipping Name** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

**Technical Name** : Epoxy Resin

**UN/NA Number** : 3082**Primary Hazard Class/Division:** 3**Packing Group** : III**Subsidiary Risk** : None**Vessel (IMO/IMDG)****Shipping Name** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.**Technical Name** : Epoxy Resin**UN/NA Number** : 3082**Primary Hazard Class/Division:** 3**Packing Group** : III**Marine Pollutant** : Yes**Label** : None**Note:** With an inner packaging < 5.0 L, this product may be shipped as a Limited Quantity.**Canadian Transportation of Dangerous Goods Regulations****Shipping Name** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.**Technical Name** : Epoxy Resin**UN/NA Number** : 3082**Primary Hazard Class/Division:** 3**Packing Group** : III**Label** : None**TDG Note:**

These Regulations do not apply to the handling, offering for transport or transporting of less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., on a road vehicle or a railway vehicle.

**15. REGULATORY INFORMATION****UNITED STATES****SARA Section 311/312 Hazard Categories****Fire Hazard** : No**Sudden Release of Pressure** : No**Reactive Hazard** : No**Product Acute Toxicity** : Yes**Product Chronic Toxicity** : Yes**EPCRA Section 313 Toxic Chemicals:**

This product does not contain any listed toxic chemicals that exceed the threshold reporting levels established by SARA Title III, Section 313.

**EPCRA Section 302 Extremely Hazardous Substances****EPCRA Status:**

This product contains no listed extremely hazardous substances that are subject to the reporting requirements of SARA Title III, Section 302.

**CERCLA Hazardous Substances and Reportable Quantities (RQ)**

**CERCLA Status:**

This product contains no CERCLA listed hazardous substances.

**TSCA (The Toxic Substances Control Act)****TSCA Status:**

All components are included or are otherwise exempt from inclusion on this inventory.

**CAA 112(b) - Hazardous Air Pollutants****CAA 112(r) - List of Substances for Accidental Release Prevention:**

This product contains no chemicals subject to CAA 112(b) or CAA 112(r).

**California Proposition 65**

| Chemical Name    | Wt.%    | Listed |
|------------------|---------|--------|
| Titanium dioxide | 1 - 1.5 | Cancer |

**OSHA Hazard Communication Standard (29 CFR 1910.1200):**

OSHA Status: Hazardous Product (See Section 2 for details).

This product has been classified in accordance with the hazard criteria of the USA OSHA Hazard Communication Standard (29CFR 1910.1200) and the Safety Data Sheet contains all the information required by the OSHA Hazard Communication Standard (HazCom 2012).

**CANADA****WHMIS Hazard Symbol and Classification**

See Section 2 for details.

**WHMIS Regulatory Status:**

This product has been classified in accordance with the hazard criteria of the Canadian Hazardous Products Regulations and the Safety Data Sheet contains all the information required by the Hazardous Products Regulations (WHMIS 2015).

**WHMIS Classification:**

WHMIS 2015 (Canada) Status: Hazardous Product (See Section 2 for details).

**CEPA - National Pollutant Release Inventory (NPRI):**

This product contains no chemicals subject to CEPA - NPRI.

**Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL):**

All components are included or are otherwise exempt from inclusion on this inventory.

**Comments**

VOC Content -- See section 9.

**16. OTHER INFORMATION**


**Reason for Issue:** NEW

**Approved By:** Jim Gordon      **Title:** R&D Chemist / Chemiste de R&D

**Prepared By :** Regulatory Compliance / Conformité réglementaire      **Date Prepared:** 12/21/2015

**Information Contact:** 905-670-5411

| HMIS RATING         |   |   |
|---------------------|---|---|
| HEALTH              | * | 2 |
| FLAMMABILITY        |   | 1 |
| PHYSICAL HAZARD     |   | 0 |
| PERSONAL PROTECTION | E |   |



**NFPA 30 / 30B Storage Classification:** Combustible Liquid IIIB

**Manufacturer Supplemental Notes:** None

**Data Sources:** Not Available

**Additional MSDS Information:**

- N/AV Not Available
- N/AP Not Applicable
- ND Not yet determined
- CAA The Clean Air Act
- CCCR The Consumer Chemicals and Containers Regulations
- CEPA The Canadian Environmental Protection Act
- CERCLA Comprehensive Environmental Response, Compensation, and Liability Act
- EPCRA The Emergency Planning and Community Right-To-Know Act
- IARC International Agency for Research on Cancer
- MSHA Mine Safety and Health Administration
- NIOSH National Institute for Occupational Safety and Health
- NTP National Toxicology Program
- OSHA The Occupational Safety and Health Act
- SARA The Superfund Amendments and Reauthorization Act
- WHMIS Workplace Hazardous Materials Information System

**General Statements:**

No data available.

**Comments:**

None

**Manufacturer Disclaimer:**

The information contained herein is based on data considered accurate. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. No responsibility is assumed for personal injury or property damage to vendees or users or third parties, caused by the material. Such vendees or users assume all risks with the use of this material.