Product Name: Multi-Fix Plastic Repair Cartridge

Product identifier: 100898 Revision Date: 08-18-2016

Replaces:



1. Identification

Product identifier used on the label:

Product Name: Multi-Fix Plastic Repair Cartridge

Product identifier: 100898

Other means of identification

Synonyms: No data available

Recommended use of the chemical and restrictions on

Plastic Repair

use:

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Chemical Manufacturer / ITW Evercoat

Importer / Distributor: a division of Illinois Tool Works Inc.

6600 Cornell Road Cincinnati, OH 45242

513-489-7600

Emergency phone number: CHEMTREC: 1-800-424-9300

CANUTEC: 1-613-996-6666

2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard Symbols:



GHS Classification: Carcinogenicity Category 1A

Reproductive Toxicity Category 1B

Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 1 Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure Category 1

Germ Cell Mutagenicity Category 2

Hazardous to the aquatic environment - Acute Category 3

GHS Signal Word: Danger

GHS Hazard Statements: Suspected of causing genetic defects.

May cause cancer.

May damage fertility or the unborn child.

Causes damage to organs.

Page 1 of 8

Product Name: Multi-Fix Plastic Repair Cartridge

Product identifier: 100898 Revision Date: 08-18-2016

Replaces:

Causes damage to organs through prolonged or repeated exposure.

Harmful to aquatic life.

GHS Precautionary Statements:

Safety Precautions: Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection.

First Aid Measures: IF exposed: Call a POISON CENTER or doctor/physician.

IF exposed or concerned: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Specific treatment (see on this label).

Storage: Store locked up.

Disposal: Dispose of contents/container in accordance with

local/regional/national/international regulation for hazardous wastes.

Hazards not otherwise

classified:

No data available

3. Composition/information on ingredients					
Chemical Component:	CAS number and other unique identifiers	% (or range) of ingredient			
25085-99-8		10 - 30			
Styrene	100-42-5	1 - 5			
Crystalline Silica (Quartz)	14808-60-7	0.1 - 1			

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion:

Eye Contact: Flush eyes with plenty of water for at least 20 minutes retracting

eyelids often. Tilt the head to prevent chemical from transferring to

the uncontaminated eye. Get immediate medical attention.

Skin Contact: Wash with soap and water. Get medical attention if irritation

develops or persists.

Inhalation: Remove to fresh air. If breathing is difficult, have a trained

individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get

medical attention immediately

Product Name: Multi-Fix Plastic Repair Cartridge

Product identifier: 100898 Revision Date: 08-18-2016

Replaces:

Ingestion: Do not induce vomiting and seek medical attention immediately.

Drink two glasses of water or milk to dilute. Provide medical care

provider with this MSDS.

Most important symptoms/effects, acute and delayed:

Most important

No data available

symptoms/effects (Acute): Most important

No data available

symptoms/effects (Delayed):

Indication of immediate medical attention and special treatment

No additional first aid information available

needed, if necessary:

5. Fire-fighting measures

Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media: Use alcohol resistant foam, carbon dioxide, or dry chemical

extinguishing agents. Water spray or fog may also be effective for extinguishing if swept across the base of the fire. Water can also be

used to absorb heat and keep exposed material from being

damaged by fire.

Unsuitable extinguishing media: No data available

Specific hazards arising from the chemical (e.g., nature of any hazardous combustion products):

Fire and/or Explosion

Hazards:

Vapors may be ignited by heat, sparks, flames or other sources of ignition at or above the low flash point giving rise to a Class B fire. Vapors are heavier than air and may travel to a source of ignition

and flash back

Hazardous Combustion

Products:

Carbon dioxide, Carbon monoxide

Special protective equipment and precautions for fire-

fighters:

Do not enter fire area without proper protection including self-contained toxic breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products.

Flammable component(s) of this material may be lighter than water and burn while floating on the surface. Use water spray/fog for cooling. Flammable component(s) of this material may be lighter

than water and burn while floating on the surface.

Product Name: Multi-Fix Plastic Repair Cartridge

Product identifier: 100898 Revision Date: 08-18-2016

Replaces:

6. Accidental release measures

Personal precautions, protective equipment, and emergency procedures: Methods and materials for containment and cleaning up: No health affects expected from the clean-up of this material if contact can be avoided. Follow personal protective equipment

recommendations found in Section VIII of this MSDS

No special spill clean-up considerations. Collect and discard in

regular trash.

7. Handling and storage

Precautions for safe handling: Mildly irritating material. Avoid unnecessary exposure. Use spark-

proof tools and explosion-proof equipment

Conditions for safe storage, including any incompatibilities

Conditions for safe storage: Store in a cool dry ventilated location. Isolate from incompatible

materials and conditions. Keep container(s) closed. Keep away

from sources of ignition

Materials to Avoid/Chemical

Incompatibility:

Strong oxidizing agents Peroxides Strong acids

8. Exposure controls/personal protection

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

Chemical Component	OSHA PEL	ACGIH TLV-TWA	ACGIH STEL
Styrene	100 ppm	20 ppm	40 ppm STEL; 170
			mg/m3 STEL

Appropriate engineering

controls:

No exposure limits exist for the constituents of this product. Use local exhaust ventilation or other engineering controls to minimize exposures and maintain operator comfort. Good general room ventilation should be sufficient to control airborne contaminates to safe levels.

Individual protection measures, such as personal protective equipment:

Eye Protection: Wear chemically resistant safety glasses with side shields when

handling this product. Do not wear contact lenses. Wear splashproof safety goggles if material could be misted or splashed into

eyes.

Skin Protection: Not normally considered a skin hazard. Where use can result in skin

contact, practice good personal hygiene and wear a barrier cream and/or impervious surgical style gloves. Wash hands and other exposed areas with mild soap and water before eating, drinking,

and when leaving work.

Product Name: Multi-Fix Plastic Repair Cartridge

Product identifier: 100898 Revision Date: 08-18-2016

Replaces:

Respiratory Protection: Respiratory protection may be required to avoid overexposure

when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms.

Other Protective Equipment: Wear splash-proof safety goggles if material could be misted or

splashed into eyes.

9. Physical and chemical properties

Appearance (physical state, color, etc.):

Appearance (physical state): Paste Color: Black

Odor:

Odor threshold:

PH:

No data available

Initial Boiling Point and Boiling Range (°C): 1000

Flash Point (°C):

Evaporation Rate:

Flammability (solid, gas):

No data available

No data available

Upper/lower flammability or explosive limits:

Upper Flammable/Explosive Limit (%):
Lower Flammable/Explosive Limit (%):
No data available
No data available
No data available
No data available

Relative Density:1.05Solubility(ies):InsolublePartition coefficient: n-octanol/water:1.36

Auto-ignition Temperature (°C):No data availableDecomposition Temperature:No data availableViscosity:No data available

10. Stability and reactivity

Reactivity: No data available

Chemical stability: Stable under normal conditions. Stable. However, may decompose

if heated

Possibility of hazardousNo data available

reactions:

Conditions to avoid (e.g., static No data available

discharge, shock, or vibration):

Incompatible materials: Strong oxidizing agents Peroxides Strong acids

Product Name: Multi-Fix Plastic Repair Cartridge

Product identifier: 100898 Revision Date: 08-18-2016

Replaces:

11. Toxicological information

Information on the likely routes Inhalation, Eye contact, Skin contact

of exposure (inhalation,

ingestion, skin and eye contact):

Symptoms related to the

No data available

physical, chemical and toxicological characteristics:

Delayed and immediate effects and also chronic effects from short- and long-term exposure:

Immediate (Acute) Health Effects by Route of Exposure:

Inhalation Irritation: Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and

headache. Can cause mechanical irritation if dusts are generated.

Inhalation Toxicity:Non-Toxic. Not known to cause systemic damage.
Skin Contact:
Can cause minor skin irritation, defatting, and dermatitis.

Skin Absorption: No absorption hazard in normal industrial use.

Eye Contact: Can cause moderate irritation, tearing and reddening, but not likely to permanently

injure eye tissue. Can causes slight irritation.

Ingestion Irritation: Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea,

vomiting and diarrhea. No hazard in normal industrial use.

Ingestion Toxicity: Harmful if swallowed. May cause systemic poisoning.

Long-Term (Chronic) Health Effects:

Carcinogenicity: May cause cancer.

Reproductive and May damage fertility or the unborn child.

Developmental Toxicity:

Mutagenicity: Suspected of causing genetic defects.

Inhalation: Upon prolonged and/or repeated exposure, can cause moderate respiratory

irritation, dizziness, weakness, fatique, nausea and headache.

Skin Contact: Upon prolonged or repeated contact, can cause minor skin irritation, defatting, and

dermatitis.

Skin Absorption: Upon prolonged or repeated exposure, no hazard in normal industrial use.

Numerical measures of toxicity (such as acute toxicity estimates)

Component Toxicology Data

Chemical Component	Oral LD50	Dermal LD50	Inhalation LC50
Styrene	Oral LD50 Rat 5000 mg/kg		Inhalation LC50 (4h) Rat 24 g/m3

Whether the hazardous chemical is listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen	
Styrene	N	Υ	Υ	

Product Name: Multi-Fix Plastic Repair Cartridge

Product identifier: 100898 Revision Date: 08-18-2016

Replaces:

$\overline{}$				
	Crystalline Silica (Quartz)	Υ	Υ	Υ

12. Ecological information

Ecotoxicity (aquatic and

Toxic to aquatic life.

terrestrial, where available): Persistence and degradability:

No data available

Bioaccumulative potential:

No data

Mobility in soil: Other adverse effects (such as No data available No data available

hazardous to the ozone layer):

Ecological Toxicity Data

Chemical Component	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish	
No data available				

13. Disposal considerations

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging

Description of waste residues: Spent or discarded material is a hazardous waste.

Waste treatment methods Dispose of by incineration following Federal, State, Local, or

(including packaging): Provincial regulations.

Waste Disposal Code(s): D001

14. Transport information

UN number:

UN proper shipping name:

Not Regulated

No data available

No data available

No data available

No data available

The shipper is responsible for following all applicable regulations. The transportation classification provided is based on ITW Evercoat original packaging, which is suitable for domestic ground transport only.

15. Regulatory information

Safety, health and environmental regulations specific for the product in question

TSCA Status: All components in this product are on the TSCA Inventory.

Product Name: Multi-Fix Plastic Repair Cartridge

Product identifier: 100898 Revision Date: 08-18-2016

Replaces:

Regulated Components

Chemical Component	CAS number and other unique identifiers	CERCLA	SARA EHS	SARA 313	California Prop 65
Styrene	100-42-5	N	N	Υ	Υ
Crystalline Silica (Quartz)	14808-60-7	N	N	N	Υ

16. Other information, including date of preparation or last revision.

Revision Date: 08-18-2016

Revision Number: 10

Disclaimer: NOTICE: The information accumulated herein is believed to be correct as of the date issued from sources, which are believed to be accurate and reliable. Since it is not possible to anticipate all circumstances of use, recipients are advised to confirm, in advance of need, that the information is current, applicable and suitable to their circumstances