

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.10.2017

Page 1 of 14

## POR-15 FUEL TANK SEALER

### SECTION 1: Identification

#### Product identifier

**Product name:** POR-15 FUEL TANK SEALER

**Product code:** 49201; 49204; 49205; 49208; 49216; 49255; 249204;  
249205; 249208; 249216; 249255



#### Recommended use of the product and restriction on use

**Relevant identified uses:** Paints and coatings.

**Uses advised against:** Not determined or not applicable.

**Reasons why uses advised against:** Not determined or not applicable.

#### Manufacturer or supplier details

**Manufacturer:**

**United States**

P.O.R. Products

38 Portman Road

New Rochelle, NY 10801

914-636-0700

#### Emergency telephone number:

**United States**

**ChemTel Inc.**

+1 800 255 3924

+1 813 248 0585

### SECTION 2: Hazard(s) identification

#### GHS classification:

Flammable liquids, category 3

Eye irritation, category 2A

Skin irritation, category 2

Respiratory sensitization, category 1

Aspiration hazard, category 1

Acute toxicity (inhalation), category 4

Specific target organ toxicity - single exposure, category 3, respiratory irritation

Specific target organ toxicity - single exposure, category 3, central nervous system

Specific target organ toxicity - repeated exposure, category 1

Carcinogenicity, category 2

#### Label elements

##### Hazard pictograms:



**Signal word:** Danger

#### Hazard statements:

H226 Flammable liquid and vapor

H319 Causes serious eye irritation

H315 Causes skin irritation

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.10.2017

Page 2 of 14

## POR-15 FUEL TANK SEALER

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled

H304 May be fatal if swallowed and enters airways

H332 Harmful if inhaled

H335 May cause respiratory irritation

H336 May cause drowsiness or dizziness

H372 Causes damage to organs through prolonged or repeated exposure

H351 Suspected of causing cancer

### Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking

P233 Keep container tightly closed

P240 Ground/bond container and receiving equipment

P241 Use explosion-proof electrical/ventilating/light/equipment

P242 Use only non-sparking tools

P243 Take precautionary measures against static discharge

P280 Wear protective gloves/protective clothing/eye protection/face protection

P264 Wash skin thoroughly after handling

P285 In case of inadequate ventilation wear respiratory protection

P271 Use only outdoors or in a well-ventilated area

P260 Do not breathe dust/fume/gas/mist/vapors/spray

P270 Do not eat, drink or smoke when using this product

P201 Obtain special instructions before use

P202 Do not handle until all safety precautions have been read and understood

P303+P361+P353 If on skin (or hair): Immediately remove/take off all contaminated clothing. Rinse skin with water/shower

P370+P378 In case of fire: Use agents recommended in section 5 for extinction

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing

P321 Specific treatment (see supplemental first aid instructions on this label).

P362 Take off contaminated clothing and wash before reuse

P302+P352 If on skin: Wash with soap and water

P332+P313 If skin irritation occurs: Get medical advice/attention

P331 Do not induce vomiting

P301+P310 If swallowed: Immediately call a poison center or doctor/physician

P304+P340+P312 If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell

P308+P313 If exposed or concerned: Get medical advice/attention

P405 Store locked up

P403+P233 Store in a well ventilated place. Keep container tightly closed

P501 Dispose of contents and container as instructed in Section 13

**Hazards not otherwise classified:** None

## SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS number: 95-63-6	1, 2, 4-Trimethylbenzene	<12
CAS number: 64742-48-9	Naphtha (petroleum), hydrotreated heavy	<3
CAS number: 1330-20-7	Xylene	<1

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.10.2017

Page 3 of 14

## POR-15 FUEL TANK SEALER

CAS number: 64742-95-6	Solvent naphtha (petroleum), light arom.	30-35
CAS number: 9016-87-9	Isocyanic acid, polymethylenepolyphenylene ester	3-8
CAS number: 7429-90-5	Aluminum	<3
CAS number: 26447-40-5	Methylenediphenyl diisocyanate	<5
CAS number: 101-68-8	4,4'-Methylenediphenyl diisocyanate	5-13
CAS number: 98-82-8	Cumene	<0.5
CAS number: 67815-87-6	Isocyanic acid, polymethylenepolyphenylene ester, polymer with 1,2-ethanediamine, 2-methyloxirane and 1,2-propanediol	35-65

**Additional Information:** None

## SECTION 4: First aid measures

### Description of first aid measures

#### General notes:

Get medical attention if you feel unwell

#### After inhalation:

Loosen clothing as necessary and position individual in a comfortable position  
Maintain an unobstructed airway  
Get medical advice/attention if you feel unwell  
Take precautions to ensure your own safety  
Remove source of exposure or move person to fresh air  
Get medical advice if you feel unwell or concerned

#### After skin contact:

Rinse affected area with soap and water  
If symptoms develop or persist, seek medical attention  
Take off all contaminated clothing  
Gently blot or brush away excess product  
Wash with plenty of lukewarm, gently flowing water  
Get medical advice if skin irritation occurs or you feel unwell

#### After eye contact:

Rinse/flush exposed eye(s) gently using water for 15-20 minutes  
If symptoms develop or persist, seek medical attention  
Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open  
Remove contact lenses, if present and easy to do so  
Continue rinsing for 15-20 minutes  
Get medical advice if eye irritation persists

#### After swallowing:

Rinse mouth thoroughly  
Seek medical attention if irritation, discomfort, or vomiting persists

### Most important symptoms and effects, both acute and delayed

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.10.2017

Page 4 of 14

## POR-15 FUEL TANK SEALER

### Acute symptoms and effects:

May cause breathing difficulty, asthma attack, nausea, allergic reaction

### Delayed symptoms and effects:

Not determined or not applicable.

### Immediate medical attention and special treatment

#### Specific treatment:

Not determined or not applicable.

#### Notes for the doctor:

Contains isocyanates, consult literature for specific treatment

## SECTION 5: Firefighting measures

### Extinguishing media

#### Suitable extinguishing media:

Use Water (fog only), dry chemical, chemical foam, carbon dioxide, or alcohol-resistant foam

#### Unsuitable extinguishing media:

Do not use a water stream as an extinguisher

### Specific hazards during fire-fighting:

Thermal decomposition can lead to release of irritating gases and vapors

Vapors can flow to distant ignition sources and flashback

Liquid is volatile and may generate an explosive atmosphere

### Special protective equipment for firefighters:

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit

### Special precautions:

Shut off sources of ignition

Carbon monoxide and carbon dioxide may form upon combustion

Heating causes a rise in pressure, risk of bursting and combustion

## SECTION 6: Accidental release measures

### Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation

Ensure air handling systems are operational

Wear protective eye wear, gloves and clothing

Beware of vapors accumulating to form explosive concentrations

Vapors can accumulate in low areas

### Environmental precautions:

Should not be released into the environment

Prevent from reaching drains, sewer or waterway

### Methods and material for containment and cleaning up:

Wear protective eye wear, gloves and clothing

Use spark-proof tools and explosion-proof equipment

Absorb with non-combustible liquid-binding material (sand, diatomaceous earth (clay), acid binders, universal binders)

Dispose of contents / container in accordance with local regulations

### Reference to other sections:

Not determined or not applicable.

## SECTION 7: Handling and storage

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.10.2017

Page 5 of 14

### POR-15 FUEL TANK SEALER

**Precautions for safe handling:**

- Use only with adequate ventilation.
- Avoid breathing mist or vapor.
- Do not eat, drink, smoke or use personal products when handling chemical substances.
- Take precautionary measures against electrostatic discharges.
- Use only non-sparking tools.

**Conditions for safe storage, including any incompatibilities:**

- Keep container tightly sealed.
- Protect from freezing and physical damage.
- Store in a cool, well-ventilated area.
- Store away from all ignition sources (open flames, hot surfaces, direct sunlight, spark sources).

### SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

**Occupational Exposure limit values:**

Country (Legal Basis)	Substance	Identifier	Permissible concentration
ACGIH	4,4'-Methylenediphenyl diisocyanate	101-68-8	ACGIH TLV TWA: 0.0050 ppm
	Xylene	1330-20-7	ACGIH TWA: 100.0 ppm
	Xylene	1330-20-7	ACGIH STEL: 150.0 ppm
	Aluminum	7429-90-5	ACGIH TLV TWA 10.0 mg/m <sup>3</sup> (Metal dust)
	Aluminum	7429-90-5	ACGIH TLV TWA 2.0 mg/m <sup>3</sup> (Soluble salts)
	Aluminum	7429-90-5	ACGIH TLV TWA 5.0 mg/m <sup>3</sup> (Pyro powders, welding fumes)
	Aluminum	7429-90-5	ACGIH TLV TWA: 1.0 mg/m <sup>3</sup> (Respirable fraction)
	Cumene	98-82-8	ACGIH TLV TWA: 50 ppm
United States (OSHA)	4,4'-Methylenediphenyl diisocyanate	101-68-8	OSHA C 0.02 ppm, 0.2 mg/m <sup>3</sup>
	Xylene	1330-20-7	STEL: 655 mg/m <sup>3</sup> (150 ppm)
	Naphtha (petroleum), hydrotreated heavy	64742-48-9	OSHA Z-1 TWA 500 ppm (2,000 mg/m <sup>3</sup> )
	Aluminum	7429-90-5	OSHA PEL TWA 15 mg/m <sup>3</sup> (Total dust)
	Aluminum	7429-90-5	OSHA PEL TWA 5 mg/m <sup>3</sup> (Respirable fraction)
	Xylene	1330-20-7	OSHA TWA: 435.0 mg/m <sup>3</sup> (100.0 ppm)
	Cumene	98-82-8	OSHA PEL TWA 50 ppm, 245.0 mg/m <sup>3</sup>
NIOSH	4,4'-Methylenediphenyl diisocyanate	101-68-8	NIOSH REL TWA 0.0050 ppm, 0.05 mg/m <sup>3</sup>
	4,4'-Methylenediphenyl diisocyanate	101-68-8	NIOSH REL C 0.2 ppm, 0.2 mg/m <sup>3</sup>
	Aluminum	7429-90-5	NIOSH REL TWA 10 mg/m <sup>3</sup> (Total dust)
	Aluminum	7429-90-5	NIOSH REL TWA 5.0 mg/m <sup>3</sup> (Respirable fraction)
	Xylene	1330-20-7	REL TWA: 435.0 mg/m <sup>3</sup> (100.0 ppm)

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.10.2017

Page 6 of 14

## POR-15 FUEL TANK SEALER

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Xylene	1330-20-7	REL ST: 655 mg/m <sup>3</sup> (150 ppm)
	Cumene	98-82-8	NIOSH REL TWA 50 ppm, 245.0 mg/m <sup>3</sup>
	1, 2, 4-Trimethylbenzene	95-63-6	NIOSH REL TWA 25 ppm, 125.0 mg/m <sup>3</sup>
Australia	Aluminum	7429-90-5	TWA: 10 mg/m <sup>3</sup> (metal dust); TWA: 5 mg/m <sup>3</sup> (welding fumes as Al); TWA: 5 mg/m <sup>3</sup> (Pyro Powders, as Al)
	4,4'-Methylenediphenyl diisocyanate	101-68-8	TWA: 0.02 mg/m <sup>3</sup> ; STEL: 0.07 mg/m <sup>3</sup>
	Cumene	98-82-8	TWA: 125 mg/m <sup>3</sup> (25 ppm) ; STEL: 375 mg/m <sup>3</sup> (75 ppm)
	Xylene	1330-20-7	TWA: 350 mg/m <sup>3</sup> (80 ppm) ; STEL: 655 mg/m <sup>3</sup> (150 ppm)

### Biological limit values:

No biological exposure limits noted for the ingredient(s).

### Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls.

Biological monitoring may also be appropriate for some substances.

### Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above. Use explosion-proof ventilation equipment.

### Personal protection equipment

#### Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

#### Skin and body protection:

Select glove material impermeable and resistant to the substance.

Wear appropriate clothing to prevent any possibility of skin contact.

#### Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

### General hygienic measures:

Avoid contact with skin, eyes and clothing.

Wash hands before breaks and at the end of work.

Wash contaminated clothing before reuse.

## SECTION 9: Physical and chemical properties

### Information on basic physical and chemical properties

Appearance	Semi-Transparent Silver Colored Liquid
Odor	Not determined or not available.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.10.2017

Page 7 of 14

## POR-15 FUEL TANK SEALER

Odor threshold	Not determined or not available.
pH	Not determined or not available.
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	>284°F (>140°C)
Flash point (closed cup)	>103°F (>39.4°C)
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Not determined or not available.
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	38 mmHg
Vapor density	Not determined or not available.
Density	1.09 g/mL
Relative density	Not determined or not available.
Solubilities	Not miscible.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	Not determined or not available.
Dynamic viscosity	200-500 cPs
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

### Other information

VOC Content	310 g/L (US EPA Method 24A)
Recommended Storage Temperature	50°F - 95°F
Recommended Shelf Life	3 Years Un-Opened

## SECTION 10: Stability and reactivity

### Reactivity:

Does not react under normal conditions of use and storage.

### Chemical stability:

Stable under normal conditions of use and storage.

### Possibility of hazardous reactions:

None under normal conditions of use and storage.

### Conditions to avoid:

Keep away from heat, sparks and flames.

### Incompatible materials:

None known.

### Hazardous decomposition products:

None known.

## SECTION 11: Toxicological information

### Acute toxicity

**Assessment:** Harmful if inhaled

**Product data:** No data available.

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.10.2017

Page 8 of 14

### POR-15 FUEL TANK SEALER

#### Substance data:

Name	Route	Result
Isocyanic acid, polymethylenepolyphenylene ester	inhalation	LC50 - Rat - 490 mg/m <sup>3</sup> /4h
Methylenediphenyl diisocyanate	inhalation	LC50 - Rat - 369 mg/cu m/4 h
4,4'-Methylenediphenyl diisocyanate	inhalation	LC50 - Rat - 369 mg/cu m/4 h
Xylene	dermal	LD50 - Rat - > 1,700 mg/kg
	inhalation	LC50 - Rat - 5,000 ppm/4 h
1, 2, 4-Trimethylbenzene	inhalation	LC50 - Rat - 18,000 mg/m <sup>3</sup>

#### Skin corrosion/irritation

**Assessment:** Causes skin irritation

#### Product data:

No data available.

#### Substance data:

Name	Result
Isocyanic acid, polymethylenepolyphenylene ester, polymer with 1,2-ethanediamine, 2-methyloxirane and 1,2-propanediol	Irritating to the skin.
Isocyanic acid, polymethylenepolyphenylene ester	Moderate skin irritation.
Methylenediphenyl diisocyanate	Irritating to the skin.
4,4'-Methylenediphenyl diisocyanate	Irritating to the skin.
Naphtha (petroleum), hydrotreated heavy	Irritating to the skin.
Xylene	Irritating to the skin.
1, 2, 4-Trimethylbenzene	Irritating to the skin.

#### Serious eye damage/irritation

**Assessment:** Causes serious eye irritation

#### Product data:

No data available.

#### Substance data:

Name	Result
Isocyanic acid, polymethylenepolyphenylene ester, polymer with 1,2-ethanediamine, 2-methyloxirane and 1,2-propanediol	Irritating effect on the eyes.

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.10.2017

Page 9 of 14

### POR-15 FUEL TANK SEALER

Name	Result
Isocyanic acid, polymethylenepolyphenylene ester	Irritating effect on the eyes.
Methylenediphenyl diisocyanate	Moderate eye irritation.
4,4'-Methylenediphenyl diisocyanate	Moderate eye irritation.
1, 2, 4-Trimethylbenzene	Irritating effect on the eyes.

#### Respiratory or skin sensitization

**Assessment:** May cause allergy or asthma symptoms or breathing difficulties if inhaled

**Product data:**

No data available.

**Substance data:**

Name	Result
Isocyanic acid, polymethylenepolyphenylene ester, polymer with 1,2-ethanediamine, 2-methyloxirane and 1,2-propanediol	Sensitization possible through skin and respiratory contact.
Isocyanic acid, polymethylenepolyphenylene ester	May cause sensitization by respiratory contact.
Methylenediphenyl diisocyanate	May cause sensitization by inhalation and skin contact.
4,4'-Methylenediphenyl diisocyanate	May cause sensitization by inhalation and skin contact.
Cumene	No skin irritation
	No eye irritation

#### Carcinogenicity

**Assessment:** Suspected of causing cancer

**Product data:** No data available.

**Substance data:**

Name	Species	Result
Methylenediphenyl diisocyanate	Methylenediphenyl diisocyanate	May cause cancer.
4,4'-Methylenediphenyl diisocyanate		May cause cancer.
Solvent naphtha (petroleum), light arom.	Solvent naphtha (petroleum), light arom.	Component may cause cancer.

#### International Agency for Research on Cancer (IARC):

Name	Classification
Isocyanic acid, polymethylenepolyphenylene ester	Group 3 - Not classifiable as to its carcinogenicity to humans
Xylene	Group 3 - Not classifiable as to its carcinogenicity to humans

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.10.2017

Page 10 of 14

## POR-15 FUEL TANK SEALER

Name	Classification
Cumene	Group 2B - Possibly carcinogenic to humans

**National Toxicology Program (NTP):** None of the ingredients are listed.

### Germ cell mutagenicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:**

Name	Result
Solvent naphtha (petroleum), light arom.	May cause genetic defects.

### Reproductive toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:** No data available.

### Specific target organ toxicity (single exposure)

**Assessment:** May cause respiratory irritation May cause drowsiness or dizziness

**Product data:**

No data available.

**Substance data:**

Name	Result
Isocyanic acid, polymethylenepolyphenylene ester, polymer with 1,2-ethanediamine, 2-methyloxirane and 1,2-propanediol	May cause respiratory tract irritation through single or repeated exposure.
Isocyanic acid, polymethylenepolyphenylene ester	Component affects the respiratory system through single and repeated exposure.
Methylenediphenyl diisocyanate	Component affects the respiratory system through single and repeated exposure.
4,4'-Methylenediphenyl diisocyanate	Component affects the respiratory system through single and repeated exposure.
Naphtha (petroleum), hydrotreated heavy	Component affects the central nervous system.
Cumene	Component affects the respiratory system.
1, 2, 4-Trimethylbenzene	Component affects the respiratory system.

### Specific target organ toxicity (repeated exposure)

**Assessment:** Causes damage to organs through prolonged or repeated exposure

**Product data:**

No data available.

**Substance data:** No data available.

### Aspiration toxicity

**Assessment:** May be fatal if swallowed and enters airways

**Product data:**

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.10.2017

Page 11 of 14

## POR-15 FUEL TANK SEALER

No data available.

### Substance data:

Name	Result
Naphtha (petroleum), hydrotreated heavy	May be fatal if swallowed and enters airway.
Solvent naphtha (petroleum), light arom.	May be fatal if swallowed and enters airway.

### Information on likely routes of exposure:

No data available.

### Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

### Other information:

No data available.

## SECTION 12: Ecological information

### Acute (short-term) toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

### Substance data:

Name	Result
Cumene	EC50 - Daphnia magna - 1.4 mg/L - 24 h
	LC50 - Pimephales promelas - 6.32 mg/L - 96 h
1, 2, 4-Trimethylbenzene	LC50 - Pimephales promelas - 7.72 mg/L - 96 h

### Chronic (long-term) toxicity

**Product data:** No data available.

**Substance data:** No data available.

### Persistence and degradability

**Product data:** No data available.

**Substance data:** No data available.

### Bioaccumulative potential

**Product data:** No data available.

**Substance data:** No data available.

### Mobility in soil

**Product data:** No data available.

**Substance data:** No data available.

**Other adverse effects:** No data available.

## SECTION 13: Disposal considerations

### Disposal methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

## SECTION 14: Transport information

### United States Transportation of dangerous goods (49 CFR DOT)

UN number	1263
UN proper shipping name	Paint

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.10.2017

Page 12 of 14

## POR-15 FUEL TANK SEALER

UN transport hazard class(es)	3	
Packing group	III	
Environmental hazards	None	
Special precautions for user	None	
Passenger air/rail	60L	
Cargo aircraft only	220L	
Stowage category	A	

### International Maritime Dangerous Goods (IMDG)

UN number	1263	
UN proper shipping name	Paint	
UN transport hazard class(es)	3	
Packing group	III	
Environmental hazards	None	
Special precautions for user	None	
EmS number	F-E, S-E	
Stowage category	A	
Excepted quantities	E1	
Limited quantity	5L	

### International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	1263	
UN proper shipping name	Paint	
UN transport hazard class(es)	3	
Packing group	III	
Environmental hazards	None	
Special precautions for user	None	
ERG code	3L	
Excepted quantities	E1	
Passenger and cargo	60L	
Cargo aircraft only	220L	
Limited quantity	10L	

### Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Bulk Name	None
Ship type	None
Pollution category	None

## SECTION 15: Regulatory information

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.10.2017

Page 13 of 14

### POR-15 FUEL TANK SEALER

#### United States regulations

##### Inventory listing (TSCA):

67815-87-6	Isocyanic acid, polymethylenepolyphenylene ester, polymer with 1,2-ethanediamine, 2-methyloxirane and 1,2-propanediol	Listed
9016-87-9	Isocyanic acid, polymethylenepolyphenylene ester	Listed
26447-40-5	Methylenediphenyl diisocyanate	Listed
101-68-8	4,4'-Methylenediphenyl diisocyanate	Listed
64742-48-9	Naphtha (petroleum), hydrotreated heavy	Listed
64742-95-6	Solvent naphtha (petroleum), light arom.	Listed
7429-90-5	Aluminum	Listed
1330-20-7	Xylene	Listed
98-82-8	Cumene	Listed
95-63-6	1, 2, 4-Trimethylbenzene	Listed

**Significant New Use Rule (TSCA Section 5):** Not determined.

**Export notification under TSCA Section 12(b):** Not determined.

**SARA Section 302 extremely hazardous substances:** Not determined.

##### SARA Section 313 toxic chemicals:

9016-87-9	Isocyanic acid, polymethylenepolyphenylene ester	Not Listed
101-68-8	4,4'-Methylenediphenyl diisocyanate	Not Listed
7429-90-5	Aluminum	Listed
1330-20-7	Xylene	Listed
98-82-8	Cumene	Not Listed
95-63-6	1, 2, 4-Trimethylbenzene	Not Listed

##### CERCLA:

1330-20-7	Xylene	Listed	100 lb
-----------	--------	--------	--------

##### RCRA:

1330-20-7	Xylene	Listed	U239
-----------	--------	--------	------

**Section 112(r) of the Clean Air Act (CAA):** Not determined.

##### Massachusetts Right to Know:

101-68-8	4,4'-Methylenediphenyl diisocyanate	Listed
64742-48-9	Naphtha (petroleum), hydrotreated heavy	Not Listed
64742-95-6	Solvent naphtha (petroleum), light arom.	Not Listed
7429-90-5	Aluminum	Listed
1330-20-7	Xylene	Listed
98-82-8	Cumene	Listed
95-63-6	1, 2, 4-Trimethylbenzene	Listed

##### New Jersey Right to Know:

9016-87-9	Isocyanic acid, polymethylenepolyphenylene ester	Listed
101-68-8	4,4'-Methylenediphenyl diisocyanate	Listed

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.10.2017

Page 14 of 14

## POR-15 FUEL TANK SEALER

64742-48-9	Naphtha (petroleum), hydrotreated heavy	Not Listed
64742-95-6	Solvent naphtha (petroleum), light arom.	Not Listed
7429-90-5	Aluminum	Listed
1330-20-7	Xylene	Listed
98-82-8	Cumene	Listed
95-63-6	1, 2, 4-Trimethylbenzene	Listed

### New York Right to Know:

101-68-8	4,4'-Methylenediphenyl diisocyanate	Listed
64742-48-9	Naphtha (petroleum), hydrotreated heavy	Not Listed
64742-95-6	Solvent naphtha (petroleum), light arom.	Not Listed
7429-90-5	Aluminum	Listed
1330-20-7	Xylene	Listed
98-82-8	Cumene	Listed
95-63-6	1, 2, 4-Trimethylbenzene	Listed

### Pennsylvania Right to Know:

101-68-8	4,4'-Methylenediphenyl diisocyanate	Listed
7429-90-5	Aluminum	Listed
1330-20-7	Xylene	Listed
98-82-8	Cumene	Listed
95-63-6	1, 2, 4-Trimethylbenzene	Listed

### California Proposition 65:

 **WARNING:** This product can expose you to Cumene, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## SECTION 16: Other information

**Abbreviations and Acronyms:** None

### Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

**NFPA:** 3-2-0

**HMIS:** 3-2-0

**Initial preparation date:** 10.10.2017

**End of Safety Data Sheet**