COMPRO TM/MC XL-S 100



000003000239

Version 3.0 Revision Date 2021/02/18 Print Date 2021/02/19

SECTION 1. IDENTIFICATION

Product name : COMPRO TM/MC XL-S 100

Product code : CPXS100BLK, CPXS100P20, CPXS100, CPXS100DRM

Manufacturer or supplier's details

Petro-Canada Lubricants Inc. 2310 Lakeshore Road West Mississauga ON L5J 1K2

Canada

Telephone: 1-905-403-6785

Emergency telephone number

Emergency telephone num- : CHEMTREC: 1-800-424-9300;

ber

Poison Control Centre: Consult local telephone directory for

emergency number(s).

Recommended use of the chemical and restrictions on use

Recommended use : COMPRO XL-S Compressor Fluids are used for the lubrica-

tion of air and inert gas compressors of the reciprocating, rota-

ry screw, and rotary vane types.

These compressor oils should NEVER be used in equipment compressing pure oxygen or other chemically active gases

such as chlorine or hydrogen chloride.

DO NOT USE in breathing air apparatus or medical equip-

ment.

Prepared by : Product Safety: +1 905-491-0565

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

IARC No component of this product present at levels greater than

or equal to 0.1% is identified as probable, possible or con-

firmed human carcinogen by IARC.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

COMPRO TM/MC XL-S 100



000003000239

ersion 3.0	Revision Date 2021/02/18	Print Date 2021/02/19
Lubricating oils (petroleum), C20-50 hydrotreated neutral oil-based, high viscosity; Baseoil — unspecified		70 - 90
Lubricating oils (petroleum), C20-50 hydrotreated neutral oil-based; Baseoil — unspecified	0, 72623-87-1	30 - 50
Lubricating oils (petroleum), C15-30 hydrotreated neutral oil-based; Baseoil — unspecified	0, 72623-86-0	10 - 20

Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

If inhaled : Move to fresh air.

Artificial respiration and/or oxygen may be necessary.

Seek medical advice.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Wash skin thoroughly with soap and water or use recognized

skin cleanser.

Wash clothing before reuse.

Seek medical advice.

In case of eye contact : Remove contact lenses.

Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Obtain medical attention.

If swallowed : Rinse mouth with water.

DO NOT induce vomiting unless directed to do so by a physi-

cian or poison control center.

Never give anything by mouth to an unconscious person.

Seek medical advice.

Most important symptoms and effects, both acute and

delayed

First aider needs to protect himself.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Unsuitable extinguishing

media

No information available.

Specific hazards during fire-

fighting

Cool closed containers exposed to fire with water spray.

Hazardous combustion prod: :

ucts

Carbon oxides (CO, CO2), smoke and irritating vapours as

products of incomplete combustion.

Further information : Prevent fire extinguishing water from contaminating surface

Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license.

COMPRO TM/MC XL-S 100



000003000239

Version 3.0 Revision Date 2021/02/18 Print Date 2021/02/19

water or the ground water system.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Use personal protective equipment.

Ensure adequate ventilation.

Evacuate personnel to safe areas.

Material can create slippery conditions.

Mark the contaminated area with signs and prevent access to

unauthorized personnel.

Only qualified personnel equipped with suitable protective

equipment may intervene.

Environmental precautions : If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Prevent further leakage or spillage if safe to do so.

Remove all sources of ignition.

Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation. Contact the proper local authorities.

SECTION 7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

None known.

Advice on safe handling : For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin, eyes and clothing.

Do not ingest.

Keep away from heat and sources of ignition. Keep container closed when not in use.

Conditions for safe storage : Store in original container.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Keep in a dry, cool and well-ventilated place.

Keep in properly labelled containers.

To maintain product quality, do not store in heat or direct sun-

light.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Lubricating oils (petroleum), C20-50, hydrotreated neutral	72623-85-9	TWA (Mist)	5 mg/m3	CA AB OEL

Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license.

COMPRO TM/MC XL-S 100



000003000239

Version 3.0 Revision Date 2021/02/18 Print Date 2021/02/19

oil-based, high-viscosity; Baseoil — unspecified				
		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV (Mist)	5 mg/m3	CA QC OEL
		STEV (Mist)	10 mg/m3	CA QC OEL
		TWA (Mist)	1 mg/m3	CA GC OEL
		· · · · · · · · · · · · · · · · · · ·		ACGIH
		TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil — unspeci- fied	72623-87-1	TWA (Mist)	5 mg/m3	CA AB OEL
		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV (Mist)	5 mg/m3	CA QC OEL
		STEV (Mist)	10 mg/m3	CA QC OEL
		TWA (Mist)	1 mg/m3	CA BC OEL
		TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil — unspeci- fied	72623-86-0	TWA (Mist)	5 mg/m3	CA AB OEL
		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV (Mist)	5 mg/m3	CA QC OEL
		STEV (Mist)	10 mg/m3	CA QC OEL
		TWA (Mist)	1 mg/m3	CA BC OEL
		TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH

Engineering measures

No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Filter type : organic vapour filter

Hand protection

Material : neoprene, nitrile, polyvinyl alcohol (PVA), Viton(R).

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license.

COMPRO TM/MC XL-S 100



000003000239

Version 3.0 Revision Date 2021/02/18 Print Date 2021/02/19

essary.

Eye protection : Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Protective measures : Wash hands and face before breaks and immediately after

handling the product.

Wash contaminated clothing before re-use.

Hygiene measures : Remove and wash contaminated clothing and gloves, includ-

ing the inside, before re-use.

Wash face, hands and any exposed skin thoroughly after

handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : viscous liquid

Colour : Pale yellow

Odour : Hydrocarbon.

Odour Threshold : No data available

pH : No data available

Pour point : -36 °C (-33 °F)

Boiling point/boiling range : No data available

Flash point : 261 °C (502 °F)

Method: Cleveland open cup

Fire Point : 287 °C (549 °F)

Evaporation rate : No data available

Flammability : Remarks: Low fire hazard. This material must be heated be-

fore ignition will occur.

Auto-Ignition Temperature : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

COMPRO TM/MC XL-S 100



000003000239

Version 3.0 Revision Date 2021/02/18 Print Date 2021/02/19

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : 0.868 kg/l (15 °C)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

No data available

Viscosity

Viscosity, kinematic : 101.1 cSt (40 °C / 104 °F)

14.0 cSt (100 °C / 212 °F)

Explosive properties : Do not pressurise, cut, weld, braze, solder, drill, grind or ex-

pose containers to heat or sources of ignition.

SECTION 10. STABILITY AND REACTIVITY

Possibility of hazardous reac- :

tions

Hazardous polymerisation does not occur.

Stable under normal conditions.

Conditions to avoid : No data available

Incompatible materials : Reactive with oxidising agents, acids, alkalis and reducing

agents.

Hazardous decomposition

products

May release COx, NOx, SOx, methacrylate monomers, smoke

and irritating vapours when heated to decomposition.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Information on likely routes of:

exposure

Eye contact Ingestion

> Inhalation Skin contact

Acute toxicity

Product:

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: No data available

Acute dermal toxicity : Assessment: The substance or mixture has no acute dermal

Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license. Page: 6 / 10

Petro-Canada Lubricants is a HollyFrontier brand

COMPRO TM/MC XL-S 100



000003000239

Version 3.0 Revision Date 2021/02/18 Print Date 2021/02/19

toxicity

Remarks: No data available

Components:

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high-viscosity;

Baseoil — unspecified:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,

Acute inhalation toxicity : LC50 (Rat): > 5.2 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg,

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil — unspeci-

fied:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,

Acute inhalation toxicity : LC50 (Rat): > 5.2 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg,

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil — unspeci-

fied:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,

Acute inhalation toxicity : LC50 (Rat): > 5.2 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg,

Skin corrosion/irritation

Product:

Remarks : No data available

Serious eye damage/eye irritation

Product:

Remarks : No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

COMPRO TM/MC XL-S 100



000003000239

Version 3.0 Print Date 2021/02/19 Revision Date 2021/02/18

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish Remarks: No data available

Toxicity to daphnia and other : Remarks: No data available

aquatic invertebrates

Toxicity to algae/aquatic

plants

Remarks: No data available

Toxicity to microorganisms Remarks: No data available

Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues The product should not be allowed to enter drains, water

courses or the soil.

Offer surplus and non-recyclable solutions to a licensed dis-

posal company.

Waste must be classified and labelled prior to recycling or

disposal.

Send to a licensed waste management company.

Dispose of product residue in accordance with the instructions

of the person responsible for waste disposal.

COMPRO TM/MC XL-S 100



000003000239

Version 3.0 Revision Date 2021/02/18 Print Date 2021/02/19

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

National Regulations

TDG

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

The components of this product are reported in the following inventories:

DSL : On the inventory, or in compliance with the inventory

TSCA : All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

IECSC : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table

2: OEL)

CA BC OEL : Canada. British Columbia OEL

CA QC OEL : Québec. Regulation respecting occupational health and safe-

ty, Schedule 1, Part 1: Permissible exposure values for air-

borne contaminants

ACGIH / TWA : 8-hour, time-weighted average
CA AB OEL / TWA : 8-hour Occupational exposure limit
CA AB OEL / STEL : 15-minute occupational exposure limit

CA BC OEL / TWA : 8-hour time weighted average

CA QC OEL / TWAEV : Time-weighted average exposure value

CA QC OEL / STEV : Short-term exposure value

AICS - Australian Inventory of Chemical Substances; AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); Ecx - Concentration associated with x% response; Elx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in

COMPRO TM/MC XL-S 100



000003000239

Version 3.0 Revision Date 2021/02/18 Print Date 2021/02/19

Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC -No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS -Workplace Hazardous Materials Information System

For Copy of SDS : Internet: lubricants.petro-canada.com/sds

Western Canada, telephone: 1-800-661-1199; fax: 1-800-378-

4518

Ontario & Central Canada, telephone: 1-800-268-5850; fax: 1-

800-201-6285

Quebec & Eastern Canada, telephone: 1-800-576-1686; fax:

1-800-201-6285

For Product Safety Information: 1 905-491-0565

Prepared by : Product Safety: +1 905-491-0565

Revision Date : 2021/02/18 Date format : yyyy/mm/dd

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN