



Material Safety Data Sheet

Three Step with Throttle Body Kit

Date Issued: 06/10/2013

PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: QMI Three Step with Throttle Body Kit
GENERAL USE: Automotive Aftermarket
PRODUCT DESCRIPTION: Fuel system cleaner kit
PRODUCT CODE: EK13

DISTRIBUTOR

ITW Professional Automotive Products
3606 Craftsman Blvd.
Lakeland, FL 33803
Customer Service: 863-665-3338

24 HR EMERGENCY TELEPHONE NUMBERS

Poison Control Center: (877) 800-5533
CHEMTEL: (813) 248-0585

MSDSs for the following products are included

GL1810

QMI Fuel Injector Cleaner

GL1808

QMI Volumetric Efficiency Restorer

GL1806/B

QMI Throttle Body Cleaner



Safety Data Sheet

Fuel Injector Cleaner

Date Issued: 06/10/2013

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: QMI Fuel Injector Cleaner
GENERAL USE: Automotive Aftermarket
PRODUCT DESCRIPTION: Cleaning product
PRODUCT CODE: GL1810

DISTRIBUTOR

ITW Professional Automotive Products
3606 Craftsman Blvd.
Lakeland, FL 33803
Customer Service: 863-665-3338

24 HR EMERGENCY TELEPHONE NUMBERS

Poison Control Center: (877) 800-5533
CHEMTEL: (813) 248-0585

2. HAZARD IDENTIFICATION

GHS CLASSIFICATION

FLAMMABLE Category 2
ASPIRATION HAZARD Category 1
EYE IRRITANT Category 2A
STOT SE 3

GHS LABEL ELEMENTS



Signal word: Danger

Hazard statement: Highly flammable liquid and vapor. May be fatal if swallowed and enters airways.
Causes serious eye irritation. May cause drowsiness or dizziness.

Precautionary statements: Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Keep container tightly closed. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/eye protection. Wash thoroughly after handling. Avoid breathing vapors. Use and store in a well-ventilated area. In case of fire: Use CO₂, dry chemical to extinguish. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do not induce vomiting. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If on skin or hair, take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center if you feel unwell. Store locked up. All disposal practices must be in accordance with local, national and international regulations. KEEP OUT OF REACH OF CHILDREN.



Safety Data Sheet

Fuel Injector Cleaner

Date Issued: 06/10/2013

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS	Concentration, %
Xylene	1330-20-7	30 - 50
Isopropanol	67-63-0	20 - 30
Aliphatic Hydrocarbons	64742-88-7	20 - 30
Tall Oil Fatty Acids	61790-12-3	1 - 5

4. FIRST AID MEASURES

EYES: Flush eyes gently with water for at least 15 minutes while holding eyelids apart. Seek immediate medical attention if irritation persists.

SKIN: Remove contaminated clothing. Flush exposed area with large amounts of water. Seek immediate medical attention if irritation persists.

INGESTION: DO NOT induce vomiting. If vomiting occurs keep head below hips to help keep liquid from getting into lungs. Call for medical attention.

INHALATION: Move individual away from exposure and into fresh air. If symptoms do not abate or breathing difficulty develops, seek medical attention. Do not leave individual unattended.

NOTE TO PHYSICIANS: Aspiration into the lungs during ingestion or vomiting can result in severe pulmonary damage.

5. FIRE FIGHTING MEASURES

FLASH POINT, PMCC: 61°F (16°C)

EXTINGUISHING MEDIA: CO₂, or dry chemical. Use water to cool fire-exposed containers.

HAZARDOUS COMBUSTION PRODUCTS: Carbon Dioxide, Carbon Monoxide.

6. ACCIDENTAL RELEASE MEASURES

Use suitable PPE and ensure adequate ventilation. Eliminate all ignition sources including pilot lights and electric motors. Use non-sparking tools. Prevent runoff into drains, sewers, streams, or other bodies of water. Absorb liquid with vermiculite, floor absorbent or other absorbent material. Scoop or scrape up absorbent and put in the appropriate container for disposal.

7. HANDLING AND STORAGE

HANDLING: Keep away from heat and flame. Avoid prolonged skin contact, breathing vapors, and contaminated clothing. Use with adequate ventilation. Wear recommended protective equipment. Practice good personal hygiene after handling. Empty containers retain material residue. Do not cut, weld, braze, solder or expose containers to other ignition sources. Follow all SDS/label precautions even after container is emptied because it may retain product residues.

STORAGE: Keep container tightly closed in a cool, well-ventilated area. KEEP OUT OF REACH OF CHILDREN.



Safety Data Sheet

Fuel Injector Cleaner

Date Issued: 06/10/2013

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits	Concentration	OSHA PEL	ACGIH TWA
Chemical Name	percent	mg/m ³	ppm
Xylene	30 - 50	435	N/E
Isopropanol	20 - 30	980	200

ENGINEERING CONTROLS: Use with adequate ventilation. Explosion proof local exhaust is recommended in enclosed area.

PERSONAL PROTECTIVE EQUIPMENT

EYES: Appropriate eye protection.

SKIN: Nitrile or other chemical-resistant gloves.

RESPIRATORY: NIOSH approved respirator if engineering controls are insufficient to maintain concentrations below PEL limits

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Odor and appearance:	Clear, amber. Mild odor, possibly ammoniacal.
Specific Gravity:	0.83
pH:	N/A
Flash Point, PMCC	61°F (16°C)

10. STABILITY AND REACTIVITY

Stability:	Normally stable at ambient temperature and pressure.
Conditions to Avoid:	Heat, flame, sparks at temperatures at or above the flash point; contact with strong oxidizing agents.
Polymerization:	Will not occur.
Thermal Decomposition:	Oxides of carbon, nitrogen, and sulfur.

11. TOXICOLOGICAL INFORMATION

Component	Concentration, %	LD50 mg/kg, Rat, Oral	LD50 mg/kg, Rabbit, Dermal
Xylene	30 - 50	10 mL/kg	4300
Isopropanol	20 - 30	5045	12800



Safety Data Sheet

Fuel Injector Cleaner

Date Issued: 06/10/2013

POTENTIAL HEALTH EFFECTS

EYES: Can cause mild to moderate eye irritation.

SKIN: Can cause skin irritation and dryness. May absorb and/or defat skin on prolonged contact.

INGESTION: Ingestion may result in nausea or stomach discomfort. Due to its low viscosity, material may enter lungs during swallowing or vomiting. Once in lungs serious damage may occur.

INHALATION: Inhalation of vapors or mist can cause irritation to respiratory tract. High level exposure may result in central nervous system exposure. Kidney damage may result following aspiration pneumonia.

CHRONIC TOXICITY: May absorb and/or defat skin on prolonged contact.

CARCINOGENICITY: This material contains a trace amount of chemical that has been identified as a carcinogen by NTP, IARC or OSHA.**ROUTES OF ENTRY:** Skin, Eyes, Ingestion, and Inhalation.

PHYSICAL HAZARD – Flammable Liquid

12. ECOLOGICAL INFORMATION

No ecological data are available for this product.

13. DISPOSAL CONSIDERATIONS

Consult federal, state, and local regulations regarding disposal.

14. TRANSPORT INFORMATION

DOT GROUND	UN1993, Flammable liquids, N.O.S. (Contains Xylene), 3, II Limited Quantities
DOT AIR	UN1993, Flammable liquids, N.O.S. (Contains Xylene), 3, II
IATA	UN1993, Flammable liquids, N.O.S. (Contains Xylene), 3, II
IMDG	UN1993, Flammable liquids, N.O.S. (Contains Xylene), 3, II Limited Quantities

15. REGULATORY INFORMATION

TSCA:	All components are on the US TSCA Inventory.
Cal. Prop. 65	This product contains chemicals known to the State of California to cause cancer, birth defects, or any other reproductive harm.
SARA 313:	The following components are listed in 40 CFR Part 372.

Component	CAS	Percent in product
Xylene	1330-20-7	30 - 50
Isopropanol	67-63-0	20 - 30



Safety Data Sheet

Fuel Injector Cleaner

Date Issued: 06/10/2013

RCRA: The following components are listed in 40 CFR Part 302.4.


Component	CAS	Percent in product	RCRA waste no.	RQ lb (kg)
Xylene	1330-20-7	30 - 50	U239	100 (45.4)

16. OTHER INFORMATION

HMIS Rating

HEALTH:	2	
FLAMMABILITY:	3	
PHYSICAL HAZARD:	0	
PERSONAL PROTECTION:	B	

NFPA Codes



DISCLAIMER:

ITW Professional Automotive Products (ITWProAp) believes the information contained in this data sheet is accurate as of the date compiled. However, ITWProAp makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. ITWProAp disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web sites (www.wynnsusa.com or www.qmiitw.com).



Material Safety Data Sheet

Volumetric Efficiency Restorer

Date Issued: 03/27/2013

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: QMI V.M.E.R (Volumetric Efficiency Restorer)
GENERAL USE: Automotive Aftermarket
PRODUCT DESCRIPTION: Fuel Treatment
PRODUCT CODE: GL1808

DISTRIBUTOR

ITW Professional Automotive Products
3606 Craftsman Blvd.
Lakeland, FL 33803
Customer Service: 863-665-3338

24 HR EMERGENCY TELEPHONE NUMBERS

Poison Control Center: (877) 800-5533
CHEMTEL: (813) 248-0585

2. HAZARD IDENTIFICATION

POTENTIAL HEALTH EFFECTS

EYES: Can cause eye irritation.

SKIN: Can cause skin irritation and dryness. May absorb and/or defat skin on prolonged contact.

INGESTION: Ingestion may result in nausea or stomach discomfort. Due to its low viscosity, material may enter lungs during swallowing or vomiting. Once in lungs serious damage may occur.

INHALATION: Inhalation of vapors or mist can cause irritation to respiratory tract. High level exposure may result in central nervous system exposure.

CHRONIC TOXICITY: May absorb and/or defat skin on prolonged contact.

CARCINOGENICITY: Marine diesel fuel is possibly carcinogenic to humans (Group 2B). Distillate (light) diesel fuels are not classifiable as to their carcinogenicity to humans (Group 3)

ROUTES OF ENTRY: Skin, Eyes, Ingestion, and Inhalation.

PHYSICAL HAZARD – Combustible Liquid

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS	Concentration, %
Hydrocarbon distillates	68476-34-6	40 – 60
Solvent naphtha (petroleum), light aromatics	64742-95-6	5 – 15
Poly(oxyalkylene) alkaryl ether	Proprietary	5 – 10
Polyolefin alkyl phenol alkyl amine	Proprietary	5 – 10
Trimethylbenzene	Mixture	3 – 7



Material Safety Data Sheet

Volumetric Efficiency Restorer

Date Issued: 03/27/2013

4. FIRST AID MEASURES

EYES: Flush eyes gently with water for at least 15 minutes while holding eyelids apart. Seek immediate medical attention if irritation persists.

SKIN: Remove contaminated clothing. Flush exposed area with large amounts of water. Seek immediate medical attention if irritation persists.

INGESTION: DO NOT induce vomiting. If vomiting occurs keep head below hips to help keep liquid from getting into lungs. Call for medical attention.

INHALATION: Move individual away from exposure and into fresh air. If symptoms do not abate or breathing difficulty develops, seek medical attention. Do not leave individual unattended.

NOTE TO PHYSICIANS: Aspiration into the lungs during ingestion or vomiting can result in severe pulmonary damage.

5. FIRE FIGHTING MEASURES

FLASH POINT, PMCC: 146°F (63.3°C)

EXTINGUISHING MEDIA: CO₂, dry chemical, or foam. Use water to cool fire-exposed containers.

HAZARDOUS COMBUSTION PRODUCTS: Carbon Dioxide, Carbon Monoxide.

6. ACCIDENTAL RELEASE MEASURES

Use suitable PPE and ensure adequate ventilation. Eliminate all ignition sources including pilot lights and electric motors. Use non-sparking tools. Prevent runoff into drains, sewers, streams, or other bodies of water. Absorb liquid with vermiculite, floor absorbent or other absorbent material. Scoop or scrape up absorbent and put in the appropriate container for disposal.

7. HANDLING AND STORAGE

HANDLING: Keep away from heat and flame. Avoid prolonged skin contact, breathing vapors, and contaminated clothing. Use with adequate ventilation. Wear recommended protective equipment. Practice good personal hygiene after handling. Empty containers retain material residue. Do not cut, weld, braze, solder or expose containers to other ignition sources. Follow all MSDS/label precautions even after container is emptied because it may retain product residues.

STORAGE: Keep container tightly closed in a cool, well-ventilated area. KEEP OUT OF REACH OF CHILDREN.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits	Concentration	OSHA PEL	ACGIH TLV-TWA
Chemical Name	percent	mg/m ³	mg/m ³
Hydrocarbon distillates	40 – 60	N/E	N/E
Solvent naphtha (petroleum), light aromatics	5 – 15	N/E	N/E



Material Safety Data Sheet

Volumetric Efficiency Restorer

Date Issued: 03/27/2013

ENGINEERING CONTROLS: Use with adequate ventilation. Explosion proof local exhaust is recommended in enclosed area.

PERSONAL PROTECTIVE EQUIPMENT

EYES: Appropriate eye protection.

SKIN: Nitrile or other chemical-resistant gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid
Odor and appearance: Clear, light amber
Specific Gravity: 0.82
pH: N/A
Flash Point, PMCC 146°F (63.3°C)

10. STABILITY AND REACTIVITY

Stability: Normally stable at ambient temperature and pressure.
Conditions to Avoid: Heat, flame, sparks at temperatures at or above the flash point; contact with strong oxidizing agents.
Polymerization: Will not occur.
Thermal Decomposition: Oxides of carbon, nitrogen, and sulfur.

11. TOXICOLOGICAL INFORMATION

Component	LD50 mg/kg, Rat, Oral
Hydrocarbon distillates	N/E
Solvent naphtha (petroleum), light aromatics	N/E

12. ECOLOGICAL INFORMATION

No ecological data are available for this product.

13. DISPOSAL CONSIDERATIONS

Consult federal, state, and local regulations regarding disposal.

14. TRANSPORT INFORMATION

DOT Ground N/A (Not regulated in quantities less than 119 gallons per container)
DOT Air Not Regulated
IATA Not Regulated
IMDG Not Regulated



Material Safety Data Sheet

Volumetric Efficiency Restorer

Date Issued: 03/27/2013

15. REGULATORY INFORMATION


TSCA: All components are on the US TSCA Inventory.
RCRA: Not listed in 40 CFR Part 302.4.
Cal. Prop. 65 This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive harm.

16. OTHER INFORMATION

HMIS Rating

HEALTH:	2	
FLAMMABILITY:	2	
PHYSICAL HAZARD:	0	
PERSONAL PROTECTION:	B	

NFPA Codes



DISCLAIMER:

ITW Professional Automotive Products (ITWProAp) believes the information contained in this data sheet is accurate as of the date compiled. However, ITWProAp makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. ITWProAp disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web sites (www.wynnsusa.com or www.qmiitw.com).



Material Safety Data Sheet

Throttle Body Cleaner

Date Issued: 06/10/2013

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: QMI Throttle Body Cleaner
GENERAL USE: Automotive Aftermarket
PRODUCT DESCRIPTION: Cleaning Product
PRODUCT CODE: GL1806/B

DISTRIBUTOR

ITW Professional Automotive Products
3606 Craftsman Blvd.
Lakeland, FL 33803
Customer Service: 863-665-3338

24 HR EMERGENCY TELEPHONE NUMBERS

Poison Control Center: (877) 800-5533
CHEMTEL: (813) 248-0585

2. HAZARD IDENTIFICATION

POTENTIAL HEALTH EFFECTS

EYES: Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes.

SKIN: May cause mild skin irritation. Prolonged or repeated contact may dry the skin.

INGESTION: Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

INHALATION: Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful.

CHRONIC TOXICITY: May absorb and/or defat skin on prolonged contact.

CARCINOGENICITY: This material does not contain components that are listed as a carcinogen by the IARC, the NTP, or OSHA.

ROUTES OF ENTRY: Skin, Eyes, Ingestion, and Inhalation.

PHYSICAL HAZARD – Extremely Flammable

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS
2-Propanone	67-64-1
Xylene	1330-20-7
Ethylbenzene	100-41-4
Carbon Dioxide	124-38-9



Material Safety Data Sheet

Throttle Body Cleaner

Date Issued: 06/10/2013

4. FIRST AID MEASURES

EYES: Flush eyes gently with water for at least 15 minutes while holding eyelids apart. Seek immediate medical attention.

SKIN: Remove contaminated clothing. Flush exposed area with large amounts of water. Seek medical attention if symptoms persist.

INGESTION: Seek medical attention. Do not induce vomiting. This material is an aspiration hazard.

INHALATION: Move individual away from exposure and into fresh air. If symptoms do not abate or breathing difficulty develops, seek medical attention. Do not leave individual unattended.

5. FIRE FIGHTING MEASURES

Flammability per Flame Projection Test: EXTREMELY FLAMMABLE

EXTINGUISHING MEDIA: CO₂, dry chemical, or foam. Use water to cool fire-exposed containers.

SPECIAL FIRE FIGHTING PROCEDURES: Keep containers cool using water spray to avoid bursting containers. Wear full firefighting turn-out gear and respiratory protection. Material is volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, flames, sparks, heaters, smoking, electric motors, static discharge or other ignition sources at locations near the material handling point.

UNUSUAL HAZARDS: Contents under pressure. Do not use near fire, sparks, or flame. Do not puncture or incinerate container. Exposure to temperatures above 120°F may cause container to burst.

6. ACCIDENTAL RELEASE MEASURES

Use suitable PPE and ensure adequate ventilation. Eliminate all ignition sources including pilot lights and electric motors. Use non-sparking tools. Prevent runoff into drains, sewers, streams, or other bodies of water. Absorb liquid with vermiculite, floor absorbent or other absorbent material. Scoop or scrape up absorbent and put in the appropriate container for disposal.

7. HANDLING AND STORAGE

HANDLING: DANGER! EXTREMELY FLAMMABLE. VAPOR HARMFUL. VAPOR MAY CAUSE FLASH FIRE. SKIN, EYE AND RESPIRATORY IRRITANT. HARMFUL OR FATAL IF INHALED OR SWALLOWED.

Keep out of reach of children. Read label cautions carefully. Follow label directions to avoid injury. Use with adequate ventilation. Do not use in confined areas. Do not use near sparking tools. Keep away from heat, sparks or open flames. Wash hands after each use before eating, drinking or smoking. Do not smoke while using. Avoid contact with skin and eyes. Do not place near source of heat as container may burst. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Do not puncture container.



Material Safety Data Sheet

Date Issued: 06/10/2013

Throttle Body Cleaner

STORAGE: Keep out of reach of children. Do not incinerate container. Do not store near heat, sparks, or open flames. Store in a cool, dry, well ventilated area away from incompatible materials. Do not expose to temperatures above 120°F as container may vent, rupture or burst. Do not puncture or incinerate container. Do not store in direct sunlight. Store in accordance with NFPA 30B for Level 2 Aerosols.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits	OSHA PEL	OSHA PEL	NIOSH
Chemical Name	mg/m ³	ppm	ppm
2-Propanone	2400	1000	250
Xylene	435	100	100, 150 STEL
Ethylbenzene	435	100	100, 125 STEL
Carbon Dioxide	9000	5000	5000, 30,000 STEL

ENGINEERING CONTROLS: Use with adequate ventilation. Explosion proof local exhaust is recommended in enclosed area.

PERSONAL PROTECTIVE EQUIPMENT

EYES: Appropriate eye protection.

SKIN: Nitrile or other chemical-resistant gloves.

INHALATION: Use organic vapor respirator only as a last resort to control exposure.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid packaged in a pressurized aerosol spray can.
Odor and appearance:	Colorless clear-cloudy liquid with a solvent odor
Specific Gravity:	0.805 – 0.815
pH:	N/A
% VOC Content	9.94
Evaporation Rate (BeAc=1)	>1.00

10. STABILITY AND REACTIVITY

Stability:	Normally stable at ambient temperature and pressure.
Conditions to Avoid:	Fire, flame, sparks, temperatures above 120°F. Incompatible with acids, alkalis, reducing agents, chlorine, hypochlorites, strong oxidizing agents
Polymerization:	Will not occur.
Thermal Decomposition:	Oxides of carbon, aldehydes, hydrocarbons



Material Safety Data Sheet

Throttle Body Cleaner

Date Issued: 06/10/2013

11. TOXICOLOGICAL INFORMATION

Component	LD50 mg/kg, Rat, Oral	LD50 mg/kg, Rabbit, Dermal
2-Propanone	5800	20,000
Xylene	3523	>43,000
Ethylbenzene	5460	17800

12. ECOLOGICAL INFORMATION

No ecological data are available for this product.

13. DISPOSAL CONSIDERATIONS

DISPOSAL: Before offering for recycling, empty the container by using the product according to the label. If recycling is not available, wrap the container and discard in the trash. Dispose of unused product in accordance with regulations.

14. TRANSPORT INFORMATION

DOT Ground UN1950, Aerosols, 2.1 Limited Quantities
DOT Air UN1950, Aerosols, 2.1 Limited Quantities
IATA UN1950, Aerosols, 2.1 Limited Quantities
IMDG UN1950, Aerosols, 2.1 Limited Quantities

15. REGULATORY INFORMATION

TSCA: All components are on the US TSCA Inventory.
Cal. Prop. 65 This product may contain a chemical known to the State of California to cause cancer, birth defects, or other reproductive harm.

US EPA CERCLA Hazardous Substances (40CFR 302)	CAS	RCRA waste number	Quantity, lb
2-Propanone	67-64-1	U002	5000
Xylene	1330-20-7	U239	100
Ethyl Benzene	100-41-4	N/A	1000

SARA 313 Chemicals	CAS	Percent in product
Xylene	1330-20-7	Not Reported
Ethyl Benzene	100-41-4	Not Reported



Material Safety Data Sheet

Throttle Body Cleaner


Date Issued: 06/10/2013

16. OTHER INFORMATION

HMIS Rating

HEALTH:	2	
FLAMMABILITY:	4	
PHYSICAL HAZARD:	0	
PERSONAL PROTECTION:	B	

NFPA Codes



DISCLAIMER:

ITW Professional Automotive Products (ITWProAp) believes the information contained in this data sheet is accurate as of the date compiled. However, ITWProAp makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. ITWProAp disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web sites (www.wynnsusa.com or www.qmiitw.com).