

SAFETY DATA SHEET

Revision Date 30-Jan-2017 Version 2

1. IDENTIFICATION

Product identifier

Product Name QMI Throttle Body Cleaner

Other means of identification

Product Code QMI GL1806B

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use See directions provided with product

Uses advised against All other applications

Details of the supplier of the safety data sheet

Supplier Address Manufacturer Address Manufactured and Distributed by:

ITW Professional Automotive Products

3606 Craftsman Blvd. Lakeland, FL 33803

Distributor May Also Be Distributed by:

ITW Professional Automotive Products

1-35 Brownridge Road

Halton Hills, ON, Canada L7G OC6

Company Phone Number 863-665-3338

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003583

E-mail address EHS@itwproap.com

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

NOTE:

| Acute toxicity - Inhalation (Vapors) | Category 4 |
|--|---------------|
| Serious eye damage/eye irritation | Category 2 |
| Specific target organ toxicity (single exposure) | Category 3 |
| Specific target organ toxicity (repeated exposure) | Category 2 |
| Aspiration toxicity | Category 1 |
| Flammable aerosols | Category 1 |
| Gases under pressure | Dissolved gas |

Label elements

| ⊨mer | gency | Over | view |
|------|-------|------|------|
| | | | |

| Emergency everyter |
|--------------------|
| Warning |
| |
| |
| |

Causes serious eye irritation

May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure

Harmful if inhaled

May be fatal if swallowed and enters airways

Extremely flammable aerosol

Contains gas under pressure; may explode if heated



Appearance Clear liquid

Physical state Flammable Aerosol

Odor Solvent

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling

Wear eye/face protection

Do not breathe dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Do not spray on an open flame or other ignition source

Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

Get medical advice/attention if you feel unwell

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water

Take off contaminated clothing and wash before reuse

If skin irritation occurs: Get medical advice/attention

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

Precautionary Statements - Storage

Store in a well-ventilated place

Protect from sunlight

Store locked up

Do not expose to temperatures exceeding 122 °F (50 °C)

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

- Causes mild skin irritation

Unknown acute toxicity

8 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance(s)

Revision Date 30-Jan-2017

| Chemical Name | CAS No | Weight-% | Trade Secret |
|----------------|-----------|----------|--------------|
| 2-Propanone | 67-64-1 | 60 - 100 | * |
| Xylene | 1330-20-7 | 5 - 10 | * |
| Carbon Dioxide | 124-38-9 | 5 - 10 | * |
| Ethylbenzene | 100-41-4 | 1 - 5 | * |

4. FIRST AID MEASURES

Description of first aid measures

General advice Get medical advice/attention if you feel unwell.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Skin contact IF ON SKIN:. Wash skin with soap and water. If skin irritation persists, call a physician.

Wash contaminated clothing before reuse.

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician.

Self-protection of the first aiderUse personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

Flammable.

Explosion data

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautionsRemove all sources of ignition. Use personal protective equipment as required.

Environmental precautions

Environmental precautions See Section 12 for additional ecological information. Do not flush into surface water or

sanitary sewer system.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning upSoak up with inert absorbent material.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not

puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top

of can.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

Incompatible materials Strong oxidizing agents

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|----------------|-----------------|--|-------------------------------|
| 2-Propanone | STEL: 500 ppm | TWA: 1000 ppm | IDLH: 2500 ppm |
| 67-64-1 | TWA: 250 ppm | TWA: 2400 mg/m ³ | TWA: 250 ppm |
| | | (vacated) TWA: 750 ppm | TWA: 590 mg/m ³ |
| | | (vacated) TWA: 1800 mg/m ³ | |
| | | (vacated) STEL: 2400 mg/m ³ The | |
| | | acetone STEL does not apply to the | |
| | | cellulose acetate fiber industry. It is | |
| | | in effect for all other sectors | |
| | | (vacated) STEL: 1000 ppm | |
| Xylene | STEL: 150 ppm | TWA: 100 ppm | - |
| 1330-20-7 | TWA: 100 ppm | TWA: 435 mg/m ³ | |
| | | (vacated) TWA: 100 ppm | |
| | | (vacated) TWA: 435 mg/m ³ | |
| | | (vacated) STEL: 150 ppm | |
| | | (vacated) STEL: 655 mg/m ³ | |
| Carbon Dioxide | STEL: 30000 ppm | TWA: 5000 ppm | IDLH: 40000 ppm |
| 124-38-9 | TWA: 5000 ppm | TWA: 9000 mg/m ³ | TWA: 5000 ppm |
| | | (vacated) TWA: 10000 ppm | TWA: 9000 mg/m ³ |
| | | (vacated) TWA: 18000 mg/m ³ | STEL: 30000 ppm |
| | | (vacated) STEL: 30000 ppm | STEL: 54000 mg/m ³ |
| | | (vacated) STEL: 54000 mg/m ³ | |
| Ethylbenzene | TWA: 20 ppm | TWA: 100 ppm | IDLH: 800 ppm |
| 100-41-4 | | TWA: 435 mg/m ³ | TWA: 100 ppm |
| | | (vacated) TWA: 100 ppm | TWA: 435 mg/m ³ |
| | | (vacated) TWA: 435 mg/m ³ | STEL: 125 ppm |
| | | (vacated) STEL: 125 ppm | STEL: 545 mg/m ³ |
| | | (vacated) STEL: 545 mg/m ³ | |

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

Respiratory protectionUse NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as

appropriate.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of

equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Flammable Aerosol

Appearance Clear liquid
Odor Solvent
Color White

Odor threshold No information available

Property Values Remarks • Method

pH No information available

Melting point / freezing point

Boiling point / boiling range
Flash point

Evaporation rate
Flammability (solid, gas)

No information available

> 35 °C / 95 °F

< 30 °C / < 86 °F

No information available

No information available

Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
Vapor pressure
Vapor density

No information available
No information available
No information available

Relative density 0.805 - 0.815 **Water solubility** Partially soluble

Solubility in other solvents
Partition coefficient
Autoignition temperature
Decomposition temperature
No information available
No information available
No information available

Kinematic viscosity 2 mm2/s

Dynamic viscosityNo information availableExplosive propertiesNo information availableOxidizing propertiesNo information available

Other Information

Softening pointNo information availableMolecular weightNo information available

VOC Content (%)

Density
No information available
Bulk density
No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Excessive heat.

Incompatible materials

Strong oxidizing agents

Hazardous Decomposition Products

Carbon oxides

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation May cause irritation of respiratory tract.

Eye contact Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

Skin contact May cause skin irritation and/or dermatitis.

Ingestion Ingestion may cause irritation to mucous membranes.

| Chemical Name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|--------------------------|--------------------|------------------------------|-------------------------------------|
| 2-Propanone | = 5800 mg/kg (Rat) | - | = 50100 mg/m ³ (Rat) 8 h |
| 67-64-1 | | | |
| Xylene | = 3500 mg/kg (Rat) | > 4350 mg/kg (Rabbit) > 1700 | = 29.08 mg/L (Rat) 4 h = 5000 |
| 1330-20-7 | | mg/kg (Rabbit) | ppm(Rat)4 h |
| Ethylbenzene 100-41-4 | = 3500 mg/kg (Rat) | = 15400 mg/kg (Rabbit) | = 17.2 mg/L (Rat)4 h |

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization Germ cell mutagenicityNo information available.
No information available.

CarcinogenicityThe table below indicates whether each agency has listed any ingredient as a carcinogen.

| Chemical Name | ACGIH | IARC | NTP | OSHA |
|---------------|-------|----------|-----|------|
| Xylene | - | Group 3 | - | - |
| 1330-20-7 | | | | |
| Ethylbenzene | A3 | Group 2B | - | X |
| 100-41-4 | | - | | |

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans Not classifiable as a human carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Target Organ Effects Central nervous system, Central Vascular System (CVS), Eyes, Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document.

 ATEmix (oral)
 5807 mg/kg

 ATEmix (dermal)
 11938 mg/kg

 ATEmix (inhalation-gas)
 23333 mg/l

ATEmix (inhalation-dust/mist) 11.4 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

8 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

| Chemical Name | Partition coefficient |
|--------------------------|-----------------------|
| 2-Propanone 67-64-1 | -0.24 |
| Xylene 1330-20-7 | 2.77 - 3.15 |
| Ethylbenzene 100-41-4 | 3.118 |

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastesDisposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number U002 U239

This product contains one or more substances that are listed with the State of California as a hazardous waste.

| Chemical Name | California Hazardous Waste Status |
|---------------|-----------------------------------|
| 2-Propanone | Ignitable |
| 67-64-1 | |
| Xylene | Toxic |
| 1330-20-7 | Ignitable |
| Ethylbenzene | Toxic |
| 100-41-4 | Ignitable |

14. TRANSPORT INFORMATION

NOTE:

DOT

UN/ID no 1950

Proper shipping name: Aerosols, Limited Quantity (LQ)

Hazard Class 2.1

IATA

UN/ID no 1950

Proper shipping name: Aerosols, Limited Quantity (LQ)

Hazard Class 2.1

IMDG

UN/ID no 1950

Proper shipping name: Aerosols, Limited Quantity (LQ)

Hazard Class 2.1

15. REGULATORY INFORMATION

International Inventories

Complies **TSCA DSL/NDSL** Complies **EINECS/ELINCS** Complies **ENCS** Complies Complies **IECSC** Complies **KECL** Complies **PICCS AICS** Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

| Chemical Name | SARA 313 - Threshold Values % | |
|-------------------------|-------------------------------|--|
| Xylene - 1330-20-7 | 1.0 | |
| Ethylbenzene - 100-41-4 | 0.1 | |

SARA 311/312 Hazard Categories

Acute health hazard No
Chronic Health Hazard No
Fire hazard Yes
Sudden release of pressure hazard No
Reactive Hazard No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

| Chemical Name | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous Substances |
|--------------------------|--------------------------------|------------------------|---------------------------|-------------------------------|
| Xylene 1330-20-7 | 100 lb | - | - | X |
| Ethylbenzene 100-41-4 | 1000 lb | X | Х | Х |

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

| Chemical Name | Hazardous Substances RQs | CERCLA/SARA RQ | Reportable Quantity (RQ) |
|---------------|--------------------------|----------------|--------------------------|
| 2-Propanone | 5000 lb | - | RQ 5000 lb final RQ |
| 67-64-1 | | | RQ 2270 kg final RQ |

| Xylene 1330-20-7 | 100 lb | - | RQ 100 lb final RQ RQ 45.4 kg final RQ |
|--------------------------|---------|---|---|
| Ethylbenzene 100-41-4 | 1000 lb | - | RQ 1000 lb final RQ RQ 454 kg final RQ |

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

| Chemical Name | California Proposition 65 | |
|-------------------------|---------------------------|--|
| Ethylbenzene - 100-41-4 | Carcinogen | |

U.S. State Right-to-Know Regulations

| Chemical Name | New Jersey | Massachusetts | Pennsylvania |
|----------------------------|------------|---------------|--------------|
| 2-Propanone | X | X | X |
| 67-64-1 | | | |
| Xylene 1330-20-7 | X | X | X |
| Carbon Dioxide 124-38-9 | X | Х | X |
| Ethylbenzene 100-41-4 | Х | X | X |

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

D2A - Very toxic materials

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 3 Instability 0

HMIS Health hazards 2 Flammability 3 Physical hazards 0 Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date 30-Jan-2017

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet