



Material Safety Data Sheet

Triple T

Date Issued: 04/10/2013

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: QMI Triple T Tune that Tank
GENERAL USE: Automotive Aftermarket
PRODUCT DESCRIPTION: Fuel Treatment
PRODUCT CODE: TTT10

DISTRIBUTOR

ITW Professional Automotive Products
3606 Craftsman Blvd.
Lakeland, FL 33803
Customer Service: 863-665-3338

24 HR EMERGENCY TELEPHONE NUMBERS

Poison Control Center: (877) 800-5533
CHEMTEL: (813) 248-0585

2. HAZARD IDENTIFICATION

POTENTIAL HEALTH EFFECTS

EYES: Can cause eye irritation.

SKIN: Can cause mild skin irritation and dryness. May absorb and/or defat skin on prolonged contact.

INGESTION: Ingestion may result in nausea or stomach discomfort. Due to its low viscosity, material may enter lungs during swallowing or vomiting. Once in lungs serious damage may occur.

INHALATION: Vapors generated at elevated temperatures can cause irritation to respiratory tract.

CHRONIC TOXICITY: May absorb and/or defat skin on prolonged contact.

CARCINOGENICITY: This material does not contain components that are listed as a carcinogen by the IARC, the NTP, or OSHA.

ROUTES OF ENTRY: Skin, Eyes, Ingestion, and Inhalation.

PHYSICAL HAZARD – Combustible Liquid

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS	Concentration, %
Aliphatic Naphtha	8052-41-3	35 – 45
Ethylene Glycol Monobutyl Ether	111-76-2	30 – 40
Petroleum distillates, paraffinic	Mixture	15 – 20
Polyethylene glycol ethers	Mixture	5 – 10



Material Safety Data Sheet

Triple T

Date Issued: 04/10/2013

4. FIRST AID MEASURES

EYES: Flush eyes gently with water for at least 15 minutes while holding eyelids apart. Seek immediate medical attention if irritation persists.

SKIN: Remove contaminated clothing. Flush exposed area with large amounts of water.

INGESTION: Seek medical attention. Do not induce vomiting.

INHALATION: Move individual away from exposure and into fresh air. If symptoms do not abate or breathing difficulty develops, seek medical attention. Do not leave individual unattended.

5. FIRE FIGHTING MEASURES

FLASH POINT: 118°F (48°C)

EXTINGUISHING MEDIA: CO₂, dry chemical, or foam. Use water to cool fire-exposed containers.

HAZARDOUS COMBUSTION PRODUCTS: Carbon Dioxide, Carbon Monoxide.

6. ACCIDENTAL RELEASE MEASURES

Use suitable PPE and ensure adequate ventilation. Eliminate all ignition sources including pilot lights and electric motors. Use non-sparking tools. Prevent runoff into drains, sewers, streams, or other bodies of water. Absorb liquid with vermiculite, floor absorbent or other absorbent material. Scoop or scrape up absorbent and put in the appropriate container for disposal.

7. HANDLING AND STORAGE

HANDLING: Keep away from heat and flame. Avoid prolonged skin contact, breathing vapors, and contaminated clothing. Use with adequate ventilation. Wear recommended protective equipment. Practice good personal hygiene after handling. Empty containers retain material residue. Do not cut, weld, braze, solder or expose containers to other ignition sources. Follow all MSDS/label precautions even after container is emptied because it may retain product residues.

STORAGE: Keep container tightly closed in a cool, well-ventilated area. KEEP OUT OF REACH OF CHILDREN.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits	Concentration	OSHA PEL	OSHA PEL	NIOSH
Chemical Name	percent	mg/m ³	ppm	mg/m ³
Aliphatic Naphtha	35 – 45	2900	500	350 (1800, 15 min)
Ethylene Glycol Monobutyl Ether	30 – 40	240	50	24
Petroleum distillates, paraffinic, as mist	15 – 20	5	n/a	5
Polyethylene glycol ethers	5 – 10	n/a	n/a	n/a



Material Safety Data Sheet

Triple T

Date Issued: 04/10/2013

ENGINEERING CONTROLS: Use with adequate ventilation. Explosion proof local exhaust is recommended in enclosed area.

PERSONAL PROTECTIVE EQUIPMENT

EYES: Appropriate eye protection.

SKIN: Nitrile or other chemical-resistant gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid
Odor and appearance: Clear, green. Petroleum odor.
Specific Gravity: 0.85
pH: N/A
Flash Point, PMCC 118°F (48°C)

10. STABILITY AND REACTIVITY

Stability: Normally stable at ambient temperature and pressure.
Conditions to Avoid: Heat, flame, sparks at temperatures at or above the flash point; contact with strong oxidizing agents.
Polymerization: Will not occur.
Thermal Decomposition: Oxides of carbon, smoke, toxic fumes

11. TOXICOLOGICAL INFORMATION

Component	LD50 mg/kg, Rat, Oral
Aliphatic Naphtha	>5000
Ethylene Glycol Monobutyl Ether	1480
Petroleum distillates, paraffinic	>5000
Polyethylene glycol ethers	NE

12. ECOLOGICAL INFORMATION

No ecological data are available for this product.

13. DISPOSAL CONSIDERATIONS

Consult federal, state, and local regulations regarding disposal.



Material Safety Data Sheet

Triple T

Date Issued: 04/10/2013

14. TRANSPORT INFORMATION

DOT Ground N/A (Not regulated in quantities less than 119 gallons per container)
DOT Air UN1993, Flammable liquid, N.O.S. (Contains Petroleum Distillates), 3, III Limited Quantities
IATA UN1993, Flammable liquid, N.O.S. (Contains Petroleum Distillates), 3, III Limited Quantities
IMDG UN1993, Flammable liquid, N.O.S. (Contains Petroleum Distillates), 3, III Limited Quantities

15. REGULATORY INFORMATION


TSCA: All components are on the US TSCA Inventory.
RCRA: Not listed in 40 CFR Part 302.4.
Cal. Prop. 65 This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive harm.

16. OTHER INFORMATION

HMIS Rating

HEALTH:	2	
FLAMMABILITY:	2	
PHYSICAL HAZARD:	0	
PERSONAL PROTECTION:	B	

NFPA Codes



DISCLAIMER:

ITW Professional Automotive Products (ITWProAp) believes the information contained in this data sheet is accurate as of the date compiled. However, ITWProAp makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. ITWProAp disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site (www.qmiitw.com).