•

Page 1 of 9

SECTION 1. IDENTIFICATION

Product identifier used on the label

: DRY GRAPHITE

Product Code(s) : BGS1

Recommended use of the chemical and restrictions on use

: Lubricant (aerosol).

Restrictions on use: Not available.

: Mixture of: Alcohol; Propellant

Name, address, and telephone number of

the supplier:

Chemical family

Name, address, and telephone number of the manufacturer:

Refer to supplier

Radiator Specialty Co., of Canada

3-3055 Dundas St West, Suite 50 Mississauga, ON, Canada

L5L 3R8

Supplier's Telephone # : (905) 625-9117 (Mon.-Fri., 8 am - 4 pm)

24 Hr. Emergency Tel # : Not available.

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical

Black liquid, contained in pressurized aerosol can. Hydrocarbon odour.

environment. See Section 12 for more environmental information.

Most important hazards:

Extremely flammable aerosol. May be ignited by open flames and sparks. Contents under pressure. Container may explode if heated.

Irritating to eyes and respiratory system. Inhalation may cause central nervous system depression. Occupational exposure to the substance or mixture may cause adverse effects. For further information, please refer to section 11 of the SDS. An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Avoid release to the

This product is packaged and sold as a consumer product. The Hazardous Products Act (HPA) does not apply to consumer products [Hazardous Products Act Section 12(j)]. The below WHMIS 2015 classification and labeling information is being provided for informational purposes.

This material is classified as hazardous under Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification:

Flammable aerosol - Category 1 Gases under pressure - Liquefied gas

Eye damage/irritation -Category 2A

Specific target organ toxicity, single exposure - Category 3 (Respiratory irritation; Narcotic effects)

Label elements

Hazard pictogram(s)



Signal Word DANGER!

Hazard statement(s)

Extremely flammable aerosol

Contains gas under pressure; may explode if heated.

Causes serious eye irritation.

May cause respiratory irritation.

May cause drowsiness or dizziness.

SDS Preparation Date (mm/dd/yyyy): 03/20/2019

DRY GRAPHITE BGS1

Page 2 of 9

SAFETY DATA SHEET

Precautionary statement(s)

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources - No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Avoid breathing mist or vapours.

Wash exposed skin thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear eye/face protection.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local regulation.

Other hazards

Other hazards which do not result in classification:

Toxic fumes may be released during a fire. May cause mild skin irritation. May cause gastrointestinal irritation. Ingestion of larger amounts may cause defects to the central nervous system (e.g. dizziness, headache). May be harmful if swallowed and enters airways.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Chemical name	Common name and synonyms	CAS#	Concentration (% by weight)
Isopropanol	Isopropyl alcohol 2-Propanol	67-63-0	65.0 - 85.0
Propane	Dimethylmethane Propyl hydride	74-98-6	10.0 - 30.0

The exact concentrations of the above listed chemicals are being withheld as a trade secret.

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

Ingestion

: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.

: IF INHALED: Remove person to fresh air and keep comfortable for breathing. If breathing is Inhalation

difficult, give oxygen by qualified medical personnel only. If breathing has stopped, give artificial respiration. Call a POISON CENTER or doctor/physician if you feel unwell.

: For skin contact, wash with soap and water while removing contaminated clothing. If Skin contact irritation or symptoms develop, seek medical attention. Launder clothing before reuse.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Flush eyes with water for at least 15 minutes. If

eye irritation persists: get medical advice/attention.

DRY GRAPHITE BGS1

Page 3 of 9

SAFETY DATA SHEET

Most important symptoms and effects, both acute and delayed

 Causes serious eye irritation. Symptoms may include redness, pain, tearing and conjunctivitis.

May cause respiratory irritation. Symptoms may include upper respiratory irritation, coughing and breathing difficulties. Inhalation may cause headache, nausea and central nervous effects such as dizziness, coordination difficulties and unconsciousness. May cause mild skin irritation. Direct skin contact may cause temporary redness. Prolonged or repeated contact may cause drying, cracking and defatting of the skin. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Ingestion of larger amounts may cause defects to the central nervous system (e.g. dizziness, headache). May be harmful if swallowed and enters airways. Product may present an aspiration hazard, if ingested in large amounts, causing life-threatening lung injury.

Indication of any immediate medical attention and special treatment needed

: Immediate medical attention is required. Product may present an aspiration hazard, if ingested in large amounts, causing life-threatening lung injury. Provide general supportive measures and treat symptomatically. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media

: Dry chemical, foam, carbon dioxide and water fog.

Unsuitable extinguishing media

: Do not use a solid water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture / Conditions of flammability

Extremely flammable aerosol. May be ignited by open flames and sparks. This product is contained under pressure, and could explode when exposed to heat and flame. Vapours are heavier than air and collect in confined and low-lying areas. Product may float, and be re-ignited at the water's surface. Toxic fumes, gases or vapours may evolve on burning.

Hazardous combustion products

: Carbon oxides; unburned alcohols.

Special protective equipment and precautions for firefighters

Protective equipment for fire-fighters

Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Special fire-fighting procedures

Move containers from fire area if safe to do so. Cool closed containers exposed to fire with water spray. Shield personnel to protect from venting or rupturing containers. Do not allow run-off from fire fighting to enter drains or water courses. Dike for water control.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: All persons dealing with the clean-up should wear the appropriate personal protective equipment. Keep all other personnel upwind and away from the spill/release. Restrict access to area until completion of clean-up. Refer to protective measures listed in sections 7 and 8.

Environmental precautions

: Prevent product from entering drains, sewers, waterways and soil.

DRY GRAPHITE BGS1

SDS Preparation Date (mm/dd/yyyy): 03/20/2019

Page 4 of 9

SAFETY DATA SHEET

Methods and material for containment and cleaning up

: Ventilate area of release. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. Use only non-sparking tools and equipment in the clean-up process. For spilled liquids: absorb spill with inert, non-combustible material such as sand, then place into suitable containers. Do not use combustible absorbents, such as sawdust. Keep in properly labelled containers. Notify the appropriate authorities as required. Refer to Section 13 for disposal of contaminated material.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

Use only outdoors or in a well-ventilated area. Wear suitable protective equipment during handling. Wear eye/face protection. Avoid breathing mist or vapours. Avoid contact with skin, eyes and clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Keep away from incompatibles. Always replace cap after use. Wash thoroughly after handling.

Conditions for safe storage

Store in a cool, well-ventilated area. Store locked up. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking in the area. Have appropriate fire extinguishers and spill clean-up equipment in or near storage area. Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F. Keep away from incompatibles.

Incompatible materials

: Strong oxidizing agents; Strong acids; Halogenated compounds; Alkali metals.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:							
Chemical Name	ACGIH TLV OSHA PEL						
	TWA	<u>STEL</u>	<u>PEL</u>	<u>STEL</u>			
Isopropanol	200 ppm	400 ppm	400 ppm (980 mg/m³)	N/Av			
Propane	N/Av	N/Av	1000 ppm (1800 mg/m³)	N/Av			

Exposure controls

Ventilation and engineering measures

: Use only outdoors or in a well-ventilated area. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. In case of insufficient ventilation wear suitable respiratory equipment.

Respiratory protection

: If airbourne concentrations are above the permissible exposure limit or are not known, use NIOSH-approved respirators. Refer to CSA Z94.3 or other appropriate standards. Advice should be sought from respiratory protection specialists.

Skin protection

Gloves impervious to the material are recommended. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Wear sufficient clothing to prevent skin contact.

Eye / face protection

Wear eye/face protection. Wear as appropriate: Safety glasses with side shields; Tightly fitting safety goggles .A full face shield may also be necessary.

Other protective equipment

Ensure that eyewash stations and safety showers are close to the workstation location. Other equipment may be required depending on workplace standards.

General hygiene considerations

: Avoid breathing mist or vapours. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Remove and wash contaminated clothing before re-use. Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Black liquid, contained in pressurized aerosol can.

Odour : Hydrocarbon odour.

DRY GRAPHITE BGS1

SDS Preparation Date (mm/dd/yyyy): 03/20/2019

SAFETY DATA SHEET

Odour threshold : N/Av pH : N/Av

Melting/Freezing point : Freezing point: - 90°C (- 130°F)(approximately)

Melting point: N/Av

Initial boiling point and boiling range

: 83°C (181°F)

Flash point : 14°C (57.2°F) (liquid)

Flashpoint (Method) : TCC

Evaporation rate (BuAe = 1) : > 1 (butyl acetate = 1)

Flammability (solid, gas) : Not applicable.

Lower flammable limit (% by vol.)

2.0%

Upper flammable limit (% by vol.)

: 12%

Oxidizing properties : No oxidizing properties.

Explosive properties: Aerosols are sensitive to mechanical impact. Closed containers are contained under

pressure and may explode if exposed to excess heat for a prolonged period of time.

Page 5 of 9

Vapour pressure : N/A

Vapour density : > 1 (Air = 1.0)

Relative density / Specific gravity

Relative density: 760 - 800 kg/m³

Specific Gravity: 0.76 - 0.80

Solubility in water : N/Av Other solubility(ies) : N/Av

Partition coefficient: n-octanol/water or Coefficient of water/oil distribution

: N/Av

Auto-ignition temperature : 399°C (750°F)

Decomposition temperature : N/Av Viscosity : N/Av Volatiles (% by weight) : N/Av Volatile organic Compounds (VOC's)

: N/Av

Absolute pressure of container

: N/Av

Flame projection length : > 45 cm (17.7")

Other physical/chemical comments

: Flashback Observed: N/Av

Chemical heat of combustion: N/Av

SECTION 10. STABILITY AND REACTIVITY

Reactivity: Not normally reactive.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions

Hazardous polymerization does not occur. No dangerous reaction known under conditions

of normal use.

Conditions to avoid : Direct sources of heat. Do not use in areas without adequate ventilation. Avoid contact with

incompatible materials. Protect from sunlight and do not expose to temperatures exceeding

50 °C/122 °F.

Incompatible materials : Strong oxidizing agents; Strong acids; Halogenated compounds; Alkali metals.

Hazardous decomposition products

: Not available.

Refer also to hazardous combustion products, Section 5.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Routes of entry inhalation : YES
Routes of entry skin & eye : YES
Routes of entry Ingestion : YES
Routes of exposure skin absorption

: NO

Potential Health Effects:

Signs and symptoms of short-term (acute) exposure

Sign and symptoms Inhalation

• May cause respiratory irritation. Symptoms may include upper respiratory irritation, coughing and breathing difficulties. Inhalation may cause headache, nausea and central nervous effects such as dizziness, coordination difficulties and unconsciousness. In extremely high concentrations, product may act as an asphyxiant and cause increased breathing and pulse rates, fatigue and unconsciousness.

Sign and symptoms ingestion

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May be harmful if swallowed and enters airways. Product may present an aspiration hazard, if ingested in large amounts, causing life-threatening lung injury. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal.

Sign and symptoms skin

Direct skin contact may cause slight or mild, transient irritation. Direct skin contact may cause temporary redness.

Sign and symptoms eyes

Causes serious eye irritation. Symptoms may include redness, pain, tearing and conjunctivitis.

Potential Chronic Health Effects

: Prolonged skin contact may cause dermatitis (rash), characterized by red, dry, itching skin.

Mutagenicity

No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity

: No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP.

Reproductive effects & Teratogenicity

: This product is not expected to cause reproductive or developmental effects.

Sensitization to material

: Not expected to be a skin or respiratory sensitizer.

Specific target organ effects

This material is classified as hazardous under Canadian WHMIS regulations (Hazardous

Products Regulations) (WHMIS 2015). Classification:

Specific target organ toxicity, single exposure - Category 3. May cause drowsiness or

dizziness. May cause respiratory irritation.

According to the classification criteria of Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015), this product is not expected to cause specific target organ toxicity (STOT) through repeated exposures.

Medical conditions aggravated by overexposure

: Pre-existing skin, eye, respiratory and central nervous system disorders.

Synergistic materials

: None known or reported by the manufacturer.

Toxicological data

: There is no available data for the product itself, only for the ingredients. See below for individual ingredient acute toxicity data.

	LCso (4hr)	LD50		
Chemical name	inh, rat	(Oral, rat)	(Rabbit, dermal)	
Isopropanol	17 000 ppm (41.8 mg/L) (vapour)	4720 mg/kg	12 890 mg/kg	
Propane	N/Av	N/Ap (gas)	N/Ap (gas)	

Page 7 of 9

SAFETY DATA SHEET

Other important toxicological hazards

: None known or reported by the manufacturer.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

: No data is available on the product itself. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters.

See the following tables for individual ingredient ecotoxicity data.

Ecotoxicity data:

la sua dianta	2121		Toxicity to Fish		
<u>Ingredients</u>	CAS No	LC50 / 96h	NOEC / 21 day	M Factor	
Isopropanol	67-63-0	9640 mg/L (Fathead minnow)	N/Av	None.	
Propane	74-98-6	N/Ap	N/Ap	N/Ap	

<u>Ingredients</u>	CAS No	Toxicity to Daphnia				
		EC50 / 48h	NOEC / 21 day	M Factor		
Isopropanol	67-63-0	> 10 000 mg/L/24hr (Daphnia magna)	30 mg/L	None.		
Propane	74-98-6	N/Ap	N/Ap	N/Ap		

<u>Ingredients</u>	CAS No	Toxicity to Algae			
		EC50 / 96h or 72h	NOEC / 96h or 72h	M Factor	
Isopropanol	67-63-0	N/Av	N/Av	None.	
Propane	74-98-6	N/Ap	N/Ap	N/Ap	

Persistence and degradability

: The product itself has not been tested.

The following ingredients are considered to be readily biodegradable: Isopropanol.

Bioaccumulation potential

: The product itself has not been tested. See the following data for ingredient information.

	Components	Partition coefficient n-octanol/water (log Kow)	Bioconcentration factor (BCF)
Is	sopropanol (CAS 67-63-0)	0.05	1.0

Mobility in soil

: The product itself has not been tested.

Other Adverse Environmental effects

: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13. DISPOSAL CONSIDERATIONS

Handling for Disposal

: Handle in accordance with good industrial hygiene and safety practice. Refer to protective measures listed in sections 7 and 8.

This material and its container must be disposed of in a safe way. Empty containers retain residue and can be dangerous. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

Methods of Disposal

: Dispose of in accordance with federal, provincial and local hazardous waste laws.

SECTION 14. TRANSPORT INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
TDG	UN1950	AEROSOLS	2.1	None	2
TDG Additional information		as LIMITED QUANTITY when transported in containers no lar ss. Under the TDGR, refer to Section 1.17 for additional exemp			

Special precautions for user

: Appropriate advice on safety must accompany the package. Keep away from heat, sparks

and open flame. - No smoking.

Environmental hazards

: This product does not meet the criteria for an environmentally hazardous mixture, according

to the IMDG Code. See ECOLOGICAL INFORMATION, Section 12.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: Not applicable.

SECTION 15 - REGULATORY INFORMATION

Canadian Information:

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

Canadian National Pollutant Release Inventory (NPRI): This product contains the following substances listed on the NPRI: Isopropanol (Part 1, Group A Substance; Part 5: Individual Substances)

Propane (Part 5: Individual Substances)

WHMIS information: Refer to Section 2 for a WHMIS Classification for this product.

US Federal Information:

TSCA: All listed ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

International Information:

Components listed below are present on the following International Inventory list:

Ingredients	CAS#	European EINECs	Australia AICS	Philippines PICCS	Japan ENCS	Korea KECI/KECL	China IECSC	New Zealand IOC
Isopropanol	67-63-0	200-661-7	Present	Present	(2)-207	KE-29363	Present	HSR001180
Propane	74-98-6	200-827-9	Present	Present	(2)-3	KE-29258	Present	HSR001010

SECTION 16. OTHER INFORMATION

Legend

: ACGIH: American Conference of Governmental Industrial Hygienists

AICS: Australian Inventory of Chemical Substances

CAS: Chemical Abstract Services CSA: Canadian Standards Association EC50: Effective Concentration 50%

EINECS: European Inventory of Existing Commercial chemical Substances

HSDB: Hazardous Substances Data Bank

IARC: International Agency for Research on Cancer

IBC: Intermediate Bulk Container

IECSC: Inventory of Existing Chemical Substances IMDG: International Maritime Dangerous Goods

Inh: Inhalation

IOC: Inventory of Chemicals

KECI: Korean Existing Chemicals Inventory KECL: Korean Existing Chemicals List

LC: Lethal Concentration

LD: Lethal Dose N/Ap: Not Applicable N/Av: Not Available

NIOSH: National Institute of Occupational Safety and Health

NOEC: No observable effect concentration NTP: National Toxicology Program

OECD: Organisation for Economic Co-operation and Development

OSHA: Occupational Safety and Health Administration

PEL: Permissible exposure limit

PICCS: Philippine Inventory of Chemicals and Chemical Substances

RTECS: Registry of Toxic Effects of Chemical Substances

SDS: Safety Data Sheet

STEL: Short Term Exposure Limit

TDG: Canadian Transportation of Dangerous Goods Act & Regulations

TLV: Threshold Limit Values TWA: Time Weighted Average

WHMIS: Workplace Hazardous Materials Identification System

References

- ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices for 2018.
- 2. International Agency for Research on Cancer Monographs, searched 2019.
- Canadian Centre for Occupational Health and Safety, CCInfoWeb databases, 2019 (Chempendium, HSDB and RTECs).
- 4. Material Safety Data Sheets from manufacturer.
- 5. OECD The Global Portal to Information on Chemical Substances eChemPortal, 2019.

Preparation Date (mm/dd/yyyy)

: 03/20/2019

Other special considerations for handling

: Provide adequate information, instruction and training for operators.

Prepared for:

Radiator Specialty Co. of Canada 3-3055 Dundas St West, Suite 50 Mississauga, ON, Canada, L5L 3R8

Telephone: 905-625-9117 (Mon. - Fri., 8 AM - 4 PM) Please direct all enquiries to Radiator Specialty.

Prepared by:

ICC The Compliance Center Inc.

Telephone: (888) 442-9628 (U.S.): (888) 977-4834 (Canada)

http://www.thecompliancecenter.com



DISCLAIMER

This Safety Data Sheet was prepared by ICC The Compliance Center Inc. using information provided by Radiator Specialty Co. of Canada and CCOHS' Web Information Service. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and Radiator Specialty Co. of Canada expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other process.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc. and Radiator Specialty Co. of Canada.

END OF DOCUMENT