



## Safety Data Sheet

# Gator Skin Auto Body Rubberized Undercoating Spray Aerosol

### SECTION 1. IDENTIFICATION

**Product Identifier** Gator Skin Auto Body Rubberized Undercoating Spray Aerosol  
**Other Means of Identification** Code No. A847  
**Recommended Use** Rubberized Coating.  
**Restrictions on Use** Use only as directed according to label instructions.  
**Manufacturer/Supplier Identifier** Leysons Products, a division of 1787528 Ontario Inc., 1366 Sandhill Drive, Ancaster, Ontario, L9G 4V5, (905) 648-7832  
**Emergency Phone No.** CANUTECH, 613-996-6666, 24-hr for Emergencies involving Dangerous Goods  
**SDS No.** 0592

### SECTION 2. HAZARD IDENTIFICATION

#### Classification

Flammable aerosol - Category 1; Gas under pressure - Compressed gas; Skin irritation - Category 2; Eye irritation - Category 2A; Respiratory sensitization - Category 1B; Carcinogenicity - Category 1A; Specific target organ toxicity (repeated exposure) - Category 2

#### Label Elements



Danger  
Extremely flammable aerosol.  
Contains gas under pressure; may explode if heated.  
May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
Causes skin and eye irritation.  
May cause damage to organs through prolonged or repeated exposure.  
Suspected of damaging fertility or the unborn child.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name          | CAS No.   | %     | Other Identifiers | Other Names |
|------------------------|-----------|-------|-------------------|-------------|
| Acetone                | 67-64-1   | 30-60 |                   |             |
| n-Butane               | 106-97-8  | 15-40 |                   |             |
| Propane                | 74-98-6   | 10-30 |                   |             |
| Toluene                | 108-88-3  | 10-30 |                   |             |
| Xylene (mixed isomers) | 1330-20-7 | 3-7   |                   |             |
| Carbon black           | 1333-86-4 | 1-5   |                   |             |

Product Identifier: Gator Skin Auto Body Rubberized Undercoating Spray Aerosol - Ver. 1  
Date of Preparation: February 08, 2018  
Date of Last Revision:

SDS No.: 0592

Page 01 of 06

|                                |            |         |  |  |
|--------------------------------|------------|---------|--|--|
| Light aromatic solvent naphtha | 64742-95-6 | 0.1-1.0 |  |  |
|--------------------------------|------------|---------|--|--|

## SECTION 4. FIRST-AID MEASURES

### First-aid Measures

#### Inhalation

If irritation is experienced, remove person to fresh air.

If experiencing respiratory symptoms (e.g. coughing, shortness of breath, wheezing), call a Poison Centre or doctor.

#### Skin Contact

In case of contact, immediately flush skin with plenty of water.

If skin irritation or a rash occurs, get medical advice or attention.

#### Eye Contact

Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open.

Remove contact lenses, if present and easy to do.

If eye irritation persists, get medical advice or attention.

#### Ingestion

Never give anything by mouth if person is rapidly losing consciousness, or is unconscious or convulsing. Do not induce vomiting.

If vomiting occurs naturally, lie on your side in the recovery position. Rinse mouth with water again.

Immediately call a Poison Centre or doctor.

### Most Important Symptoms and Effects, Acute and Delayed

May irritate the respiratory system.

May cause severe eye irritation or burns.

May cause skin irritation on prolonged contact.

Harmful if swallowed.

### Immediate Medical Attention and Special Treatment

#### Target Organs

Eyes, skin, respiratory system.

#### Medical Conditions Aggravated by Exposure

Asthma, skin allergies.

## SECTION 5. FIRE-FIGHTING MEASURES

### Extinguishing Media

#### Suitable Extinguishing Media

Carbon dioxide, dry chemical powder or appropriate foam.

#### Unsuitable Extinguishing Media

Water.

### Specific Hazards Arising from the Product

Extremely flammable liquid and vapour. Can ignite at room temperature. Releases vapour that can form explosive mixture with air.

### Special Protective Equipment and Precautions for Fire-fighters

Wear full fire fighting equipment and respirator.

Containers may explode if heated.

Fire-fighters may enter the area if positive pressure SCBA and full Bunker Gear is worn.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

### Personal Precautions, Protective Equipment, and Emergency Procedures

Use the personal protective equipment recommended in Section 8 of this safety data sheet.

Increase ventilation to area or move leaking container to a well-ventilated and secure area.  
Eliminate all ignition sources. Use grounded, explosion-proof equipment.

#### Environmental Precautions

Do not allow into any sewer, on the ground or into any waterway.  
If the spill is inside a building, prevent product from entering drains, ventilation systems and confined areas.  
Minimize the use of water to prevent environmental contamination.

#### Methods and Materials for Containment and Cleaning Up

Place used absorbent into suitable, covered, labelled containers for disposal.

## SECTION 7. HANDLING AND STORAGE

#### Precautions for Safe Handling

Do not get in eyes, on skin or on clothing.  
Do not spray on an open flame or other ignition source. Do not pierce or burn container, even after use.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Avoid breathing in this product.

#### Conditions for Safe Storage

Store in a cool dry area away from incompatible materials.  
Keep out of reach of children in a tightly closed container away from food, drink and animal feed.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control Parameters

| Chemical Name                  | ACGIH TLV® |          | OSHA PEL |         | AIHA WEEL |     |
|--------------------------------|------------|----------|----------|---------|-----------|-----|
|                                | TWA        | STEL     | TWA      | Ceiling | 8-hr TWA  | TWA |
| Propane                        | 1800 mg/m3 |          |          |         |           |     |
| n-Butane                       |            | 1000 ppm |          |         |           |     |
| Acetone                        | 250 ppm    |          | 1000 ppm |         |           |     |
| Toluene                        | 20 ppm     |          | 100 ppm  |         |           |     |
| Xylene (mixed isomers)         | 100 ppm    | 150 ppm  |          |         |           |     |
| Carbon black                   | 7 mg/m3    |          |          |         |           |     |
| Light aromatic solvent naphtha | 21 ppm     |          |          |         |           |     |

#### Appropriate Engineering Controls

Use ventilation adequate to keep exposures (airborne levels of vapour) below the recommended exposure limits.

#### Individual Protection Measures

##### Eye/Face Protection

Wear chemical safety goggles and face shield when contact is possible.

##### Skin Protection

Wear protective gloves and clothing to prevent skin contact.

##### Respiratory Protection

Use in well ventilated areas. In case of insufficient ventilation, wear suitable respiratory equipment.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Basic Physical and Chemical Properties

|                              |                          |
|------------------------------|--------------------------|
| Appearance                   | Black.                   |
| Odour                        | hydrocarbon odour        |
| pH                           | Not applicable           |
| Melting Point/Freezing Point | Not available (freezing) |
| Flash Point                  | ~ -104 °C (-155 °F)      |

Product Identifier: Gator Skin Auto Body Rubberized Undercoating Spray Aerosol - Ver. 1  
Date of Preparation: February 08, 2018  
Date of Last Revision:

SDS No.: 0592

Page 03 of 06

|                                                    |                                              |
|----------------------------------------------------|----------------------------------------------|
| <b>Evaporation Rate</b>                            | > 1                                          |
| <b>Upper/Lower Flammability or Explosive Limit</b> | Not available (upper); Not available (lower) |
| <b>Vapour Pressure</b>                             | Not available                                |
| <b>Vapour Density (air = 1)</b>                    | > 1                                          |
| <b>Solubility</b>                                  | Not applicable in water                      |
| <b>Other Information</b>                           |                                              |
| <b>Physical State</b>                              | Gas                                          |
| <b>Bulk Density</b>                                | ~ 0.86 kg/L                                  |

## SECTION 10. STABILITY AND REACTIVITY

### Reactivity

Not reactive under normal conditions of use.

### Chemical Stability

Normally stable.

### Conditions to Avoid

High temperatures.

Freezing.

Incompatible materials.

### Incompatible Materials

Strong acids (e.g. hydrochloric acid), strong oxidizing agents (e.g. perchloric acid), strong reducing agents (e.g. hydrides).

### Hazardous Decomposition Products

May include but are not limited to oxides of carbon, nitrogen and ammonia.

## SECTION 11. TOXICOLOGICAL INFORMATION

### Likely Routes of Exposure

Inhalation.

Skin contact.

Skin absorption.

Eye contact.

Ingestion.

### Acute Toxicity

| Chemical Name                  | LC50                                          | LD50 (oral)         | LD50 (dermal)         |
|--------------------------------|-----------------------------------------------|---------------------|-----------------------|
| Propane                        | 658 mg/L (rat) (4-hour exposure) (gas)        |                     |                       |
| n-Butane                       | 658,000 mg/L (rat) (4-hour exposure) (vapour) |                     |                       |
| Acetone                        |                                               | 5,800 mg/kg (rat)   |                       |
| Toluene                        | 28.1 mg/L (rat) (4-hour exposure)             | > 5000 mg/kg (rat)  | > 5000 mg/kg (rabbit) |
| Xylene (mixed isomers)         |                                               | 4300 mg/kg (rat)    |                       |
| Carbon black                   |                                               | > 8,000 mg/kg (rat) |                       |
| Light aromatic solvent naphtha |                                               | 5,000 mg/kg (rat)   |                       |

### Skin Corrosion/Irritation

May cause irritation or symptoms such as redness, edema, drying, defatting or cracking of the skin.

Product Identifier: Gator Skin Auto Body Rubberized Undercoating Spray Aerosol - Ver. 1  
Date of Preparation: February 08, 2018  
Date of Last Revision:

SDS No.: 0592

Page 04 of 06

**Serious Eye Damage/Irritation**

May cause serious eye irritation based on information for closely related materials.

**STOT (Specific Target Organ Toxicity) - Single Exposure****Inhalation**

May cause irritation of the respiratory system.

**Skin Absorption**

May cause irritation on prolonged contact.

**Ingestion**

Harmful if swallowed.

**Aspiration Hazard**

May be drawn into the lungs (aspirated) if swallowed or vomited.

**STOT (Specific Target Organ Toxicity) - Repeated Exposure**

May cause damage to organs through prolonged or repeated exposure.

**Respiratory and/or Skin Sensitization**

Not expected to produce any respiratory system problems when used in a well ventilated area.

**Carcinogenicity**

Not known to cause cancer.

**Reproductive Toxicity****Development of Offspring**

May harm the unborn child.

**Sexual Function and Fertility**

Not known to cause effects on sexual function or fertility.

**Effects on or via Lactation**

Not known to cause effects on or via lactation.

**Germ Cell Mutagenicity**

No information was located.

**Interactive Effects**

No information was located.

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

May cause long-term adverse effects in the aquatic environment.

**Persistence and Degradability**

May cause long-term adverse effects in the aquatic environment.

**Bioaccumulative Potential**

No information was located.

**Mobility in Soil**

No information was located.

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal Methods**

Dispose of contents and container in accordance with local, regional, national and international regulations.

## SECTION 14. TRANSPORT INFORMATION

| Regulation   | UN No. | Proper Shipping Name | Transport Hazard Class(es) | Packing Group   |
|--------------|--------|----------------------|----------------------------|-----------------|
| Canadian TDG | 1950   | Aerosols, Flammable  | 2.1                        | Not applicable. |

**Special Precautions** Please note: This product meets the exemption requirements and may be shipped as a "Limited Quantity".

**Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code**


Not applicable

## SECTION 15. REGULATORY INFORMATION

### Safety, Health and Environmental Regulations

#### Canada

##### WHMIS 1988 Classification



Class A



Class B5



Class D2B

A - Compressed Gas; B5 - Flammable Aerosol; D2B - Toxic (Skin irritant; Eye irritant; Mutagenicity)

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all of the information required by the Controlled Products Regulations.

## SECTION 16. OTHER INFORMATION

**SDS Prepared By** Mark Bryans

**Phone No.** (905) 648-7832 ext 351

**Date of Preparation** February 08, 2018

#### Disclaimer

The user of this product assumes all risks incident to the use of this product.

To the best of our knowledge, the information contained herein is accurate.

However, the supplier assumes no liability whatsoever for the accuracy or completeness of the information contained herein.

No representation of warranties, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to the information or the product to which the information refers.

The data contained on this sheet apply to the products supplied to the user.

Product Identifier: Gator Skin Auto Body Rubberized Undercoating Spray Aerosol - Ver. 1

SDS No.: 0592

Date of Preparation: February 08, 2018

Date of Last Revision:

Page 06 of 06