

# SAFETY DATA SHEET



The information in this Safety Data Sheet is required pursuant to Hazardous Product Regulations 2015.

Date of issue/Date of revision 28 May 2021

Version 14

## Section 1. Identification

Product name : 2.1 EPOXY HARDENER

Product code : ESU479

Other means of identification : Not available.

Product type : Liquid.

### Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications.

Use of the substance/  
mixture : Coating. Paints. Painting-related materials.

Uses advised against : Not applicable.

Supplier : PPG Canada Inc.  
2301 Royal Windsor Drive  
Mississauga, ON L5J 1K5  
Canada  
+1 888-310-4762

PPG Industries, Inc.  
One PPG Place,  
Pittsburgh, PA 15272

Emergency telephone number : (412) 434-4515 (U.S.)  
(514) 645-1320 (Canada)  
SETIQ Interior de la República: 800-00-214-00 (México)  
SETIQ Ciudad de México: (55) 5559-1588 (México)

Technical Phone Number : 1-800-647-6050

## Section 2. Hazard identification

Classification of the  
substance or mixture : FLAMMABLE LIQUIDS - Category 3  
ACUTE TOXICITY (inhalation) - Category 4  
SKIN IRRITATION - Category 2  
SERIOUS EYE DAMAGE - Category 1  
SKIN SENSITIZATION - Category 1B  
CARCINOGENICITY - Category 2  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract  
irritation) - Category 3  
Health Hazards Not Otherwise Classified - Category 1

### GHS label elements

## Section 2. Hazard identification

**Hazard pictograms**

:

**Signal word**

: Danger

**Hazard statements**

: Flammable liquid and vapor.  
Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye damage.  
Harmful if inhaled.  
May cause respiratory irritation.  
Suspected of causing cancer.  
Prolonged or repeated contact may dry skin and cause irritation.

**Precautionary statements****Prevention**

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Avoid breathing vapor. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

**Response**

: IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

**Storage**

: Store locked up. Store in a well-ventilated place. Keep container tightly closed.

**Disposal**

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Supplemental label elements**

: Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing. Wash thoroughly after handling. Emits toxic fumes when heated.  
Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity:  
37.3% (oral), 37.3% (dermal), 50.9% (inhalation)

## Section 3. Composition/information on ingredients

**Substance/mixture**

: Mixture

**Product name**

: 2.1 EPOXY HARDENER

**Other means of identification**

: Not available.

**CAS number/other identifiers**

## Section 3. Composition/information on ingredients

| Ingredient name                                    | Synonyms       | % (w/w)  | CAS number |
|----------------------------------------------------|----------------|----------|------------|
| 4-chloro- $\alpha,\alpha,\alpha$ -trifluorotoluene | Not available. | 10 - 30* | 98-56-6    |
| xylene                                             | Not available. | 10 - 30* | 1330-20-7  |
| docusate sodium                                    | Not available. | 5 - 10*  | 577-11-7   |
| butan-1-ol                                         | Not available. | 3 - 7*   | 71-36-3    |
| Naphtha (petroleum), hydrotreated heavy            | Not available. | 1 - 5*   | 64742-48-9 |
| 2,4,6-tris(dimethylaminomethyl)phenol              | Not available. | 1 - 5*   | 90-72-2    |
| Isopropyl alcohol                                  | Not available. | 1 - 5*   | 67-63-0    |

\*Ranges if listed above for hazardous ingredient(s) are prescribed ranges. The actual concentration(s) or actual concentration range(s) are being withheld as a trade secret.

SUB codes represent substances without registered CAS Numbers.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First-aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

### Description of necessary first aid measures

- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : Harmful if inhaled. May cause respiratory irritation.
- Skin contact** : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing

## Section 4. First-aid measures

- Skin contact** : Adverse symptoms may include the following:  
pain or irritation  
redness  
dryness  
cracking  
blistering may occur
- Ingestion** : Adverse symptoms may include the following:  
stomach pains

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

- Specific hazards arising from the chemical** : Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon oxides  
nitrogen oxides  
sulfur oxides  
halogenated compounds  
carbonyl halides  
metal oxide/oxides
- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Special precautions** : If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.

## Section 7. Handling and storage

### Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### Conditions for safe storage, including any incompatibilities

: Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

| Ingredient name                                    | Exposure limits                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|----------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 4-chloro- $\alpha,\alpha,\alpha$ -trifluorotoluene | IPEL (-).<br>TWA: 0.57 ppm<br>STEL: 1.71 ppm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| xylene                                             | <b>CA Alberta Provincial (Canada, 6/2018).</b><br>15 min OEL: 651 mg/m <sup>3</sup> 15 minutes.<br>15 min OEL: 150 ppm 15 minutes.<br>8 hrs OEL: 434 mg/m <sup>3</sup> 8 hours.<br>8 hrs OEL: 100 ppm 8 hours.<br><b>CA British Columbia Provincial (Canada, 1/2020).</b><br>STEL: 150 ppm 15 minutes.<br>TWA: 100 ppm 8 hours.<br><b>CA Quebec Provincial (Canada, 7/2019).</b><br>STEV: 651 mg/m <sup>3</sup> 15 minutes.<br>STEV: 150 ppm 15 minutes.<br>TWA EV: 434 mg/m <sup>3</sup> 8 hours.<br>TWA EV: 100 ppm 8 hours.<br><b>CA Ontario Provincial (Canada, 6/2019).</b><br>STEL: 150 ppm 15 minutes.<br>TWA: 100 ppm 8 hours.<br><b>CA Saskatchewan Provincial (Canada, 7/2013).</b><br>STEL: 150 ppm 15 minutes.<br>TWA: 100 ppm 8 hours. |
| docusate sodium                                    | None.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| butan-1-ol                                         | <b>CA British Columbia Provincial (Canada, 1/2020).</b><br>C: 30 ppm 15 minutes.<br>TWA: 15 ppm 8 hours.<br><b>CA Ontario Provincial (Canada, 6/2019).</b><br>TWA: 20 ppm 8 hours.<br><b>CA Quebec Provincial (Canada, 7/2019).</b><br>Absorbed through skin.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |

## Section 8. Exposure controls/personal protection

Naphtha (petroleum), hydrotreated heavy  
2,4,6-tris(dimethylaminomethyl)phenol  
Isopropyl alcohol

STEV: 152 mg/m<sup>3</sup> 15 minutes.  
STEV: 50 ppm 15 minutes.

**CA Alberta Provincial (Canada, 6/2018).**  
**Skin sensitizer.**

8 hrs OEL: 60 mg/m<sup>3</sup> 8 hours.

8 hrs OEL: 20 ppm 8 hours.

**CA Saskatchewan Provincial (Canada, 7/2013).**

STEL: 30 ppm 15 minutes.

TWA: 20 ppm 8 hours.

None.

None.

**CA Alberta Provincial (Canada, 6/2018).**  
15 min OEL: 984 mg/m<sup>3</sup> 15 minutes.

8 hrs OEL: 200 ppm 8 hours.

15 min OEL: 400 ppm 15 minutes.

8 hrs OEL: 492 mg/m<sup>3</sup> 8 hours.

**CA British Columbia Provincial (Canada, 1/2020).**

TWA: 200 ppm 8 hours.

STEL: 400 ppm 15 minutes.

**CA Ontario Provincial (Canada, 6/2019).**

TWA: 200 ppm 8 hours.

STEL: 400 ppm 15 minutes.

**CA Quebec Provincial (Canada, 7/2019).**

TWAEV: 400 ppm 8 hours.

TWAEV: 983 mg/m<sup>3</sup> 8 hours.

STEV: 500 ppm 15 minutes.

STEV: 1230 mg/m<sup>3</sup> 15 minutes.

**CA Saskatchewan Provincial (Canada, 7/2013).**

STEL: 400 ppm 15 minutes.

TWA: 200 ppm 8 hours.

Consult local authorities for acceptable exposure limits.

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

## Section 8. Exposure controls/personal protection

|                               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|-------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Hygiene measures</b>       | : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.                                                                                                                                         |
| <b>Eye/face protection</b>    | : Chemical splash goggles and face shield.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Skin protection</b>        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Hand protection</b>        | : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. |
| <b>Gloves</b>                 | : butyl rubber                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Body protection</b>        | : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.                                                                                                                                                                                    |
| <b>Other skin protection</b>  | : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Respiratory protection</b> | : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.                                                                                                                                                               |

## Section 9. Physical and chemical properties

### Appearance

|                                                     |                              |
|-----------------------------------------------------|------------------------------|
| <b>Physical state</b>                               | : Liquid.                    |
| <b>Color</b>                                        | : Not available.             |
| <b>Odor</b>                                         | : Not available.             |
| <b>Odor threshold</b>                               | : Not available.             |
| <b>pH</b>                                           | : Not applicable.            |
| <b>Melting point</b>                                | : Not available.             |
| <b>Boiling point</b>                                | : >37.78°C (>100°F)          |
| <b>Flash point</b>                                  | : Closed cup: 23.89°C (75°F) |
| <b>Auto-ignition temperature</b>                    | : Not available.             |
| <b>Decomposition temperature</b>                    | : Not available.             |
| <b>Flammability (solid, gas)</b>                    | : Not available.             |
| <b>Lower and upper explosive (flammable) limits</b> | : Not available.             |
| <b>Evaporation rate</b>                             | : Not available.             |
| <b>Vapor pressure</b>                               | : Not available.             |
| <b>Vapor density</b>                                | : Not available.             |

## Section 9. Physical and chemical properties

|                                        |                                                              |
|----------------------------------------|--------------------------------------------------------------|
| Relative density                       | : 1.04                                                       |
| Density ( lbs / gal )                  | : 8.68                                                       |
| Solubility                             | : Insoluble in the following materials: cold water.          |
| Partition coefficient: n-octanol/water | : Not applicable.                                            |
| Viscosity                              | : Kinematic (40°C (104°F)): >21 mm <sup>2</sup> /s (>21 cSt) |
| Volatility                             | : 52% (v/v), 51.759% (w/w)                                   |
| % Solid. (w/w)                         | : 48.241                                                     |

## Section 10. Stability and reactivity

|                                    |                                                                                                                                                                                                    |
|------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Reactivity                         | : No specific test data related to reactivity available for this product or its ingredients.                                                                                                       |
| Chemical stability                 | : The product is stable.                                                                                                                                                                           |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur.                                                                                                                  |
| Conditions to avoid                | : When exposed to high temperatures may produce hazardous decomposition products.<br>Refer to protective measures listed in sections 7 and 8.                                                      |
| Incompatible materials             | : Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.                                                                   |
| Hazardous decomposition products   | : Depending on conditions, decomposition products may include the following materials:<br>carbon oxides nitrogen oxides sulfur oxides halogenated compounds carbonyl halides<br>metal oxide/oxides |

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

| Product/ingredient name                            | Result                | Species | Dose                    | Exposure |
|----------------------------------------------------|-----------------------|---------|-------------------------|----------|
| 4-chloro- $\alpha,\alpha,\alpha$ -trifluorotoluene | LC50 Inhalation Vapor | Rat     | 33080 mg/m <sup>3</sup> | 4 hours  |
| xylene                                             | LD50 Dermal           | Rabbit  | >2.7 g/kg               | -        |
|                                                    | LD50 Oral             | Rat     | 13 g/kg                 | -        |
|                                                    | LD50 Dermal           | Rabbit  | 1.7 g/kg                | -        |
|                                                    | LD50 Oral             | Rat     | 4.3 g/kg                | -        |
| docusate sodium                                    | LD50 Dermal           | Rabbit  | >10 g/kg                | -        |
|                                                    | LD50 Oral             | Rat     | 3080 mg/kg              | -        |
| butan-1-ol                                         | LC50 Inhalation Vapor | Rat     | 24000 mg/m <sup>3</sup> | 4 hours  |
|                                                    | LC50 Inhalation Vapor | Rat     | 8000 ppm                | 4 hours  |
|                                                    | LD50 Dermal           | Rabbit  | 3400 mg/kg              | -        |
|                                                    | LD50 Oral             | Rat     | 790 mg/kg               | -        |
| Naphtha (petroleum), hydrotreated heavy            | LD50 Dermal           | Rabbit  | >5000 mg/kg             | -        |
|                                                    | LD50 Oral             | Rat     | >6 g/kg                 | -        |
| 2,4,6-tris (dimethylaminomethyl)                   | LD50 Oral             | Rat     | >6 g/kg                 | -        |
|                                                    | LD50 Dermal           | Rabbit  | 1.28 g/kg               | -        |

## Section 11. Toxicological information

|                   |                       |        |                         |         |
|-------------------|-----------------------|--------|-------------------------|---------|
| phenol            | LD50 Dermal           | Rat    | 1280 mg/kg              | -       |
|                   | LD50 Oral             | Rat    | 1200 mg/kg              | -       |
| Isopropyl alcohol | LC50 Inhalation Vapor | Rat    | 72600 mg/m <sup>3</sup> | 4 hours |
|                   | LD50 Dermal           | Rabbit | 12800 mg/kg             | -       |
|                   | LD50 Oral             | Rat    | 5045 mg/kg              | -       |

**Conclusion/Summary** : There are no data available on the mixture itself.

Irritation/Corrosion

| Product/ingredient name                | Result                   | Species | Score | Exposure        | Observation |
|----------------------------------------|--------------------------|---------|-------|-----------------|-------------|
| xylene                                 | Skin - Moderate irritant | Rabbit  | -     | 24 hours 500 mg | -           |
| 2,4,6-tris (dimethylaminomethyl)phenol | Skin - Visible necrosis  | Rabbit  | -     | 4 hours         | 7 days      |

Conclusion/Summary

**Skin** : There are no data available on the mixture itself.

**Eyes** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

Sensitization

| Product/ingredient name                 | Route of exposure | Species    | Result      |
|-----------------------------------------|-------------------|------------|-------------|
| 2,4,6-tris (dimethylaminomethyl) phenol | skin              | Guinea pig | Sensitizing |

**Skin** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

Mutagenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

Carcinogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

Classification

| Product/ingredient name                            | OSHA | IARC | NTP |
|----------------------------------------------------|------|------|-----|
| 4-chloro- $\alpha,\alpha,\alpha$ -trifluorotoluene | -    | 2B   | -   |
| xylene                                             | -    | 3    | -   |
| Isopropyl alcohol                                  | -    | 3    | -   |

Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4

NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen

OSHA: +

Not listed/not regulated: -

Reproductive toxicity

**Conclusion/Summary** : There are no data available on the mixture itself.

Teratogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

## Section 11. Toxicological information

| Name                                               | Category   | Route of exposure | Target organs                |
|----------------------------------------------------|------------|-------------------|------------------------------|
| 4-chloro- $\alpha,\alpha,\alpha$ -trifluorotoluene | Category 3 | -                 | Respiratory tract irritation |
| xylene                                             | Category 3 | -                 | Respiratory tract irritation |
| butan-1-ol                                         | Category 3 | -                 | Respiratory tract irritation |
| Naphtha (petroleum), hydrotreated heavy            | Category 3 | -                 | Narcotic effects             |
| Isopropyl alcohol                                  | Category 3 | -                 | Respiratory tract irritation |
|                                                    |            |                   | Narcotic effects             |

### Specific target organ toxicity (repeated exposure)

Not available.

### Target organs

- : Contains material which causes damage to the following organs: brain, central nervous system (CNS).
- : Contains material which may cause damage to the following organs: blood, kidneys, lungs, the nervous system, liver, spleen, upper respiratory tract, skin, adrenal, ears, eye, lens or cornea.

### Aspiration hazard

| Name                                    | Result                         |
|-----------------------------------------|--------------------------------|
| xylene                                  | ASPIRATION HAZARD - Category 1 |
| Naphtha (petroleum), hydrotreated heavy | ASPIRATION HAZARD - Category 1 |

## Information on the likely routes of exposure

### Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : Harmful if inhaled. May cause respiratory irritation.
- Skin contact** : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing
- Skin contact** : Adverse symptoms may include the following:  
pain or irritation  
redness  
dryness  
cracking  
blistering may occur
- Ingestion** : Adverse symptoms may include the following:  
stomach pains

## Section 11. Toxicological information

### Delayed and immediate effects and also chronic effects from short and long term exposure

**Conclusion/Summary** : There are no data available on the mixture itself. Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. There is some evidence that repeated exposure to organic solvent vapors in combination with constant loud noise can cause greater hearing loss than expected from exposure to noise alone. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

### Short term exposure

**Potential immediate effects** : There are no data available on the mixture itself.

**Potential delayed effects** : There are no data available on the mixture itself.

### Long term exposure

**Potential immediate effects** : There are no data available on the mixture itself.

**Potential delayed effects** : There are no data available on the mixture itself.

### Potential chronic health effects

**General** : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Carcinogenicity** : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.

**Mutagenicity** : No known significant effects or critical hazards.

**Reproductive toxicity** : No known significant effects or critical hazards.

### Numerical measures of toxicity

#### Acute toxicity estimates

| Product/ingredient name                            | Oral (mg/kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapors) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|----------------------------------------------------|--------------|----------------|--------------------------|----------------------------|-------------------------------------|
| 2.1 EPOXY HARDENER                                 | 4200.2       | 2708.6         | N/A                      | 36.2                       | 4.9                                 |
| 4-chloro- $\alpha,\alpha,\alpha$ -trifluorotoluene | 13000        | 2500           | N/A                      | 33.08                      | N/A                                 |
| xylene                                             | 4300         | 1700           | N/A                      | 11                         | 1.5                                 |
| docusate sodium                                    | 3080         | N/A            | N/A                      | N/A                        | N/A                                 |
| butan-1-ol                                         | 790          | 3400           | N/A                      | 24                         | N/A                                 |
| 2,4,6-tris(dimethylaminomethyl)phenol              | 1200         | 1280           | N/A                      | N/A                        | N/A                                 |
| Isopropyl alcohol                                  | 5045         | 12800          | N/A                      | 72.6                       | N/A                                 |

## Section 12. Ecological information

### Toxicity

| Product/ingredient name     | Result                            | Species                                 | Exposure |
|-----------------------------|-----------------------------------|-----------------------------------------|----------|
| docusate sodium             | Acute EC50 39.5 mg/l Fresh water  | Algae - Pseudokirchneriella subcapitata | 72 hours |
|                             | Acute LC50 36 mg/l                | Daphnia - Daphnia magna                 | 48 hours |
|                             | Acute LC50 37 mg/l                | Fish - Lepomis macrochirus              | 96 hours |
| butan-1-ol                  | Acute LC50 1376 mg/l              | Fish                                    | 96 hours |
| 2,4,6-tris                  | Acute LC50 175 mg/l               | Fish                                    | 96 hours |
| (dimethylaminomethyl)phenol |                                   |                                         |          |
| Isopropyl alcohol           | Acute EC50 10100 mg/l Fresh water | Daphnia - Daphnia magna                 | 48 hours |

### Persistence and degradability

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|-------------------------|-------------------|------------|------------------|
| xylene                  | -                 | -          | Readily          |

### Bioaccumulative potential

| Product/ingredient name     | LogP <sub>ow</sub> | BCF         | Potential |
|-----------------------------|--------------------|-------------|-----------|
| xylene                      | 3.12               | 7.4 to 18.5 | low       |
| docusate sodium             | -                  | 9.33        | low       |
| butan-1-ol                  | 1                  | -           | low       |
| 2,4,6-tris                  | 0.219              | -           | low       |
| (dimethylaminomethyl)phenol |                    |             |           |
| Isopropyl alcohol           | 0.05               | -           | low       |

### Mobility in soil

Soil/water partition coefficient (K<sub>oc</sub>) : Not available.

## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

|                                        |                                  |                   |
|----------------------------------------|----------------------------------|-------------------|
| <b>Product code</b> ESU479             | <b>Date of issue</b> 28 May 2021 | <b>Version</b> 14 |
| <b>Product name</b> 2.1 EPOXY HARDENER |                                  |                   |

## Section 14. Transport information

|                                    | <b>TDG</b>      | <b>IMDG</b>     | <b>IATA</b>     |
|------------------------------------|-----------------|-----------------|-----------------|
| <b>UN number</b>                   | UN1263          | UN1263          | UN1263          |
| <b>UN proper shipping name</b>     | PAINT           | PAINT           | PAINT           |
| <b>Transport hazard class (es)</b> | 3               | 3               | 3               |
| <b>Packing group</b>               | III             | III             | III             |
| <b>Environmental hazards</b>       | No.             | No.             | No.             |
| <b>Marine pollutant substances</b> | Not applicable. | Not applicable. | Not applicable. |

### Additional information

**TDG** : None identified.

**IMDG** : None identified.

**IATA** : None identified.

**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Transport in bulk according to IMO instruments** : Not applicable.

**Proof of classification statement** : Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3).

## Section 15. Regulatory information

### National Inventory List

**Canada inventory ( DSL )** : All components are listed or exempted.

## Section 16. Other information

### Hazardous Material Information System (U.S.A.)

**Health** : 3 \* **Flammability** : 3 **Physical hazards** : 0

( \* ) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

### National Fire Protection Association (U.S.A.)

**Health** : 3 **Flammability** : 3 **Instability** : 0

**Date of issue/Date of revision** 28 May 2021

## Section 16. Other information

Organization that prepared the SDS : EHS

Key to abbreviations : ATE = Acute Toxicity Estimate  
BCF = Bioconcentration Factor  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
N/A = Not available  
SGG = Segregation Group  
UN = United Nations

Indicates information that has changed from previously issued version.

### Disclaimer

*The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.*